




Wilson Staff



## MULTI FIT SYSTEM INSTRUCTION MANUAL

### FG TOUR™ M3 DRIVER: FITTING GUIDE

The FG TOUR™ M3 Driver features six lofts with six corresponding face angle settings. The driver head comes set at an initial loft of 9.5°. Based on your preferred ball flight, lofts can be adjusted from 8.5° to 11.5° in half degree increments.



**FACE ANGLE**  
(Example: +1.5 = 1.5° Open)



#### HOSEL ADJUSTABILITY: 9.5 DRIVER

| LOFT | 8.5  | 9.0  | 9.5  | 10.5 | 11.0 | 11.5 |
|------|------|------|------|------|------|------|
| FACE | +2.5 | +2.0 | +1.5 | +1.0 | +0.5 | 0.0  |



## MULTI FIT SYSTEM

With the Multi Fit System from Wilson Staff® players can customize loft and weight to optimize ball flight. Six adjustable hosel settings and three interchangeable sole weights can be changed to maximize club head and ball speeds, while getting the right launch angle and spin rate for more distance and lower scores.

**IMPORTANT:** Immediately after purchase tighten both the hosel screw and the sole weight. This can be done by performing the steps in this manual.

### ADJUSTING THE HOSEL

Each FG TOUR™ M3 Driver, Fairway Wood and Hybrid has six hosel settings. To make loft adjustments:

1. Place the end of the grip on the ground, while holding the club head.
2. To loosen, place the wrench tip into the hosel screw. Turn the wrench counter-clockwise approximately eight times while lifting up slightly on the head to disengage the hosel.
3. Rotate the shaft so that the dot for the desired loft setting aligns with the line on the back of the hosel. Place the head back on the adaptor.
4. To tighten, place the end of the grip on the ground. Put the wrench tip back into the hosel screw and turn the wrench clockwise until the wrench clicks.

### FG TOUR™ M3 FAIRWAY WOODS: FITTING GUIDE

Like the Driver, each FG TOUR™ M3 Fairway Wood features six lofts with six corresponding face angle settings. The three heads come standard at initial lofts of 13.5°, 15.0° and 17.0°. Based on your preferred ball flight, lofts can be adjusted in half degree increments.

#### HOSEL ADJUSTABILITY: 13.5 WOOD

| LOFT | 12.5 | 13.0 | 13.5 | 14.5 | 15.0 | 15.5 |
|------|------|------|------|------|------|------|
| FACE | +2.5 | +2.0 | +1.5 | +1.0 | +0.5 | 0.0  |

#### HOSEL ADJUSTABILITY: 15.0 WOOD

| LOFT | 14.0 | 14.5 | 15.0 | 16.0 | 16.5 | 17.0 |
|------|------|------|------|------|------|------|
| FACE | +2.5 | +2.0 | +1.5 | +1.0 | +0.5 | 0.0  |

#### HOSEL ADJUSTABILITY: 17.0 WOOD

| LOFT | 16.0 | 16.5 | 17.0 | 18.0 | 18.5 | 19.0 |
|------|------|------|------|------|------|------|
| FACE | +2.0 | +1.5 | +1.0 | +0.5 | 0.0  | -0.5 |

### ADJUSTING THE SOLE WEIGHT

Each FG TOUR™ M3 Driver, Fairway Wood and Hybrid has three interchangeable sole weights. To make weight adjustments:

1. Place the end of the grip on the ground, while holding the club head.
2. To loosen, place the wrench tip into the sole weight and turn the wrench counter-clockwise until the weight disengages from the head.
3. Place a different weight in the opening and turn clockwise by hand to engage the threads.
4. To tighten, place the wrench tip back into the sole weight and turn the wrench clockwise until the wrench clicks.

**NOTE:** Both the hosel screw and sole weights should thread and tighten smoothly without binding. If difficult to turn, stop, remove and start over. Make sure the wrench and screw or weight are in a straight alignment.

### FG TOUR™ M3 HYBRIDS: FITTING GUIDE

For the FG TOUR™ M3 Hybrids, six different hosel settings are available. Choose from three unique loft settings with an upright lie angle option for each loft.

#### HOSEL ADJUSTABILITY: 17.0 HYBRID

| LOFT | 16.0 | 17.0 | 18.0 | 16.0 U | 17.0 U | 18.0 U |
|------|------|------|------|--------|--------|--------|
| FACE | +1.0 | +0.5 | 0.0  | +1.0   | +0.5   | 0.0    |
| LIE  | Std  | Std  | Std  | 2 Up   | 2 Up   | 2 Up   |

#### HOSEL ADJUSTABILITY: 19.0 HYBRID

| LOFT | 18.0 | 19.0 | 20.0 | 18.0 U | 19.0 U | 20.0 U |
|------|------|------|------|--------|--------|--------|
| FACE | +1.0 | +0.5 | 0.0  | +1.0   | +0.5   | 0.0    |
| LIE  | Std  | Std  | Std  | 2 Up   | 2 Up   | 2 Up   |

#### HOSEL ADJUSTABILITY: 21.0 HYBRID

| LOFT | 20.0 | 21.0 | 22.0 | 20.0 U | 21.0 U | 22.0 U |
|------|------|------|------|--------|--------|--------|
| FACE | +1.0 | +0.5 | 0.0  | +1.0   | +0.5   | 0.0    |
| LIE  | Std  | Std  | Std  | 2 Up   | 2 Up   | 2 Up   |

#### HOSEL ADJUSTABILITY: 23.0 HYBRID

| LOFT | 22.0 | 23.0 | 24.0 | 22.0 U | 23.0 U | 24.0 U |
|------|------|------|------|--------|--------|--------|
| FACE | +1.0 | +0.5 | 0.0  | +1.0   | +0.5   | 0.0    |
| LIE  | Std  | Std  | Std  | 2 Up   | 2 Up   | 2 Up   |



## MULTI FIT SYSTEM

With the Multi Fit System from Wilson Staff players can customize loft and weight to optimize ball flight. Six adjustable hosel settings and three interchangeable sole weights can be changed to maximize club head and ball speeds, while getting the right launch angle and spin rate for more distance and lower scores.

**READ INSTRUCTIONS COMPLETELY BEFORE USE.** Failure to follow these instructions may create a dangerous condition whereby a club head could disengage from the shaft and/or a weight from the head, possibly causing serious injury. Clubs and club components should be inspected frequently, before and during play, to ensure all connections and parts are secure. All components must be tightened prior to first use.

Only the Wilson Staff® Multi Fit System wrench should be used with adjustable FG TOUR™ M3 products. Also, only Wilson Staff® approved shafts, hosel adaptors and weights should be used with adjustable FG TOUR™ M3 products. Use of components and/or wrenches from any other source could damage the club, void the warranty and/or cause injury.



Wilson Staff

WILSON.COM

**Wilson**

Wilson Sporting Goods Co.  
8750 W. Bryn Mawr Ave.  
Chicago, IL 60631

Amer Sports Canada, Inc.  
85 Davy Road, PO Box 909  
Belleville, Ontario, K8N 5B6



Amer Sports Europe Services GmbH  
Parking 15-17, D-85748 Garching  
Germany



### FG TOUR™ M3 WEIGHT OPTIONS

An ever-increasing number of tour players have switched to lighter weight equipment in recent years. Extensive testing by Wilson Staff® R&D has shown that virtually all players, including low handicap players and tour players, will increase both distance and control by using what we call The Right Light™ technology. This includes optimizing head, shaft and grip weight. We are confident that with a little experimentation, you will hit the ball farther and with more accuracy than ever before.



#### 3-GRAM SOLE WEIGHT

// Silver in color  
// Super Light Weighting



#### 7-GRAM SOLE WEIGHT

// Gold in color  
// Standard on all FG Tour M3 products  
// The Right Light™ Weighting



#### 11-GRAM SOLE WEIGHT

// Black in color  
// Traditional Weighting

#### ALDILA RIP PHENOM SHAFT

// Standard on all FG TOUR™ M3 Driver, Woods & Hybrids  
// Additional shafts available through Wilson Staff® Custom Fit



Wilson Staff




## MULTI FIT SYSTEM


MANUEL D'INSTRUCTIONS

### BOIS N° 1 FG TOUR™ M3: GUIDE D'AJUSTAGE

Le bois n° 1 FG Tour™ M3 propose six angles d'ouverture avec six réglages correspondants d'angle de face. La tête du bois n° 1 est réglée à un angle d'ouverture initial de 9.5°. Basé sur l'envoi de balle que vous préférez, l'angle d'ouverture peut être ajusté entre 8.5° et 11.5° en pas d'un demi-degré.



ANGLE DE FACE  
(Exemple: +1.5 = 1.5° ouvert)



#### AJUSTABILITÉ DU COL: BOIS N° 19.5

| LOFT | 8.5  | 9.0  | 9.5  | 10.5 | 11.0 | 11.5 |
|------|------|------|------|------|------|------|
| FACE | +2.5 | +2.0 | +1.5 | +1.0 | +0.5 | 0.0  |



## MULTI FIT SYSTEM

Le système Multi Fit Wilson Staff® permet aux golfeurs d'ajuster l'angle d'ouverture et le poids pour obtenir un envol optimal de la balle. Six ajustements du col et trois poids de semelle interchangeables permettent de maximiser la vitesse de la tête du bâton et de la balle tout en réalisant l'angle d'amorce et l'effet requis pour augmenter la distance et améliorer le score

**IMPORTANT:** Serrez la vis du col et le poids de la semelle immédiatement après l'achat. Ceci peut être réalisé en suivant les directives dans ce manuel.

### AJUSTEMENT DU COL

Chaque bois n° 1, bois d'allée et hybride FG Tour™ M3 est doté d'un col à six positions. Pour ajuster l'angle d'ouverture:

1. Placez l'extrémité du manche contre le sol tout en tenant la tête du bâton.
2. Pour desserrer, placez la pointe de la clé dans la vis du col. Tournez la clé dans le sens antihoraire environ huit fois tout en soulevant légèrement la tête pour désengager le col.
3. Tournez la tige de façon à ce que le point de l'angle d'ouverture désiré s'aligne avec la ligne au dos du col. Remettez la tête sur l'adaptateur.
4. Pour serrer, placez l'extrémité du manche contre le sol. Remettez la pointe de la clé sur la vis du col et tournez la clé dans le sens horaire jusqu'à ce que la clé produise un son de déclic.

### BOIS D'ALLÉE FG TOUR™ M3: GUIDE D'AJUSTAGE

Tout comme le bois n°1, chaque bois d'allée FG Tour™ M3 propose six angles d'ouverture avec six réglages correspondants d'angle de face. Les trois têtes viennent avec un angle d'ouverture initial de 13.5°, 15.0° et 17.0°. Basé sur l'envoi de balle que vous préférez, l'angle d'ouverture peut être ajusté en pas d'un demi-degré.

#### AJUSTAGE DU COL: 13.5 BOIS N° 1

| LOFT | 12.5 | 13.0 | 13.5 | 14.5 | 15.0 | 15.5 |
|------|------|------|------|------|------|------|
| FACE | +2.5 | +2.0 | +1.5 | +1.0 | +0.5 | 0.0  |

#### AJUSTABILITÉ DU COL: BOIS 15.0

| LOFT | 14.0 | 14.5 | 15.0 | 16.0 | 16.5 | 17.0 |
|------|------|------|------|------|------|------|
| FACE | +2.5 | +2.0 | +1.5 | +1.0 | +0.5 | 0.0  |

#### AJUSTABILITÉ DU COL: BOIS 17.0

| LOFT | 16.0 | 16.5 | 17.0 | 18.0 | 18.5 | 19.0 |
|------|------|------|------|------|------|------|
| FACE | +2.0 | +1.5 | +1.0 | +0.5 | 0.0  | -0.5 |

### AJUSTEMENT DU POIDS DE LA SEMELLE

Chaque bois n° 1, bois d'allée et hybride FG Tour™ M3 vient avec trois poids de semelle interchangeables. Pour ajuster le poids:

1. Placez l'extrémité du manche contre le sol tout en tenant la tête du bâton.
2. Pour desserrer, placez la pointe de la clé dans le poids de la semelle et tournez la clé dans le sens antihoraire jusqu'à ce que le poids se dégage du talon.
3. Placez un autre poids dans l'ouverture et tournez-le dans le sens horaire à la main pour engager le filetage.
4. Pour serrer, placez la pointe de la clé dans le poids de la semelle et tournez la clé dans le sens horaire jusqu'à ce que la clé produise un son de déclic.

**NOTE:** Voyez à engager le filetage de la vis du col et du poids de la semelle avec soin afin de ne pas le gâcher. S'ils sont difficiles à tourner, arrêtez, dévissez-les et recommencez. Assurez-vous que la clé et la vis ou le poids sont alignés bien droit.

### HYBRIDES FG TOUR™ M3: GUIDE D'AJUSTAGE

Les hybrides FG Tour™ M3 offrent six réglages de col. Choisissez parmi trois réglages uniques d'angle d'ouverture avec possibilité d'angle de positionnement droit pour chacun.

#### AJUSTABILITÉ DU COL: HYBRIDE 17.0

| LOFT | 16.0 | 17.0 | 18.0 | 16.0 U | 17.0 U | 18.0 U |
|------|------|------|------|--------|--------|--------|
| FACE | +1.0 | +0.5 | 0.0  | +1.0   | +0.5   | 0.0    |
| LIE  | Std  | Std  | Std  | 2 Up   | 2 Up   | 2 Up   |

#### AJUSTABILITÉ DU COL: HYBRIDE 19.0

| LOFT | 18.0 | 19.0 | 20.0 | 18.0 U | 19.0 U | 20.0 U |
|------|------|------|------|--------|--------|--------|
| FACE | +1.0 | +0.5 | 0.0  | +1.0   | +0.5   | 0.0    |
| LIE  | Std  | Std  | Std  | 2 Up   | 2 Up   | 2 Up   |

#### AJUSTABILITÉ DU COL: HYBRIDE 21.0

| LOFT | 20.0 | 21.0 | 22.0 | 20.0 U | 21.0 U | 22.0 U |
|------|------|------|------|--------|--------|--------|
| FACE | +1.0 | +0.5 | 0.0  | +1.0   | +0.5   | 0.0    |
| LIE  | Std  | Std  | Std  | 2 Up   | 2 Up   | 2 Up   |

#### AJUSTABILITÉ DU COL: HYBRIDE 23.0

| LOFT | 22.0 | 23.0 | 24.0 | 22.0 U | 23.0 U | 24.0 U |
|------|------|------|------|--------|--------|--------|
| FACE | +1.0 | +0.5 | 0.0  | +1.0   | +0.5   | 0.0    |
| LIE  | Std  | Std  | Std  | 2 Up   | 2 Up   | 2 Up   |



## MULTI FIT SYSTEM

Le système Multi Fit Wilson Staff® permet aux golfeurs d'ajuster l'angle d'ouverture et le poids pour obtenir un envol optimal de la balle. Six ajustements du col et trois poids de semelle interchangeables permettent de maximiser la vitesse de la tête du bâton et de la balle tout en réalisant l'angle d'amorce et l'effet requis pour augmenter la distance et améliorer le score.

LISEZ TOUTES LES INSTRUCTIONS AVANT L'UTILISATION. Un manque à suivre ces instructions peut engendrer une situation dangereuse où la tête du bâton pourrait se séparer de la tige ou un poids se séparer de la tête et causer des blessures graves. Inspectez régulièrement les bâtons et leurs éléments, avant et pendant le jeu, afin d'assurer que tous les raccords et tous les éléments soient bien attachés. Tous les éléments doivent être serrés avant la première utilisation.

Seule la clé Multi Fit System Wilson Staff® devrait être utilisée pour les produits ajustables FG Tour™ M3. De plus, seuls les tiges, adaptateurs de col et poids Wilson Staff® devraient être utilisés avec les produits ajustables FG Tour™ M3. L'utilisation d'éléments ou de clés provenant d'une autre source pourrait endommager le bâton, rendre la garantie nulle et/ou causer des blessures.



Wilson Staff

WILSON.COM

Wilson

Wilson Sporting Goods Co.  
8750 W. Bryn Mawr Ave.  
Chicago, IL 60631

Amer Sports Canada, Inc.  
85 Davy Road, PO Box 909  
Belleville, Ontario, K8N 5B6



Amer Sports Europe Services GmbH  
Parking 15-17, D-85748 Garching  
Germany

AMERICAN EXPRESS  
13+



### CHOIX DE POIDS FG TOUR™ M3

Un nombre sans cesse grandissant de golfeurs ont opté pour un équipement plus léger ces dernières années. Des tests poussés par le service de la R&D Wilson Staff® ont démontré que pratiquement tous les golfeurs, même ceux avec un faible handicap et les en tournoi, amélioreront la distance et le contrôle en utilisant ce que nous appelons la technologie "The Right Light™". Elle comprend l'optimisation du poids de la tête, de la tige et du manche. Nous sommes convaincus qu'avec un peu d'expérimentation, vous frapperez la balle plus loin et avec plus de précision que jamais auparavant.



#### POIDS DE SEMELLE 3 G

// Argenté  
// Empesage ultra léger



#### POIDS DE SEMELLE 7 G

// Doré  
// Standard sur tous les FG Tour™ M3  
// Empesage The Right Light™



#### POIDS DE SEMELLE 11 G

// Noir  
// Empesage traditionnel

#### TIGE ALDILA RIP PHENOM

// Standard sur tous les bois n° 1, bois et hybrides FG Tour™ M3  
// Autres tiges offertes par l'entremise de l'Ajustage spécial Wilson Staff®