### **Rotary Cutter**

Series I and II

# bühler



### **TOUGH JOBS NEED A TOUGH CUTTER**



SERIES I			II		
MODEL	Y410LS	Y510LS	Y510	Y620	Y720
Cutting width	48"	60"	60"	72"	84"
Cutting height	Min: 3"	Min: 4"	Min: 4"	Min: 4"	Min: 4"
Blade tip speed	13,098 ft/min	12,721 ft/min	12,721 ft/min	14,758 ft/min	14,283 ft/min
Spring steel blades	½" x 3" heat treated	½" x 3" heat treated	½" x 3" heat treated	½" x 3" heat treated	½" x 3" heat treated
Deck material	11 gauge	11 gauge	10 gauge	10 gauge	10 gauge
Gearbox	Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)
Gearbox rating	30 hp	40 hp	40 hp	60 hp	65 hp
Tractor HP requirement	20 - 45	25 - 55	25 - 65	35 - 65	45 - 75
PTO shaft	Shear pin	Shear pin	Shear pin	Slip clutch	Slip clutch
3-point hitch*	Cat. I standard	Cat. I standard	Cat. I standard	Cat. II standard	Cat. II standard
Tire - 3-point	15" laminated	15" laminated	16" solid rubber	16" solid rubber	20" solid rubber
Tire/wheels - trailing	n/a	n/a	Solid rubber or 15" rim	Solid rubber or 15" rim	15" rim
Stump-jumper	n/a	n/a	Standard: 24" diameter	Standard: 24" diameter	Standard: 24" diameter
Parking jack	n/a	n/a	Optional	Optional	Optional
Chain kit	Optional	Optional	Optional	Optional	Optional
Weight - 3-point	450 lbs (est)	520 lbs (est)	601 lbs	777 lbs	989 lbs
Weight - trailing	n/a	n/a	686 lbs	856 lbs	1080 lbs

<sup>\*</sup>All models are quick hitch compatible

#### Shred weeds :: clear brush :: mow the clutter

Buhler Farm King Rotary Cutters are made to clear those rough areas where stones, tree stumps and debris are hidden by weeds. These rotary cutters, available in two series, easily clear heavy weeds and thick rough and require minimal maintenance. Series I, with a 3-point hitch, is available in 48" or 60" widths. Series II is available in 60", 72" and 84" and is equipped with either a trailing style or 3-point hitch. The 3-point hitch on both series is Buhler Quick Hitch compatible so it is easy to attach and unhook. 3-point hitch models include a single solid rubber or laminated trailing wheel, while rotary cutters with a trailing hitch have two wheels, either air-filled or made of solid rubber.

#### Heavy metal for heavy jobs

Buhler Farm King Rotary Cutters are built tough and made to last. The blades are heat-treated to enhance rigidity and the heavy-duty gearbox is designed to be rugged and durable. The access panel on the deck makes it easy to inspect or replace the blades. An optional chain kit minimizes the possibility of flying debris.

The stump-jumper is a 24" plate mounted to the blades below the gearbox. Standard on Series II Rotary Cutters, the stump-jumper allows the blade assembly to move up and down to minimize stress on the deck and gearbox. The power take-off (PTO) shaft on the Series II 60" Rotary Cutter includes a shear pin to protect the gearbox in the event of an unforeseen obstacle. The 72" and 84" rotary cutters are equipped with a slip clutch to prevent gearbox damage.

The Y720T with the trailing style hitch includes a two-piece PTO shaft for a tighter turning radius. An 8" cylinder and hoses are optional for all trailing models.



Established in 1933 as an agricultural equipment manufacturer, Standard Gas Engine Works was purchased by John Buhler in 1969. Through steady expansion, new products and acquisitions, the company has experienced steady growth and has evolved into one brand name: Buhler. Over the years, many brands have joined the Buhler family: Farm King, Allied, Inland and Versatile. Buhler maintains several well-stocked parts warehouses and is committed to continuous product improvement and incorporating new value-added features. That tradition of excellence will continue well into the future.



## bühler

301 Mountain Street South

Morden, Manitoba :: Canada R6M 1X7

Ph.: 204.822.4467 :: Fax: 204.822.6348

Toll Free: 888.524.1004 E-mail: info@buhler.com www.buhler.com

#### TSX:BUI

Equipment shown is subject to change without notice. ©2007 Buhler Manufacturing. Printed in Canada.

Ref: 112007-3000-PG