

Rotary Tiller

Series 25, 45 and 65

bühler



SOLID CONSTRUCTION AND HEAVY-DUTY COMPONENTS



SERIES	25			45		65			
MODEL	C2540	C2548	C2560	C4560	C4572	C6550	C6560	C6572	C6582
Tillage width	36"	45"	54"	55"	69"	46"	56"	68"	77"
Overall width	46 1/2"	54 1/2"	66 1/2"	66"	78"	56"	66"	78"	88"
Tractor HP requirement	12 - 18	14 - 22	18 - 25	25 - 40	30 - 45	30 - 40	35 - 45	45 - 55	55 - 65
3-point hitch*	Cat. I			Cat. I		Cat. I, optional fit Cat. II			
Gearbox	Heavy-duty oil bath (540 RPM)			Heavy-duty oil bath (540 RPM)		Heavy-duty oil bath (540 RPM)			
Chain in oil bath	#60H	#60H	#60H	#80H	#80H	#100H	#100H	#100H	#100H
Rotor speed RPM	196 RPM or 880 ft/min			203 RPM or 865 ft/min		196 RPM or 880 ft/min			
Sideshift	2 1/2"	4 1/2"	7 1/2"	6 3/4"	8 1/2"	5"	8"	15"	n/a
PTO shaft	Slip clutch, shear bolt optional			Slip clutch		Slip clutch			
Tine size	1/4" x 2 1/4"	1/4" x 2 1/4"	1/4" x 2 1/4"	1/4" x 2 1/4"	1/4" x 2 1/4"	5/16" x 3 1/4"	5/16" x 3 1/4"	5/16" x 3 1/4"	5/16" x 3 1/4"
Number of tines	4 flanges 4 tines/flange	5 flanges 4 tines/flange	6 flanges 4 tines/flange	6 flanges 4 tines/flange	8 flanges 4 tines/flange	5 flanges 6 tines/flange 4 tine opt.	6 flanges 6 tines/flange 4 tine opt.	7 flanges 6 tines/flange 4 tine opt.	8 flanges 6 tines/flange 4 tine opt.
Weight	425 lbs	458 lbs	517 lbs	613 lbs	688 lbs	774 lbs	835 lbs	906 lbs	968 lbs

*All models are quick hitch compatible



Get closer to the edge

Getting close to fences, hedges or covering a tire track is easy with the sideshift feature. The entire unit can be pushed to one side, while the PTO shaft remains in line with the tractor to minimize stress on the universal joint. The sideshift feature is available on all Buhler Farm King Rotary Tillers except the C6582.

TILLERS FOR ALL YOUR TILLING NEEDS



The perfect tillers for thorough soil preparation

Buhler Farm King has a collection of rotary tiller models to suit your garden and landscaping needs. The tiller attaches to the three-point hitch and is designed to fit a variety of tractors, from 12 hp to 65 hp. Tilling widths range from 36" to 54" in the 25 Series and from 55" to 69" in the 45 Series. The 65 Series is available in 46" to 77" widths.

Break ground with ease

The tilling shaft is equipped with four to eight flanges, depending on the model. Flanges on all series are available with four tines, and six tines per flange are standard on the 65 Series. This provides an optimum balance between performance and durability, even in heavy soils and when breaking untilled soil.

Set the right depth

Standard on all Buhler Farm King Rotary Tillers, the skid shoes are adjustable so it is easy to set the perfect tilling depth.

Low maintenance :: long life

All models are equipped with an automatic chain tightener that ensures the chain remains tight under the toughest tilling conditions. Housed in a sealed oil bath, the chain tightener assembly is resistant to heat, dust, debris and moisture, which reduces maintenance and enhances the longevity of the chain and sprockets.



[1] Adjustable skid shoes to set the tillage depth.

[2] Flange with four tines.

[3] Parking stand (shown in up position).

[4] Automatic chain tightener (shown with sealed oil bath housing removed).



bühler

301 Mountain Street South
Morden, Manitoba :: Canada R6M 1X7
Ph.: 204.822.4467 :: Fax: 204.822.6348
Toll Free: 888.524.1004
E-mail: info@buhler.com
www.buhler.com

TSX:BUI

Equipment shown is subject to change without notice.
©2007 Buhler Manufacturing. Printed in Canada.
Ref: 112007-3000-PG