VERNIERN

ANALOGUE COUNTING DIAL 15 TURNS



FEATURES

- Round Vernier Scale
- 7/8" Dia.
- · 1/4" or 1/8" Shaft Adapter
- · Satin Chrome Finish with Black or White Markings

MECHANICAL SPECIFICATIONS	
PARAMETER	
Mounting	Install mounting bracket
	between panel and panel nut.
	Multidial shall mount directly
	to shaft with No. 2 - 56
	spline socket set screw,
	located adjacent to No. 50
	on graduated dial
Numeral Size	0.75 Inches H
Graduation Size:	
Numeral	0.45 Inches L (1.14cm)
Intermediate	0.030 Inches L (0.76cm)
Weight	0.7 oz maximum (19.84gm)

OPERATIONAL SPECIFICATIONS Readout and Operation 15 turns total The number in the window (0 thru 14) indicates completed number of turns of the drive sleeve. Graduated circular dial indicates the percent of the partial turn of the drive sleeve Transfer Point The number in the window shall change as graduated dial rotates between 94 and 0 Rotation Readout shall increase with clockwise and decrease with counterclockwise rotation Brake Lever 1st position (15" to 0 movement of brake lever) operates a high torque system for fine adjustment; 2nd position (15° additional movement of brake lever) actuates brake Zero backlash between graduated Accuracy dial and the drive sleeve



DIMENSIONS in inches (millimeters)