

SETTING THE PREMIUM STANDARD FOR SUB-COMPACT BACKHOES.

The Sc2450 is the sub-compact tractor that performs in big ways, from performance to comfort. Innovative Shift-On-The-Go[®] technology lets you shift from high to low without stopping. Plus, its specially designed frame, curved boom attachments, powerful hydraulics and efficient engine deliver an all-around superior performance. And when you get an open, comfortable operator station with swivel seat and backhoe boom float control, you also get an experience way beyond the expected.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE IS THE

CUB CADET YANMAR ADVANTAGE



CURVED BOOM LOADER AND BACKHOE

Designed to get the most out of your tractor, the innovative backhoe with float control will take on any challenge. Plus, the curved boom loader offers the highest lift capacity in its class with greater visibility from behind the wheel. When you can dig deeper with more precision, you can effortlessly tackle the toughest jobs — that's a premium experience.



24 HP* DIRECT-INJECTION DIESEL ENGINE

This high-performance, 3-cylinder, liquid-cooled diesel engine burns cleaner and more efficiently. The advanced combustion chamber design allows for better fuel atomization and a longer stroke — creating better torque reserve so that you'll have power when you need it.

.....



DUAL HYDRAULIC PUMPS

Separate hydraulic pumps deliver a more efficient flow of hydraulic fluid for a smooth hydraulic response without compromising horsepower. Whether you're using the curved boom loader or accelerating through rough terrain with power steering, you'll have the power you need to handle demanding jobs with ease. Sc2450 MULTI-PURPOSE SUB-COMPACT TRACTOR

FEATURES

SELECTABLE 4WD WITH DIFFERENTIAL LOCK

SHIFT-ON-THE-GO®

HYDRAULIC

POWER STEERING

BACKHOE BOOM FLOAT CONTROL

.....

POP-UP SWIVEL SEAT

SHORT-STROKE BACKHOE CONTROLS

CRUISE CONTROL

ELECTRO-HYDRAULIC

REVERSE-OVERRIDE SWITCH FOR SAFE PTO OPERATION

ONE-PIECE HOOD FOR EASE OF MAINTENANCE

12-VOLT DC OUTLET

REVERSE-MOUNTED

WIDE OPERATOR'S

STATION 3-POINT HITCH

POSITION CONTROL**

POWERTRAIN WARRANTY[†]

*as rated by engine manufacturer •See Cub Cadet Yanmar Independent Dealer for warranty information

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS ABOUT THE MANY BENEFITS OF OWNING A CUB CADET YANMAR.

cubcadetyanmar.com



Sc2450 Specifications

| POWERTRAIN Gross HP | 24 HP* diesel |
|--|---------------------------------------|
| PTO HP (Hyd) | 16.5 at 3,200 RPM |
| Rated RPM | 3,200 RPM |
| Number of cylinders | 3 |
| Bore and stroke | 72 x 74 mm |
| Total displacement | 55.1 cu. in. |
| Ignition type | Indirect injection |
| Lubrication | Full pressure |
| Oil filter | Spin-on/full flow |
| Cooling system | Liquid cooled |
| Air cleaner | 4" single dry |
| Preheat system | Glow plug |
| Alternator | 40 amp. |
| Exhaust | Right side pointing down |
| CAPACITIES | |
| Fuel tank | 5.8 gal. |
| Cooling system | 3.4 qt. |
| Engine oil | 2.5 qt. |
| Transmission case | 2.0 gal. |
| | 5di. |
| | I haden at a fa |
| Transmission type | |
| Number of ranges | 2 Shift-On-The-Go® |
| 4WD operations | 2WD & 4WD selectable |
| Cruise control Rear differential lock | Selectable |
| | Foot pedal operation |
| PTO type | Independent |
| Mid PTO/RPM (standard) | 2,100/3,338 |
| Rear PTO/RPM (standard) | 540/3,111 |
| Brake | Wet disc |
| MAXIMUM TRAVELING SPEED | |
| Forward low | 6.0 mph |
| Forward high | 9.3 mph |
| Reverse low | 3.6 mph |
| Reverse high | 5.6 mph |
| HYDRAULICS | |
| Туре | Open center |
| Pump | Gear/Trochoid |
| Steering/SCV/backhoe/3-pt hitch | 3.5 GPM at 3,200 RPM |
| Transmission/hydraulic PTO | 3.4 GPM at 3,200 RPM |
| Maximum pump capacity | 6.9 GPM at 3,200 RPM |
| 3-point hitch** | Limited Category 1 |
| 3-point lift capacity at 24" behind | 661 lbs. |
| Hydraulic control system | Position control |
| DIMENSIONS | |
| Wheelbase | 55.1" |
| Width | 44.5" |
| Overall length w/ | |
| loader and backhoe | 172.5" |
| Ground clearance | 7.5" (w/R4) |
| Weight w/ROPS & fluids | 2,525 lbs. |
| TIRE SIZE | |
| Front industrial/turf | 18" x 8.5" – 10" |
| | 26" x 12.0" – 12" |
| Rear Industrial/turr | |
| Rear industrial/turf RESIDENTIAL/COMMERCIAL | |
| | 2-year or 2,000-hour limited warranty |

Sc2450 Attachment Specifications

CL100 CURVED BOOM LOADER

| Bucket options RESIDENTIAL/COMMERCIAL WARRANTY ⁺ | |
|---|--------------|
| | |
| Bucket options | |
| | 8", 12" |
| Street pads | Optional |
| Ramp angle (w/industrial tires) | 20.5° |
| Operating pressure | 1,857 PSI |
| Weight (less bucket) | 620 lbs. |
| Dipperstick cylinder digging force | 1,187 lbs. |
| Bucket cylinder digging force | 2,036 lbs. |
| Stabilizer spread (down) | 74" |
| Undercut | 17" |
| Transport overhang | 37" |
| Loading reach | 33" |
| Bucket rotation | 180° |
| Transport height | 66" |
| Reach from swing pivot | 104" |
| Loading height (bucket at 60°) | 60" |
| Swing arc | 150° |
| Digging depth (2' flat bottom) | 74.5" |
| Maximum digging depth | 76.5" |
| URVED BOOM BACKHOE | |
| Relief valve | 1,813 PSI |
| Rated flow | 3.5 GPM |
| Attachment dumping time | 1.5 sec. |
| Attachment rollback time | 2 sec. |
| Lowering time w/o load (power down) | 2.5 sec. |
| Raising time to full height w/o load | 3.5 sec. |
| forward of the pivot pins | 1050 lbs. |
| Breakout force at 500 mm | |
| Breakout force at bucket pins | 1,350 lbs. |
| Lift capacity at pivot pins, maximum height | 700 lbs. |
| Lift capacity 500 mm forward of the pivot pins, maximum height | 550 lbs. |
| Bucket capacity | 5 cu. ft. |
| Bucket width/weight | 48"/125 lbs. |
| Maximum lift height under bucket | 66" |
| Length of attachment (bucket bottom) | 19.25" |
| Overall height in carry position | 37" |
| Digging depth | 4" |
| Maximum rollback angle | 25° |
| Reach w/bucket on ground | 40" |
| Maximum dump angle | 45° |
| Reach at maximum height | 27" |
| Dump clearance | 54" |
| | |

* as rated by engine manufacturer

**3-point hitch is optional * See your local Cub Cadet Yanmar Independent Dealer for warranty details.

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications. Please visit cubcadetyanmar.com for more information.