



GETS THE JOB DONE!

6" Chippers!



Has a 360-degree rotating bed, you can feed the hopper from any direction. These towable chippers come standard with a torsion axle suspension.



Chipper is pre-wired for the optional (73244) digital programmable feed sensor and hour meter. This option is available only on the CH6614H (72620).

"We've always been very satisfied with ECHO Bear Cat equipment. It is very durable and we would recommend it to anyone."

Ron Williams Orangeville, Ontario



Model CH6614H (72620)

Model	Engine	Size (LxWxH)	Chipper Capacity	Feed System	Feed Opening	Start	Weight (Lbs.)	Tires Base
CH6614 (71620)	Honda 614cc	76"x80"x90"	6"	Manual feed	9"x9"	Electric	1445	5.30" x 12" pneumatic
CH6614H (72620)	Honda 614cc	93"x80"x90"	6"	Hydraulic	9"x9"	Electric	1865	5.30" x 12" pneumatic

Option:

73244 Digital Programmable Feed Sensor and Hour Meter for Model 72620



Find a dealer near you!

Call us at 800.247.7335 or

Log onto www.BearCatProducts.com

237 12th St. NW • P.O. Box 849, West Fargo, ND 58078

Email: sales@bearcatproducts.com

Fax: 701.282.9522



6" Chipper Specs

76cm [30"] DIAMETER DISC

1.25" [76cm] diameter by 1.25" [3.2cm] thick rotor disc that weighs 275 lbs. [125kg]. Machined to balance. Disc turns at 1500 RPM. .75" [4.45cm] diameter rotor shaft.

FOUR CHIPPING BLADES

All have the same reversible chipper blades, heat treated chipper steel with a chrome content

ENGINE

Honda 20 hp engine with electric start
6.6 gallon [25 liters] fuel tank
Fuel consumption is 1.92 gal. [7.27 liters] pH at full load

MANUAL BELT ENGAGEMENT LEVER ON TOWABLE MODELS

FEED SYSTEM

45-Degree chipping blade edge angle pulls the logs and limbs into the 71620. The Hydraulic feed helps guide wood into the chipping mechanism on model 72620.

EASY ACCESS DISC

The rotor is accessible through the hinged disc cover, which exposes one half of the disc for easy access to the chipping blades and for easy clean out.

HEAVY-DUTY CONSTRUCTION

.375" [9.5mm] thick steel face plate on the disc housing
.25" [6.35mm] thick steel on the wrap
around with welded construction

INTEGRATED DISCHARGE BLOWER

Put the chips where you want them with the dedicated blower. 360° rotatable, 8" [20cm] diameter steel tubing with adjustable spout cap allows you to put the chips where you want them the first time. Discharge chute is 95" [2.41m] high.

FEED CHUTE

Has an opening size of 30.25" x 30.75" [76.8cm x 78.1cm], tray 28.31" [71.9cm] off the ground. Feed table is 38" [96.5cm] long.

MAXIMUM FEED SIZE - 6"

ADJUSTABLE JACK (Towable Models Only)

Roller wheel with 850 lbs. [372 kg] rating. Adjustable jack allows one person to easily maneuver the chipper around and hook up to a vehicle.

HIGHWAY TOWABLE

68" [172cm] tread width (center to center), 5.30" x 12" [13.5cm x 30.5 cm] tires, coupled with torsion axle suspension enables the chipper to be easily towed down the highway. Light kit, and safety chains are standard, with 2,250 lb. axle.

DIMENSIONS:

- CH6614 (71620) - Length 76" • Width 80" • Height 90"
- CH6614H (72620) - Length 93" • Width 80" • Height 90"

Weight

- CH6614 (71620) - 1445 lbs
- CH6614H (72620) - 1865 lbs

Safety

- Meets all ANSI safety standards.
- 12 Volt Safety and Directional Lighting



Find a dealer near you!

Call us at 800.247.7335 or

Log onto www.BearCatProducts.com

237 12th St. NW • P.O. Box 849, West Fargo, ND 58078

Email: sales@bearcatproducts.com

Fax: 701.282.9522