



RELIABLE POWER YOU CAN TAKE WITH YOU!

4" & 5" PTO Chippers



Shown above is the CH4540 (73454) 4" PTO Chipper.



Fold down feed tray comes standard on the CH5540H (74554) Hydraulic PTO Chipper.



Model CH5540H (74554)

"There's no need to change anything --- it is head and shoulders above the competition!"

Richard Raynes

Cutts Island, Kittery Point, Maine

Model	Engine (LxWxH)	Size	Chipper Capacity	Feed System	Feed Opening	Weight (Lbs.)	3 Point Hitch	PTO
CH4540* (73454)	PTO	48"x45"x87"	4"	manual feed	5.5"x7"	600	Cat. 1	540 rpm
CH5540H* (74554)	PTO	94"x40"x93"	5"	hydraulic	5.5"x7"	980	Cat. 1	540 rpm

Option:

73071 Digital Programmable Feed Sensor and Hour Meter for (Model 74554 only)

*Models CH4540 (73454) and CH5540H (74554) - Tractors with 540 rpm PTO Drive, Engine HP Ratings from 13 hp diesel and 15 hp gas to 45 hp.

Category 1 Tree Point Hitch



Find a dealer near you!

Call us at 800.247.7335 or

Log onto www.BearCatProducts.com

P.O. Box 849, West Fargo, ND 58078

Email: sales@BearCatProducts.com

Fax: 701.282.9522



4" & 5" PTO Chipper Specs

Models CH4540 (73454), CH5540H (74554)

20" [51cm] DIAMETER DISC

20" [51cm] x 1.25 [3.175cm] thick rotor disc weighs 140 lbs. [63.5kg], machine balanced.

PTO DRIVE

The PTO Drive, category one 3-point that weighs 600 lbs. [272kg.] Belt Driven.

FOUR CHIPPING BLADES

All have the same reversible chipper blades, heat treated chipper steel with a chrome content. 3.125" x .25"

ADJUSTABLE, 4-WAY ANVIL

To ensure good quality chipping ability.

DOUBLE BANDED BELT DRIVE

HYRAULIC FEED SYSTEM on Model CH5540H ONLY

- 15" Diameter feed roller
- Maximum capacity of 3 Gallons/minute at 2500 PSI
- Electric/Hydraulic system to control feed roller direction

MANUAL FEED SYSTEM on Model CH4540 ONLY

- 45-Degree chipping blade edge angle helps pull the logs and limbs into the 73454.

EASY ACCESS DISC

The rotor is accessible through the hinged disc cover by removing one bolt, which exposes one half of the disc for easy access to the chipping blades and for easy inspection and maintenance.

HEAVY-DUTY CONSTRUCTION

- .25" Thick steel throughout, seam welded.

INTEGRATED DISCHARGE CHUTE

Put the chips where you want them with the dedicated blower. 360° rotatable, 8" [20cm] diameter steel tubing with adjustable spout cap allows you to put the chips where you want them the first time.

LARGE FEED HOPPER

Feed your prunings or limbs into a 27" x 28" [68.6cm x 71.1cm] opening.

CHIPPER CHUTE

Opening is 5.5" x 7" [14cm x 17.8cm] (for side limbs)

MAXIMUM FEED SIZE

- CH4540 (73454) - 4"
- CH5540H (74554) - 5"

2" [5.08CM] BALL COUPLER

WEIGHT

- CH4540 (73454) PTO CHIPPER Weighs 600lbs.
- CH5540H (74554) PTO CHIPPER Weighs 980lbs.

SAFETY

- Meets all ANSI safety standards.



Find a dealer near you!

Call us at 800.247.7335 or
Log onto www.BearCatProducts.com

P.O. Box 849, West Fargo, ND 58078
Email: sales@BearCatProducts.com
Fax: 701.282.9522