

PS-7910 H

Powerful chain saw for professional users

Power, torque and light weight - just what the professional chain saw operator requires for efficient and low-effort forestry work such as tree felling and stripping.



Optimum chip exhaust for avoiding jams



Lateral chain tensioning



Easy filter maintenance

Technical specifications

Displacement	78,5 cm ³	Automatic oilpump	yes
Power rating	4,3 kW	Handle Heating	yes
Power rating	5,9 PS	Sound pressure level	105,1 dB(A)
Weight (dry, w/o bar)	6,8 kg	Sound power level	115,3 dB(A)
Fuel tank capacity	0,75 l	Uncertainty K according to 2006/42/EC	2,5 dB(A)
Oil tank capacity	0,42 l	Vibration acceleration Front	6,6 m/s ²
Vibration damping	yes	Vibration acceleration Rear	4,5 m/s ²
Chain tensioning	Lateral tensioning	Uncertainty K according to 2006/42/EC	2,0 m/s ²

- Low emissions according 2002/88/EC for environmental and user benefit with SLR technology
- Up to 15% less fuel consumption with SLR technology
- Tool-less filter maintenance
- Manual and inertial released chain brake
- Vibration damping with oil and fuel resistant steel springs for user's comfort and health
- Lateral chain tensioning provides easy operator access
- Decompression valve
- Optimum chip flow through
- Adjustable oil pump, disabled at engine idling
- Handle heating system

DOLMAR GmbH .

A Member of the Makita Group

www.dolmar.com

DOLMAR