PNC 206136 🗆



Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 1 Well 24.5 litres

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



Modular Cooking Range Line

700XP Freestanding Electric Pasta Cooker, 1 Well 24.5 litres

371098 (E7PCED1KF0)

700XP FREESTANDING ELECTRIC PASTA COOKER 24.5 LT WELL, 1 WELL - 400 V

Short Form Specification

14000	м	_
1114111	IN	ш

Infrared heating system positioned below the well. Constant starch removal during the cooking process. Pressed tank in 316 AISI stainless steel to protect against corrosion. Manual water tap. Height adjustable feet in stainless steel. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings, vegetables and soups for large or small servings.
- Unit to have infared heating system positioned beneath the base of the well.
- Water basin in 316 type Stainless steel.
- Water basin is seamlessly welded into the top of the appliance.
- Drainage surface is provided on which baskets can be placed for draining purposes.
- 24.5 liters water basin.
- Unit to feature skimming zone for starch removal: improved water quality over time.
- Easy-to-use control panel.
- · Safety thermostat to avoid operation without water.
- Continuous water filling regulated through a manual water tap.
- Large drain with manual ball-valve for fast emptying of well.
- ESD available as accessory (installed separately): energy saving device uses heat produced by water drained through the overflow to pre-heat tap-in water up to 60°C, for constant water boiling.
- EnergyControl: unique feature for fine power control to control boiling level and optimize energy consumption.
- Automatic lifting system (optional accessory): 200mm wide unit with two stainless steel basket supports, holding one GN 1/2 basket each, to be placed on either or both sides of machine to provide automatic lifting for four small portion baskets (to be ordered separately). Possibility to memorize nine cooking times through digital control.
- All major compartments located in front of unit for ease of maintenance.
- IPX4 water resistance certification.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

Construction

Flanged feet kit

- Exterior panels in Stainless Steel with Scotch Brite finish
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories Optional Accessories

•	Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210 □
•	Pair of side kicking strips for concrete installation	PNC 206265 □
•	Water column with swivel arm (water column extension not included)	PNC 206289 □
•	Water column extension for 700 line	PNC 206291 🗅

APPROVAL:



Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 1 Well 24.5 litres

•	Support frame for 4 baskets for 24,5lt pasta cookers	PNC 921606 🗅
•	Lid for 24,5lt pasta cookers	PNC 921607 🗆
•	2 half size baskets 170x220 for 24,5lt pasta cookers	PNC 921610 🗅
•	Full size basket for 24,5lt pasta cookers	PNC 921611 🗆
•	4 baskets 105x160 for 24,5lt pasta cookers (921606 must be ordered together)	PNC 921618 🗅
•	2 half size baskets 105x350 for pasta cookers for 24,5lt pasta cookers	PNC 921619 🗅












Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 1 Well 24.5 litres



15 3/4 ' 400 mm E 3/4 33

290 mm


55 mm

CWI = Cold Water inlet

D Drain =

D0 Overflow drain pipe EI = Electrical connection

55 mm











Electric

Front

Top

Supply voltage:

371098(E7PCED1KF0) 400 V/3N ph/50/60 Hz

Connected load: 6 kW Total Watts: 6 kW

Water:

Drain "D": 1" **Incoming Cold Water line size:** 1/2" Total hardness: 5-50 ppm

Electrolux recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

Key Information:

Usable well dimensions (width): 250 mm Usable well dimensions (height): 300 mm Usable well dimensions (depth): 400 mm 24.5 It MAX Well Capacity (MAX): Net weight: 50 kg Shipping weight: 55 kg Shipping height: 850 mm Shipping width: 400 mm Shipping depth: 730 mm Shipping volume: 0.24 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 1 Well 24.5 litres