

REIGN X2

Big rocks, sick drops, log crossings—Reign X rules it all with true full-suspension confidence. If you thrive on that jagged line between all-mountain and pure downhill, this is your machine. Ride *anywhere* there's a possible line.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,L
	COLORS	Black Anodized
	FRAME	ALUXX SL-Grade Aluminum, 6.7" Maestro Suspension
	FORK	Marzocchi 55R, 160mm w/ 20mm Thru Axle
COMPONENTS	SHOCK	Marzocchi Roco R, coil
	HANDLEBAR	Race Face Evolve AM low rise, 31.8
	STEM	Race Face Evolve AM
	SEATPOST	Race Face Ride XC 350x30.9mm
	SADDLE	WTB Pure V Race
	PEDALS	Alloy Platform
DRIVETRAIN	SHIFTERS	SRAM X5, trigger
	FRONT DERAILLEUR	Shimano SLX w/ Race Face Atlas Shiftguide
	REAR DERAILLEUR	SRAM X5
	BRAKES	Hayes Stroker Ryde, Custom for Giant 180F/160R
	BRAKE LEVERS	Hayes
	CASSETTE	SRAM PG 950 11/34, 9-speed
WHEELS	CHAIN	Shimano HG-73
	CRANKSET	Truvativ Ruktion 2.0, 24/36/RG
	BOTTOM BRACKET	Truvativ Howitzer, External
	RIMS	WTB Dual Duty FR
	HUBS	Formula disc w / 20mm front
	SPOKES	Stainless Steel, 14/15g
	TIRES	WTB Prowler MX/XT, 26x2.3
EXTRAS	Large has 180R rotor	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Reign X's 6.7 inches of always-active Maestro Suspension let you pound pedals uphill and blitz down. Buttressed, hydro-formed, perfectly welded ALUXX SL aluminum and the best suspension on the trail make this the ultimate all-mountain machine.



FEATURES

- Marzocchi 55R 160mm suspension fork, Marzocchi Roco R coil rear shock
- SRAM X.5 shifters/X.5 rear derailleur with Hayes Stroker Ryde custom hydraulic disc brakes
- Race Face Evolve AM handlebar and stem with Race Face Ride XC seatpost
- WTB Dual Duty FR rim/Formula disc 20mm hub wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches		degrees	degrees	inches	inches	inches	inches	inches
XS/15	346742	67.0	72.5	22.0	4.6	17.3	43.7	31.7
S/16	346743	67.0	72.5	22.4	4.6	17.3	44.1	31.5
M/18	346744	67.0	72.5	23.2	5.0	17.3	44.9	30.7
L/20	346745	67.0	72.0	24.1	5.9	17.3	45.7	31.0

*Seat angle is effective

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire