

TCR ADVANCED SL 1

All new. All race. All conquering. That's the TCR Advanced SL. Developed for the pro ranks, tested in the world's toughest races from the Spring Classics to the Tour de France and the choice of High Road's Team Columbia. Ready to ride. Ready to rip. Ready to win.



SPECIFICATIONS

FRAME	SIZES	XS,S,M/M/L,L,XL
	COLORS	Composite/Team Blue
	FRAME	Advanced SL-Grade Composite, Integrated Seatpost
	FORK	Advanced SL-Grade Composite, Full Composite OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Race Face Revolution, 31.8
	STEM	Race Face Revolution
	SEATPOST	Advanced SL-Grade Composite, Integrated Design
	SADDLE	Fi'zi:k Arione w/ Kium rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano Dura-Ace 7900
	FRONT DERAILLEUR	Shimano Dura-Ace 7900
	REAR DERAILLEUR	Shimano Dura-Ace 7900
	BRAKES	Shimano Dura-Ace 7900
	BRAKE LEVERS	Shimano Dura-Ace 7900
	CASSETTE	Shimano Dura-Ace 7900 12/25, 10-speed
	CHAIN	Shimano Dura-Ace 7900
WHEELS	CRANKSET	Shimano Dura-Ace 7900, 39/53
	BOTTOM BRACKET	Shimano Dura-Ace, Internal Press Fit
	RIMS	Mavic Ksyrium Premium
	HUBS	Mavic Ksyrium Premium
	SPOKES	Mavic Ksyrium Premium
	TIRES	Michelin Pro Race3, 700x23
	EXTRAS	2 ISP clamps provided : Regular 20mm & XL 40mm

FRAME TECHNOLOGY

Giant's lightest, stiffest, fastest road racer ever. Handcrafted, engineered precision creates the new benchmark for pedaling stiffness and efficiency. From its sleek integrated seatpost to the massive MegaDrive rectangular downtube and oversized toptube, this is pure Advanced SL-grade composite performance. Without compromise.



KEY UPGRADES (FROM TCR ADVANCED SL 2)

- Shimano Dura-Ace 7900 component group
- Integrated seatmast
- Mavic Ksyrium Premium wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	387042	71.0	74.5	52.0	12.0	40.5	97.7	28.5
S/46.5 cm	387043	72.0	73.5	53.5	13.5	40.5	97.4	29.2
M/50.0 cm	387044	73.0	73.0	55.5	15.0	40.5	98.0	30.1
M/L/53.5 cm	387045	73.0	72.0	57.0	17.0	40.5	98.6	31.0
L/55.5 cm	387046	73.0	72.0	58.5	18.5	40.5	100.1	31.7
XL/58.5 cm	387047	73.0	72.0	60.5	20.0	40.5	102.1	32.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire