

INSTRUCTIONS

-J00087 REV. 07-26-03

Kit Number 38620-96, 38662-00 and 38663-00

Installation

CLUTCH CABLE KIT

General

Kit 38620-96 is designed for installation on:

- 1996 through 1999 XLH Sportster® 883 Hugger,
- 1996 through 1999 XLH Sportster 1200, and
- 1996 through 1999 XL 1200C Sportster Custom.

Kit 38662-00 is designed for installation on:

- 2000 through 2003 XLH Sportster 883 Hugger, and
- 2000 through 2003 XLH Sportster 1200.

Kit 38663-00 is designed for installation on:

- 2000 through 2003 XLH Sportster 883,
- 2000 through 2003 XL 883C Sportster Custom,
- 2000 through 2003 XL 1200C,
- 2000 through 2003 Sportster 1200 Custom, and
- 2000 through 2003 XL 1200S Sportster Sport.

See the Service Parts illustration for kit contents.

AWARNING

A Service Manual is necessary for installation of this kit. The rider's safety depends upon the correct installation of this kit. If the procedure is not within your capabilities or you do not have the correct tools, have your Harley-Davidson dealer perform the installation. Improper installation of this kit could result in death or serious injury.

NOTE

A Service Manual for your model motorcycle is available from any Harley-Davidson dealer.

To prevent accidental vehicle start-up, which could cause death or serious injury, disconnect negative (-) battery cable before proceeding. (00048a)

AWARNING

1. Refer to the Service Manual and follow the instructions given to remove the seat and disconnect the negative battery cable. Retain all seat mounting hardware.

NOTE

Before removing clutch cable, make careful note of the existing cable routing. Pay special attention to existing cable strap locations before removing so new straps can be placed into the same locations.

- 2. Refer to CLUTCH CONTROL, REMOVAL in the Service Manual to remove the old clutch cable.
- 3. See CLUTCH CONTROL, INSTALLATION in the Service Manual to install the new clutch cable.
- 4. Adjust the clutch cable according to the procedures in the Service Manual.
- Refer to the Service Manual and follow the instructions given to re-attach the negative battery cable and install the seat.

