

IRON-A-WAY®

Built-In Ironing Centers



** All units can be provided with a left hinge upon request. Right hinge standard.
 **** Door Hardware not included.

A-42

The Model A-42 is skillfully designed with a 90 degree left/right, industry standard 42-inch, ventilated steel swivel board, giving flexibility in confined areas like corners in the laundry room or kitchen. Its easy 4-inch height adjustment automatically returns to its normal ironing board position every time the board is put away.

The solid-state silent timer, premium sized hot iron storage compartment, built-in work light, storage shelves, electrical cord wrap, and on/off indicator light are the outstanding standard accessories that complete this ultimate ironing center.

IRONING CENTER SPECIFICATIONS

Refer to chart for standard and optional features.

COMPONENT	Model A-42
Ironing Board	42" Ventilated Steel with 4" Vertical Adjustment
Hot Iron Storage Compartment	Standard
Storage Shelf	Standard
Full Length Piano Hinge	Standard
Ironing Board Cover and Pad	Standard
Electrical System	Motor Timer, Safety Door Switch, Appliance Outlet, Indicator Light
Hot Iron Rest	Optional
Electrical Cord Cover	Not Available
Electrical Cord Wrap	Standard
Garment Bar	Optional
Garment Hook	Standard
Adjustable Swivel Board	Standard
Spotlight (Less Bulb)	Standard
Steam/Dry Iron	Optional
Sleeveboard	Optional
Surface Mount Trim	Optional
Mirror and Brackets	Optional
Birch Veneer Door **	Standard
Oak Raised Panel Door **	Optional
Maple Raised Panel Door **	Optional
Pine Raised Panel Door **	Optional
White Raised Panel Door **	Optional
White Flat Door **	Optional
No Door ****	Optional
Interior Color	Cool Gray
Exterior Finish	Unfinished
Outside Dimensions	15 x 47 7/8" x 7 3/4"
Rough-In Opening Size	14 1/4" x 47 1/8" x 3 7/8"
Outside Door Dimensions	15" x 47 7/8"
Box Carton Dimensions	17 1/2" x 56 1/2" x 9 7/8"
Box Cubic Feet	5.7
Approximate Shipping Weight	75#
Units per Pallet	12

INSTALLATION

All IRON-A-WAY models may be surface mounted. All except the NE-242, may be recessed into any wall with standard 16 inch center studs. Special surface mount trim is available. Complete installation instructions are available from your dealer, in the product package, or downloaded from www.ironaway.com.

Cut Opening Above floor:	Regular Position	Adjusted Position
28"	35"	39"
27"	34"	38"
26"	33"	37"
25"	32"	36"