

The background of the page is a blurred, artistic photograph of a fire extinguisher. The image is heavily motion-blurred, creating a sense of dynamic movement. The colors are a mix of warm tones like red, orange, and yellow, and cooler tones like blue and grey. The fire extinguisher's cylindrical body and handle are visible but indistinct due to the blur. The overall composition is framed by a large, curved, semi-transparent shape that separates the background image from the white foreground at the bottom.

# Service Lite

Portable Fire Extinguishers





Kidde is a leading global supplier of fire and safety products, systems and services under a range of well-known and trusted brand names to industrial, commercial, aerospace, combustion control and retail customers. The Kidde Group comprises three divisions: Aerospace & Specialist Equipment, Residential & Commercial Fire Protection and Industrial Fire Protection and has operating companies in 29 countries together with worldwide distribution for its products and systems.

---

**Kidde Residential & Commercial is the world's leading manufacturer of home safety products, including fire extinguishers, carbon monoxide alarms, smoke alarms and fire escape ladders.**

---

**Kidde Residential and  
Commercial Division  
1394 South Third Street  
Mebane, NC 27302  
Tel. 919.563.2711  
[www.kiddeUS.com](http://www.kiddeUS.com)**



# Service Lite Fire Extinguisher

Part number 21006401

Multipurpose use

Single Use

## UL Rated 1-A, 10-B:C



## Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The XL2.5MP is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Available with metal retention bracket.  
Order pt # 21006402

## At a Glance

- Model XL2.5MP
- Multipurpose Dry Chemical
- Single Use
- UL listed
- UL rated 1-A,10-B:C
- U.S.C.G, DOT approved
- Monoammonium Phosphate
- 12 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



## Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2.6 lb. of fire extinguishing agent (Average)
- 12 year limited warranty
- UL approved plastic strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection
- Available with metal strap bracket Pt. # 21006402



## Product Specification

Net agent weight (Average)	2.6 lb.
Unit weight (Average)	3.9 lb.
Diameter	3.25 inches
Height	15.0 inches
Discharge time	8-12 seconds
Discharge range	10-15 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

## Packaging Options



MASTER PACK

21006401  
UPC: 0-47871-06401-4  
I2F: 100-47871-06401-1

21006402  
UPC: 0-47871-06402-1  
I2F: 100-47871-06402-8

# Service Lite Fire Extinguisher

Part number 21006204

Low & Moderate Hazard use

Single use

## UL Rated 3-A, 40-B:C



## Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The FX340SC is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder & nylon valve assembly.

## FOR LOW & MODERATE HAZARDS

A 3-A:40-B:C rated extinguisher is required for protecting both LOW & MODERATE hazard occupancies such as: living areas of the home, offices, churches, assembly halls, classrooms, hotel guest areas, home garage & workshop, light manufacturing, dining areas, auto showrooms, parking garages & storage areas.

## Features

- Pressure gauge allows for immediate pressure status check
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 5 lb. of fire extinguishing agent (Average)
- 12 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection

For use on the following types of fire:



UPC: 0-47871-06204-1  
12F: 100-47871-06204-8

## Product Specification

Net agent weight (Average)	5.0 lb.
Unit weight (Average)	7.75 lb.
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Wall hanger	UL Listed

## Packaging Options

Master pack 21006204



MASTER PACK