

**Rotary Cutters, Single Deck**

| <b>RCR15 Series</b>  |  |   |
|--|--|---|
|  | <b>RCR1542</b>   | <b>RCR1548</b>  |
| <b>Hitch</b>   | Category I   |   |
| <b>Working Width</b>                                       | 42"  | 45 1/2"   |
| <b>Overall Width</b>                                       | 47 1/2"  | 50"   |
| <b>Overall Length (Including Tailwheel)</b>                | 86"  | 90"   |
| <b>Machine Weight (with Front Guard)</b>                   | 432#   | 475#  |
| <b>Blade Tip Speed</b>                                     | 11,459 fpm   | 13,090 fpm  |
| <b>Deck Material Thickness</b>                             | 12 Gauge   |   |
| <b>Gearbox Rating</b>                                      | 50 HP  |   |
| <b>Horsepower Rating</b>                                   | 15-50  |   |
| <b>Cutting Height</b>                                      | 1 3/4" - 11 1/2"   |   |
| <b>Cutting Capacity</b>                                    | Grass, weeds & light brush   |   |
| <b>Safety Guards</b>                                       | Rubber (front) or Chain (front or rear)  |   |
| <b>Skids</b>   | 1/4" X 2" Weld on  |   |
| <b>Deck Height (Bottom of Deck to Bottom of Skid Shoe)</b> | 7 1/4"   |   |
| <b>Blades</b>  | 1/2" x 3" Heat Treated Alloy Steel<br>Free-Swinging Blades                                 |   |
| <b>Stump Jumper</b>  | Round Pan 10 ga. x 24"   | Round Pan<br>10 ga. x 24"                                 |
| <b>Driveline</b>   | ASAE Category 3  |   |
| <b>Driveline Safety Protection</b>                         | Standard 1/2"<br>Center Shearbolt protection<br>Optional - Center Bolt 2 plate Slip Clutch |   |
| <b>Gearbox (Speed up beveled gears)</b>                    | 540 rpm PTO Driven Gearbox<br>1:1.93<br>Cast Iron Housing                                  | 540 rpm PTO Driven Gearbox<br>1:1.47<br>Cast Iron Housing |
| <b>Gear Box Oil</b>  | Gear Lube 80-90W EP  |   |
| <b>Tailwheel</b>   | 4" x 8" x 15" Laminated Tire, cast iron hub<br>Optional - 4" x 16" Solid Rubber Tire       |   |

*Designs, specifications, features and information are subject to change without notice.*