

Specifications & Capacities

Rotary Cutters, Single Deck

RCR1860 and RCR1872 Series		
	RCR1860	RCR1872
Cutting Width	60"	72"
Overall Width	65"	77"
Overall Length	97"	110"
Blade Tip Speed	16,363 fpm	14,955 fpm
Machine Weight (with laminated tailwheel, slip clutch driveline, Front Rubber Guards and Rear Metal Band)	599 lbs.	737 lbs.
Driveline	ASAE Category 3 Shear Bolt or 2-plate Slip Clutch	
Recommended Tractor PTO HP	20-50 HP	
PTO Speed	540 rpm	
Gearbox	1:1.93 Speed-Up Beveled Gears Cast Iron Housing 50 HP	1:1.46 Speed-Up Beveled Gears Cast Iron Housing 50 HP
Gearbox Lubricant	EP 80-90W oil	
Cutting Height	1 1/2" - 13"	1 1/2" to 11 1/2"
Deck Construction	All Welded Deck	
Deck Material Thickness	11 Ga. (.120")	10 Ga. (.134")
Side Skirt Material Thickness	11 Ga.	10 Ga.
Deck Height (Bottom of Deck to Bottom of Skid Shoe)	7 1/2"	9"
Skid Construction	Full length welded on	
Tailwheel Mount Assembly	Welded A-arm and Caster Fork with 360 degree swivel	
Tailwheel	4" x 8" x 15" Laminated Tire with cast iron hub or 4" x 16" Molded Rubber Tire	
Hitch	Category I with Floating Clevis Top Link, Quick Hitch Adaptable	
Blade Holder	Blade Holder Bar with Stump Jumper Round Pan 10 ga. x 24"	
Blades	2 each, 1/2" x 3" Heat Treated Alloy Steel Free-Swinging High Lift - Low Friction	
Blade Bolts	Keyed with harden flat washers & lock nuts.	
Blade Cutting Capacity	1" Diameter	
Optional Front Guard	Rubber Belting or Chain Guard	
Rear Guard	Standard Metal Banding or Optional Rubber Belting or Optional Chain Guard	

Designs, specifications, features and information are subject to change without notice.