

## Rotary Cutters, Single Deck

RCR2596, RCR2510 & RCRM2510 Series		
	RCR2596 (540 RPM)	RCR2510 (540 RPM) RCRM2510 (1000 RPM)
<b>Hitch</b>	Lift-Type Category 1 & 2 Quick hitch adaptable Pull-Type - w/Dual Level Rods	Lift-Type Category 2 & 3 Quick-Hitch adaptable Pull-Type - w/Dual Level Rods
<b>Working Width</b>	94"	118"
<b>Overall Width</b>	100"	123.5"
<b>Overall Length</b>	Lift-Type: 105" Pull-Type: 135"	Lift-Type: 110" Pull-Type: 145"
<b>Cutter Weight (Without Chain or Rubber Shields)</b>	Lift-Type 1068 lbs.	Lift-Type 1400 lbs.
<b>Blade Tip Speed</b>	540 RPM 14,592 fpm	540 RPM 17,749 fpm 1000 RPM 18,035 fpm
<b>Deck Material Thickness</b>	10 gauge	
<b>Gearbox Oil Type</b>	80-90W EP	
<b>Gearbox Rating H.P.</b>	Center - 100 HP Outboard 60 HP	
<b>H.P. Rating (PTO)</b>	Lift-Type: 45 - 110 Pull-Type: 30 - 110	Lift-Type: 50 - 110 Pull-Type: 35 - 110
<b>Cutting Height</b>	2" - 12"	
<b>Cutting Capacity</b>	1"	
<b>Optional Safety Shields</b>	Front & Rear Chain/ Front & Rear Rubber	
<b>Skids</b>	Replaceable	
<b>Deck Height</b>	9 5/8"	
<b>Blades</b>	1/2" x 4" Heat Treated Free-Swinging Suction Blades	
<b>Stump Jumper</b>	Round Pan 3/16"	
<b>Driveline</b>	Cat 4, w/Equal Angle U-Joint	Cat 4 w/Equal Angle U-Joint or Constant Velocity U-Joint
<b>Driveline Safety Protection</b>	540 rpm - 4 plate slip clutch 1000 rpm - 2 plate slip clutch	
<b>Gearbox (Speed up beveled gears)</b>	540 rpm or 1000 rpm PTO Driven Gearbox Cast Iron Housing, Beveled Gears	
<b>Tailwheel</b>	Lift-Type: 2 ea. 4" x 8" x 15 1/4" Laminated Pull-Type: 2 ea. 6" x 9" x 21" Laminated or 24" Aircraft tires or 15" Automotive Rims	

Designs, specifications, features and information are subject to change without notice.