

60

## Rotary Cutters, Folding Deck

## RCR3515 & RCRM3515 Models

Features	Benefits
Surpassed rugged industry standards	All Land Pride Rotary Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Tractor HP rating	50- 160 HP
540 or 1000 RPM	Fits wide variety of tractors.
Quality Gearboxes	Gearboxes rated at 160 HP splitter box and 110 HP wing box to handle the jobs suited for this Rotary Cutter.
Gearbox warranty	5 years Parts and Labor.
4 Gearboxes vs. 3	Spreads overall weight out and evenly disburses horsepower to each spindle.
Mostly factory assembled	Arrives for quick and easy set-up. Minimal time is wasted setting or prepping the unit.
Low tongue weight	Ideal for smaller HP tractors by reducing the amount of weight on the drawbar.
Narrow tongue construction	Allows for a tighter turning radius.
Round back design	Allows for more efficient handling and dispersing of material.
2" to 14" Cutting Height	Cover a wide range of cutting conditions.
1/4 " Sidewall thickness	Increased thickness reduces damage from objects being thrown into the deck sides from the blades.
3/16" Round stump jumper	Standard thick stump jumper material keeps damage to a minimum.
High Blade tip speed	(540 rpm = 15,268 fpm center & 15,000 fpm wings) (1,000 rpm = 15,578 fpm center & 14,620 fpm wings) Allows clean cutting of material.
Replaceable skid shoes	Skid shoes protect the deck in uneven terrain. Can be easily replaced if damaged or worn out.
CV Input Driveline	Cat. 5 driveline is matched just right for capacity of tractor. Constant velocity (CV) U-joint allows for 80 degree turns without doing damage to the driveline.
Wing driveline Cat. 4 with slip-clutch	Cat. 4 is sized right for what cutter is intended to be used for. Slip-clutch will slip under load instead of twisting driveline. (Optional Cat. 5 driveline is available.)
Slip-clutch drivelines	Slip-clutch designed to slip to minimize twist damage to profile of driveline.
Transport wing locks	Transport wing locks securely hold the wings in the folded position in case of hydraulic failure.
4 or 6 Wheels	Choice of laminated tires for eliminating flats, used aircraft tires for cushioning during field and road use or bare rims for suppling your own automotive tires.
Spring cushioned center-axle	Protects unit from bumps and ground shock.
Paint options	Choice of red, green or tan to match popular tractor lines.

5/22/07 318-301F