

## **Primary Seeders**

## **PS20 Series**

PS2096 (Base Unit)	
Overall Width	9'-4"
Seeding Width (Broadcast)	8'-6"
Weight (Approximate Pounds)	1690 lbs.
Main box construction	Continuous welded construction
Lid construction	Heavy duty precision fit with seed splash guard
Seed Capacity	1 Bushel/Foot (total capacity: 8 bushels)
Seed Cup Drive	Chain Driven from right side of front roller
Seed Cup Agitation	Chain driven paddle type agitators above main box seed cups
Seed Settings	Wide range of calibration
Seed Drop	Wind guarded
Track Removers	Double torsion spring height adjustable and replaceable, Two each
Packer Wheels- Front	12" OD notched, cast iron, 42 each with 1 1/2" sealed greaseable bearings
Packer Wheels- Rear	9 1/2" OD notched, cast iron, 43 each with free floating mounting tube and 1" greaseable bearing mounted on pivoting spring loaded arms
Hitch	Category 2 & 3; Quick Hitch Adaptable, Optional Pull type hitch (see below)
Small Seed Box	Optional small seeds box with 2 bushel capacity may be added to the PS2096

Optional Pull Type Hitch	
Wheel Base	69" Center to Center
Length	95"
Hook-Up	Quick Attach Type Hook-Up
Tires - 2 ea.	9.5" L X 15" 12 Ply Tires
Cylinders	4" X 14" with Transport Lock valve
Tongue Jack	Standard
Weight (Approximate Pounds)	720 lbs.

5/27/05