

Box Scrapers

HR15 & MR15 Series (Retractable)

	HR			MR			
	1548	1554	1560	1548	1554	1560	1572
Working Width	48"	54"	60"	48"	54"	60"	72"
Weight (Pounds)	460	501	534	420	465	493	615
Number of Shanks	4	5	5	4	5	5	7
Shank Penetration	2-positions (5/8" & 2 5/8" below end plates)			2-positions (3/4" & 3 1/4" below end plates)			
Lift Mechanism	Hydraulic cylinder pivots shank tube to lift shanks up			Mechanical lever lift with spring assist			
Side Plates	1/4" thick x 19" high x 29" deep			1/4" thick x 18" high x 27 1/2" deep			3/8" thick x 18" high x 27 1/2" deep
Overall Length	35" (Front to back)			32 5/16" (Front to back)			
Height of Moldboard	19"						
Shank Material	3/4" x 2 1/2" heat treated spring steel						
Shank Tip Construction	Replaceable heat treated tips						
Grader Blades	1/2" x 6" high carbon, heat treated cutting edges; reversible and replaceable						
Maximum H.P. Rating	40 HP for 4 wheel tractors 50 HP for 2 wheel tractors						
3-Point Hitch Type	Category I & Quick Hitch						

HR25 Series (Retractable)

	HR2560	HR2566	HR2572
Working Width	60"	66"	72"
Weight (Pounds)	743	797	851
Number of Shanks	5	6	7
Shank Penetration	2-positions (3/4" & 3 1/4" below end plates)		
Lift Mechanism	Hydraulic cylinder pivots shank tube to lift shanks up		
Side Plates	3/8" thick x 21" high x 34" deep		
Overall Length	41" (Front to back)		
Height of Moldboard	21"		
Shank Material	3/4" x 2 1/2" heat treated spring steel		
Shank Tip Construction	Replaceable heat treated tips		
Grader Blades	1/2" x 6" high carbon, heat treated cutting edges; reversible and replaceable		
Maximum H.P. Rating	50 HP for 4-wheel drive tractors 60 HP for 2-wheel drive tractors		
Hitch Type	Category I & Quick Hitch		

Designs, specifications, features and information are subject to change without notice.