

## Features and Benefits

### *Rotary Tillers, Reverse Tine Rotation*

#### RTR20 & RTA20 Series

Features	Benefits
<b>20 Series</b>	Fills the gap between our 15 and 25 Series Tillers, both in size and price.
<b>Tractor HP</b>	23 - 40 HP.
<b>Gearbox Warranty</b>	5 Years Parts and Labor. Shows our confidence in the product.
<b>Working Widths</b>	64" & 72" Meets a wide range of customer needs.
<b>Formed Deck</b>	Handles material more efficiently, sheds water.
<b>Integral Hitch</b>	Upper hitch, gearbox and gearbox mount brought together to form a stronger overall hitch frame.
<b>Clevis Style Lower Hitch</b>	Allows easier hook-up of lower 3-point arms.
<b>Cat. 1 Hitch fits Land Pride Quick-Hitch</b>	Allows for quick and easy one-person hook-up. Offset is not comparable with Quick-Hitch.
<b>RTR Reverse rotation model or RTA forward rotation model</b>	Land Pride has the market on reverse rotation. This brings in a quality tiller at a more affordable price for landscapers. We offer forward rotation for contractors who want it.
<b>Reverse tilling action</b>	Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.
<b>Sideshift capability</b>	Sideshifts by loosening 6 U-bolts and sliding hitch points and gearbox over. Allows covering right tire track.
<b>Parking Stand</b>	Allows for easy hook-up and storage
<b>Six tines standard on RTR20 Four tines standard on RTA20 with six being optional</b>	Six tines cut through the ground smoother.
<b>C Tines</b>	C Tines take less horsepower to move through the ground.
<b>17" Rotor swing diameter</b>	For deep tilling action.
<b>Double lip seal on rotor bearing</b>	Double lip seal keeps the dirt out and the grease in.
<b>#80 Drive chain enclosed in oil bath</b>	Heavy-duty drive chain reduces stretching. Oil keeps constant lubrication and holds wear to a minimum.
<b>Easy to adjust chain tightener</b>	Cast iron chain tightener is a simple bolt adjustment to keep constant tension on the chain.
<b>Stamped chain cover</b>	Stamped forming adds additional strength.
<b>Adjustable skid shoes</b>	Control depth from various settings.
<b>Cat. 3 driveline with slip-clutch (option)</b>	Heavy driveline for rough conditions. Slip-clutch protects other drive train components.
<b>Material separator behind tilling action (RTR only)</b>	3/8" Rods sift the material letting bigger items fall first. Sifted soil falls last burying the bigger items. Attachment is one all welded piece for easy assembly.
<b>Formed rear deflector with springs</b>	Formed steel gives the rear deflector additional strength. Springs allow deflector to bounce as it hits obstructions.

*Designs, specifications, features and information are subject to change without notice.*