Strobe
WMSTR-WR-P01, WMSTR-WR-P02

- **ADM loop technology with System Sensor/200 protocol**

- **Long lifetime of strobe due to the use of LEDs**

- **Low power consumption**

- **Versions with or without integrated dual-isolator available**

- **Various base types available – IP24, IP44, IP65**

Description

The loop powered strobe is fitted into a round, red plastic case. It is powered and actuated as a module via the ADM loop with System Sensor/200 protocol.

The address of the strobe is selected with two decadic rotary switches located at the bottom of the device.

The strobe is designed for indoor or outdoor wall mounting. For this purpose a special base is needed. Various base types for protection classes IP24, IP44 or IP65 are available, depending on the application. An optional mounting plate can be supplied for surface mounted cabling.

The strobe is available in two different versions: With or without integrated dual-isolator module.

Specifications

Operating voltage	Supply through loop voltage
Flash frequency	1Hz
Ambient temperature	-25°C to +70°C
Dimensions ø × H	112 × 37 (mm) (incl. base LPBW)
Weight	80g
Colour	red

Building Safety. Building Security.

Loop strobe without isolator	
Current consumption from loop	max. 450µA (strobe off) max. 3.8mA (strobe active)
Order number	356140
Order name	Strobe/WM/200/Red WMSTR-WR-P01
Loop strobe with isolator	
Current consumption from loop	max. 450µA (strobe off) max. 4.0mA (strobe active)
Order number	356141
Order name	Strobe/WM/200ISM/Red WMSTR-WR-P02

Base and accessories

For wall mounting of the strobe, various base types with protection classes IP24, IP44 or IP65 are available.
For surface mounted cabling with base LPBW, an optional mounting plate can be supplied.

LPBW

SDBR

DBSPD

Specifications

Base IP24	
Order number	359040
Order name	Base Sounder & Strobe/IP24/White LPBW
Base IP44	
Order number	359041
Order name	Base Sounder & Strobe/IP44/Red SDBR
Base IP65 (not illustrated)	
Order number	359042
Order name	Base Sounder & Strobe/IP65/Red WDBR
Mounting plate for surface mounted cabling with base LPBW, 5 Pieces	
Order number	359049
Order name	Mounting Plate for Sounder/200/5 pcs. DBSPD/5

Building Safety. Building Security.