



# Savory<sup>®</sup> Synergy<sup>™</sup> Conveyor Toaster

The Synergy<sup>™</sup> Conveyor Toaster by Savory<sup>®</sup> utilizes the perfect combination of infrared and convection heat to produce perfectly toasted sandwiches, chicken nuggets, pretzels, tortillas and a wide variety of appetizers. With the ability to toast from 160-240 sandwiches per hour, the Synergy<sup>™</sup> is the perfect partner for expanding your menu, while increasing your speed of service and overall sales!

## Standard Features:

- Stainless steel construction
- Independent top and bottom heating elements
- Removable crumb tray
- Energy-saving sleep mode
- Cool skin front and rear panels stay cool to the touch during operation
- Innovative air curtain prevents heat loss
- Units available with 10" or 14" wide belts

## Optional Features:

- Analog or digital controls
- Digital control models available in red

**Controls:** Models available with digital or analog controls, both located on the front of the unit. Analog controls include power on/off switch, conveyor speed control, independent top and bottom heat intensity controls, and conveyor direction.

Digital controls include power on/off switch, conveyor speed control, independent top and bottom heat intensity controls, two programmable pre-sets, digital display, conveyor direction control, and sleep mode.

**Construction:** Exterior is fabricated from stainless steel. Conveyor belts are manufactured from flexible stainless steel and are available in either 10" or 14" widths. Units feature hinged entry and exit shelves with removable crumb trays.

**Electrical Requirements:** Heat is supplied by nine (9) or twelve (12) infrared heating elements on top and nine (9) or twelve (12) infrared heating elements on the bottom

of the unit. Each unit is rated at 3.8 kW or 6.6 kW. A separate circuit breaker is required for each toaster with the proper voltage, amperage, and hertz as indicated by model number.

**Ventilation:** Ventilation is not required but local codes prevail. These are the "authority having jurisdiction" as stated by the National Fire Protection Association, Inc. in NFPA 96-1994.

**Spacing:** The toaster must have 6" (152 mm) of clearance from combustible surfaces and 24" (610 mm) clearance on both sides from other cooking equipment.

**Savory<sup>®</sup> Guarantee:** Savory<sup>®</sup> equipment is guaranteed to be free from quality problems in material and workmanship for a period of one (1) year parts and labor from date of purchase, or eighteen (18) months from date of shipment from factory, whichever comes first.

**For more information, contact your Merco<sup>®</sup> Savory<sup>®</sup> Representative or visit our website at: [www.mercosavory.com](http://www.mercosavory.com).**