

Pyle Audio Inc. will give a one year limited on parts and labor on all Pyle products, unless otherwise stated. In warranty merchandise will be repaired or replaced at the discretion of Pyle Audio Inc. Service Department. Just follow the instructions on the warranty card enclosed with every item to obtain warranty service. Out of warranty merchandise will be repaired with nominal charges for parts and labor. This warranty will not be extended to any product subject to misuse, abuse, neglect, accident, improper installation, installed in a commercial vehicle or used in violation of instruction furnished by us or to product which has been repaired or altered outside of the factory. In no way shall Pyle Audio Corp. be held responsible for consequential or inconsequential damages. Some states do not allow this exclusion, so the above may not apply to you. You may also have other rights which vary from state to state.



## AMPLIFIED BASS ENCLOSURE PLTA8 PLTBA10 PLTBA12

PYLE

RED LABEL

#### WWW.PYLEAUDIO.COM

PYLE AUDIO • 1600 63RD STREET • BROOKLYN • NEW YORK • 11204 • 800-444-5671 • FAX: 718-236-2400

### SYSTEM FEATURES

8"/10"/12" Pyle Red Label Long Throw Woofer Custom Designed Carpeted Enclosures w/Bass Reflex Ports Optimized for Best Bass Response Compact and Rugged Design Built-In Amplified System Adjustable Crossover Frequency Control Input Level Control 3-Way Input Phase Switch (0°/90°/180°) Automatic Turn On Feature RCA/Low Level Inputs Speaker/High Level Inputs Custom Triple Bar Grill Design

#### SPECIFICATIONS

TR	PLTA8	PLTBA10	PLTBA12
Woofer Size	8"	10"	12"
Voice Coil	1" High Temp	1.5" High Temp	2" High Temp
Magnet	20 oz	30 oz	40 oz
Freq. Resp.	50Hz-200Hz	50Hz-200Hz	50Hz-200Hz
Dimensions	9.9" x19" x13.8	12.2" x18.9" x15.8	13.8" x18.9" x16.3
Impedance	Dual 2 Ohms	Dual 2 Ohms	Dual 2 Ohms
System Watts	300 Watts	500 Watts	600 Watts

#### CONNECTION DIAGRAM

# Simple Connection Plate and Interface Allows for an Easy, Quick and Straight Forward Installation

