



# PRESSURELESS COUNTER CONVECTION STEAMERS

A Real Production Workhorse with Superior Energy and Water Savings.

## VPX

### Standard Features:

- Stainless steel exterior
- 4" legs with adjustable foot
- Stainless steel cooking compartments with coved interior corners
- Manual controls with constant steam feature
- Heavy duty door and latch mechanism



VPX3

Energy Star® Certified VPX Series Boilerless Steamers  
Simple, Reliable, Durable:  
High-Volume Products,  
High-Quality Results

Model Number	Pan Capacity 12" x 20" x 2 1/2"	Input (kW)	Approx. Ship Wt.	
			lbs	kg
VPX3	3	9/6	140	64
VPX5	5	15/10	170	78

Freight Classification: 85

**NOTE: Shipped with 208/60/3 or 240/60/3 electrical service. Can be field converted to 208/60/1 and 240/60/1.**

## OPTIONS & ACCESSORIES FOR COUNTER CONVECTION STEAMERS

Option	Available On
480 V, 60 Hz, 3 phase	VPX3 and VPX5

Accessory	Accessory Code
Stand 24" wide x 28" high	STAND 28XSGL
Stand 24" wide x 34" high	STAND 34XSGL
Extra pair of universal pan slides for stand	S/PAN SLIDES
Set of four casters, locking for STAND-28/34XSGL—Limitation Contact Factory	CASTER-XSGL
Stack stand 24" wide for stacking two VPX steamers	STAND-PXSTCK
Perforated water cover	COVER-PERF
Oven steamer accessory kit (requires 8" legs LEGSSST CX299V in lieu of standard legs)	MARINE TOP
Steam pan holder	STEAMER PANHLD
Cord and plug set 208/240/3 PH 9.25kW	CORDPLG-3PAN3P
Cord and plug set 208/240/3 PH 15.75kW	CORDPLG-5PAN3P

# ELECTRIC COUNTER CONVECTION STEAMERS

## Standard Features:

- Stainless steel exterior
- Stainless steel cooking compartments with coved interior corners
- Heavy duty door and latch mechanism
- Split water line connection
- External delimiting port

## Includes Professional Features

- Super-heated steam
- Staged water fill
- Manual control with 60-minute timer, buzzer and constant steam feature
- Cook/Ready Light
- Lighted power switch
- Auto drain with timed SmartSteam™ and PowerFlush Systems™



C24EA5 DLX  
Shown with Professional Performance Package on a STAND 34XSGL with extra pair of universal pan slides, 12" x 20" pans and pull-out shelf.

Model Number	Pan Capacity 12" x 20" x 2 1/2"	Input (kW)	Approx. Ship Wt.	
			lbs	kg
C24EA3 DLX	3	9.25	140	64
C24EA5 DLX	5	15.75	175	80
C24EA3 BSC	3	8.5	140	64
C24EA5 BCS	5	15	175	80

Freight Classification: 85

**NOTE: Shipped with 208/60-50/3 electrical service. Field converted to 208/60-50/1 and 240/60-50/3 and 240/60-50/1.**

## OPTIONS & ACCESSORIES FOR ELECTRIC COUNTER STEAMERS

Option	Available On
480 V, 60 Hz, 3 phase	C24EA3 and C24EA5

Accessory	Accessory Code	Available On
Heat shield for C24EA3/5 Counter Steamers	CTOPHTE-SHIELD	C24EA3, C24EA5
4" legs w/ adjustable foot (set of 4)	CNTLEGS-4INCH	C24EA3, C24EA5
Stand 24" wide x 28" high	STAND 28XSGL	C24EA
Stand 24" wide x 34" high	STAND 34XSGL	C24EA
Extra pair of universal pan slides for stand	S/PAN SLIDES	STAND-28/34XSGL
Set of four casters, locking for STAND-28/34XSGL - Limitation Contact Factory	CASTER-XSGL	STAND-28/34XSGL
Pull out shelf for stand with C24EA3 or C24EA5 only	S/SHELF-XSGL	STAND-28/34XSGL
Stacking kit for two C24EA3 or C24EA5 counter steamers—counter mount	STCKKIT-24EA	C24EA3, C24EA5
Leg, 6-inch for stacking kit—floor mount	STCKKIT-FLG6	STCKKIT-24EA
Casters, 6-inch, 2 locking for stacking kit—floor mount	STCKKIT-CST6	STCKKIT-24EA
Single point electrical connect kit for stacked C24EA3 or C24EA5 (3-phase only)	C24EA-SGLPT	STCKKIT-24EA
ScaleBlocker™ water filter system	SPS600V-SYSTEM	C24EA3, C24EA5
ScaleBlocker™ water filter pm kit includes cartridge, ScaleRelease & pick up tube	SPS600-PMKIT	SPS600V-SYSTEM
Cord and plug set 208/240/3 PH 9.25 kW	CORDPLG-3PAN3P	C24EA3
Cord and plug set 208/240/1 PH 8.5 kW	CORDPLG-3PAN1P	C24EA3-BSC
Cord and plug set 208/240/3 PH 15.75 kW	CORDPLG-5PAN3P	C24EA5
Oven/steamer accessory kit (requires 8" legs LEGSSST CX299V) in lieu of standard legs)	MARINE TOP	C24EA
Steam pan holder	STEAMER PANHLD	C24EA

# 5 PAN GAS CONVECTION STEAMERS

## VSX

### Standard Features:

- Stainless steel exterior finish
- Stainless steel interior compartment with covered interior corners
- Heavy gauge stainless steel slammable door
- Convection steam, pressureless free venting
- Manual control with 60-minute timer
- Generator delimiting light
- Convenient delimiting port
- Automatic generator blow-down
- Split water line
- 4" legs

### Gas VSX Convection Steamers

Model Number	Pan Capacity 12" x 20" x 2 1/2"	Input (BTU/hr)	Approx. Shipping Wt.	
			lbs	kg
VSX5G	5	45,000	625	284

Freight Classification: 85

# ACCESSORIES FOR CONVECTION STEAMERS

Accessory	Accessory Code
Stand 24" wide x 28" high	STAND RL28G
ScaleBlock™ water filter system	SPS600V-SYSTEM
ScaleBlock™ water filter pm kit includes cartridge, scale release and pick-up tube	SPS600-PMKIT

# PRESSURELESS CONVECTION STEAMERS

Super-Heated Steam Capability.

## POWERSTEAM™ SERIES

### 6 and 10 Pan Convection Steamers

PowerSteam™ enables higher production in a smaller footprint than other types of cooking equipment and requires less labor. Featuring exclusive capabilities with both super-heated steam—235 °F as it enters the cooking compartment and staged filling which prevents “killing the boil” resulting in faster cooking times with continuous high-volume steam.

#### Standard Features:

- Stainless steel exterior, frame and flanged feet
- Stainless steel cooking compartments with coved interior corners
- Manual control with 60-minute timer, buzzer and constant steam feature
- Heavy duty door and door latch mechanism
- Split water line connection, single drain connection
- Super-heated steam
- Staged water fill
- External delimiting port

#### Gas Convection Steamers on Cabinet Base

Model Number	Pan Capacity 12" x 20" x 2 ½"	Input (BTU/hr)	Approx. Shipping Wt.	
			lbs	kg
C24GA6	6	125,000	625	284
C24GA10	10	125,000	675	306

Freight Classification: 85

#### Electric Convection Steamers on Cabinet Base

Model Number	Pan Capacity 12" x 20" x 2 ½"	Input (kW)	Approx. Shipping Wt.	
			lbs	kg
C24EA6	6	17.5	550	250
C24EA10	10	30	600	273

Freight Classification: 85

**NOTE: Shipped with 208/60/3 electrical service. Field converted to 208/60-50/1 or 240/60-50/3 and 240/60-50/1.**

## OPTIONS & ACCESSORIES

Option	Available On
480 V, 60 Hz, 3 phase (includes step down transformer)	C24EA6, C24EA10

Accessory	Accessory Code	Available On
ScaleBlocker™ water filter system	SPS620V-SYSTEM	All models
ScaleBlocker™ water filter PM kit includes cartridge, ScaleRelease & pick up tube	SPS620-PMKIT	SPS620V-SYSTEM
Manual sliding shelf (12" x 20")	ADDRACK-H	All models
Set of side racks 3 or 6 pan	PANGUID-3PAN	6 pan
Set of side racks 5 or 10 pan	PANGUID-5PAN	10 pan
Heat shield for control side	CSTMHTE-SHIELD	Convection steamers



C24GA6  
PowerSteam™ Model

# BOILER BASE 6, 10 & 16 PAN CONVECTION STEAMERS

Boiler Base Steamers Help You Cook Faster with Quality Results.

## Standard Features:

- Stainless steel exterior, frame and flanged feet
- Stainless steel cooking compartments with coved interior corners
- Separate manual controls for each compartment with constant steam feature
- Heavy duty door and door latch mechanism
- CSD-1 code compliant
- Gas standard output (200,000 BTU/hr = 3.6 BHP)
- Electronic ignition (gas only)
- 15 psi kettle connection
- Split water line connection, single drain connection



VHX42ET

### Gas Atmospheric Burner Boiler Base

Model Number	Pan Capacity 12" x 20" x 2 1/2"	Input (BTU)	Approx. Shipping Wt.	
			lbs	kg
VSX24G*,**	6	200,000	800	363
VSX24G5*,**	10	200,000	825	374
VSX42GT*,**	6 + 6 gal kettle	200,000	1000	454
VSX42G5*,**	10 + 6 gal kettle	200,000	1025	465

Freight Classification: 85

### Electric Boiler Base

Model Number	Pan Capacity 12" x 20" x 2 1/2"	Input (kW)	Approx. Shipping Wt.	
			lbs	kg
VHX24E*	6	24	700	318
VHX24E5*	10	24	725	329
VHX42ET*,**	6 + 6 gal kettle	24	900	408
VHX42E5*,**	10 + 6 gal kettle	24	925	420
VH3616E*	16	42/48	1,110	503
MHB24E***	—	24	500	227

NOTE: 24 kW shipped for 208/60/3 or 240/60/3 electrical service. Can be field converted to 208/60/1 or 240/60/1. 36/42/48 kW is three phase only.

Freight Classification: 85

### Direct Steam (Potable/Clean Steam)

Model Number	Pan Capacity 12" x 20" x 2 1/2"	Input (BHP)	Approx. Shipping Wt.	
			lbs	kg
VHX24D*	6	2.4	620	281
VHX24D5*	10	4	650	295
VH3616D*	16	6.4	800	362

Freight Classification: 85

## OPTIONS & ACCESSORIES

Option	Available On
24 kW, 480 V, 3 phase (includes step-down transformer)	VHX ELE BOILER BASE
36 kW, at 208/240 V, 3 phase	VHX ELE BOILER BASE
42 kW, 208 V, 3 phase (standard on VH3616E)	VHX ELE BOILER BASE
36 kW, 480 V, 3 phase (includes step-down transformer)	VHX ELE BOILER BASE
42 kW, 240 V, 3 phase	VHX ELE BOILER BASE
48 kW, 480 V, 3 phase (includes step-down transformer)	VHX ELE BOILER BASE

NOTE: Special correctional facility packages available. Ask your dealer or customer service representative for more information.

\*Convection steamer mounted on 28" high base cabinet with stainless steel front full height doors, stainless steel side and aluminized steel rear panel. Adjustable legs with flanged feet for floor anchoring.

\*\*42" Models only: 6-gallon Kettle mounted on the left with stainless steel liner and dual temperature faucet (optional kettle on the right).

\*\*\*MHB less compartment.



# GAS BOILER BASE STEAMERS

High Output and High Efficiency.

## Standard Features:

- Stainless steel exterior, frame and flanged feet
- Stainless steel cooking compartments with coved interior corners
- Separate manual controls for each compartment with constant steam feature
- Heavy duty door and door latch mechanism
- CSD-1 code compliant
- Gas high output (270,000 BTU/hr = 5.5 BHP)
- Electronic ignition
- 15 psi kettle connection
- Split water line connection, single drain connection



VHX24G

Model Number	Pan Capacity 12" x 20" x 2 1/2"	Input (BTU/hr)	Output BHP	Approx. Shipping Wt.	
				lbs	kg
VHX24G*	6	270,000	5.5	800	363
VHX24G5*	10	270,000		825	374
VHX42GT*,**	6 + 6 gal Kettle	270,000		1,000	454
VHX42G5*,**	10 + 6 gal Kettle	270,000		1,025	465
VH3616G*	16	270,000		1,110	503
MHB24G***	—	270,000		500	227

Freight Classification: 85

## OPTIONS & ACCESSORIES

Option	Available On
Mount and interconnect boiler base with kettle modules at factory, shipped on one skid	VHX & VSX Models

Accessory	Accessory Code	Available On
Steam supply piping to connect with direct steam kettle	KIT PIPING	VHX, MBH
24" SST cabinet back	SSTBACK 24STM	VSX24, 1T4024
ScaleBlocker™ water filter system	SPS620V-SYSTEM	All models
ScaleBlocker™ water filter PM kit includes cartridge, ScaleRelease and pick up tube	SPS620-PMKIT	SPS620-SYSTEM
Manual sliding shelf (12" x 20")	ADDRACK-H	All models
Set of side racks 3 or 6 pan	PANGUID-3PAN	6 pan
Set of side racks 5 or 10 pan	PANGUID-5PAN	10 pan
Heat shield for control side	CSTMHTE-SHIELD	Convection steamers

NOTE: Special correctional facility packages available. Ask your dealer or customer service representative for more information.

\*Convection steamer mounted on 28" high base cabinet with stainless steel front full height doors, stainless steel side and aluminized steel rear panel. Adjustable legs with flanged feet for floor anchoring.

\*\*42" Models only: 6-gallon Kettle mounted on the left with stainless steel liner and dual temperature faucet (optional kettle on the right).

\*\*\*MHB less compartment.





# REGENERATED STEAM CONVECTION STEAMERS

## Standard Features:

- Stainless steel exterior
- Stainless steel cooking compartments with covered interior corners
- Separate manual controls for each compartment with constant steam feature
- Heavy duty door and door latch mechanism
- Split water line connection, single-drain connection
- Flanged feet

Model Number	Pan Capacity 12" x 20" x 2 1/2"	Input (BTU/hr)	Approx. Shipping Wt.	
			lbs	kg
VSCX2-6	6	2.5 BHP	800	363
VSCX2-10	10	2.5 BHP	825	374

Freight Classification: 85

# REGENERATED STEAM LARGE CAPACITY PRESSURE STEAMERS

## Standard Features:

- Stainless steel exterior
- Flanged feet
- Stainless steel cooking compartments
- Split water line connection, single-drain connection

## PreVent™ Automatic Steamers

- PreVent™ automatic load compensated time, combination pressure and free venting cooking with automatic exhaust

Model Number	No. of Compts.	Input (BHP)	Approx. Shipping Wt.	
			lbs	kg
VSC2-3	2	2.5 BHP	1142	518
VSC3-3	3	2.5 BHP	1380	626

Freight Classification: 85

## Timed Automatic Steamers

- Automatic time compartment controls with 60-minute timer

Model Number	No. of Compts.	Input (BHP)	Approx. Shipping Wt.	
			lbs	kg
VSC2-2	2	2.5 BHP	1142	518
VSC3-2	3	2.5 BHP	1380	626

Freight Classification: 85

# ACCESSORIES FOR REGENERATED STEAM CONVECTION STEAMERS

Accessory	Accessory Code	Available On
Steam supply piping to connect with direct steam kettle	KIT-PIPING	VSCX/VSC
24" Stainless steel cabinet back	SSTBACK-24STM	VSCX
Manual sliding shelf (12" x 20")	ADDRACK-H	VSCX
Set of side rack 3 or 6 pan	PANGUID-3PAN	VSCX
Set of side rack 5 or 10 pan	PANGUID-5PAN	VSCX
Heat shield for control side	CSTMHTE-SHIELD	VSCX
36" Stainless steel cabinet back	SSTBACK-36STM	VSC
Manual slide shelf (18" x 26")	VLSHELF-MANSLD	VSC
Stainless steel wire Adapt-A-Pan	VLSHELF-ADPAN	VSC
Set of VSC2 and VSC3 side racks	PANGUID-VL	VSC
ScaleBlocker™ water filter system	SPS620V-SYSTEMS	VSCX/VSC
ScaleBlocker™ water filter pm KIT includes cartridge, ScaleRelease and pick up tube	SPS620-PMKIT	SPS620V SYSTEM

## LARGE CAPACITY PRESSURE STEAMERS

When it Comes to Volume Cooking, these Steamers are the Solution to All Your Efficiency Needs.

### Standard Features:

- Stainless steel exterior, frame and flanged feet
- Stainless steel cooking compartments
- CSD-1 code compliant
- VL Gas standard output (200,000 BTU/hr = 3.6 BHP)
- VHL Gas high output (270,000 BTU/hr = 5.5 BHP)
- Electronic ignition
- 6 psi pressure steam cooker
- Split water line connection, single-drain connection
- Direct Steam Models: 2" diameter welded stainless steel tubing leg stand with stainless steel adjustable flanged feet for floor anchoring

# PREVENT™ AUTOMATIC STEAMERS

- PreVent™: automatic load compensated timed, combination pressure and free venting cooking with automatic exhaust

Model Number	No. of Compts.	Input	Approx. Shipping Wt.			
			Power Option:	lbs	kg	
VHL2 (GP, EP, OR DP)	2	Gas: 270,000 BTU Electric: 24 kW Direct steam 2.5 bhp/2 compartments 3.3 bhp/3 compartments	Gas	VHL2	1,142	518
				VHL3	1,380	626
Electric	VHL2		1,142	518		
	VHL3		1,380	626		
Direct steam	3		VHL2	700	318	
			VHL3	900	408	

\*Direct Steam Potable/Clean Steam.

Freight Classification: 85

NOTE: Model number must have "power source" suffix when ordering. (Example: VHL2 Gas PreVent, specify VHL2GP).

NOTE: 24 kW shipped for 208/60/3 or 240/60/3 electrical service. Can be field converted to 208/60/1 or 240/60/1. 36/42/48 kW is three phase only.

# TIMED AUTOMATIC STEAMERS

- Automatic timed compartment controls with 60-minute timer

Model Number	No. of Compts.	Input	Approx. Shipping Wt.			
			Power Option:	lbs	kg	
VHL2 (GS, ES, OR DS)	2	Gas: 270,000 BTU Electric: 24 kW Direct Steam 2.5 bhp/2 compartments 3.3 bhp/3 compartments	Gas	VHL2	1,142	518
				VHL3	1,380	626
Electric	VHL2		1,142	518		
	VHL3		1,380	626		
Direct steam	3		VHL2	700	318	
			VHL3	900	408	

\*Direct Steam Potable/Clean Steam.

Freight Classification: 85

NOTE: Model number must have "power source" suffix when ordering. (Example: VHL2 Direct Steam, specify VHL2DS).

NOTE: 24 kW shipped for 208/60/3 or 240/60/3 electrical service. Can be field converted to 208/60/1 or 240/60/1. 36/42/48 kW is three phase only.

Model Number	Number of Compartments	Input (BTU/hr)	Approx. Shipping Wt.	
			lbs	kg
VL2GSS	2	200,000	1,142	518
VL3GSS	3	200,000	1,380	626

Freight Classification: 85

# OPTIONS & ACCESSORIES FOR LARGE CAPACITY PRESSURE STEAMERS

Options For Large Capacity Pressure Steamers	Available On
24 kW, 480 V, 3 Phase (includes step-down transformer)	VHL ELE BOILER BASE
36 kW, @ 208/240 V 3 Phase	VHL ELE BOILER BASE
36 kW, 480 V 3 Phase (includes step-down transformer)	VHL ELE BOILER BASE
42 kW, 208 V 3 Phase	VHL ELE BOILER BASE
48 kW, 240 V 3 Phase	VHL ELE BOILER BASE
48 kW, 480 V 3 Phase (includes step-down transformer)	VHL ELE BOILER BASE
State of PA code construction (water level observation point)	VL
Mount and interconnect boiler base with kettle modules at factory, shipped on one skid	VL/VHL
240,000 BTU/hr input	VL
Stainless steel cabinet base in place of open leg stand	VHL2D/VHL3D
Stainless steel main frame	VL

Accessories For Large Capacity Pressure Steamers	Accessory Code	Available On
Steam supply piping to connect with direct steam kettle	KIT-PIPING	VL/VHL
36" Stainless steel cabinet back	SSTBACK-36STM	VL/VHL
Manual sliding shelf (18" x 26")	VLSHELF-MANSLD	VL/VHL
Stainless steel wire Adapt-A-Pan	VLSHELF-ADPAN	VL/VHL
Set of VL and VHL side racks	PANGUID-VL	VL/VHL
PRV—pressure reducing valve 3 - 15 psi	PRESRED VALVE	DIRECT STEAM
Inverted bucket trap	BALLFT-TRAP	DIRECT STEAM
ScaleBlocker™ water filter system	SPS620V-SYSTEM	VL/VHL
ScaleBlocker™ water filter pm kit includes cartridge, ScaleRelease and pick up tube	SPS620V-PMKIT	SPS620V-SYSTEM