

Bush Hog® TOUGH

2515 Flex Wing Rotary Cutters

Recommended Tractor HP Minimum 50 To Maximum 120 PTO

BUSH HOG® TOUGH FEATURES

TOUGH EZ Clean Sloped 10 Gauge Deck

TOUGH 7 Gauge Strongbacks

TOUGH 1/4 Inch Sidebands

TOUGH Greaseable Axle Pivot Points With Bushings

TOUGH Heavy Duty Axle With Heavy Duty Turn Buckles

TOUGH Driveline Safety Retaining Rings

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Powder Coat Paint



MODEL	2515
Cutting Width	15 ft
Cutting Capacity	2 inch Diameter
Cutting Height	2 to 14 inches
Overall Width and Length (from Clevis to Wheel Hub at Transport Height)	15 ft 6 inches x 14 ft 1 inch
Transport Width (from wing skid to wing skid)	7 ft 2 inches
Tractor PTO	540 RPM/1000 RPM
Minimum Tractor HP	50 PTO
Deck Thickness	10 gauge
Side Bands	1/4 x 9 inches
Gearbox HP	Transfer - 160, Center - 110, Wings - 110
PTO Driveline	ASAE Cat. 5 (540 RPM), ASAE Cat. 4 (1000 RPM)
Wing Driveline	ASAE Cat. 4
Slip Clutches	(3) 2 Friction Plate Clutches
Blade Tip Speed	15,268 FPM
Blades	1/2 x 4 inch Uplift with 6 inch Overlap
Type Hitch	Self Leveling Pull Type with Swivel Clevis
Wing Flex (Operating)	87° Up to 22° Down
Tires	Choice of Laminated Tire, Used Aircraft Tire, Foam-filled Used Aircraft Tire, or Pneumatic 15 inch Wheel
Axles	Greaseable pivot points with bushings
Wheel Shock Protection	Independent springs on the deck
Deflectors	Front and Rear Belting or Chains, See Model
Options	Chain Shielding, Valve & Stand Kit
Warranty	1 year limited warranty with a 5 year gearbox limited warranty

FEATURES • Quick detach gearbox shields

BUSH HOG EXCLUSIVE: Driveline safety retaining rings