

# Bush Hog® TOUGH

## 2710L Single Wing Flex Series Rotary Cutters

Recommended Tractor HP Minimum 60 PTO

### BUSH HOG® TOUGH FEATURES

**TOUGH EZ Clean Deck 11 Gauge Top & 10 Gauge Bottom**

**TOUGH 7 Gauge Strongbacks**

**TOUGH 1/4 Inch Sidebands**

**TOUGH Independent Spring Cushion At Each Axle Arm**

**TOUGH Heavy Duty Axle Turn Buckles**

**TOUGH Greaseable Axle Pivot Points**

**TOUGH Heavy Duty Wheel Hubs And Axle Spindles**

**TOUGH Driveline Safety Retaining Rings**

**TOUGH 6 Year Gearbox Limited Warranty**

**TOUGH Powder Coat Paint**



MODEL	2710L
Cutting Width	10 ft 6 inches
Cutting Capacity	3 1/2 inch diameter
Cutting Height	2 to 14 inches
Overall Width x Length (from clevis to wheel hub at transport height)	11 ft 8 inches x 14 ft 6 inches
Transport Width (from weight box to wing skid)	8 ft
Tractor PTO	540 RPM/1000 RPM
Minimum Tractor HP	60 PTO
Deck Thickness	11 gauge top/10 bottom
Side Bands	1/4 x 12 1/2 inches
Gearbox HP	235/Transfer, 205/Center & Wing
PTO Driveline	Input: Constant Velocity or Cardan/Jackshaft - Cat. 5 (540 RPM) Cat. 4 or 5 (1000 RPM)
Wing Driveline	ASAE Cat. 4
Slip Clutches	(2) 2 Friction Plates
Blade Tip Speed	16,000 FPM/540 RPM; 15,912 FPM/1000 RPM
Blades	1/2 x 4 inches – Uplift with 6 inch Overlap
Type Hitch	Self Leveling with Perma Level Hitch®, or 2 inch Ball Hitch or Swivel Clevis Hitch
Wing Flex	87° Up to 22° Down
Tires	Laminated, Pneumatic or Aircraft
Axles	Greaseable with bushings
Wheel Shock Protection	Independent Springs/Each Axle
Deflectors	Standard Front Belting and Rear Band, Optional Chains Front and Rear
Options	Chain Shielding, Tandem Walking Axle, Deck Rings
Grass Baffles	Standard
Warranty	1 year limited warranty with a 6 year gearbox limited warranty • Perma Level Hitch • Cylinder style anti wrap device around lower gearbox housing • High blade tip speeds • Deep sidebands • Heavy duty wheel hubs • Quick detach gearbox shields

### FEATURES

**BUSH HOG EXCLUSIVE:**

Driveline safety retaining rings

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE