Bush Hog® TOUGH 320 "Original Plus" Series Heavy-Duty Rotary Cutters



Bush Hog's "Original" Heavy-Duty Cutters Are Better Than Ever

Bush Hog's 300 "Original" Series Rotary Cutters helped build the Bush Hog reputation for performance you can count on. Now the new Bush Hog 320 "Original Plus" Series Rotary Cutters offer even more performance the first day on the job and for years to come.



BUSH HOG®...Choose The "Original Plus"

Bush Hog 300 "Original" Series Heavy-Duty Cutters helped make the Bush Hog name famous. Often copied, never equaled, they set the standard for heavy-duty cutters. The new and improved Bush Hog 320 "Original Plus" Series Heavy-Duty Cutters are called the "Original Plus" because they deliver all the performance and reliability of the "Original" Series plus more. Be sure you get authentic Bush Hog.

Great Performances



This Bush Hog Series 300 Heavy-Duty cutter is one of thousands of "Original" Bush Hogs that built the Bush Hog reputation for performance you can count on in tough conditions. This same model has maintained the rugged pasture at an 850-acre Texas cattle operation more than 22 years.



Bush Hog® TOUGH Features Mean

The New "Original Plus" Is Even Better Than The "Original"

10 Bush Hog TOUGH Features

- **1. TOUGH Sloped Deck.** Improved sloped deck design sheds water and debris to increase deck life.
- **2. TOUGH Deck Reinforcements.** Decks are reinforced with internal 7-gauge steel strongbacks that run the full length of the deck tying together the entire structure with the gearbox stand.
- **3. TOUGH Bush Hog Materials.** 325, 326 and 327 decks are 7-gauge thick steel. Strongbacks are 7-gauge steel.
- **4. TOUGH Bush Hog Gearboxes.** 325, 326 and 327 gearboxes are the same rugged gearboxes used on thousands of Bush Hog flex wing cutters. Rated at 190 HP, they have the highest rating in their class. They are built to exacting Bush Hog specifications and embossed with the Bush Hog brand. All models come with the TOUGH Bush Hog 5-year limited gearbox warranty.
- **5. TOUGH Sidebands.** Sidebands are strong and deep. Formed of 1/4-inch thick steel, they are 12 1/2-inches deep.
- **6. TOUGH Blade Pans.** Blade pans are 7-gauge steel formed in dished shape for extra strength.
- **7. TOUGH Bush Hog Blades.** Built of heat treated alloy steel, blades are genuine Bush Hog and have been ref ned based on years of Bush Hog experience in rugged, real world conditions.

- **8. TOUGH Tail Wheel Assembly.** Heavy-duty tail wheel assemblies are standard on all models. 327 comes equipped with a heavy-duty axle and dual wheels for both lift and pull models. Both lift and pull models come with laminated tires that are built for rugged conditions.
- **9. TOUGH Heavy-Duty Gearbox Stand.** An integral part of the cutter's structure, the gearbox stand runs between the strongbacks.
- **10. TOUGH Category 5 Driveline.** Rugged ASAE Cat 5 drivelines are standard on every 320 Series "Original Plus" cutter.

The "Plus" In Bush Hog 320 "Original Plus" Series Rotary Cutters			
New sloped deck design	+		
New internal strong backs	+		
New deeper sidebands	+		
New standard heavy-duty tail wheel	+		
New standard heavy-duty Cat. 5 driveline	+		
New f ip-up shield for easy clutch service	+		





The Bush Hog® TOUGH 320 "Original Plus" Series

PERFORMANCE FEATURES

7 5/16-inch blade to structure clearance
Blade tip speeds to 13,996 fpm
Cutting widths of 5, 6 and 7 ft
Cutting heights of two to 12 inches
3 1/2-inch cutting capacity
Standard front and rear deflectors



TOUGH Sidebands

Side bands are strong and deep. Formed of 1/4-inch thick steel, they are 12 1/2-inches deep.

Bush Hog TOUGH 320 "Original Plus" Series Heavy-Duty Rotary Cutters				
MODELS	325	326	327	
Cutting Width	5 ft	6 ft	7 ft	
Cutting Capacity	3 ^{1/2} inch diameter	3 ^{1/2} inch diameter	3 ^{1/2} inch diameter	
Cutting Height	2 - 12 inches	2 - 12 inches	2 - 12 inches	
Dimensions (width x length)	66 x 1071/2 inches	78 x 1181/2 inches	90 x 131 inches (Lift), 90 x 182 inches (Pull)	
Type Hitch	HD 3 Point Category Cat. I & II standard and Quick Hitch	HD 3 Point Category Cat. I & II standard and Quick Hitch	HD 3 Point Category Cat. II & III standard Pull Model also available	
Deck Thickness	7 gauge	7 gauge	7 gauge	
Sidebands	1/4 x 121/2 inches	1/4 x 121/2 inches	1/4 x 121/2 inches	
Driveshaft	ASAE Cat 5	ASAE Cat 5	ASAE Cat 5	
Gearbox	Heavy duty (190 HP)	Heavy duty (190 HP)	Heavy duty (190 HP)	
Tractor PTO Speed	540 RPM	540 RPM	540 RPM	
Driveline Protection	Slip Clutch Standard	Slip Clutch Standard	Slip Clutch Standard	
Blade Holder(s)	Round	Round	Round	
Blades	1/2 x 4 inch, heat treated	1/2 x 4 inch, heat treated	1/2 x 4 inch, heat treated	
Blade Tip Speed	13,572 FPM	13,996 FPM	11,875 FPM	
Tires	Laminated	Laminated	Laminated, dual - Lift Large Laminated, dual - Pull	
Minimum Tractor HP	50 PTO	60 PTO	70 PTO	
Front and Rear Deflectors	Front and rear deflectors standard, chains optional, all 3 models			
Approximate Weight	1185 lbs	1400 lbs	1950 lbs Lift, 2150 lbs Pull	
Warranty	1 year limited warranty with a 5 year gearbox limited warranty			
Options	Front & Rear chains	Front & Rear Chains	Front & Rear chains, Manual or hyd. adj. for pull & lift models	

• Floating A Frame

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Dealer Info:

FEATURES



www.bushhog.com