

Bush Hog® TOUGH 3210 Series Rotary Cutters

BUSH HOG® TOUGH FEATURES
TOUGH 10 Gauge Deck Construction
TOUGH 7 Gauge Strongbacks
TOUGH 1/4 Inch Sidebands
TOUGH Rubber Cushioned Axle Arms
TOUGH 5 Year Gearbox Limited Warranty
TOUGH Powder Coat Paint



Model 3210

MODELS	3210	3210 Offset
Cutting Width	10 ¹ / ₂ ft	10 ¹ / ₂ ft
Cutting Capacity	2 1/2 inch diameter	2 1/2 inch diameter
Offset Beyond Tractor Center Line (Offset Models Only)	N/A	7 ft 10 inches
Dimensions (width x length)	11 ft 1 inch x 9 ft 10 inches (Lift)	11 ft 1 inch x 13 ft 5 inches (Pull)
Transport Width	10 ft 11 inches	10 ft 11 inches
Type Hitch	3 Point Category II & III Standard and Quick Hitch, Cat. II & III Semi-Mount and Center Pull (self leveling)	3 Point Category II & III Semi-Mount and Pull Type (self leveling)
Cutting Height	2 to 13 inches	2 to 13 inches
Deck Thickness	10 gauge	10 gauge
Side Bands	1/4 x 10 inches	1/4 x 10 inches
Minimum Tractor HP	60 PTO (Lift), 50 PTO (Pull)	55 PTO (Semi-Mount), 50 PTO (Pull)
Driveline	ASAE Cat. 5 (540 RPM - Lift, Pull and Semi-Mount), ASAE Cat. 4 (1000 RPM Pull)	ASAE Cat. 5 (540 RPM - Pull and Semi-Mount)
Cross Shaft	ASAE Cat. 5 Rubber Element	ASAE Cat. 5 Rubber Element
Gearbox HP	(3) 205 Center, 190 Outboard	(2) 205 Main, 190 Outboard
Tractor PTO Speed	540/1000 RPM	540 RPM
Driveline Protection	4 Plate PTO Slip Clutch	4 Plate PTO Slip Clutch
Height Adjustment	Manual or hydraulic	Manual or hydraulic
Blade Holder(s)	Round	Round
Blades	1/2 x 4 inches - Uplift	1/2 x 4 inches - Uplift
Blade Tip Speed	16,881 FPM/540 RPM; 17,400/1000 RPM	16,881 FPM/540 RPM; 17,400/1000 RPM
Tires	Laminated, Pneumatic, Aircraft	Laminated, Pneumatic, Aircraft
Axles	Rubber Cushioned, Choice of Single or Dual Axles for Pull Models	
Deflectors	Front Belting, Rear Band, Optional Chains	Front Belting, Rear Band, Optional Chains
Safety Tow Chain	Standard for Pull Models	Standard for Pull Models
Approximate Weight (Pull with Single Axle)	2741 lbs	2624 lbs
Options	Chain Shielding, Third Tailwheel for Lift or Semi-Mount Models	
Warranty	1 year limited warranty with a 5 year gearbox limited warranty	

FEATURES

- High blade tip speeds
- Deep sidebands