

Bush Hog® TOUGH 280 Series Rotary Cutters

BUSH HOG® TOUGH FEATURES

TOUGH 10 Gauge Fabricated Decks

TOUGH 7 Gauge Strongbacks

TOUGH Full Length Replaceable Skids

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Powder Coat Paint



Model 287



Model 285



Model 286

MODELS	285	286	287
Cutting Width	5 ft	6 ft	7 ft
Cutting Capacity	21/2 inch Diameter	21/2 inch Diameter	21/2 inch Diameter
Cutting Height	11/2 to 101/2 inches	11/2 to 101/2 inches	11/2 to 101/2 inches
Dimensions (width x length)	65 x 102 inches	77 x 114 inches	89 x 126 inches
Type Hitch	3 Pt. Category I, Cat. II pins optional	3 Pt. Category I, Cat. II pins optional	3 Pt. Category I & II or Cat I & II QH
Deck Thickness	10 gauge	10 gauge	10 gauge
Sidebands	1/4 x 8 inches	1/4 x 8 inches	1/4 x 8 inches
Driveshaft	ASAE Category 4	ASAE Category 4	ASAE Category 4
Gearbox	110 HP	110 HP	110 HP
Tractor PTO Speed	540 RPM	540 RPM	540 RPM
Driveline Protection	Slip Clutch Standard	Slip Clutch Standard	Slip Clutch Standard
Blade Holder(s)	Round	Round	Round
Blades	1/2 x 4 inch uplift	1/2 x 4 inch uplift	1/2 x 4 inch uplift
Blade Tip Speed	15,551 FPM	14,877 FPM	14,514 FPM
Tires	Laminated	Laminated	Laminated, dual or single
Minimum Tractor HP	30 PTO	40 PTO	50 PTO
Front and Rear Deflectors	Standard Equipment - Front Belting and Rear Bands, optional chain shielding, all 3 models		
Approximate Weight	785 lbs	942 lbs	1127 lbs
Warranty	1 year limited warranty with a 5 year gearbox limited warranty		
Options	Chain Shielding Category II hitch pins	Chain Shielding Category II hitch pins	Chain Shielding

FEATURES

Available in major tractor colors

Note: You have a choice of single or dual tailwheels on Model 287 for semi-mount and quick hitch, as well as a choice of a ratchet assembly or hydraulic cylinder.