

## Outdoor unit specifications

HP		4		5		6		
Model name (SPW-)		CR365GX56	CR365GXH56	CR485GX56	CR485GXH56	CR605GX56	CR605GXH56	
Power supply		220/230/240V-1 phase/50, 60Hz						
Capacity	Cooling	(kW)	11.2	11.2	14.0	14.0	15.5	15.5
		(BTU/h)	38,200	38,200	47,800	47,800	52,900	52,900
	Heating	(kW)	—	12.5	—	16.0	—	17.6
		(BTU/h)	—	42,700	—	54,600	—	60,000
COP	Cooling (W/W)	4.06	4.06	3.66	3.66	3.39	3.39	
	Heating (W/W)	—	4.34	—	4.10	—	3.84	
Dimension (HxWxD) (mm)		1,230x940x 340						
Net weight (kg)		130						
Electrical rating	Cooling	Running amperes (A)	14.8/14.1/13.5	14.8/14.1/13.5	20.5/19.6/18.8	20.5/19.6/18.8	24.4/23.4/22.4	24.4/23.4/22.4
		Power input (kW)	2.76	2.76	3.83	3.83	4.57	4.57
	Heating	Running amperes (A)	—	15.4/14.7/14.1	—	20.8/19.9/19.1	—	24.5/23.4/22.5
		Power input (kW)	—	2.88	—	3.90	—	4.58
Color (munsell color chart)		Silky shade (1Y8.5/0.5)						
Air circulation (m <sup>3</sup> /min)		95		95		95		
Refrigerant amount at shipment (kg)		3.5		3.5		3.5		
Piping connections	Gas pipe (Flare) (mm)	ø15.88				ø19.05 x 1		
	Liquid pipe (Flare) (mm)	ø9.52						
Ambient temperature operating range		Cooling: -10°C DB ~ + 43°C DB, heating: -20°C WB ~ +15°C WB						
Maximum number of connectable indoor units		6		8		9		
Operating sound	Normal mode dB(A)	51	52	52	53	53	54	
	Silent mode dB(A)	48	49	49	50	50	51	

\* The values for performance and electric characteristics apply under the following test conditions.

At the time of cooling: Indoor suction air temperature 27°C DB, 19°C WB, outdoor suction air temperature 35°C DB

At the time of heating: Indoor suction air temperature 20°C DB, outdoor suction air temperature 7°C DB, 6°C WB

\* The operating sound has been measured in an anechoic chamber, and it is the value one meter in front of the outdoor unit at a height of 1.5 m. With actual installation, the indication value normally differs widely according to the surrounding noise and reverberations.

\*1; Tube discharge assy supplied with outdoor unit