

TX-NR808 7.2-Channel Network AV Receiver

BLACK SILVER



Microphone for Audyssey



The less-used controls are neatly tucked away behind the drop-down panel.



The Heart and Soul of Networked Home Entertainment

Meet Onkyo's mid-range powerhouse. The TX-NR808 earns its prestigious THX® Select2 Plus™ certification by blending the latest connectivity and processing technology with Onkyo's renowned amplification prowess. As a network-capable receiver, the TX-NR808 is your gateway to streaming audio from your PC or internet radio. Other connection highlights include seven HDMI® 1.4a inputs with 3D and Audio Return Channel capability; 7.1-multichannel analog inputs for legacy components; a Universal port for Onkyo peripherals; a USB port for iPod models and flash memory devices; and an analog RGB video input for your PC. Employing two advanced 32-bit DSP chips and low-jitter 24-bit Burr-Brown DACs, the TX-NR808 effortlessly handles your audio-processing needs. Whether it's lossless Dolby and DTS formats on Blu-ray Disc, or new-dimension surround formats from Audyssey and Dolby, your audio signals retain every lifelike nuance. All things considered, the TX-NR808 is a serious challenger for the middleweight crown.

HDMI® 1.4a Support for 3D Video and Audio Return Channel

The seven HDMI 1.4a inputs on the TX-NR808 let you simultaneously connect high-def sources such as a Blu-ray player, a gaming console, and a cable/satellite tuner. A single output then sends a pristine signal to your connected high-resolution display. As the latest version of this connector, HDMI 1.4a adds the exciting possibilities of 3D video and an Audio Return Channel. 3D video is the next big thing in home entertainment, with movie, game, and broadcast content on the increase and 3D-compatible TVs coming to market. The TX-NR808 also offers the convenience of an Audio Return Channel via HDMI. Audio content received directly by your HDTV's tuner can be sent "upstream" to your A/V receiver, without the need for a separate S/PDIF audio cable.

PC Audio and Internet Radio via Network Function with DLNA 1.5 and Windows® 7 Compatibility

As one of Onkyo's new breed of receivers that can link directly to the internet or to your home PC via a local network, the TX-NR808 takes streaming audio and internet radio to a whole new level. MP3, WMA, WMA Lossless, FLAC, WAV, Ogg Vorbis, AAC, and LPCM audio files—whether on your PC or from the internet—can now be played back through your main system with unprecedented power and fidelity. The TX-NR808 brings to life a huge array of internet radio channels from Last.fm, Napster, and vTuner®. As well as being compatible with earlier platforms, the receiver is compatible with Microsoft's new Windows 7 platform, which includes the DLNA 1.5-specified "Play To" media-

streaming feature. Another benefit of having the TX-NR808 connected to the internet is that you can then easily update its firmware.

*Availability of services depends on region.

Audyssey DSX™ and Dolby® Pro Logic® IIz Add New Dimensions to Surround Sound

The TX-NR808 handles two new surround-sound technologies from Audyssey and Dolby that offer exciting new ways to set up the speakers in your home cinema system. Audyssey DSX lets you incorporate "front wide" speakers, in place of the usual surround back speakers, to expand the width of the soundstage. Set up at a recommended 60° off center; these channels help to produce a more realistic soundstage and a more immersive listening experience. Alternatively, Audyssey DSX can reconfigure the TX-NR808's surround back channels to deliver "front height" channels. These channels carry ambient, non-directional audio that adds a new vertical dimension to your movies and games. Dolby Pro Logic IIz provides a similar front-height speaker option that likewise works to create a more enveloping home cinema experience.

THX® Select2 Plus™ Certified

THX Select2 Plus certification is specified for rooms where the screen-to-seat viewing distance is 3 to 4 meters and the room volume is around 56 cubic meters. To achieve THX Select2 Plus certification, the TX-NR808 had to meet the world's most demanding standards for home cinema audio quality and performance, and play at reference volume levels with minimal distortion.



TX-NR808 7.2-Channel Network AV Receiver

HDMI Video Upscaling to 1080p with Faroudja DCDi Cinema™

When it comes to video processing, Faroudja DCDi Cinema offers several advantages. This processor can accept any video signal, regardless of the source resolution, and upscale it to 1080p to match the native resolution of your high-definition display. What's more, DCDi Cinema effectively removes video artifacts such as jagged edges during the video signal deinterlacing process. You get to enjoy smooth progressive scan video images, even for fast-moving sports and action scenes.

PLL (Phase Locked Loop) Jitter-Cleaning Circuit Technology

Jitter is an unwanted side-effect of the digital-to-analog conversion process. Caused by fluctuations in the time domain of a digital signal, jitter has a detrimental impact on perceived audio quality. PLL jitter-cleaning circuit technology reduces jitter by comparing the input and output phases of the digital signal and creating an accurate clock waveform. This enhances the precision of digital signal processing and noticeably improves audio quality. Jitter-cleaning technology works both for digital signals input via HDMI and for digital signals converted from analog signals inside the receiver itself.

Playback of Different Audio Sources in Up to Three Rooms

With Powered Zone 2, you can enjoy surround-sound entertainment in the main room, while playing back a different stereo source in a second zone equipped with a pair of speakers. Alternatively, you can use the Zone 2 and Zone 3 pre-outs to send separate, unamplified audio signals to amplifiers (and speakers) in a second and third room. Naturally, you also have the option of distributing the same audio source to two or three zones simultaneously.

Bi-Directional Preprogrammed RI Remote Control with On-Screen Setup and Macro Presets for Four Activities

The TX-NR808's remote controller offers the convenience of controlling a wide range of other devices connected to the receiver. You can select your connected devices from an on-screen list and pre-program your desired settings for each device. The receiver itself can then send these settings automatically to the remote controller. Furthermore, the TX-NR808 lets you set up macro presets for up to four activity modes, which you can control via mode-key LEDs on the remote controller. A single button-press of "My Movie", for example, can simultaneously turn on the receiver, display, and Blu-ray player to your pre-programmed settings and start playing a disc automatically.

- Firmware Updates via Ethernet and USB
- Powered Zone 2 and Zone 2/3 Pre-Outs for Distributed Audio Playback in Multiple Rooms
- *Availability of services depends on region.

AMPLIFIER FEATURES

- 180 W/Ch at 6 Ω, 1 kHz, 1 Channel Driven, IEC
- WRAT (Wide Range Amplifier Technology)
- Three-Stage Inverted Darlington Circuitry
- H.C.P.S. (High Current Power Supply) Massive High Power Transformer
- Linear Optimum Gain Volume Circuitry

PROCESSING FEATURES

- Burr-Brown 192 kHz/24-Bit DACs (PCM1690) for All Channels
- Two 32-Bit Processing DSP Chips (DA830 and CS49834)
- Dolby® TrueHD, DTS-HD Master Audio™, Dolby® Digital Plus, DTS-HD High-Resolution Audio™ Decoding
- HDMI Video Upscaling to 1080p with Faroudja DCDi Cinema™
- 4 DSP Modes for Gaming: Rock, Sports, Action, and RPG
- Music Optimizer™ for Compressed Digital Music Files
- Direct Mode and Pure Audio Mode
- A-Form Listening Mode Memory

CONNECTION FEATURES

- Universal Port for Single-Cable Connection of Optional Onkyo Dock for iPhone/iPod or DAB+ Radio Tuner
- Component Video Switching (2 Inputs and 1 Output)
- 4 S-Video Inputs and 2 Outputs
- Analog RGB Video Input (D-sub, 15 pin) and Audio Input for PC
- 6 Digital Inputs (3 Optical and 3 Coaxial)
- 5 A/V Inputs (1 Front/4 Rear) and 1 Output
- Color-Coded, 7.1 Multichannel Inputs
- Video Output (Monitor)
- 1 Audio Input
- Phono Input
- Color-Coded, 7.2 Multichannel Pre Outs
- RS232 Port, IR (In/Out), and 12V Trigger Outs (Zone 2/3)
- Bi-Amping Capability
- Color-Coded, Banana Plug-Compatible Speaker Posts
- RI/HD (Remote Interactive over HDMI) for System Control

OTHER FEATURES

- Overlaid Graphical On-Screen Display (OSD) via All Video Outputs
- Audyssey Dynamic Volume™
- Audyssey Dynamic EQ® for Loudness Correction
- Crossover Adjustment (40/50/60/70/80/90/100/120/150/200 Hz)
- A/V Sync Control Function (Up to 250 ms in 5 ms Steps)
- 40 FM/AM Random Presets
- RDS (PS/RT/PTY/TP)
- Compatible with RI (Remote Interactive) Dock for iPod
- Bi-Directional, Preprogrammed, and Customizable RI Remote Control with On-Screen Setup, Mode-Key LEDs, and Macro Presets for Four Activities

SPECIFICATIONS

AMPLIFIER SECTION

Power Output	
Front L/R	180 W/Ch (6 Ω, 1 kHz, 1 channel driven, IEC)
Center	180 W (6 Ω, 1 kHz, 1 channel driven, IEC)
Surround L/R	180 W/Ch (6 Ω, 1 kHz, 1 channel driven, IEC)
Surround Back L/R, Front High L/R, Front Wide L/R, or Zone 2 L/R	180 W/Ch (6 Ω, 1 kHz, 1 channel driven, IEC)
Dynamic Power	
	300 W (3 Ω, Front)
	250 W (4 Ω, Front)
	150 W (8 Ω, Front)
THD (Total Harmonic Distortion)	
	0.08% (Rated power)
Damping Factor	
	60 (Front, 1 kHz, 8 Ω)
Input Sensitivity and Impedance	
	200 mV/47 kΩ (Line)
	2.5 mV/47 kΩ (Phono MM)
Rated RCA Output Level and Impedance	
	200 mV/470 Ω (Pre out)
Maximum RCA Output Level and Impedance	
	4.6 V/470 Ω (Pre out)
Phono Overload	
	70 mV (MM, 1 kHz, 0.5%)
Frequency Response	
	5 Hz–100 kHz+1 dB, -3 dB (Direct mode)
Tone Control	
	±10 dB, 50 Hz (Bass)
	±10 dB, 20 kHz (Treble)
Signal-to-Noise Ratio	
	110 dB (Line, IHF-A)
	80 dB (Phono, IHF-A)
Speaker Impedance	
	4 Ω–16 Ω or 6 Ω–16 Ω

VIDEO SECTION

Input Sensitivity/Output Level and Impedance	
Video	1.0 Vp-p/75 Ω (Component and S-Video Y)
	0.7 Vp-p/75 Ω (Component Pb/Cb, Pr/Cr)
	0.25 Vp-p/75 Ω (S-Video C)
	1.0 Vp-p/75 Ω (Composite)
Component Video Frequency Response	
	5 Hz–100 MHz/0 dB, -3 dB

TUNER SECTION

Tuning Frequency Range	
FM	87.5 MHz–108 MHz
AM	522 kHz–1,611 kHz
	530 kHz–1,710 kHz
FM/AM Preset Memory	
	40 stations

GENERAL

Power Supply	AC 220–240 V~, 50/60 Hz
Power Consumption	710 W
Dimensions (W x H x D)	435 x 198.5 x 435.5 mm
Weight	18.4 kg

CARTON


Dimensions (W x H x D)	587 x 337 x 553 mm
Weight	23.0 kg

Supplied Accessories

- Indoor FM antenna • AM loop antenna • Speaker cable labels
- Speaker set-up microphone • Instruction manual • Quick start guide
- Remote controller • AA (R6) batteries x 2

ADVANCED FEATURES

- THX® Select2 Plus™ Certified
- HDMI® (Version 1.4a to Support 3D and Audio Return Channel) with Deep Color™, x.v.Color™, LipSync, Dolby® TrueHD, DTS-HD Master Audio™, DVD-Audio, Super Audio CD, Multichannel PCM, and CEC
- 7 HDMI Inputs (1 Front/6 Rear) and 2 Outputs
- Audyssey DSX™ and Dolby® Pro Logic® IIz for New Surround Channels
- PLL Jitter-Cleaning Circuit Technology
- Audyssey MultEQ® for Room Acoustic Correction
- Network Capability for Streaming Audio Files (MP3, WMA, WMA Lossless, FLAC, WAV, Ogg Vorbis, AAC, LPCM)
- Internet Radio Connectivity (Last.fm, Napster, and vTuner)*
- Certified with Windows® 7 and DLNA Version 1.5
- Front-Panel USB Input for Memory Devices and iPhone/iPod Models (Enables Display of Album Artwork)



Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. THX Select2 Plus is a trademark of THX Ltd. THX may be registered in some jurisdictions. All rights reserved. Manufactured under license from Dolby Laboratories. Dolby, Pro Logic, and the double-D symbol are trademarks of Dolby Laboratories. DTS is a registered trademark and the DTS logos and Symbol are trademarks of DTS, Inc. Manufactured under license from Audyssey Laboratories. U.S. and foreign patents pending. Audyssey MultEQ and Audyssey Dynamic EQ are registered trademarks, and Audyssey DSX and Audyssey Dynamic Volume are trademarks of Audyssey Laboratories. HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. iPod and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. "Made for iPod" and "Made for iPhone" mean that an electronic accessory has been designed to connect specifically to iPod or iPhone, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. x.v.Color is a trademark of Sony Corporation. Faroudja DCDi Cinema is a registered trademark of Genesis Microchip Inc. Windows 7 and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. WRAT, Music Optimizer, and Theater-Dimensional are trademarks of Onkyo Corporation. All other trademarks and registered trademarks are the property of their respective holders.



Onkyo Corporation 2-1 Nishin-cho, Neyagawa-shi, Osaka 572-8540, JAPAN Tel: +81-72-831-8136 Fax: +81-72-833-5222 <http://www.onkyo.com/>
Onkyo Europe Electronics GmbH Liegnitzerstrasse 6, 82194 Grobenzell, GERMANY Tel: +49-8142-4401-0 Fax: +49-8142-4401-555 <http://www.eu.onkyo.com/>
Onkyo UK Office The Coach House, 81A High Street, Marlow, Buckinghamshire SL7 1AB, UNITED KINGDOM Tel: +44(0)1628-473350 Fax: +44(0)1628-401700 <http://www.onkyo.co.uk/>