American Standard

SHOWER SYSTEMS

Model #	Description/Features	Finishes	Roughing-In Dimensions				
1660.525	 "Trevi" Personal Shower Self Cleaning Patented Design: Flexible ring with spray holes prevents lime scale build up. Spray Pattern: Variable spray adjusts from a conventional spray to an aerated flow to a massage action. Lightweight, Ergonomic Design: For a sure grip even with wet, soapy hands. Flow Restrictor: 2.5 gpm/9.5L/min. 	.002 Polished Chrome .099 Polished Brass (PVD) .295 Satin Nickel (PVD)	160mm (6-1/4) 1/2" NPSM				
1660.500	"Soft" Personal Shower Spray Pattern: Variable spray adjusts from a conventional spray to a champagne flow. Simple Spray Pattern Adjustment: Spray patterns can be changed with a flick of the thumb. A true one-handed operation. Lightweight, Ergonomic Design: For a sure grip even with wet, soapy hands. Flow Restrictor: 2.5 gpm/9.5L/min.	.002 Polished Chrome .099 Polished Brass (PVD) .295 Satin Nickel (PVD)	240mm (9-1/2) 1/2" NPSM				
1660.501	 "Sport" Personal Shower Spray Pattern: Conventional spray adjusts from an invigorating needle spray to a soft drenching flow. Simple Spray Pattern Adjustment: Spray patterns can be changed with a flick of the thumb. A true one-handed operation. Lightweight, Ergonomic Design: For a sure grip even with wet, soapy hands. Flow Restrictor: 2.5 gpm/9.5L/min. 	.002 Polished Chrome .099 Polished Brass (PVD) .295 Satin Nickel (PVD)	209mm (8-1/4) 1/2" NPSM				
1660.503	"3" Function Personal Shower Spray Pattern: Variable spray adjusts from a conventional spray to an aerated flow to a massage action. Simple Spray Pattern Adjustment: Spray patterns can be changed with a flick of the thumb. A true one-handed operation. Lightweight, Ergonomic Design: For a sure grip even with wet, soapy hands. Flow Restrictor: 2.5 gpm/9.5L/min.	.002 Polished Chrome	1/01 NIDOM				
Flow Restrictor: 2.5 gpm/9.5L/min. — 1/2" NPSM NOTE: Additional handshowers appear on back. — 1/2" NPSM							

SUGGESTED SPECIFICATION:

Personal shower shall be ergonomically designed for a positive grip even when wet. Spray pattern adjustment (on applicable models) shall be performed with simple movement of thumb without need to change grip on handle. Fitting shall be American Standard Model # 1660.

American Standard

SHOWER SYSTEMS HAND HELD PERSONAL SHOWERS & BODY SPRAYS

Model #	Description/Features		Finish	es	Roughing-In Dimensions
1660.504	Adjustable Personal Shower		.002 Polished Ch		
	Spray Pattern: Conventional spray a from an invigorating needle spray to drenching flow.				73mm 2-7/8"
	Simple Spray Pattern Adjustment: Spray patterns can be changed with a flick of the thumb. A true one-handed operation.				2-7/8" 137mm (5-3/8)
	Lightweight, Ergonomic Design: sure grip even with wet, soapy hands. Flow Restrictor: 2.5 gpm/9.5L/min.	For a			
1660.505	Fixed Personal Shower		.002 Polished Chrome		
	Spray Pattern: Fixed conventional spra Lightweight, Ergonomic Design: sure grip even with wet, soapy hands. Flow Restrictor: 2.5 gpm/9.5L/min.	·			67mm (2-5/8) 146mm (5-3/4)
8888.035	59" (1500mm) Shower Hose Threads directly on 1/2" NPSM male th	readed	.002 Polished Chrome .099 Polished Brass (PVD) .295 Satin Nickel (PVD)		
8888.053	personal hand held shower. 79" (2007mm) Shower Hose		.002 Polished Chrome		
1660.400	1/2" NPT In-Line Vacuum Brea Attaches between supply outlet and pershower hose.		.002 Polished Chrome .099 Polished Brass (PVD) .295 Satin Nickel (PVD)		
1660.125	Body/Side Spray	99 Polis	hed Chrome hed Brass (PVD) ı Nickel (PVD)	38mm (1-1/2)	FINISHED WALL 2-1/4 2-1/4 (56mm) 40° DIA. (75-89mm)