

## Make your beans our business!

Simply the most innovative, technologically advanced pieces of equipment on the market. The Coffee Brew



Centers have proven to be the bench mark of success and have set new standards for the coffee brewing industry.

Taste and quality are two primary concerns Cecilware focuses on when designing and manufacturing coffee brewing equipment. While roasters spend endless hours cultivating various blends of coffee to meet and exceed their customers expectations, Cecilware's Coffee Brew Centers are designed to aid in that process.

Good tasting coffee doesn't end with the roasting, grinding and bagging process; in fact, that's only the beginning. The difference between a good cup of coffee and an excellent cup is in the brewing process -- a process that should never be overlooked.

So if you're in the market to sell delicious cups of coffee, your beans belong in a Cecilware coffee brewer.



Portable, efficient, economical & versatile, the Coffee Brew Centers provide both large and small brewing volumes requiring a minimum of counterspace.

12, 24 or 36 cup brewing cycles are available in a heavy duty, 18 gauge stainless steel construction. Designed with a unique back-up, water level control.



BC1E



FreshCallee

BC302E-BL

Attractive, modern looking, easy to operate.

- Simple maintenance; controls and components are easily accessible.
- Includes insulated 1<sup>1</sup>/<sub>2</sub> gallon portable carriers with unique locking lid design and carrier safety holder which keeps carrier firmly on brewer.
- Solid state electronic controls insure perfectly brewed coffee.
- Solid state level control maintains proper water level.
- Quick hot water recovery; large hot water tank.
- Separate hot water faucet for soup, tea, hot cocoa, etc., can be used during brewing cycle.



Model #	Cups / Brew	Cups / Hour	Width	Electrical	Ship Weight
BC1E* Single	36	250	9"	120/240V, 4.1KW, 18A	66 lbs.
BC2E* Twin	36	400	18"	120/240V, 6.2KW, 27A	110 lbs.
BC120E* Single	12/24	120	9"	120V 1.8KW, 15A	66 lbs.
BC240E* Single	12/24	200	9"	120/240V, 3.1KW, 13A	66 lbs.
BC301E* Single	12/24/36	240	9"	120/240V, 4.1KW, 18A	66 lbs.
BC 302E* Twin	12/24/36	400	18"	120/240V, 6.2KW, 27A	110 lbs.

Available in Black Finish. Add "BL" Suffix to Model Number eg. BC302E-BL Depth: 17¾" (Depth to faucet center, add 4½"); Height: 31" (includes 4" adjustable legs).

Carrier capacity is 11/2 gallons, 36 cups. All Brew Centers are single phase with 3 wires, plus a ground, except BC120 is 120V, plug-in anywhere. 3 phase voltage is available. For export voltage add suffix "X" to model number. (Example BC302E-BL-X)





### The Only Microprocessor Driven System That Gives You More Than Just Coffee



Cecilware's Coffee Brewers with "IT" will do that plus a whole lot more. "IT" gives you Total Control over the brewing cycle. From easily setting the brew temperature, to maintaining inventory control, to preventing unauthorized tampering with the brew cycle, Cecilware coffee brewers with "IT" take coffee brewing to the next level.



Cups / Brew Cups / Ship Weight Model # Width Electrical Hour Cvcle BC2E-IT\* 120/240V. 36 400 18" 110 lbs. 6.2KW, 27A Twin BC 302E-IT\* 120/240V, 12/24/36 400 18" 110 lbs. Twin 6.2KW, 27A BC301E-IT\* 120/240V, 12/24/36 240 ٥" 66 lbs. Single 4.1KW, 18A

Available in Black Finish. Add "BL" Suffix to Model Number eg. BC2E-IT-BL **Depth:** 17 3/4" (Depth to faucet center, add 4 1/2"); Height: 31" (includes 4" adjustable legs). Available for Export (220/50/1), add suffix "X" to model # (e.g. BC2E-IT-X). **Plumbing:** 1/4" water line required; Carrier capacity is 1 1/2 gal. 36 cups. All Brew Centers are single phase with 3 wires, plus a ground; 3 phase voltage is available.

### With "IT" You Can Customize Your Brew Cycle With All These Features

- Touch Pad Control Technology with LCD
- User Friendly Walk Thru Menus
- Custom Key Lock Control Prevents unauthorized tampering with the brew cycle.
- Water Temperature To extract the rich, full flavor of coffee, "IT" allows you to set the optimum water temperature to the precise degree.
- Low Temperature Lockout To help the brewing cycle reach its peak brewing performance, the Low Temperature Lockout feature prevents an operator from brewing coffee if the water tank temperature falls below the specified brewing temperature.
- Set Brew Size Gives precise brew control by volume.
- Dispense Total By working in conjunction with your Inventory Control Management, this unique feature keeps track of the total brew cycles within a specified period of time and has a non-resettable counter to control ounces dispensed.

- Freshness Control Keeping coffee fresh and hot is simple with the exclusive "Freshness Control." Incorporated into all "IT" coffee brewers, just set the system once and an audio and visual response will remind you to brew a fresh pot.
- Heat Reduction Warmers Assures an operator that a brewed pot of coffee will almost never become too hot or burn.
- Pre-infusion Pulse Brewing Bypass These brew enhancement features can be easily set to suit your coffee brewing needs.
- Sleep Mode Designed to save the operator money in electrical costs, "IT" 's Sleep Mode automatically starts when the brewer has not been used for four hours.
- Programmable Timer with Battery Backup This feature turns the brewer on and off at any prespecified time. It will not brew coffee automatically, but will heat the water and get it ready for the brew cycle to begin.



BC2E-IT

# 1% Gallon Carriers & Heated Stands



TWHC

The recent surge in coffee consumption has created a valuable and profitable market for self-service coffee stations. But not every establishment has an accessible waterline to brew coffee so customers can easily help themselves to their daily cup of java. Cecilware's 1½ gallon coffee carriers and heated stands offer an easy and practical solution to this everyday occurrence. By placing a select number of carriers and stands at self-service or waitress stations, your coffee dispensing problems are solved. When coffee is running low, simply walk a carrier over to the brewer and brew away. When finished, the self-contained thermal carrier is ready for dispensing.

Model #	Description	Width	Height	Ship Weight
CAR-1*	Carrier	9"	11"	12 lbs.
SWH*	Single Heated Stand	9"	7¾"	8½ lbs.
SWHC*	w/Carrier	9"	18¾"	21 lbs.
TWH*	Twin Heated Stand	18"	7¾"	14 lbs.
TWHC*	w/Carrier	18"	18¾"	38 lbs.

\* Available in Black Finish. Add "BL" Suffix to Model Number eg. CAR-1BL Depth: 9" (Depth to faucet center, add 4½"); Height: includes 4" adjustable legs; 120V

#### **Stainless Steel Drip Trays**

95162	Single Drip Tray	8"	3⁄4"	2 lbs.
95161	Twin Drip Tray	15"	3⁄4"	3 lbs.
Depth: 5"				



Cecilware Corporation 43-05 20th Ave., LIC, NY 11105 Tel: 800.935.2211 718.932.1414 Fax: 718.932.7860 Visit us on the web: www.cecilware.com

