

# ENVISION™

## LOW SILL CONSOLE

### Geothermal/Water Source Heat Pump

- R-410A Refrigerant
- 0.75-1.5 Ton Single Speed

Installation Information

Water Piping Connections

Electrical

Startup Procedures

Troubleshooting

Preventive Maintenance



Envision Low Sill Console Installation Manual



IM1012CNA 03/14




## Table of Contents

---

|   |       |
|---|-------|
| Model Nomenclature . . . . .                        | 4     |
| General Installation Information . . . . .          | 5     |
| Dimensional Data . . . . .                          | 6-9   |
| Physical Data . . . . .                             | 10    |
| Installation Steps . . . . .                        | 11-14 |
| System Cleaning and Flushing . . . . .              | 15    |
| Open Loop Ground Water Systems . . . . .            | 16    |
| Water Quality . . . . .                             | 16    |
| Electrical Connections . . . . .                    | 17    |
| Electrical Data . . . . .                           | 18    |
| Blower Performance Data . . . . .                   | 18    |
| Wiring Schematics . . . . .                         | 19-25 |
| Controls . . . . .                                  | 26-34 |
| Unit Startup Notes . . . . .                        | 35    |
| Unit Startup Checklist/Unit Startup Steps . . . . . | 36    |
| Operating Parameters . . . . .                      | 37    |
| Operating Limits . . . . .                          | 37    |
| Pressure Drop . . . . .                             | 38    |
| Compressor and Thermistor Resistance . . . . .      | 38    |
| Refrigerant Circuit Guideline . . . . .             | 39    |
| Heat of Extraction/Rejection Data . . . . .         | 40    |
| Reference Calculations and Legend . . . . .         | 40    |
| Startup/Troubleshooting Form . . . . .              | 41    |
| Preventive Maintenance . . . . .                    | 42    |
| Replacement Procedures . . . . .                    | 42    |
| Service Parts . . . . .                             | 43    |
| Revision Guide . . . . .                            | 45    |

# Model Nomenclature



Rev.: 02 March 2014D

**NOTES:** Chassis only available with left piping option.  
 FX10 option is only available with remote wall-mounted thermostat control.  
 09-12 only available with PSC blower.  
 15-18 only available with 3-Speed ECM blower.

## General Installation Information

---

### Safety Considerations



**WARNING: Before performing service or maintenance operations on a system, turn off main power switches to the indoor unit. If applicable, turn off the accessory heater power switch. Electrical shock could cause personal injury.**

Installing and servicing heating and air conditioning equipment can be hazardous due to system pressure and electrical components. Only trained and qualified service personnel should install, repair or service heating and air conditioning equipment. Untrained personnel can perform the basic maintenance functions of cleaning coils and cleaning and replacing filters. All other operations should be performed by trained service personnel. When working on heating and air conditioning equipment, observe precautions in the literature, tags and labels attached to the unit and other safety precautions that may apply.

Follow all safety codes. Wear safety glasses and work gloves. Use a quenching cloth for brazing operations and have a fire extinguisher available.

### Moving and Storage

Move units in the normal “up” orientation. Do not stack units. When the equipment is received, all items should be carefully checked against the bill of lading to be sure all crates and cartons have been received. Examine units for shipping damage, removing the units from the packaging if necessary. Units in question should also be internally inspected. If any damage is noted, the carrier should make the proper notation on the delivery receipt, acknowledging the damage.

### Water Piping

The proper water flow must be provided to each unit whenever the unit operates. To assure proper flow, use pressure/temperature ports to determine the flow rate. These ports should be located at the supply and return water connections on the unit. The proper flow rate cannot be accurately set without measuring the water pressure drop through the refrigerant-to-water heat exchanger.


All source water connections on commercial units are fittings that accept a male pipe thread (MPT). Insert the connectors by hand, then tighten the fitting with a wrench to provide a leakproof joint. When connecting to an open loop (groundwater) system, thread any copper MPT fitting into the connector and tighten in the same manner as described above.

### Refrigerant Systems

To maintain sealed circuit integrity, do not install service gauges unless unit operation appears abnormal. Compare the change in temperature on the air side as well as the water side to the Unit Operating Parameters tables. If the unit’s performance is not within the ranges listed, and the airflow and water flow are known to be correct, gauges should then be installed and superheat and subcooling numbers calculated. If superheat and subcooling are outside recommended ranges, an adjustment to the refrigerant charge may be necessary.

## Dimensional Data - Flat Top Cabinet

### LCW09-18




| Flat Top Configuration |     | Overall Cabinet |       |        | Grille     |               |              |     |
|------------------------|-----|-----------------|-------|--------|------------|---------------|--------------|-----|
|                        |     | A               | B     | C      | D          | E             | F            | G   |
|                        |     | Width           | Depth | Height | Grille Lid | Grille Length | Grille Width |     |
| 09-12                  | in. | 45.1            | 10.8  | 22.5   | 9.2        | 35.0          | 6.1          | 2.3 |
|                        | cm. | 114.6           | 27.4  | 57.2   | 23.4       | 88.9          | 15.6         | 5.8 |
| 15-18                  | in. | 50.0            | 12.8  | 22.5   | 9.2        | 35.0          | 6.1          | 3.3 |
|                        | cm. | 127.0           | 32.4  | 57.2   | 23.4       | 88.9          | 15.6         | 8.3 |

# Dimensional Data - Slope Top Cabinet

## LCS09-18

Right Hand Cabinet

Left Hand Cabinet






Right return cabinet shown in dimensional views




| Slope Top Configuration |     | Overall Cabinet |       |        | Grille     |               |              |     |      |
|-------------------------|-----|-----------------|-------|--------|------------|---------------|--------------|-----|------|
|                         |     | A               | B     | C      | D          | E             | F            | G   | H    |
|                         |     | Width           | Depth | Height | Grille Lid | Grille Length | Grille Width |     |      |
| 09-12                   | in. | 45.1            | 10.8  | 24.0   | 9.2        | 35.0          | 6.1          | 2.0 | 22.4 |
|                         | cm. | 114.6           | 27.4  | 61.0   | 23.4       | 88.9          | 15.6         | 5.1 | 56.9 |
| 15-18                   | in. | 50.0            | 12.8  | 24.0   | 9.2        | 35.0          | 6.1          | 2.0 | 22.5 |
|                         | cm. | 127.0           | 32.4  | 61.0   | 23.4       | 88.9          | 15.6         | 5.1 | 57.2 |

## Dimensional Data - Chassis

### LCC09-12




### LCC15-18






## Dimensional Data - Controls Detail: Flat Top Chassis



### Left Return



### Right Return



## Dimensional Data - Controls Detail: Flat Top Chassis



## Physical Data

| Model   | Console              |                         |                         |  |
|---|----------------------|-------------------------|-------------------------|--|
|   | 09                   | 12                      | 15                      | 18   |
| Compressor (1 each)   | Rotary               |                         |                         |  |
| Factory Charge R-410A, oz [kg]                              | 27 [0.77]            | 27 [0.77]               | 36 [1.02]               | 34 [1.0]                                       |
| <b>Blower Motor &amp; Blower</b>                            |                      |                         |                         |  |
| Blower Motor Type/Speeds                                    | 3-Spd<br>ECM         | N/A                     |                         | 3 Speeds                                       |
| Blower Motor - hp [W]                                       | 3-Spd<br>ECM         | N/A                     |                         | 1/4 [186]    1/4 [186]                         |
| Blower Wheel Size (Dia x W), in. [mm]                       | 3-Spd<br>ECM         | N/A                     |                         | 6.0 x 6.5 [152 x 165]    6.0 x 6.5 [152 x 165] |
| Blower Motor Type/Speeds                                    | PSC                  | 2 Speeds                |                         | N/A  |
| Blower Motor - hp [W]                                       | PSC                  | 1/16 [44.7]             | 1/16 [44.7]             | N/A  |
| Blower Wheel Size (Dia x W), in. [mm]                       | PSC                  | 5.75 x 5.50 [146 x 140] | 5.75 x 5.50 [146 x 140] | N/A  |
| <b>Coax and Water Piping</b>                                |                      |                         |                         |  |
| Water Connection Size - FPT - in [mm]                       | 1/2 [12.7]           | 1/2 [12.7]              | 1/2 [12.7]              | 1/2 [12.7]                                     |
| Coax & Piping Water Volume - gal [l]                        | 0.15 [0.6]           | 0.18 [0.7]              | 0.15 [0.6]              | 0.18 [0.7]                                     |
| <b>Air Coil</b>   |                      |                         |                         |  |
| Air Coil Dimensions (H x W), in. [mm]                       | 8 x 22 [203 x 559]   | 8 x 22 [203 x 559]      | 8 x 30 [203 x 762]      | 8 x 30 [203 x 762]                             |
| Air Coil Total Face Area, ft <sup>2</sup> [m <sup>2</sup> ] | 1.2 [0.114]          | 1.2 [0.114]             | 1.7 [0.16]              | 1.7 [0.16]                                     |
| Air Coil Tube Size, in [mm]                                 | 3/8 [9.5]            | 3/8 [9.5]               | 3/8 [9.5]               | 3/8 [9.5]                                      |
| Air Coil Number of Rows                                     | 3                    | 3                       | 4                       | 4  |
| Filter Standard - Throwaway, in [mm]                        | 23 x 9.6 [584 x 244] | 23 x 9.6 [584 x 244]    | 32 x 9.6 [813 x 244]    | 32 x 9.6 [813 x 244]                           |
| Weight - Packaged, lb [kg]                                  | 200 [91]             | 205 [93]                | 215 [98]                | 220 [100]                                      |

12/13/13

# Installation Steps

## Step 1: Unpack Equipment and Inspect for Damage

### Step 2: Determine Equipment Location

- Choose level flooring surface (Correctable with shims. Do not pitch towards drain.)
- Location of wall support and fasteners required to secure chassis backplate.
- Easy access for both installation and service.
- Consider availability and ease of wiring, water piping and condensate drain.
- No obstructions to block airflow in front of the unit.


### Step 3: Mark Unit Position

- Ensure that floor is level. If shims are required, make sure that the entire compressor compartment area is uniformly shimmed and that the backplate mounting height is increased by the thickness of the shims used.
- Position backplate in desired equipment location. To further reduce the operating sound level of the unit, 1/8-inch thick rubber matting may be placed under the chassis to eliminate vibration on hard flooring surfaces. (Make sure back plate is level).
- Mark and cut floor or wall penetrations for electrical wiring, water and condensate piping.

### Optional Electrical Disconnect

- Mark and cut wall penetrations for field fabricated outside air duct sleeve.
- Align mounting holes with backplate and attach with screws supplied.

Figure 1




## Installation Steps cont.

### Step 4: Provide Water and Condensate Drain Connections

- A two-pipe reverse return piping configuration is recommended as it equalizes the piping circuit lengths and delivers even water flow to each unit. A direct return piping configuration may be used, but it may be difficult to achieve and maintain proper water flow to the units.
- An air vent must be installed in the water distribution system.
- The supply and return water piping should be run through the wall or floor penetration and terminate with a ball valve. The piping material used must comply with all local codes.
- Refer to: *System Cleaning and Flushing procedures.*

### Pipe Locations

Figure 2



## Installation Steps cont.

---

### Step 5: Provide Line Voltage Wiring

- Check unit data plate located on control side of chassis for ampacity and fuse size.
- Remove electrical knockouts from chassis backplate.
- Run line voltage wiring through knockout and secure wiring to backplate or disconnect.

### Step 6: Chassis Installation

- Level and secure backplate to wall.
- Position the chassis against back plate. Drive (2) screws through holes in lip of backplate into top flange of chassis.

### Step 7: Final Electrical Connection

- Install flexible electrical conduit between the backplate or electrical disconnect and the unit mounted junction box.
- Make final wiring connections in disconnect and junction box, taking care to replace all covers when done. Wiring must conform to NEC and/or all local codes. **Refer to Electrical Data.**

**NOTE:** It is necessary to make final wiring connections prior to securing unit chassis to back plate on right-hand piping models with electrical disconnect.

### Step 8: Final Water Connection

- For ease of installation and sound attenuation, high pressure (recommended) flexible hoses with a swivel fitting should be provided. Apply Teflon® tape or sealant compound to threaded hose fittings.
- Combination shut-off/balancing valves should be installed on both the supply and return water lines of the unit.
- Flow control valves should be installed on the water discharge line.
- It is recommended that P/T ports be installed on the supply and return water lines.

### Step 9: Set Unit Controls

- Locate the “continuous fan/cycle fan” switch within the electrical compartment of the chassis and set to desired position. (Remote wall thermostat units do not use this optional switch.)
- Optional Control Settings-  
Remote Thermostat - Run low voltage wiring from unit to the desired thermostat location.  
Mount and wire thermostat according to manufacturer’s recommendations.

### Step 10: Secure the Cabinet Cover

- Position and lower cabinet over unit chassis. Apply pressure to the front of the cabinet to ensure that the back lip of the cabinet hooks over the tabs provided on the backplate.
- Secure cabinet to chassis with mounting screws provided.

### Step 11: Perform Final Unit Check


- Measure the pressure drop across the water coil and monitor water or air temperatures in both heating and cooling modes. The measured values should fall within the acceptable ranges shown in the **Startup Performance table.**

## Installation Steps cont.

### Field Converting Console

Chassis is normally configured with controls on right end and piping on left end (see Figure 3 top view). In this position panel number 1 would be positioned against wall or back plate. Unit may also be turned 180° against wall or back plate. In this position controls will be on left end and piping on right end panel number 2 would be positioned against wall or back plate. Chassis must be enclosed with an approved cabinet enclosure.

1. Remove 4 screws from front kick panel on cabinet.
2. Remove cabinet from chassis by lifting and sliding cabinet straight up.
3. Remove grille assembly from cabinet by removing 4 screws from brackets located on the bottom of the grille and door assemblies.
4. Replace grille/door assemblies into cabinet repositioning pieces 1, 2, and 3 into the locations directly opposite the original positions. Secure by replacing mounting brackets. (Note: Be sure that louvers on the grille assembly are facing the proper direction when replacing the grille section.)
5. Replace grille/frame assembly into cabinet, and secure by replacing mounting brackets.
6. Replace cabinet by sliding it down over the top of the chassis.
7. Remove tab on leg that extends into return air opening. When the grille side of the cabinet is flat against chassis there will be 4 holes that line up in the leg section. Only use 1 hole for alignment for opposite side of grille. (Note: The tab can be removed by twisting back and forth until it breaks off.)
8. Remove plastic strip from tab and replace on rough edge that the tab was removed from.
9. Replace screws in front kick panel to secure cabinet to chassis.
10. Mount filter bracket in designated opening area. (Note: The filter bracket will only fit in one direction if cabinet is installed properly.)



## System Cleaning and Flushing

### Cleaning and Flushing

Prior to start up of any heat pump, the water circulating system must be cleaned and flushed of all dirt and debris.

If the system is equipped with water shutoff valves, the supply and return runouts must be connected together at each unit location (This will prevent the introduction of dirt into the unit, see Figure 7). The system should be filled at the water make-up connection with all air vents open. After filling, vents should be closed.

The contractor should start the main circulator with the pressure reducing valve makeup open. Vents should be checked in sequence to bleed off any trapped air and to verify circulation through all components of the system.

As water circulates through the system, the contractor should check and repair any leaks found in the piping system. Drain(s) at the lowest point(s) in the system should be opened for initial flush and blowdown, making sure water fill valves are set at the same rate. Check the pressure gauge at the pump suction and manually adjust the make-up water valve to hold the same positive pressure both before and after opening the drain valves. Flushing should continue for at least two hours, or longer if required, until drain water is clean and clear.

The supplemental heater and/or circulator pump, if used, should be shut off. All drains and vents should be opened to completely drain the system. Short-circuited supply and return runouts should now be connected to the unit supply and return connections.

Refill the system with clean water. Test the system water for acidity and treat as required to leave the water slightly alkaline (pH 7.5 to 8.5). The specified percentage of antifreeze may also be added at this time. Use commercial grade antifreeze designed for HVAC systems only. Environol™ brand antifreeze is recommended.

Once the system has been filled with clean water and antifreeze (if used), precautions should be taken to protect the system from dirty water conditions. Dirty water will result in system-wide degradation of performance, and solids may clog valves, strainers, flow regulators, etc. Additionally, the heat exchanger may become clogged which reduces compressor service life and can cause premature unit failure.


In boiler/tower application, set the loop control panel set points to desired temperatures. Supply power to all motors and start the circulating pumps. After full flow has been established through all components including the heat rejector (regardless of season), air vented and loop temperatures stabilized, each of the units will be ready for check, test and start up and for air and water balancing.

### Ground Source Loop System Checkout

Once piping is completed between the unit pumping system and ground loop, final purging and charging of the loop is needed. A high pressure pump is needed to achieve adequate flow velocity in the loop to purge air and dirt particles from the loop itself. Antifreeze solution is used in most areas to prevent freezing. Flush the system adequately to remove as much air as possible; then pressurize the loop to a static pressure of 40-50 psi (summer) or 50-75 psi (winter). This is normally adequate for good system operation. Loop static pressure may decrease soon after initial installation, due to pipe expansion and loop temperature change. Running the unit for at least 30 minutes after the system has been completely purged of air will allow for the "break-in" period. It may be necessary to adjust static loop pressure (by adding water) after the unit has run for the first time. Loop static pressure will also fluctuate with the seasons. Pressures will be higher in the winter months than during the cooling season. This fluctuation is normal and should be considered when charging the system initially.

Ensure the pump provides adequate flow through the unit by checking pressure drop across the heat exchanger. Usually 2.25-3.0 gpm of flow per ton of cooling capacity is recommended in earth loop applications.

**Figure 7: Flushing with Water Shutoff Valve Equipped Systems**



## Open Loop Ground Water Systems

Always maintain water pressure in the heat exchanger by placing water control valves at the outlet of the unit to prevent mineral precipitation. Use a closed, bladder-type expansion tank to minimize mineral formation due to air exposure. Ensure proper water flow through the unit by checking pressure drop across the heat exchanger and comparing it to the figures in unit capacity data tables in the specification catalog. 1.5-2 gpm of flow per ton of cooling capacity is recommended in open loop applications.

Discharge water from the unit is not contaminated in any manner and can be disposed of in various ways, depending on local codes, i.e. recharge well, storm sewer, drain field, adjacent stream or pond, etc. Most local codes forbid the use of sanitary sewer for disposal. Consult your local building and zoning departments to assure compliance in your area.

**Note:** For open loop/groundwater systems or systems that do not contain an antifreeze solution, set SW1-Switch #2 to the "WELL" position (Refer to the Dip Switch Field Selection table). Slow opening/closing solenoid valves (type VM) are recommended to eliminate water hammer.

### Water Quality

In ground water situations where scaling could be heavy or where biological growth such as iron bacteria will be present, a closed loop system is recommended. The heat exchanger coils in ground water systems may, over a period of time, lose heat exchange capabilities due to a buildup of mineral deposits inside. These can be cleaned, but only by a qualified service mechanic, as special solutions and pumping equipment are required. Desuperheater coils can likewise become scaled and possibly plugged. In areas with extremely hard water, the owner should be informed that the heat exchanger may require occasional flushing.

Units with cupronickel heat exchangers are recommended for open loop applications due to the increased resistance to build-up and corrosion, along with reduced wear caused by acid cleaning.

| Material                         |   | Copper  | 90/10 Cupronickel   | 316 Stainless Steel                                       |
|----------------------------------|---|---|---|---|
| pH                               | Acidity/Alkalinity  | 7 - 9   | 7 - 9   | 7 - 9   |
| Scaling                          | Calcium and Magnesium Carbonate                           | (Total Hardness) less than 350 ppm                        | (Total Hardness) less than 350 ppm                        | (Total Hardness) less than 350 ppm                        |
| Corrosion                        | Hydrogen Sulfide  | Less than 0.5 ppm (rotten egg smell appears at 0.5 ppm)   | 10 - 50 ppm   | Less than 1 ppm   |
|                                  | Sulfates  | Less than 125 ppm   | Less than 125 ppm   | Less than 200 ppm   |
|                                  | Chlorine  | Less than 0.5 ppm   | Less than 0.5 ppm   | Less than 0.5 ppm   |
|                                  | Chlorides   | Less than 20 ppm  | Less than 125 ppm   | Less than 300 ppm   |
|                                  | Carbon Dioxide  | Less than 50 ppm  | 10 - 50 ppm   | 10 - 50 ppm   |
|                                  | Ammonia   | Less than 2 ppm   | Less than 2 ppm   | Less than 20 ppm  |
|                                  | Ammonia Chloride  | Less than 0.5 ppm   | Less than 0.5 ppm   | Less than 0.5 ppm   |
|                                  | Ammonia Nitrate   | Less than 0.5 ppm   | Less than 0.5 ppm   | Less than 0.5 ppm   |
|                                  | Ammonia Hydroxide   | Less than 0.5 ppm   | Less than 0.5 ppm   | Less than 0.5 ppm   |
|                                  | Ammonia Sulfate   | Less than 0.5 ppm   | Less than 0.5 ppm   | Less than 0.5 ppm   |
|                                  | Total Dissolved Solids (TDS)                              | Less than 1000 ppm  | 1000 - 1500 ppm   | 1000 - 1500 ppm   |
|                                  | LSI Index   | +0.5 to -0.5  | +0.5 to -0.5  | +0.5 to -0.5  |
| Iron Fouling (Biological Growth) | Iron, FE <sup>2+</sup> (Ferrous) Bacterial Iron Potential | < 0.2 ppm   | < 0.2 ppm   | < 0.2 ppm   |
|                                  | Iron Oxide  | Less than 1 ppm, above this level deposition will occur   | Less than 1 ppm, above this level deposition will occur   | Less than 1 ppm, above this level deposition will occur   |
| Erosion                          | Suspended Solids  | Less than 10 ppm and filtered for max. of 600 micron size | Less than 10 ppm and filtered for max. of 600 micron size | Less than 10 ppm and filtered for max. of 600 micron size |
|                                  | Threshold Velocity (Fresh Water)                          | < 6 ft/sec  | < 6 ft/sec  | < 6 ft/sec  |

**NOTES:** Grains = ppm divided by 17  
mg/L is equivalent to ppm

2/22/12



# Electrical Connections

## General


Be sure the available power is the same voltage and phase as that shown on the unit serial plate. Line and low voltage wiring must be done in accordance with local codes or the National Electric Code, whichever is applicable.

## 208 Volt Operation

All Envision Series 208/230 units are factory wired for 230 volt operation. For 208 volt operation, the red and blue transformer wires must be switched.

## Microprocessor Remote Thermostat Wiring

Figure 5



## Electrical Data

| Model | Rated Voltage | Voltage Min/Max | Compressor |     |      | Blower Motor FLA | Total Unit FLA | Min Circ Amp | Max Fuse/HACR |
|-------|---------------|-----------------|------------|-----|------|------------------|----------------|--------------|---------------|
|       |               |                 | MCC        | RLA | LRA  |                  |                |              |               |
| 09    | 115/60/1      | 104/127         | 12.5       | 8.0 | 50.0 | 1.5              | 9.5            | 11.5         | 15            |
|       | 208-230/60/1  | 187/253         | 6.4        | 4.1 | 21.0 | 0.6              | 4.7            | 5.7          | 10/15         |
|       | 265/60/1      | 238/292         | 6.7        | 4.3 | 22.0 | 0.6              | 4.9            | 6.0          | 10/15         |
| 12    | 115/60/1      | 104/127         | 14.8       | 9.5 | 50.0 | 1.5              | 11.0           | 13.4         | 20            |
|       | 208-230/60/1  | 187/253         | 7.7        | 4.9 | 25.0 | 0.6              | 5.5            | 6.7          | 10/15         |
|       | 265/60/1      | 238/292         | 7.0        | 4.5 | 22.0 | 0.6              | 5.1            | 6.2          | 10/15         |
| 15    | 208-230/60/1  | 187/253         | 9.2        | 5.9 | 29.0 | 2.6              | 8.5            | 10.0         | 15            |
|       | 265/60/1      | 238/292         | 7.8        | 5.0 | 28.0 | 2.5              | 7.5            | 8.7          | 10/15         |
| 18    | 208-230/60/1  | 187/253         | 10.4       | 6.7 | 33.5 | 2.6              | 9.3            | 11.0         | 15            |
|       | 265/60/1      | 238/292         | 8.7        | 5.6 | 28.0 | 2.5              | 8.1            | 9.5          | 15            |

HACR circuit breaker in USA only

6/10/13

## Blower Performance Data


| Model | CFM       |            |
|-------|-----------|------------|
|       | Low Speed | High Speed |
| 09    | 260       | 300        |
| 12    | 300       | 340        |
| 15    | 375       | 450        |
| 18    | 450       | 600        |

Air flow values are with dry coil and standard filter.

For wet coil performance, first calculate the face velocity of the air coil  
(face velocity (fpm) = airflow (cfm) / face area (sq ft))

# Wiring Schematics

## CCM with Remote Thermostat - 208-230-265/60/1




| Legend |                                      |  |                             |
|--------|--------------------------------------|--|-----------------------------|
|        | Factory low voltage wiring           |  | Quick connect terminal      |
|        | Factory line voltage wiring          |  | Wire nut                    |
|        | Factory low voltage wiring           |  | Relay coil                  |
|        | Factory line voltage wiring          |  | Capacitor                   |
|        | CC - Compressor Contactor            |  | Thermistor                  |
|        | DT - Damper Terminal Block           |  | Temperature Switch          |
|        | FS - Freeze Sensing Device           |  | Switch - High Pressure      |
|        | HP - High Pressure Switch            |  | Switch - Low Pressure       |
|        | LP - Low Pressure Switch             |  | Relay Contacts - N.O., N.C. |
|        | PB - Power Block                     |  | Ground                      |
|        | RB - Blower Relay                    |  | Relay Contacts - N.O., N.C. |
|        | RSR - Remote Start/Stop Relay        |  | Ground                      |
|        | RV - Reversing Valve Coil            |  | Relay Contacts - N.O., N.C. |
|        | ST - Entering Air Temperature Sensor |  | Relay Contacts - N.O., N.C. |

**Notes:**  
 1. Switch Red and Blue wires for 208 volt operation.  
 2. Terminal C of the 24V PB is used as "L" output for Lockout.  
 3. When installed, 24VAC connection for remote start/stop controller option.

# Wiring Schematics cont.

## CCM with Unit Mounted Thermostat - 208-230-265/60/1




### Legend

|  |  |   |  |  |
|--|--|---|--|--|
| <ul style="list-style-type: none"> <li>Factory low voltage wiring</li> <li>Factory line voltage wiring</li> <li>Field low voltage wiring</li> <li>Field line voltage wiring</li> <li>Quick connect terminal</li> <li>Wire nut</li> </ul> | <ul style="list-style-type: none"> <li>CC - Compressor Contactor</li> <li>DT - Damper Terminal Block</li> <li>FS - Freeze Sensing Device</li> <li>HP - High Pressure Switch</li> <li>LP - Low Pressure Switch</li> <li>PB - Power Block</li> <li>RB - Blower Relay</li> <li>RV - Reversing Valve Coil</li> <li>ST - Entering Air Temperature Sensor</li> </ul> | <ul style="list-style-type: none"> <li>L1 - Field wire lug</li> <li>Earth Ground</li> <li>Relay Contacts - N.O., N.C.</li> <li>Polarized Connector</li> </ul> | <ul style="list-style-type: none"> <li>Switch - High Pressure</li> <li>Switch - Low Pressure</li> <li>Relay coil</li> <li>Capacitor</li> <li>Thermistor</li> <li>Temperature Switch</li> </ul> | <p><b>Notes:</b></p> <ol style="list-style-type: none"> <li>Switch Red and Blue wires for 208 volt operation.</li> <li>Terminal C of 24 V PB is used as "L" output for Brown wire 3 for Lockout.</li> <li>Optional field installed freeze sensing device.</li> </ol> |
|--|--|---|--|--|


# Wiring Schematics cont.

## Versatec with Remote Thermostat - 208-230-265/60/1



# Wiring Schematics cont.

## Versatec with Unit Mounted Thermostat - 208-230-265/60/1




### Legend

|   |   |   |   |   |
|---|---|---|---|---|
| <p>— Factory low voltage wiring</p> <p>— Factory line voltage wiring</p> <p>..... Factory low voltage wiring</p> <p>----- Factory line voltage wiring</p> <p>○ Quick connect terminal</p> <p>▲ Wire nut</p> | <p>CC - Compressor contactor</p> <p>CO - Condensate overflow</p> <p>FS - Freeze sensing device</p> <p>HP - High pressure switch</p> <p>LP - Low pressure switch</p> <p>RB - Blower power relay</p> <p>RV - Reversing Valve coil</p> <p>SW1 - DIP switch #1</p> <p>ES - Emergency Shutdown</p> | <p>L1 Wiring lug</p> <p>⊥ Ground</p> <p>Relay Contacts - N.O., N.C.</p> | <p>HP Switch - High Pressure</p> <p>LP Switch - Low Pressure</p> <p>○ Relay coil</p> <p>Capacitor</p> <p>Thermistor</p> <p>Temperature Switch</p> | <p><b>Notes:</b></p> <p>1. Switch Red and Blue wires for 208 volt operation.</p> <p>2. Terminal 2 of the 24V PB is used as 'L' output for Brown wire 3 for Lockout.</p> <p>3. When installed, 24VAC connection for remote start/stop controller option.</p> |
|---|---|---|---|---|

# Wiring Schematics cont.

## CCM with ECM and Unit Mounted Thermostat - 208-230-265/60/1



### Legend

- Factory low voltage wiring
- Factory line voltage wiring
- - - Field low voltage wiring
- - - Field line voltage wiring
- Quick connect terminal
- ▲ Wire nut

- CC - Compressor Contactor
- DT - Damper Terminal Block
- FS - Freeze Sensing Device
- HP - High Pressure Switch
- LP - Low Pressure Switch
- PB - Power Block
- RB - Blower Relay
- RV - Reversing Valve Coil
- ST - Entering Air Temperature Sensor


- L1 Field wire lug
- Earth Ground
- Relay Contacts - N.O., N.C.
- Polarized connector

- HP Switch - High Pressure
- LP Switch - Low Pressure
- Relay coil
- Capacitor
- Thermistor
- Temperature Switch

- Notes:**
1. Switch Red and Blue wires for 208 volt operation
  2. Terminal C of 24 V PB is used as "L" output for Brown wire 3 for Lockout.
  3. Optional field installed freeze sensing device.
  4. Factory wired. Refer to blower settings.

# Wiring Schematics cont.

## FX10 with ECM and Unit Mounted Thermostat - 208-230-265/60/1



### Legend

| Factory low voltage wiring<br>Factory line voltage wiring<br>Field low voltage wiring<br>Field line voltage wiring<br>Field Zone Sensor Wiring<br>Internal junction<br>Quick connect terminal<br>Wire nut<br>Field wire lug<br>Ground | Relay Contacts - N.O., N.C.<br>Thermistor - Johnson Control<br>Relay coil<br>Open Jumper<br>Closed Jumper | Switch - High pressure<br>Switch - Low pressure<br>Polarized connector<br>Condensate Overflow | CC - Compressor Contactor<br>CO - Condensate Overflow<br>CP/FP - Compressor Proving/Fan Proving<br>DA - Discharge Air Temperature<br>DF/AP - Dirty Filter/Air Proving<br>ES - Emergency Shutdown<br>FS - Freeze Sensing Device<br>HP - High Pressure Switch<br>LP - Low Pressure Switch<br>OS - Occupied Switch<br>RB - Blower Power Relay<br>RV - Reversing Valve Coil<br>TB - Terminal Block | <p><b>Notes:</b></p> <ol style="list-style-type: none"> <li>1 - Switch Blue and Red wires for 208V operation</li> <li>2 - Disconnect for 15 degree freeze sensing</li> <li>3 - Acc 1 output is cycled with the compressor.</li> <li>4 - Acc 2 output is cycled with the fan.</li> <li>5 - R, C, Y1, O, and G inputs are for use with a wall mounted thermostat.</li> <li>6 - Factory wired. Refer to blower table settings.</li> </ol> <table border="1"> <thead> <tr> <th colspan="3">Blower Settings</th> </tr> <tr> <th></th> <th>High</th> <th>Low</th> </tr> </thead> <tbody> <tr> <td>LC15</td> <td>Orange</td> <td>Brown</td> </tr> <tr> <td>LC18</td> <td>Brown/White</td> <td>Orange</td> </tr> </tbody> </table> | Blower Settings |  |  |  | High | Low | LC15 | Orange | Brown | LC18 | Brown/White | Orange |
|---|---|---|--|--|-----------------|--|--|--|------|-----|------|--------|-------|------|-------------|--------|
| Blower Settings   |   |   |  |  |                 |  |  |  |      |     |      |        |       |      |             |        |
|   | High  | Low   |  |  |                 |  |  |  |      |     |      |        |       |      |             |        |
| LC15  | Orange  | Brown   |  |  |                 |  |  |  |      |     |      |        |       |      |             |        |
| LC18  | Brown/White   | Orange  |  |  |                 |  |  |  |      |     |      |        |       |      |             |        |



# Wiring Schematics cont.

## Versatec Control Board

Normal Mode Control Timing Table

|   |   |
|---|---|
| Blower off delay                            | 30 seconds                                    |
| Compressor on delay                         | 10 seconds                                    |
| Compressor short cycle delay                | 5 minutes                                     |
| Minimum compressor on time                  | 2 minutes (except for fault condition)        |
| High pressure fault recognition delay       | Less than 1 second                            |
| Low pressure fault recognition delay        | 30 seconds                                    |
| Freeze sensing fault recognition delay      | 30 seconds                                    |
| Condensate overflow fault recognition delay | 30 seconds                                    |
| Low pressure fault bypass delay             | 2 minutes (for first fault only, 0 sec after) |
| Freeze sensing fault bypass delay           | 2 minutes (for first fault only, 0 sec after) |
| Power on delay                              | 5 minutes                                     |

Test Mode Control Timing Table

|   |  |
|---|--|
| Blower off delay                            | 5 seconds                              |
| Compressor on delay                         | 2 seconds                              |
| Compressor short cycle delay                | 15 seconds                             |
| Minimum compressor on time                  | 5 seconds (except for fault condition) |
| High pressure fault recognition delay       | Less than 1 second                     |
| Low pressure fault recognition delay        | 30 seconds                             |
| Freeze sensing fault recognition delay      | 30 seconds                             |
| Condensate overflow fault recognition delay | 30 seconds                             |
| Low pressure fault bypass delay             | 0 seconds                              |
| Freeze sensing fault bypass delay           | 0 seconds                              |
| Power on delay                              | 15 seconds                             |
| Fault off time                              | 5 minutes                              |

LED Display Mode Table


| LED        | Normal Display Mode                            |
|------------|--|
|            | SW1-4 On, SW2 Off                              |
| Drain      | Drain pan overflow lockout                     |
| Water Flow | FS thermistor (loop<=15°F, well<=30°F) lockout |
| High Press | High pressure lockout                          |
| Low Press  | Low pressure lockout                           |
| Air Flow   | Not used                                       |
| Status     | Microprocessor malfunction*                    |
| DHW Limit  | Not Used                                       |
| HWD        | SW2 status (Off=down position, On=up position) |

Diagnostic Modes

| LED        | Current Fault Status                   | Inputs                  | Outputs                |
|------------|--|-------------------------|------------------------|
|            | SW1-4 On, SW2 On                       | SW1-4 Off, SW2 Off      | SW1-4 Off, SW2 On      |
| Drain      | Drain pan overflow                     | Y                       | Compressor             |
| Water Flow | FS thermistor (loop<=15°F, well<=30°F) | G                       | Blower                 |
| High Press | High pressure                          | O                       | O                      |
| Low Press  | Low pressure                           | ES                      | ES                     |
| Air Flow   | Not used                               | Not Used                | Not Used               |
| Status     | Not used                               | Not Used                | Not Used               |
| DHW Limit  | Not used                               | Not Used                | Not Used               |
| HWD        | SW2 in the On position                 | SW2 in the Off position | SW2 in the On position |

\*Flashing Status light indicates microprocessor is functioning properly. Solid "on" indicates a microprocessor malfunction.

Versatec Logic Board Physical Layout



Logic Board DIP Switch Settings







| Switch  | OFF  | ON   |
|---------|--|--|
| SW1 - 1 | Test Mode - Selected timings sped up to facilitate troubleshooting | Normal Mode - Standard timings                       |
| SW1 - 2 | Loop - Closed loop freeze sensing setting (15°F)                   | Well - Open loop freeze sensing setting (30°F)       |
| SW1 - 3 | Commercial - Enables NS features when TA32U02 thermostat is used   | Normal - Standard thermostat operation               |
| SW1 - 4 | IO Display* - Enables Input/Output display on external LED board*  | Normal* - Unit status display                        |
| SW1 - 5 | Split Mode - Dual-Speed-Compressor and with No blower              | Normal - Single-Speed Compressor with blower         |
| SW2     | OFF* - Normal or Input display mode activated                      | ON* - Current fault or Output display mode activated |

\* Refer to LED Display Mode table for position of SW1-4 and SW2

Operational Logic Table

| Mode   | Inputs | Blower | Comp | RV  |
|--------|--------|--------|------|-----|
| Htg    | Y      | ON     | ON   | OFF |
| Clg    | Y,O    | ON     | ON   | ON  |
| Blower | G      | ON     | OFF  | OFF |

## Controls

| Control   | General Description  | Application  | Display/Interface  | Protocol                                 | Thermostat Options                   |
|---|--|--|--|--|--------------------------------------|
|  <p>CCM Control</p>        | <p>The CCM (Compressor control module) is a more reliable replacement for electro-mechanical control applications. It features a small microprocessor board that handles the lockout function of the unit. A second microprocessor handles the unit mounted thermostat for maintaining accurate room temperature.</p>  | <p>Residential and commercial applications requiring minimal but reliable controls. Includes Random Start, High and low pressure switches and auto changeover capability.</p>  | <p>Dial thermostat with Hi and Low blower speeds, and auto changeover or continuous blower selection switches.</p> | <p>None</p>                              | Unit Mounted Digital Dial Thermostat |
|   |  |  |  |  | Remote Mounted Standard Thermostat   |
|  <p>Versatec Control</p>   | <p>The Versatec Control is a microprocessor based board that adds the features of emergency shutdown (ES), water freeze detection (FD) and condensate overflow (CO). The Versatec Control also features Optional Field servicing LEDs for mode, Fault and diagnostic indication.</p>   | <p>Residential and commercial applications requiring more controls features than CCM and Includes Random Start, High and low pressure switches, auto changeover capability, emergency shutdown (ES), water freeze detection (FD), and condensate overflow (CO).</p>                  | <p>Optional field servicing LED board for mode, fault and diagnostic indication</p>                                | <p>None</p>                              | Unit Mounted Digital Dial Thermostat |
|   |  |  |  |  | Remote Mounted Standard Thermostat   |
|  <p>FX10</p>               | <p>The FX10 microprocessor control is self contained control featuring LP, LOC, HP, LWT, and condensate overflow fault modes can be displayed on BAS system. Optional handheld Medium User Interface (MUI) Control can be used for additional setup or servicing. Program customization is possible. This control is suited for both single and dual capacity compressors as well as PSC and ECM2.3 blower motors.</p> | <p>Commercial applications using single and dual capacity compressors with either PSC or ECM2.3 blower motors. Also suitable for multi-compressor products. Cannot be integrated with centralized building automation systems. Software can be customized for specific projects.</p> | <p>Optional Medium User Interface (MUI) can be used as a field service tool.</p>                                   | <p>Standalone</p>                        | Remote Mounted Standard Thermostat   |
|   |  |  |  |  | Remote Mounted Sensor                |
|  <p>FX10 w/ N2</p>       | <p>FX10 Control functions as both unitary heat pump control and DDC communication, therefore detail operational and fault information is available to BAS. Other features are same as FX10 with addition of Johnson Controls N2 compatibility.</p>   | <p>Same as FX10 with Johnson Controls N2 BAS compatibility.</p>  | <p>Optional Medium User Interface (MUI) can be used as a field service tool.</p>                                   | <p>Johnson Controls N2 network</p>       | Remote Mounted Standard Thermostat   |
|   |  |  |  |  | Remote Mounted Sensor                |
|  <p>FX10 w/ LonWorks</p> | <p>FX10 Control functions as both unitary heat pump control and DDC communication, therefore detail operational and fault information is available to BAS. Other features are same as FX10 with addition of LonWorks compatibility.</p>  | <p>Same as FX10 with LonWorks BAS compatibility.</p>   | <p>Optional Medium User Interface (MUI) can be used as a field service tool.</p>                                   | <p>LonWorks</p>                          | Remote Mounted Standard Thermostat   |
|   |  |  |  |  | Remote Mounted Sensor                |
|  <p>FX10 w/ BACnet</p>   | <p>FX10 Control functions as both unitary heat pump control and DDC communication, therefore detail operational and fault information is available to BAS. Other features are same as FX10 with addition of BACnet compatibility.</p>  | <p>Same as FX10 with BACnet BAS compatibility.<br/><br/>Due to communication speed, no more than 30 units should be connected to a single trunk of the network.</p>  | <p>Optional Medium User Interface (MUI) can be mounted or used as a field service tool.</p>                        | <p>BACnet - MS/TP (19,200 Baud Rate)</p> | Remote Mounted Standard Thermostat   |
|   |  |  |  |  | Remote Mounted Sensor                |

### Standard CCM Control Features

Compressor control module (CCM) controls are standard on the Envision Series Low Sill Console heat pump. This control features unit mounted thermostat and switches, Features of the standard control are:


- Easy to understand color coded thermostat adjustment markings.
- Large, rocker type mode and blower switches.

- Internally mounted blower switch to choose cycled or constant blower operation.
- High pressure and low pressure safety controls to protect the unit components.
- Lockout circuit to shut down unit operation upon receipt of a fault indicator from the safety controls.
- A 24 volt control circuit allows for safe and easy diagnosis.

## Controls cont.

The user selects either “Heat/Cool” or “Fan Only” on the mode switch, then either “High” or “Low” at the blower speed switch. The temperature can be controlled by rotating the thermostat control knob.

### Unit Mounted Control



The “Fan Only” setting provides constant blower operation.

In the “Heat” mode, a call for heat by the thermostat closes the compressor contactor contacts, energizing the compressor, which will run until the thermostat is satisfied.

In the “Cool” mode, a call for cooling by the thermostat energizes the reversing valve and closes the compressor contactor contacts, energizing the compressor, which will run until the thermostat is satisfied.

If either the low or high pressure safety switches are opened, the compressor and reversing valve are disabled by the lockout relay. Unit operation will resume only after the voltage to the unit is interrupted or the mode switch is placed in the “Off” position.

### Optional Versatec Microprocessor Control Features

The Versatec microprocessor board provides control of the entire unit as well as outputs for status modes, faults and diagnostics. The control system is a microprocessor-based control board that is located in the unit control box. This feature is available for either unit mounted controls or optional remote wall mounted thermostat. A 9-pin low voltage terminal strip provides all necessary terminals for the wall mounted thermostat.

#### Startup

The unit will not operate until all the inputs and safety controls are checked for normal operating conditions.

#### Fault Retry

All faults are retried twice before finally locking the unit out to prevent nuisance service calls.

### Component Sequencing Delays

Components are sequenced and delayed for optimum unit performance.

### Emergency Shutdown

A grounded signal to common or connecting 24 VAC to the ES terminal places the controller into the emergency shutdown mode. The compressor and blower operation are suspended while in the emergency shutdown mode.

### Condensate Overflow Protection

The board incorporates an impedance liquid sensor at the top of the condensate drain pan. Upon a continuous 30-second sensing of the condensate, the cooling operation of the unit is suspended.

### Safety Controls

The microprocessor board receives separate signals from a high pressure switch for safety, a low pressure switch to prevent loss of refrigerant charge and a low suction temperature thermistor for freeze detection. Upon a continuous 30-second measurement of the fault (immediate for high pressure), compressor operation is stopped.

## Controls cont.

### Control Tables for Optional Versatec Microprocessor

#### Logic Board DIP Switch Settings

| Switch         | OFF  | ON  |
|----------------|--|---|
| <b>SW1 - 1</b> | Test - Selected timings sped up to facilitate troubleshooting    | Normal - Standard timings                           |
| <b>SW1 - 2</b> | Loop - Closed loop freeze detection setting (15°F)               | Well - Open loop freeze detection setting (30°F)    |
| <b>SW1 - 3</b> | Commercial - Enables NS features when TA32U02 thermostat is used | Normal - Standard thermostat operation              |
| <b>SW1 - 4</b> | IO Display* - Enables Input/Output display on external LED board | Normal* - Unit status display                       |
| <b>SW1 - 5</b> | Configures board for 2-speed compressor without blower           | Configures board for 2-speed compressor with blower |

#### Normal Control Timing

|  |  |
|--|--|
| <b>Blower off delay</b>                            | 30 seconds                             |
| <b>Compressor on delay</b>                         | 10 seconds                             |
| <b>Short cycle delay</b>                           | 5 minutes                              |
| <b>Minimum compressor on time</b>                  | 2 minutes (except for fault condition) |
| <b>High pressure fault recognition delay</b>       | Less than 1 second                     |
| <b>Low pressure fault recognition delay</b>        | 30 seconds                             |
| <b>Freeze detection fault recognition delay</b>    | 30 seconds                             |
| <b>Condensate overflow fault recognition delay</b> | 30 seconds                             |
| <b>Low pressure fault bypass delay</b>             | 2 minutes                              |
| <b>Freeze detection fault bypass delay</b>         | 2 minutes                              |
| <b>Power on delay</b>                              | 5 minutes                              |

#### Operational Logic

| Mode          | Inputs | Blower | Comp | RV  |
|---------------|--------|--------|------|-----|
| <b>Htg</b>    | Y      | ON     | ON   | OFF |
| <b>Clg</b>    | Y,O    | ON     | ON   | ON  |
| <b>Blower</b> | G      | ON     | OFF  | OFF |

#### Test Control Timing


|  |  |
|--|--|
| <b>Blower off delay</b>                            | 5 seconds                              |
| <b>Compressor on delay</b>                         | 2 seconds                              |
| <b>Short cycle delay</b>                           | 15 seconds                             |
| <b>Minimum compressor on time</b>                  | 5 seconds (except for fault condition) |
| <b>High pressure fault recognition delay</b>       | Less than 1 second                     |
| <b>Low pressure fault recognition delay</b>        | 30 seconds                             |
| <b>Freeze detection fault recognition delay</b>    | 30 seconds                             |
| <b>Condensate overflow fault recognition delay</b> | 30 seconds                             |
| <b>Low pressure fault bypass delay</b>             | 0 seconds                              |
| <b>Freeze detection fault bypass delay</b>         | 0 seconds                              |
| <b>Power on delay</b>                              | 15 seconds                             |
| <b>Fault off time</b>                              | 5 minutes                              |

#### Diagnostic Modes

| LED               | Current Fault Status<br>SW1 - #4 On, SW2 On | Inputs<br>SW1 - #4 Off, SW2 Off | Outputs<br>SW1 - #4 Off, SW2 On |
|-------------------|---|---------------------------------|---------------------------------|
| <b>Drain</b>      | Drain pan overflow                          | Y                               | Compressor                      |
| <b>Water Flow</b> | FD thermistor (loop <15°F, well <30°F)      | G                               | Blower                          |
| <b>High Press</b> | High pressure >600 psi                      | O                               | O                               |
| <b>Low Press</b>  | Low pressure <40 psi                        | ES                              | ES                              |
| <b>Air Flow</b>   | Not used                                    | Not Used                        | Not Used                        |
| <b>Status</b>     | Not used                                    | Not Used                        | Not Used                        |
| <b>DHW Limit</b>  | Not used                                    | Not used                        | Not used                        |
| <b>HWD</b>        | SW2 in the On position                      | Off position                    | On position                     |

## Controls cont.

### Optional FX10 Control



**Main FX 10 Board**

The optional FX10 control provides unparalleled capability in several areas including performance monitoring, zoning, humidity, energy management, and service diagnosis, and then communicates it all thru standard DDC protocols like N2, Lon and BACnet (MS/TP @ 19,200 Baud rate).

The most unique feature is integrating the FX10 into the Envision series as both the heat pump and DDC controller providing both a cost advantage and providing features not typically found on WLHP controls. This integration allows heat pump monitoring sensors, status and service diagnosis faults to be communicated thru the DDC direct to the building automation system (BAS), giving building supervisors detailed and accurate information on every piece of equipment without removing an access panel.

#### FX10 Advanced Control Overview

The Johnson Controls FX10 board is specifically designed for commercial heat pumps and provides control of the entire unit as well as input ports for Open N2, LonTalk, BACnet (MS/TP @ 19,200 Baud rate) communication protocols as well as an input port for a user interface. The user interface is an accessory item that can be used to aid in diagnostics and unit setup. A 16-pin low voltage terminal board provides terminals for common field connections. The FX10 Control provides:

- Operational sequencing
- High and low-pressure switch monitoring
- General lockout
- Freeze detection
- Condensate overflow sensing
- Lockout mode control
- Emergency shutdown mode
- Random start and short cycle protection

#### Short Cycle Protection

Allows a minimum compressor “off” time of four minutes and a minimum “on” time of two minutes.

#### Random Start

A delay of 1 to 120 seconds is generated after each power-up to prevent simultaneous startup of all units within a building after the release from an unoccupied cycle or power loss.

#### Emergency Shutdown

A field-applied dry contact can be used to place the control into emergency shutdown mode. During this mode, all outputs on the board are disabled.

#### Freeze Detection Limit

Field selectable for 15° or 30°F (-9° or -1°C)

#### Installation Options

- Standalone controlled by standard room thermostat
- Standalone with a Zone Temperature Sensor (must have user interface to change set points beyond the allowed +/- 5°F)
- Integrated into BAS by adding communication module

#### Accessory Outputs

Quantity 2. One cycled with blower, other with compressor.

#### User Interface

4 x 20 backlit LCD.

#### Optional Plug-in Communication Modules - (compatible with standard BAS protocols)

- Open N2
- LonTalk
- BACnet (MS/TP @ 19,200 Baud rate)

#### Display

Requires DLI Card/Kit. Up to 2 displays, either 1 local and 1 remote, or 2 remote. (A 2-display configuration requires identical displays.) Local display can be up to 3 meters from the controller, power supply, and data communication. Remote display can be up to 300 meters from the controller. Remote display must be independently powered with data communication done via 3 pole shielded cable.

#### Control Timing & Fault Recognition Delays

|   |               |
|---|---------------|
| Lead compressor “ON” delay.....               | 90 seconds    |
| (not applicable for single compressor models) |               |
| Minimum compressor “ON” time .....            | 2 minutes     |
| (except for fault condition)                  |               |
| Short cycle delay.....                        | 5 minutes     |
| Random start delay.....                       | 0-120 seconds |
| High pressure fault .....                     | <1 second     |
| Low pressure fault .....                      | 30 seconds    |
| Freeze detection fault.....                   | 30 seconds    |

## Controls cont.

|                                    |            |
|------------------------------------|------------|
| Condensate overflow fault .....    | 30 seconds |
| Low pressure fault bypass .....    | 2 minutes  |
| Freeze detection fault bypass..... | 2 minutes  |

### Optional FX10 Microprocessor and BAS Interface



The FX10 is a microprocessor based control that not only monitors and controls the heat pump but also can communicate any of this information back to the building automation system (BAS). This means that not only does the control monitor the heat pump at the unit you can also monitor and control many the features over the BAS. This clearly puts the FX10 in a class of its own.

The control will enumerate all fault conditions (HP, LP, CO, LOC, and Freeze Detection) over a BAS as well as display them on a medium user interface (MUI). HP, LP, CO and Freeze Detection faults can all be reset over a BAS. A Loss Of Charge fault can not be reset or bypassed until the problem has been corrected. A MUI is invaluable as a service tool for the building service team.

The unit can be commanded to run by a typical heat pump thermostat or run based on heating and cooling set points supplied by a BAS. The control board is wired with quick connect harnesses for easy field change out of a bad control board. An alarm history can be viewed through the MUI and will be held in memory until the unit is power cycled. Relative humidity can be read by a 0-5VDC humidity sensor that is displayed over the network.

The FX10 control has unused analog and digital inputs for field installed items such as air temperature, water temperature, CO<sup>2</sup> or current status switches. The control has unused binary and PWM outputs that can be commanded over the BAS for field use. An optional Medium User Interface (MUI) for control setup and advanced diagnostics is available with some mounting kits, MUIK3 - Panel mount version and the MUIK4 - Wall mount version.

### Zone Sensors

There are two options for zone sensors that can be used with the FX10 control. Both sensors use a Johnson controls A99 positive temperature coefficient type sensor. The TAXXJ02 has a set point adjustment now which will give the end user a +/- 5°F adjustment from the set point as well as a push button that can be used for temporary occupancy. The control leaves the factory set to operate with a TAXXJ02 sensor and can be changed to read the TAXXA04 sensor through a building automation system or with a user interface.

### Standard Features

- Anti Short Cycle
- High Pressure Protection
- Low Pressure Protection
- Freeze Detection
- Loss Of Charge Detection
- Random Start
- Display for diagnostics
- Reset Lockout at disconnect or through BAS
- 2 Accessory outputs
- Optional BAS add-on controls

### DDC Operation and Connection

Other optional network protocol boards that can be added to the FX10 are:

- Johnson Control N2
- LonWorks
- BACnet
  - MS/TP @ 19,200 Baud rate
  - Limit devices to 30 on a single trunk line.

### Control and Safety Feature Details Emergency Shutdown

The emergency shutdown mode can be activated by a command from a facility management system or a closed contact on BI-2. The default state for the emergency shutdown data point is off. When the emergency shutdown mode is activated, all outputs will be turned off immediately and will remain off until the emergency shutdown mode is de-activated. The first time the compressor starts after the emergency shutdown mode has been de-activated, there will be a random start delay present.

### Lockout Mode

Lockout mode can be activated by any of the following fault signals: refrigerant system high pressure, refrigerant system low pressure, freeze detection, and condensate overflow. When any valid fault signal remains continuously active for the length of its recognition delay, the controller will go into fault retry mode, which will turn off the compressor. After the Compressor short cycle delay, the compressor will attempt to operate once again. If three

## Controls cont.

consecutive faults occur in 60 minutes during a single heating or cooling demand, the unit will go into lockout mode, turning off the compressor, and enabling the alarm output until the controller is reset. If the control faults due to the low pressure input (BI-3) being open during the pre-compressor startup check, the control will go into lockout mode immediately, disabling the compressor from starting and enabling the alarm output (BO-6). The lockout condition can be reset by powering down the controller, by a command from the BAS, or by the holding the ESC and Return keys on the MUI for 5 seconds.

### Freeze Detection Limit (AI-5)

The freeze detection limit sensor will monitor the liquid refrigerant temperature entering the water coil in the heating mode. If the temperature drops below the freeze detection limit trip point for the recognition delay period, the condition will be recognized as a fault. The freeze detection limit trip point will be factory set for 30°F and will be field selectable for 15°F by removing a jumper wire on BI-5. The freeze detection limit fault condition will be bypassed 2 minutes at normal compressor startup, to allow the refrigeration circuit to stabilize. If the freeze detection limit sensor becomes unreliable at any time compressor operation will immediately be suspended until the problem is corrected. This should be displayed as an alarm on the BAS and the MUI. This alarm will be reported a “Water Low Temp Limit” fault.

### High Pressure (BI-11)

The high-pressure switch shall be a normally closed (NC) switch that monitors the systems refrigerant pressure. If the input senses the high-pressure switch is open it must disable the compressor output immediately and count the fault. The compressor minimum on time does not apply if the high-pressure switch opens. The compressor will not restart until the compressor short cycle time delay has been satisfied.

### Low Pressure (BI-3)

The low-pressure switch shall be a normally closed (NC) switch that monitors the systems refrigerant pressure. The input shall be checked 15 seconds before compressor start up to be sure the pressure switch is closed and then ignored for the first 2 minutes after the compressor output (BO-2) is enabled. If the switch is open continuously for (30) seconds during compressor operation the compressor output (BO-2) will be disabled. The compressor will not restart until the compressor short cycle time delay has been satisfied.

### Condensate Overflow

The condensate overflow sensing circuit will monitor the condensate level as a resistance input to AI-3. If the condensate water level rises resulting in the input resistance rising above the set point for the recognition delay period, the condition will be recognized as a fault.

The condensate will be subjected to a (30) second lockout delay which requires that the fault be sensed for a continuous (30) seconds before suspending unit operation.

### Alarm Output (BO-6)

The alarm output will be enabled when the control is in the lockout mode and will be disabled when the lockout is reset.

### Test Mode

Raising the zone temperature input (AI-1) reading to 180–220°F or by holding the ESC and down arrow keys on the MUI for 5 seconds will put the control into test mode. In test mode the random start delay and the compressor fixed on delay time will both be shortened to 5 seconds and the reversing valve will be allowed to cycle with out shutting down the compressor. If an MUI is connected to the control LED 8 will flash and the words “Test Mode Enabled” will be shown on the LCD display when the control is in test mode. Test mode will be disabled after a power cycle, 30 minute timeout, or by holding the ESC and Up arrow keys on the MUI.

## Sequence of Operation

### Power Fail Restart

When the controller is first powered up, the outputs will be disabled for a random start delay. The delay is provided to prevent simultaneous starting of multiple heat pumps. Once the timer expires, the controller will operate normally.

### Random Start Delay

This delay will be used after every power failure, as well as the first time the compressor is started after the control exits the unoccupied mode or the emergency shutdown mode. The delay should not be less than 1 second and not longer than 120 seconds. If the control is in test mode the random start delay will be shortened to 5 seconds.

### Compressor Fixed On Delay Time

The Compressor Fixed On Delay Time will ensure that the compressor output (BO2) is not enabled for (90) seconds after the control receives a call to start the compressor. This delay is adjustable from 30 – 300 seconds over a BAS or a MUI. If the control is in test mode the Compressor Fixed On Delay Timer will be shortened to 5 seconds.



## Controls cont.

### Compressor Minimum On Delay

The compressor minimum on delay will ensure that the compressor output is enabled for a minimum of (2) minute each time the compressor output is enabled. This will apply in every instance except in the event the high pressure switch is tripped or emergency shutdown then the compressor output will be disable immediately.

### Compressor Short Cycle Delay Time

The compressor short cycle time delay will ensure that the compressor output will not be enabled for a minimum of (5) minutes after it is disabled. This allows for the system refrigerant pressures to equalize after the compressor is disabled.

### Heating Cycle

On a call for heating, the blower enable output and accessory output 2 will turn on immediately after the random start delay timer has been satisfied. If the compressor short cycle time delay has been satisfied, the compressor will turn on after the blower enable and accessory output 2 are on and the fixed compressor start delay timers have been satisfied.

### Cooling Cycle

On a call for cooling, the blower enable output and accessory output 2 will turn on immediately after the random start delay timer has been satisfied. If the compressor short cycle time delay has been satisfied, the compressor will turn on after the blower enable and accessory output 2 are on and the fixed compressor start delay timers have been satisfied.

### MUI Alarm History Reporting

If a fault occurs the fault will be recorded in history for display on the medium user interface in the History Menu. Each fault type will be displayed in the history menu with a number between 0 and 3. A reading of 3+ will mean that fault has occurred more than three times in the past. The history menu can be cleared with a power cycle only. Alarm date and time are not included in the history.

## Inputs and Outputs Configuration Field Selectable Options

### Freeze Detection Limit Set Point (BI-5)

The freeze detection limit set point input allows you to adjust the freeze detection limit set point (AI-5). When the jumper is installed on BI-5 (Wire #24) the freeze detection limit set point is factory set for 30°F. When the jumper on BI-5 (Wire #24) is removed the freeze detection limit set point will be 15°F.

### Accessory Outputs (BO-7 and BO-8)

Accessory Output 1 will be energized 90 seconds prior to the compressor output being energized. Accessory Output 2 will be energized with the fan output (BO-1). When the corresponding compressor output is turned off the accessory output will be deactivated immediately. These outputs are selectable for normally open or normally closed operation through the Medium User interface or through the Building Automation System.

| SINGLE and DUAL STAGE WATER-TO-AIR  |       |                           |        |
|-------------------------------------|-------|---------------------------|--------|
| Input Name                          | Input | Output Name               | Output |
| Zone Temp 1                         | AI 1  | Fan Enable                | BO1    |
| Relative Humidity Input             | AI 2  | Comp – Low Capacity       | BO2    |
| Condensate Level                    | AI 3  | Reversing Valve           | BO3    |
| Universal Temp Input                | AI 4  | Comp – Full Capacity      | BO4    |
| Water Coil Low Temperature Limit    | AI 5  | Network Output/EH Output  | BO5    |
| Warm/Cool Adjust and Temp Occ       | AI 6  | Alarm                     | BO6    |
|                                     |       | Accessory 1 Output        | BO7    |
| Occupied                            | BI 1  | Accessory 2 Output        | BO8    |
| Emergency Shutdown                  | BI 2  | Network Controlled Output | BO9    |
| Stage 1 Low Pressure                | BI 3  |                           |        |
| Network Viewable Input 1            | BI 4  | ECM2 Fan                  | PWM1   |
| Water Coil Low Temp Limit Set Point | BI 5  | Network Controlled Output | PWM2   |
| Network Viewable Input 2            | BI 6  |                           |        |
| Thermostat Y1                       | BI 7  |                           |        |
| Thermostat Y2                       | BI 8  |                           |        |
| Thermostat O                        | BI 9  |                           |        |
| Thermostat G                        | BI 10 |                           |        |
| Stage 1 High Pressure               | BI 11 |                           |        |
| Compressor Proving                  | BI 12 |                           |        |
| XP10 Expansion Card                 |       |                           |        |
| Input Name                          | Input | Output Name               | Output |
| Unused                              | AI 1  | Unused                    | BO 1   |
| Unused                              | AI 2  | Unused                    | BO 2   |
| Unused                              | AI 3  | Unused                    | BO 3   |
| Unused                              | AI 4  | Unused                    | BO 4   |

## Control Accessories

### Zone Sensors

- TAXXJ02 Room Command Module
- TAXXA04 LCD Room Command Module
- A99 Sensor


### MUI (LCD User interface) for diagnostics and commissioning.

- MUIK3 - Panel Mount, Portable
- MUIK4 - Wall Mount



# Controls cont.


## FX10 User Interface (MUI) Physical Layout



- Alarm LED** - Indicates a **Lock-Out** or a bad **Freeze Sensor**
- Power LED** - Shows FX processor is operational
- LED 1** - Flashing shows **Compressor 1** running
- LED 2** - Flashing shows **Full Capacity Compressor** running

- LED 3** - On shows **Fan** running
- LED 4** - On shows **Reversing Valve** in cool
- LED 8** - Flashing shows unit in **'Test' Mode**


## MUI Menu Navigation for Single Compressor - Envision Water-to-Air



| Info            | Status       | Temps         | Outputs       | Settings        |
|-----------------|--------------|---------------|---------------|-----------------|
| WFI             | Run Mode     | Zone Temp     | nvoFanStatus  | Unit of Measure |
| Envision Series | Auto         | 77.2 °F       | ON            | F               |
| PROFXENV-XX     | Eff Occup'y  | Dis Air Temp  | CmpCmd Status | Occ Clg Setpt   |
| 3/8/07          | Occ          | 51.0 °F       | OFF           | 73.9 °F         |
|                 | Y1 Input     | Eff Clg Setpt | Cmp Capacity  | Occ Htg Setpt   |
|                 | OFF          | 70.0 °F       | OFF           | 69.9 °F         |
|                 | Y2 Input     | Eff Htg Setpt | Rev Valve     | Unocc Clg       |
|                 | OFF          | 66.0 °F       | Heat          | 84.0 °F         |
|                 | G Input      | Water Coil    | X1 Output     | Unocc Htg       |
|                 | OFF          | 77.8 °F       | OFF           | 60.0 °F         |
|                 | O Input      | Low WC Limit  | X2 Output     | DeHumSetpt      |
|                 | OFF          | 30.0 °F       | OFF           | 0%              |
|                 | Occ Input    | Humidity      | PWMOut        | SensorSelect    |
|                 | Occ          | 56.7 %RH      | 98%           | TAXXJ02         |
|                 | Temp Occ Inp | WarmCool AI   | BO5           |                 |
|                 | OFF          | 14.6          | OFF           |                 |
|                 | Condensate   | WarmCoolAdj   | BO9           |                 |
|                 | NML          | 0.2           | OFF           |                 |
|                 | Emg Input    |               | AO2 Output    |                 |
|                 | Run          |               | 0%            |                 |
|                 | Lo Press     |               |               |                 |
|                 | ON           |               |               |                 |
|                 | Hi Press     |               |               |                 |
|                 | ON           |               |               |                 |
|                 | Rndm Tmr     |               |               |                 |
|                 | 0            |               |               |                 |
|                 | Bl-4 Input   |               |               |                 |
|                 | OFF          |               |               |                 |

## Controls cont.


### MUI Menu Navigation for Single Compressor - Envision Water-to-Air



| Alarms          |
|-----------------|
| ALARM SUMMARY   |
| ^/High Pressure |

| Alm-History  |         |
|--------------|---------|
| Alarm        | #Events |
| Condensate   | 0       |
| Hi Pressure  | 0       |
| Low Pressure | 0       |
| Low Temp     | 0       |
| Bad Sensor   | 0       |

**NOTE:** This FX10 application implements an **alarm history** which is reset only by cycling power. This history shows on the Alm-History page. Any alarm showing 4+ events has occurred more than 4 times.

**Alarm lock-outs** are reset by cycling power, by pressing the "ESC" and Return  keys simultaneously for a minimum of 15 seconds, or by commanding the nviAlarmReset over the BAS network.

**Test mode** is enabled by holding the 'Esc' and Down Arrow simultaneously for a minimum of 15 seconds and releasing. Test mode times out after 30 minutes, and may also be ended by pressing 'ESC' and Up Arrow simultaneously and releasing. Test Mode bypasses the On Delay (90 sec) and Random Start timers for quicker troubleshooting. It also allows cycling the reversing valve without compressor shutdown.

## Unit Startup Notes

---

### Electrical Disconnect

Optional field installed console disconnect provides a permanent electrical connection to the main electrical supply branch. Wiring between the disconnect and the unit chassis is field supplied and allows the electrical power source to the chassis to be interrupted for unit servicing.

#### Non-Fused

Constructed of heavy gauge galvanized steel, the rocker style disconnect switch provides reliable electrical control. Wiring pigtails, using 12-gauge wires, are factory installed to simplify field wiring.

#### Fused

Similar in construction to the non-fused electrical disconnect. The fused disconnect is available in five models with equipment rated fuses to provide additional circuit protection. The fuses are panel mounted to allow easy inspection and removal without removing the cover on the disconnect.

- CFD-10 - 10 amp rated fuse
- CFD-12 - 12 amp rated fuse
- CFD-15 - 15 amp rated fuse
- CFD-20 - 20 amp rated fuse
- CFD-25 - 25 amp rated fuse

### Hydronic Loop Controller for Boiler/Tower Installations

The hydronic loop controller is a microprocessor based control panel for control of water loop heat rejector (tower), heat supplier (boiler), and/or water well pumps and circulation pumps. Includes audible and visual alarms, temperature indication, and add-on options of low switches, remote alarm sensor wells and pump alternator.

## Unit Startup Checklist/Unit Startup Steps

---

### Before Powering Unit, Check The Following:

- High voltage is correct and matches nameplate.
- Fuses, breakers and wire size correct.
- Low voltage wiring complete.
- Piping completed and water system cleaned and flushed.
- Air is purged from closed loop system.
- Isolation valves are open, water control valves or loop pumps wired.
- Condensate line open and correctly pitched.
- Transformer switched to 208V if applicable.
- Dip switches are set correctly, if applicable.
- Blower rotates freely
- Air filter is clean and in position.
- Service/access panels are in place.
- Return air temperature is between 50-80°F heating and 60-95°F cooling.
- Check air coil cleanliness to ensure optimum performance. Clean as needed according to maintenance guidelines. To obtain maximum performance the air coil should be cleaned before startup. A 10-percent solution of dishwasher detergent and water is recommended for both sides of coil, a thorough water rinse should follow.

### Startup Steps

**Note:** Complete the Equipment Start-Up/Commissioning Check Sheet during this procedure. Refer to thermostat operating instructions and complete the startup procedure.

1. Initiate a control signal to energize the blower motor. Check blower operation.
2. Initiate a control signal to place the unit in the cooling mode. Cooling setpoint must be set below room temperature.
3. Be sure that the compressor and water control valve or loop pump(s) are activated.
4. Verify that the water flow rate is correct by measuring the pressure drop through the heat exchanger using the P/T plugs and comparing to unit capacity data in specification catalog.
5. Check the temperature of both the supply and discharge water (Refer to Unit Operating Parameters tables).
6. Check for an air temperature drop of 15°F to 25°F across the air coil, depending on the fan speed and entering water temperature.
7. Adjust the cooling setpoint above the room temperature and verify that the compressor and water valve or loop pumps deactivate.
8. Initiate a control signal to place the unit in the heating mode. Heating set point must be set above room temperature.
9. Check the temperature of both the supply and discharge water (Refer to Unit Operating Parameters tables).
10. Check for an air temperature rise of 20°F to 35°F across the air coil, depending on the fan speed and entering water temperature.
11. Adjust the heating setpoint below room temperature and verify that the compressor and water valve or loop pump deactivate.
12. During all testing, check for excessive vibration, noise or water leaks. Correct or repair as required.
13. Set system to desired normal operating mode and set temperature to maintain desired comfort level.
14. Instruct the owner/operator in the proper operation of the thermostat and system maintenance.

**Note:** Be certain to fill out and forward all warranty registration papers.

## Operating Parameters

| Entering Water Temp °F | Water Flow gpm/ton | Cooling               |                         |           |            |                    |                     |
|------------------------|--------------------|-----------------------|-------------------------|-----------|------------|--------------------|---------------------|
|                        |                    | Suction Pressure psig | Discharge Pressure psig | Superheat | Subcooling | Water Temp Rise °F | Air Temp Drop °F DB |
| 30                     | 1.5                | 100 - 115             | 170 - 190               | 17 - 26   | 10 - 14    | 18 - 22            | 20 - 30             |
|                        | 3.0                | 115 - 125             | 150 - 170               | 20 - 29   | 7 - 11     | 8 - 10             | 20 - 30             |
| 50                     | 1.5                | 133 - 148             | 225 - 245               | 8 - 11    | 7 - 11     | 18 - 22            | 20 - 30             |
|                        | 3.0                | 129 - 144             | 185 - 205               | 8 - 11    | 6 - 10     | 8 - 10             | 20 - 30             |
| 70                     | 1.5                | 139 - 154             | 300 - 320               | 6 - 10    | 6 - 10     | 18 - 22            | 18 - 26             |
|                        | 3.0                | 137 - 152             | 250 - 270               | 6 - 10    | 6 - 10     | 8 - 10             | 18 - 26             |
| 90                     | 1.5                | 143 - 158             | 360 - 380               | 6 - 10    | 6 - 10     | 18 - 22            | 18 - 26             |
|                        | 3.0                | 141 - 156             | 330 - 350               | 6 - 10    | 6 - 10     | 8 - 10             | 18 - 26             |
| 110                    | 2.3                | 143 - 158             | 360 - 380               | 6 - 10    | 6 - 10     | 18 - 22            | 18 - 22             |
|                        | 3.0                | 141 - 156             | 440 - 460               | 6 - 10    | 6 - 10     | 8 - 10             | 18 - 22             |

| Entering Water Temp °F | Water Flow gpm/ton | Heating               |                         |           |            |                    |                     |
|------------------------|--------------------|-----------------------|-------------------------|-----------|------------|--------------------|---------------------|
|                        |                    | Suction Pressure psig | Discharge Pressure psig | Superheat | Subcooling | Water Temp Drop °F | Air Temp Rise °F DB |
| 30                     | 1.5                | 73 - 79               | 305 - 330               | 7 - 13    | 7 - 11     | 7 - 10             | 20 - 26             |
|                        | 3.0                | 79 - 85               | 315 - 345               | 7 - 13    | 7 - 11     | 3 - 6              | 20 - 26             |
| 50                     | 1.5                | 103 - 109             | 330 - 370               | 7 - 13    | 7 - 11     | 8 - 11             | 22 - 32             |
|                        | 3.0                | 115 - 130             | 350 - 380               | 7 - 13    | 7 - 11     | 4 - 7              | 22 - 32             |
| 70                     | 1.5                | 145 - 155             | 375 - 410               | 7 - 13    | 7 - 11     | 11 - 14            | 28 - 38             |
|                        | 3.0                | 155 - 165             | 415 - 435               | 10 - 14   | 7 - 11     | 7 - 10             | 35 - 45             |
| 90                     | 1.5                | 170 - 185             | 435 - 470               | 11 - 18   | 7 - 11     | 8 - 11             | 42 - 50             |
|                        | 3.0                | 174 - 190             | 465 - 500               | 11 - 18   | 7 - 11     | 8 - 11             | 42 - 50             |
| 110                    | 2.3                |                       |                         |           |            |                    |                     |
|                        | 3.0                |                       |                         |           |            |                    |                     |

**NOTES:** Cooling performance based on entering air temperatures of 80°F DB, 67°F WB.

6/20/11

Heating performance based on entering air temperature of 70°F DB.

## Operating Limits

| Operating Limits         | Cooling   |         | Heating |      |
|--------------------------|-----------|---------|---------|------|
|                          | (°F)      | (°C)    | (°F)    | (°C) |
| <b>Air Limits</b>        |           |         |         |      |
| Min. Ambient Air         | 45        | 7.2     | 45      | 7.2  |
| Rated Ambient Air        | 80        | 26.7    | 70      | 21.1 |
| Max. Ambient Air         | 100       | 37.8    | 85      | 29.4 |
| Min. Entering Air        | 50        | 10.0    | 40      | 4.4  |
| Rated Entering Air db/wb | 80.6/66.2 | 27/19   | 68      | 20.0 |
| Max. Entering Air db/wb  | 110/83    | 43/28.3 | 80      | 26.7 |
| <b>Water Limits</b>      |           |         |         |      |
| Min. Entering Water      | 30        | -1.1    | 20      | -6.7 |
| Normal Entering Water    | 50-110    | 10-43.3 | 30-70   | -1.1 |
| Max. Entering Water      | 120       | 48.9    | 90      | 32.2 |

**NOTE:** Minimum/maximum limits are only for start-up conditions, and are meant for bringing the space up to occupancy temperature. Units are not designed to operate at the minimum/maximum conditions on a regular basis. The operating limits are dependant upon three primary factors: 1) water temperature, 2) return air temperature, and 3) ambient temperature. When any of the factors are at the minimum or maximum levels, the other two factors must be at the normal level for proper and reliable unit operation.

## Pressure Drop

| Model | GPM | Pressure Drop (psi) |      |      |      |       |
|-------|-----|---------------------|------|------|------|-------|
|       |     | 30°F                | 50°F | 70°F | 90°F | 110°F |
| 09    | 1.2 | 1.0                 | 0.9  | 0.8  | 0.7  | 0.6   |
|       | 1.8 | 2.3                 | 2.2  | 2.0  | 1.9  | 1.8   |
|       | 2.5 | 3.8                 | 3.7  | 3.5  | 3.3  | 3.1   |
| 12    | 1.5 | 0.9                 | 0.8  | 0.7  | 0.6  | 0.5   |
|       | 2.3 | 1.7                 | 1.5  | 1.4  | 1.3  | 1.1   |
|       | 3.5 | 3.0                 | 2.7  | 2.5  | 2.4  | 2.2   |
| 15    | 2.0 | 1.7                 | 1.6  | 1.5  | 1.4  | 1.3   |
|       | 3.0 | 3.3                 | 3.2  | 3.0  | 2.9  | 2.8   |
|       | 4.5 | 5.7                 | 5.5  | 5.3  | 5.1  | 4.9   |
| 18    | 3.0 | 1.7                 | 1.6  | 1.5  | 1.4  | 1.3   |
|       | 4.0 | 4.1                 | 4.0  | 3.9  | 3.7  | 3.6   |
|       | 5.5 | 7.9                 | 7.6  | 7.4  | 7.2  | 6.9   |

6/10/13

## Compressor and Thermistor Resistance

### Compressor Resistance

| Model | 115/60/1    |             | 208-230/60/1 |             | 265/60/1    |             |
|-------|-------------|-------------|--------------|-------------|-------------|-------------|
|       | Run         | Start       | Run          | Start       | Run         | Start       |
| 09    | 0.77 - 0.89 | 1.79 - 2.05 | 3.65 - 4.19  | 3.75 - 4.31 | 3.73 - 4.27 | 4.45 - 5.13 |
| 12    | 0.77 - 0.89 | 1.79 - 2.05 | 3.35 - 3.85  | 2.80 - 3.22 | 3.73 - 4.27 | 4.45 - 5.13 |
| 15    |             |             | 2.74 - 3.16  | 2.60 - 3.00 | 3.03 - 3.49 | 2.39 - 2.75 |
| 18    |             |             | 2.24 - 2.58  | 2.84 - 3.26 | 3.03 - 3.49 | 2.39 - 2.75 |

6/10/13

### Thermistor Resistance

| Thermistor Temperature (°F) | Microprocessor Resistance (Ohms) | FX10 Resistance (Ohms) |
|-----------------------------|----------------------------------|------------------------|
| 5                           | 75757-70117                      | 746-770                |
| 14                          | 57392-53234                      | 775-803                |
| 23                          | 43865-40771                      | 808-836                |
| 32                          | 33809-31487                      | 841-869                |
| 41                          | 26269-24513                      | 875-903                |
| 50                          | 20570-19230                      | 910-938                |
| 59                          | 16226-15196                      | 946-974                |
| 68                          | 12889-12093                      | 981-1013               |
| 77                          | 10310-9688                       | 1019-1051              |
| 86                          | 8300-7812                        | 1058-1090              |
| 95                          | 6723-6337                        | 1097-1129              |
| 104                         | 5480-5172                        | 1137-1169              |
| 113                         | 4490-4246                        | 1179-1211              |
| 122                         | 3700-3504                        | 1221-1253              |
| 131                         | 3067-2907                        | 1261-1297              |
| 140                         | 2554-2424                        | 1305-1341              |
| 149                         | 2149-2019                        | 1350-1386              |

7/6/10

## Refrigerant Circuit Guideline

| Symptom                                       | Head Pressure   | Suction Pressure | Compressor Amp Draw | Superheat   | Subcooling  | Air Temp. Differential | Water Temp. Differential |
|---|---|------------------|---------------------|-------------|-------------|------------------------|--------------------------|
| Under Charged System (Possible Leak)          | Low   | Low              | Low                 | High        | Low         | Low                    | Low                      |
| Over Charged System                           | High  | High             | High                | Normal      | High        | Normal/Low             | Normal                   |
| Low Air Flow Heating                          | High  | High             | High                | High/Normal | Low         | High                   | Low                      |
| Low Air Flow Cooling                          | Low   | Low              | Low                 | Low/Normal  | High        | High                   | Low                      |
| Low Water Flow Heating                        | Low/Normal  | Low/Normal       | Low                 | Low         | High        | Low                    | High                     |
| Low Water Flow Cooling                        | High  | High             | High                | High        | Low         | Low                    | High                     |
| High Air Flow Heating                         | Low   | Low              | Low                 | Low         | High        | Low                    | Low                      |
| High Air Flow Cooling                         | Low   | High             | Normal              | High        | Low         | Low                    | Normal                   |
| High Water Flow Heating                       | Normal  | Low              | Normal              | High        | Normal      | Normal                 | Low                      |
| High Water Flow Cooling                       | Low   | Low              | Low                 | Low         | High        | Normal                 | Low                      |
| Low Indoor Air Temperature Heating            | Low   | Low              | Low                 | Normal      | High        | Normal                 | Normal/High              |
| Low Indoor Air Temperature Cooling            | Low   | Low              | Low                 | Normal/Low  | High        | Low                    | Low                      |
| High Indoor Air Temperature Heating           | High  | High             | High                | Normal/High | Normal/Low  | Low                    | Normal                   |
| High Indoor Air Temperature Cooling           | High  | High             | High                | High        | Low         | Low                    | High                     |
| Restricted TXV (Check Service Advisory)       | High  | Low              | Normal/Low          | High        | High        | Low                    | Low                      |
| Insufficient Compressor (Possible Bad Valves) | Low   | High             | Low                 | High        | Normal/High | Low                    | Low                      |
| TXV - Bulb Loss of Charge                     | Low   | Low              | Low                 | High        | High        | Low                    | Low                      |
| Scaled Coaxial Heat Exchanger Heating         | Low   | Low              | Low                 | Normal/Low  | High        | Low                    | Low                      |
| Scaled Coaxial Heat Exchanger Cooling         | High  | High             | High                | Normal/Low  | Low         | Low                    | Low                      |
| Restricted Filter Drier                       | Check temperature difference (delta T) across filter drier. |                  |                     |             |             |                        |                          |

7/6/10

## Heat of Extraction/Rejection Data

| Model | gpm | Heat of Extraction (HE) |      |      |      | Heat of Rejection (HR) |      |      |      |       |
|-------|-----|-------------------------|------|------|------|------------------------|------|------|------|-------|
|       |     | 30°F                    | 50°F | 70°F | 90°F | 30°F                   | 50°F | 70°F | 90°F | 110°F |
| 09    | 1.2 |                         | 6.2  | 8.1  | 10.6 |                        | 12.9 | 12.1 | 11.8 |       |
|       | 1.8 | 5.0                     | 6.6  | 8.5  | 10.8 | 13.9                   | 13.1 | 12.4 | 11.7 | 10.9  |
|       | 2.5 | 5.0                     | 6.9  | 9.0  | 10.9 | 14.0                   | 13.4 | 12.6 | 11.8 | 11.0  |
| 12    | 1.5 |                         | 7.8  | 10.1 | 12.4 |                        | 15.2 | 14.4 | 13.9 |       |
|       | 2.3 | 6.3                     | 8.1  | 10.4 | 12.6 | 16.3                   | 15.4 | 14.6 | 13.9 | 12.9  |
|       | 3.5 | 6.2                     | 8.6  | 10.9 | 12.8 | 16.3                   | 15.8 | 14.9 | 14.0 | 13.0  |
| 15    | 2.0 |                         | 10.3 | 12.4 | 16.4 |                        | 19.7 | 18.2 | 19.9 |       |
|       | 3.0 | 8.8                     | 10.7 | 12.9 | 16.7 | 19.4                   | 19.8 | 18.2 | 20.0 | 18.7  |
|       | 4.5 | 7.4                     | 11.3 | 13.7 | 17.0 | 19.5                   | 19.9 | 18.2 | 20.2 | 18.9  |
| 18    | 3.0 |                         | 12.0 | 15.2 | 17.6 |                        | 23.8 | 22.0 | 20.7 |       |
|       | 4.0 | 9.5                     | 12.2 | 15.5 | 17.9 | 23.4                   | 23.9 | 21.9 | 20.7 | 19.4  |
|       | 5.5 | 8.5                     | 12.6 | 16.0 | 18.2 | 23.5                   | 23.9 | 21.9 | 20.9 | 19.5  |

Data provided in MBtu/h

6/10/13

## Reference Calculations

| Heating Calculations:                    | Cooling Calculations:                            |
|--|--|
| $LWT = EWT - \frac{HE}{gpm \times 500}$  | $LWT = EWT + \frac{HR}{gpm \times 500}$          |
| $LAT = EAT + \frac{HC}{cfm \times 1.08}$ | $LAT(DB) = EAT(DB) - \frac{SC}{cfm \times 1.08}$ |
| $TH = HC + HWC$                          | $LC = TC - SC$                                   |
|  | $S/T = \frac{SC}{TC}$                            |

## Legend

### ABBREVIATIONS AND DEFINITIONS:

cfm = airflow, cubic feet/minute  
 EWT = entering water temperature, Fahrenheit  
 gpm = water flow in gallons/minute  
 WPD = water pressure drop, psi and feet of water  
 EAT = entering air temperature, Fahrenheit (dry bulb/wet bulb)  
 HC = air heating capacity, MBtu/h  
 TC = total cooling capacity, MBtu/h  
 SC = sensible cooling capacity, MBtu/h  
 KW = total power unit input, kilowatts  
 HR = total heat of rejection, MBtu/h

HE = total heat of extraction, MBtu/h  
 HWC = hot water generator capacity, MBtu/h  
 EER = Energy Efficient Ratio  
 = Btu output/Watt input  
 COP = Coefficient of Performance  
 = Btu output/Btu input  
 LWT = leaving water temperature, °F  
 LAT = leaving air temperature, °F  
 TH = total heating capacity, MBtu/h  
 LC = latent cooling capacity, MBtu/h  
 S/T = sensible to total cooling ratio



DEALER: \_\_\_\_\_

PHONE #: \_\_\_\_\_ DATE: \_\_\_\_\_

PROBLEM: \_\_\_\_\_


MODEL #: \_\_\_\_\_

SERIAL #: \_\_\_\_\_



### Startup/Troubleshooting Form


### COOLING CYCLE ANALYSIS



**Heat of Extraction/Rejection = GPM x 500 (485 for water/antifreeze) x ΔT**

**Note: DO NOT** hook up pressure gauges unless there appears to be a performance problem.

### HEATING CYCLE ANALYSIS



## Preventive Maintenance

---

### Water Coil Maintenance

1. Keep all air out of the water. An open loop system should be checked to ensure that the well head is not allowing air to infiltrate the water line. Lines should always be airtight.
2. Keep the system under pressure at all times. It is recommended in open loop systems that the water control valve be placed in the discharge line to prevent loss of pressure during off cycles. Closed loop systems must have positive static pressure.

**Note:** On open loop systems, if the installation is in an area with a known high mineral content (125 PPM or greater) in the water, it is best to establish with the owner a periodic maintenance schedule so the coil can be checked regularly. Should periodic coil cleaning be necessary, use standard coil cleaning procedures which are compatible with either the cupronickel or copper water lines. Generally, the more water flowing through the unit the less chance for scaling.

### Other Maintenance

#### Filters

Filters must be clean to obtain maximum performance. They should be inspected monthly under normal operating conditions and be replaced when necessary. Units should never be operated without a filter.

### Condensate Drain

In areas where airborne bacteria produce a slime in the drain pan, it may be necessary to treat chemically to minimize the problem. The condensate drain can pick up lint and dirt, especially with dirty filters. Inspect twice a year to avoid the possibility of overflow.

### Blower Motors

Blower motors are equipped with sealed ball bearings and require no periodic oiling.

### Air Coil

The air coil must be cleaned to obtain maximum performance. Check once a year under normal operating conditions and, if dirty, brush or vacuum (with a brush attachment) clean. Care must be taken not to damage the aluminum fins while cleaning.



**CAUTION: Fin edges are sharp.**

## Replacement Procedures

---

### Obtaining Parts

When ordering service or replacement parts, refer to the model number and serial number of the unit as stamped on the serial plate attached to the unit. If replacement parts are required, mention the date of installation of the unit and the date of failure, along with an explanation of the malfunctions and a description of the replacement parts required.

### In-Warranty Material Return

Material may not be returned except by permission of authorized warranty personnel. Contact your local distributor for warranty return authorization and assistance.

## Service Parts

|                          |                                       | Low Sill Consoles |           |           |           |
|--------------------------|---------------------------------------|-------------------|-----------|-----------|-----------|
|                          |                                       | 09                | 12        | 15        | 18        |
| Compressor               | Compressor 115/60/1                   | 34P590-09         | 34P591-09 | N/A       | N/A       |
|                          | Compressor 208-230/60/1               | 34P590-01         | 34P591-01 | 34P592-01 | 34P593-01 |
|                          | Compressor 265/60/1                   | 34P590-02         | 34P591-02 | 34P592-02 | 34P593-02 |
|                          | Run Capacitor 115/60/1                | 16P002D36         | 16P002D36 | N/A       | N/A       |
|                          | Run Capacitor 208-230/60/1            | 16P002D17         | 16P002D18 | 16P002D19 | 16P002D19 |
|                          | Run Capacitor 265/60/1                | 16P002D27         | 16P002D27 | 16P002D30 | 16P002D30 |
|                          | Sound Jacket                          | 92P504A01         |           |           |           |
| PSC Motor & Blower       | PSC Motor 115/60/1                    | 14P506-03         |           | N/A       |           |
|                          | PSC Motor 208-230/60/1                | 14P506-02         |           | N/A       |           |
|                          | PSC Motor 265/60/1                    | 14P506-02         |           | N/A       |           |
|                          | Blower Housing                        | 53P518-02         |           | N/A       |           |
|                          | Blower Capacitor 208-230/60/1         | 16P002D10         |           | N/A       |           |
|                          | Blower Capacitor 265/60/1             | 16P002D37         |           | N/A       |           |
| ECM Motor & Blower       | ECM Motor 115/208-230/265/60/1        | N/A               |           | 14P550-01 |           |
|                          | ECM Motor Module 115/208-230/265/60/1 | N/A               |           | 17P577-01 |           |
|                          | Blower Housing                        | N/A               |           | 53P514B01 |           |
| Refrigeration Components | Air Coil                              | 61P714-41         |           | 61P724-41 |           |
|                          | Coax                                  | 62P558-03         | 62P559-03 | 62P560-01 |           |
|                          | TXV                                   | 33P605-09         |           | 33P605-08 |           |
|                          | Reversing Valve                       | 33P502-05         |           |           |           |
|                          | Filter Drier                          | 36P500B01         |           |           |           |
| Controls                 | CCM Board                             | 17P535-03         |           |           |           |
|                          | Versatec Controller                   | 17P529A01         |           |           |           |
|                          | Contactors                            | 13P004A03         |           |           |           |
| Transformer              | Transformer 208-230/60/1              | 15P514-01         |           |           |           |
|                          | Transformer 265/60/1                  | 15P515-01         |           |           |           |
| Sensors & Safeties       | High Pressure Switch                  | 35P506B02         |           |           |           |
|                          | Low Pressure Switch                   | 35P506B01         |           |           |           |

Part numbers subject to change

12/13/2013

## Notes

---

## Revision Guide

---

| <b>Pages:</b> | <b>Description:</b>                 | <b>Date:</b> | <b>By:</b> |
|---------------|-------------------------------------|--------------|------------|
| All           | Updated with All-Aluminum Air Coils | 03 Mar 2014  | DS         |
| All           | Added 15 & 18 Models                | 09 Oct 2013  | DS         |
| 45            | Added Revision Table                | 09 Oct 2013  | DS         |







Manufactured by  
WaterFurnace International, Inc.  
9000 Conservation Way  
Fort Wayne, IN 46809  
[www.waterfurnace.com](http://www.waterfurnace.com)

Product: **Envision Series Low Sill Console**  
Type: Geothermal/Water Source Heat Pump  
Size: 0.75-1.0 Ton  
Document: Installation Manual

IM1010CNA 03/14