

Maintenance and Operating Instructions of oiled surfaces.

Maintenance.

Oiled surfaces shall be maintained with new oiling.

If oiled products are used outdoors, these should be maintenance oiled spring and autumn. For products indoors as needed.

New oiling should be preceded by polishing with sandpaper in size 220 to 240.

Grinding must be carried in the fiber direction! Not across fibers, this gives ugly cross scratches. After sanding, wipe surfaces with a well-wrung cloth.

New oiling is recommended immediately after polishing.

Select oil products for use, indoor or outdoor environment. Your local paint dealer can recommend the right oil product and quantity needed.

Never place hot and / or humid objects directly on the table surface.

Spills of leftovers or beverages should be removed immediately to eliminate stains / discoloration. Damp outsides of glasses, bottles, etc. with water, alcohol or otherwise, should not be left directly on the table surface.

Cleaning.

For tough dirt, use a mild cleaning agent (without ammonia and/or abrasives). The cleaner should be diluted according to the manufacturer's recommendations.

After wiping with a damp cloth, surfaces should be wiped with soft cloth that does not scratch the surface.

Never use solvents, acids, alkalis or other harsh detergents.

Never use steel wool, steelwool pad or other mechanical cleaning aids.

The above will result in permanent damage.