

**ABUS 16-channel / 8-channel
Network video recorder NVR
TVVR45021 / TVVR35011**



User manual

English

This user manual contains important information for installation and operation.

This should be also noted when this product is passed on to a third party.

Therefore look after these operating instructions for future reference!

A list of contents with the corresponding page number can be found in the index.



See **System operation** on page 80.




Pay attention to the information in the separate quick guide, plus the notes on the CD and in the accompanying documentation on “Web server control” and “Clients Software”. These can be found on the Internet under www.abus.com.


Device overview

i See **System operation** on page 80.


Front



Rearside TVVR35011



Rearside TVVR45021



System operation

General information

The device can be controlled as follows:

- Using the operating elements on the front of the device
- Using the remote control
- Using the USB mouse

Operating elements on the device



Note

Pay attention to the overview on page 79.

No.	Name Function
1	<p>Recorder operating keys:</p> <p>MENU:</p> <ul style="list-style-type: none"> • Calls up the main menu • Switches the key tones on and off (press and hold down for 5 seconds) <p>REC:</p> <ul style="list-style-type: none"> • Calls up the menu for manual recording <p>PLAY:</p> <ul style="list-style-type: none"> • Opens the playback menu <p>ZOOM+:</p> <ul style="list-style-type: none"> • Zooms in on the image section in PTZ mode <p>ZOOM-:</p> <ul style="list-style-type: none"> • Zooms out of the image section in PTZ mode • Switches the video output in live mode: Monitor – Spot Monitor or Video Out – Video Spot Out <p>FOCUS+:</p> <ul style="list-style-type: none"> • Sets the focus in PTZ mode <p>FOCUS-:</p> <ul style="list-style-type: none"> • Sets the focus in PTZ mode <p>IRIS+:</p> <ul style="list-style-type: none"> • Opens the iris <p>IRIS-:</p> <ul style="list-style-type: none"> • Closes the iris in PTZ mode <p>PTZ:</p> <ul style="list-style-type: none"> • Activates the PTZ control <p>MODE:</p> <ul style="list-style-type: none"> • Switches the screen view <p>KEYLOCK:</p> <ul style="list-style-type: none"> • Locks the control keys
2	<p>USB ports:</p> <p>For external USB 2.0 devices (e.g. mouse, external disk drive or DVR burner)</p>

No.	Name Function
3	<p>Camera selection keys (1, 2, 3...):</p> <p>Displays the camera status:</p> <ul style="list-style-type: none"> • White: Camera is connected • Blue: Connected camera is recording • Not lit: No camera connected <p>In the live view:</p> <ul style="list-style-type: none"> • Selects the camera and displays the full-screen view
4	<p>Directional keypad:</p> <p>During playback:</p> <ul style="list-style-type: none"> • ▲, ▼ Sets the speed • ◀, ▶ Previous / next day <p>In the live view:</p> <ul style="list-style-type: none"> • Selects the channel <p>In menus:</p> <ul style="list-style-type: none"> • Navigation <p>OK key:</p> <ul style="list-style-type: none"> • Press and hold for 5 seconds to switch the device on and off • Confirms the selection • Ticks / unticks the boxes <p>During playback:</p> <ul style="list-style-type: none"> • PLAY/PAUSE <p>Increased/ decreased playback speed:</p> <ul style="list-style-type: none"> • Normal playback speed
5	<p>Jog Shuttle:</p> <p>During playback:</p> <ul style="list-style-type: none"> • Outer ring (shuttle ring) change playback speed • Inner ring to play single frames in single mode <p>In menus:</p> <ul style="list-style-type: none"> • Inner ring moves the cursor upwards / downwards • Outer ring moves the cursor left / right <p>In the live view:</p> <ul style="list-style-type: none"> • Selects the channel
6	<p>NVR status LED:</p> <p>Displays the device status:</p> <ul style="list-style-type: none"> • White (constantly lit): System status is OK • White (flashing): System status is OK, recording settings are stored, surveillance mode is active • Blue (constantly lit): At least one camera is currently recording • Red (constantly lit): System maintenance required
7	<p>IR receiver:</p> <p>For the remote control</p>

Connections on the rear of the device



Note

Pay attention to the overview on page 79.


19

VGA:

- VGA monitor connection (9-pin), video output signal

No.	Name Function
8	VIDEO OUT: BNC video output BNC connector for video output for connecting a monitor as an alternative to VGA-/HDMI output (no. 18 / no. 19)
9	AUDIO OUT: <ul style="list-style-type: none"> • BNC (TVVR35011) audio output • (TVVR45021) cinch audio output (synchronised with video output)
10	LINE IN: <ul style="list-style-type: none"> • BNC (TVVR35011) audio input • Cinch audio input (TVVR45021) (is not recorded, only transmitted via network)
11	RS-232: <ul style="list-style-type: none"> • Serial port – no functionality
12	eSATA connection (TVVR45021 only) <ul style="list-style-type: none"> • Serial connection for external SATA hard disk drive
13	Mains power connection: <ul style="list-style-type: none"> • 100-240 VAC, 50-60 Hz (TVVR45021) • 12 VDC, 3A (TVVR35011)
14	Power switch
15	ALARM IN: <ul style="list-style-type: none"> • RS485 connection for PTZ cameras • Max. 16 alarm inputs / 4 alarm inputs ALARM OUT: Max. 4 relay outputs / 2 relay outputs
16	LAN: <ul style="list-style-type: none"> • Ethernet LAN connection
17	USB: <ul style="list-style-type: none"> • USB Connector
18	HDMI: <ul style="list-style-type: none"> • HDMI monitor connection

Remote control (TVAC40930)



Operating elements on the remote control



Note

Pay attention to the remote control diagram on page 67.

No.	Name Function
20	DEV: Assigns the remote control with the device ID
21	Alphanumeric keys: <ul style="list-style-type: none"> • Selects the camera (channel) in the live view • Entry of letters and digits in system fields
22	A: Changes the entry format (upper / lower case, symbols, digits)
23	PLAY: Starts playback
24	VOIP: <ul style="list-style-type: none"> • Not used
25	PREV: Changes the screen display in the live view
26	Navigation keys: During playback: <ul style="list-style-type: none"> • ▲, ▼ Sets the speed • ◀, ▶ Previous / next day In the live view: <ul style="list-style-type: none"> • Selects the camera (channel selection) In menus: <ul style="list-style-type: none"> • Navigation
27	ESC: <ul style="list-style-type: none"> • Not used

No.	Name Function
28	Not used
29	Not used
30	Zoom +: Zooms in on the image section in PTZ mode
31	F1: In lists: <ul style="list-style-type: none"> • Selects all available options
32	Zoom -: Zooms out of the image section in PTZ mode
33	F2: Switches between tabs
34	IRIS-: In PTZ mode: <ul style="list-style-type: none"> • Closes the iris
35	Focus-: In PTZ mode: <ul style="list-style-type: none"> • Brings the image section into focus
36	IRIS+: In PTZ mode: <ul style="list-style-type: none"> • Opens the iris
37	Focus+: In PTZ mode: <ul style="list-style-type: none"> • Brings the image section into focus

38	◀ : Pause / reverse playback
39	■: Stops playback
40	PTZ: Switches on PTZ control
41	Enter ▶ : <ul style="list-style-type: none"> • Confirms the selection • Ticks / unticks the boxes During playback: <ul style="list-style-type: none"> • PLAY/PAUSE Single play mode: <ul style="list-style-type: none"> • Advances by a single frame
42	MENU: <ul style="list-style-type: none"> • Calls up the main menu • Switches the key tones on and off (press and hold down for 5 seconds)
43	REC: Opens / starts manual recording
44	INFO: <ul style="list-style-type: none"> • Switches to another monitor in the live view
45	EDIT: General use: <ul style="list-style-type: none"> • Activates the text entry; backspace in text fields
46	⏻ POWER: Switches on/off (hold down for 5 seconds)

Mouse operation



Note

Further descriptions in these operating instructions are made with the mouse.

The device is suitable for use with a USB mouse. Connect the mouse to the USB port.

Button	Function
Left	Single-click: <ul style="list-style-type: none"> • Selection in menu, activation of an entry field or tab Double-click: <ul style="list-style-type: none"> • Switches between the screen display of single and multiple images in the live view and during playback Click and drag: <ul style="list-style-type: none"> • In PTZ mode: Camera control • Set-up of alarm areas or zones
Right	Single-click: <ul style="list-style-type: none"> • Calls up the pop-up menu
Scroll wheel	In the live view: <ul style="list-style-type: none"> • Shows previous / next camera In menus: <ul style="list-style-type: none"> • Scrolls through the menus

Geräteübersicht	3
Systembedienung	4
Allgemeines	4
Bedienelemente am Gerät	4
Anschlüsse an der Rückseite	5
Bedienelemente der Fernbedienung	7
Bedienung mit der Maus	7
Kurzanleitung	23
Bevor Sie beginnen	23
Festplatte installieren	23
Anschlüsse herstellen	23
Gerät konfigurieren	23
Wichtige Sicherheitshinweise	24
Symbolerklärung	24
Bestimmungsgemäße Verwendung	24
Allgemein	24
Stromversorgung	24
Überlastung/Überspannung	25
Kabel	25
Aufstellort/Betriebsumgebung	25
Fernbedienung	25
Wartung und Pflege	26
Zubehör	26
Inbetriebnahme	26
Kinder	26
Einführung	27
Allgemeine Informationen	27
Auspacken	27
Lieferumfang	27
Bildschirmtastatur	28
Gerät starten	28
Gerät ausschalten, sperren, neu starten	28
Statusanzeigen	29
Allgemeines	29
NVR Status LED	29
Kamera-Auswahltasten Status LED	29
Anzeigen am Monitor	29
Einrichtungsassistent	30
System einrichten	30
Administrator einrichten	30
Systemzeit-/und Datum	30
Netzwerkeinstellungen	31
Festplattenverwaltung	31
Einrichtung von Netzwerkkameras	31
Kameraaufzeichnung	32
Liveansicht	33
Überblick	33
Statussymbole	33
Popup-Menü bei Mausbedienung	33
Auswahlleiste im Kamerabild	34

Einstellungen	35
Kameraausgang einstellen.....	35
Wiedergabe in der Liveansicht.....	36
Allgemeines	36
Der Wiedergabe-Bildschirm	36
Steuerung über Kontrollfeld.....	36
Rechtsklick bei laufender Wiedergabe.....	37
Gerätemenü	38
Menü-Übersicht.....	38
Menübeschreibung	38
Einstellungen.....	39
Menübeschreibung	39
Konfiguration.....	40
Überblick.....	40
Allgemeine Einstellungen	40
Begriffe	41
Netzwerkaufbau.....	42
Netzwerk-Konfiguration	42
Warnung.....	48
Benutzer.....	48
Kamera.....	50
OSD	50
Bild	50
PTZ	51
Bewegung	51
Reaktion	51
Einrichten	53
Zeitplan.....	53
Kodierung	54
Erweiterte Einstellung (nur TVVR45021)	54
Urlaub	55
Festplatten	56
Festplatte einbauen.....	56
Parameter der Festplattenverwaltung	56
Festplatteneinstellungen der Kameras	57
Festplatten Einstellung.....	57
Festplattenstatus überprüfen.....	58
Festplattenalarme einrichten	58
Dauer	59
Ereignis	59
Markierung	59
Bild	60
Wartung.....	61
System Info	61
Protokoll Suche.....	61
Import / Export	62
Update.....	62
System Reset durchführen	63
Netzwerk	63
Video Export.....	65
Dauer	65
Ereignis (Ereignistyp ‚Alarmeinang‘).....	66

Contents

Ereignis (Ereignistyp ‚Bewegung‘)	66
Panikaufzeichnung	67
Rekord.....	67
Fortlaufende Sofortbilder	67
Alarm.....	67
Herunterfahren	68
Anzeige.....	68
Einstellungen: Aufzeichnung	68
Einstellungen: PTZ	68
Einstellungen: Netzwerk.....	68
Einstellungen: Alarm	68
Einstellungen: RS232.....	68
Störungsbehebung	69
Gerät reinigen und Pflege	69
Hinweis.....	69
Technische Daten	70
Entsorgen	72
Hinweis auf die Elektro- und Elektronik Altgeräte EG-Richtlinie.....	72
Hinweise zum Umgang mit Batterien.....	72
Wichtiger Hinweis zur Entsorgung von Batterien	72
Hinweis auf RoHS EG-Richtlinie.....	72
Glossar	73
Verwendete Fachbegriffe.....	73
Über das interne Festplattenlaufwerk.....	75
Device overview	79
System operation.....	80
General information	80
Operating elements on the device	80
Connections on the rear of the device	81
Operating elements on the remote control	83
Mouse operation	83
Quick guide.....	99
Before you start.....	99
Installing the HDD	99
Establishing the connections	99
Configuring the device	99
Important safety information	100
Explanation of symbols	100
Proper use	100
General information	100
Power supply	100
Overloading / overvoltage.....	101
Cables.....	101
Installation location / operating environment	101
Remote control.....	101
Care and maintenance.....	102
Accessories.....	102
Putting into operation	102
Children and the device	102

Introduction	103
General information	103
Unpacking the device.....	103
Scope of delivery	103
On-screen keyboard	104
Starting the device	104
Switching off, locking and rebooting the device.....	104
Status displays.....	105
General information	105
DVR status LED.....	105
Camera selection keys – status LED.....	105
Displays on the monitor	105
Setup wizard.....	106
Setting up the system	106
Setting up the administrator.....	106
Time / Date	106
Network Settings.....	107
HDD Management	107
Setting up network cameras	107
Camera recording	108
Live view	109
Overview	109
Status symbols	109
Pop-up menu for mouse operation	109
Selection bar in the camera image	110
Settings	111
Setting the camera output	111
Playback.....	112
General information	112
Playback screen	112
Using the control panel.....	112
Right click when playback is running	113
Main menu	114
Menu overview.....	114
Menu description	114
Menu description	115
Settings	116
Overview.....	116
General.....	116
Terms and definitions	118
Network layout.....	119
Network-configuration	119
Live view	125
Warning.....	125
User.....	125
Camera	127
OSD	127
Image	127
PTZ	128
Motion	128
Handling.....	128
Setting up.....	130

Contents

Schedule.....	130
Encoding.....	131
Confirm the settings by clicking Apply and leave the menu with Back.	132
Advanced settings (only TVVR45021)	132
Holidays.....	132
HDDs.....	133
Installing the HDD	133
HDD Management parameters	133
HDD settings of the cameras	134
Hard disc setting	134
Checking the HDD status	135
Setting up the HDD alarm	135
S.M.A.R.T.....	135
Continuous Recording	136
Event.....	136
Marking	136
Image	136
Maintenance	138
System Info	138
Log Search.....	138
Import / Export	139
Upgrade	139
Default.....	140
Network.....	140
Video Export.....	142
Duration.....	142
Event (event type 'Alarm input').....	143
Event (event type 'Motion')	143
Manual Management.....	144
Record.....	144
Continuous Capture	144
Alarm.....	144
Shutdown.....	144
Troubleshooting.....	145
Device cleaning and care	145
Note.....	145
Technical data	146
Disposal	148
Information on the EU directive on waste electrical and electronic equipment	148
Information on handling batteries	148
Important information on disposing of batteries.....	148
Information on the European RoHS directive	148
Glossary.....	149
Overview of specialist terms	149
Internal HDD	151
Overzicht.....	155
Bediening van het systeem.....	156
Algemeen.....	156
Bedieningselementen op de recorder	156

Aansluitingen aan de achterzijde	157
Bedieningselementen op de afstandsbediening	159
Bediening met de muis	159
Korte handleiding	175
Voordat u begint.....	175
Installeren van de harde schijf	175
Aansluiten	175
Apparaat configureren	175
Belangrijke veiligheidsinstructies.....	176
Verklaring van de symbolen.....	176
Gebruik volgens voorschrift	176
Algemeen	176
Voedingsspanning	176
Overbelasting/overspanning	177
Kabels	177
Plaatsing/werkomgeving	177
Afstandsbediening	177
Onderhoud en reiniging	178
Accessoires.....	178
Ingebruikname	178
Kinderen.....	178
Inleiding	179
Algemene informatie	179
Uitpakken	179
Leveringsomvang.....	179
Beeldschermtoetsenbord	180
Apparaat starten	180
Apparaat uitschakelen, vergrendelen, opnieuw opstarten.....	180
Statusindicatoren.....	181
Algemeen	181
DVR status LED.....	181
Selectietoetsen voor de camera's status LED	181
Informatie op de monitor	181
Hulpprogramma instellingen	182
Systeem configureren.....	182
Beheerder aanmaken	182
Datum / tijd.....	182
Netwerkinstellingen.....	183
Harde schijf beheer	183
Installatie van netwerkcamera's.....	183
Cameraopname	184
Live weergave	185
Overzicht	185
Statussymbolen	185
Pop-up menu bij bediening met de muis	185
Selectielijst in het camerabeeld	186
Instellingen.....	187
Camera-uitgang instellen	187
Weergave	188
Algemeen.....	188
Het weergavescherm	188

Contents

Bediening via de besturingstoetsen	188
Rechtermuisklik bij lopende weergave	189
Hoofd Menu	190
Overzicht	190
Menubeschrijving	190
Overzicht	192
Algemeen	192
Netwerkconfiguratie	194
Begrippen	194
Opbouw van het netwerk	195
Netwerkconfiguratie	195
Alarm	199
RS232	200
Live Kijken	200
Waarschuwing	201
Gebruikers	201
Kamera	203
OSD	203
Beeld	203
PTZ	204
Beweging	204
Acties	205
Instellen	206
Tijdschema	206
Codeer	207
Bevestig de instellingen door te klikken op Toepassen en verlaat het menu met Back.	208
Geavanceerde instelling (alleen TVVR45021)	208
Vakantie	208
Harde schijven	209
Harde schijf inbouwen	209
Parameters van het harde-schijfbeheer	209
Harde-schijfinstellingen van de camera's	210
HDD status controleren	211
Harde schijf alarm instellen	211
S.M.A.R.T.	211
Opname plannen	212
Bij Evenement	212
Markering	212
Beeld	213
Onderhoud	214
Systeem Informatie	214
Log zoeken	214
Configuratie	215
Firmware Upgrade	215
Standaard	216
Netwerk	216
Uitschakelen	217
Backup	218
Opname plannen	218
Evenement (gebeurtenistype „Alarm ingang”)	219
Evenement (gebeurtenistype „Beweging”)	219
Handmatig Management	220
Record	220

Opeenvolgende directe beelden	220
Alarm	220
Oplossen van storingen	221
Recorder reinigen en onderhouden	221
Opmerking	221
Technische gegevens.....	222
HDD opslagcapaciteit.....	223
Overzicht van verbinding combinaties	223
Afvoeren.....	224
Verwijzing naar de EG-richtlijn voor oude elektrische- en elektronische apparatuur	224
Informatie over de omgang met batterijen	224
Belangrijke opmerking met betrekking tot het afvoeren van batterijen.....	225
EU-richtlijn 2002/95/EG (RoHS-richtlijn).....	225
Glossarium	226
Gebruikte vaktermen.....	226
Over de ingebouwde harde schijf	228
Vue d'ensemble de l'appareil.....	232
Commande du système.....	233
Généralités.....	233
Dispositifs de commande sur l'appareil	233
Connecteurs au dos de l'appareil	234
Touches de commande sur la télécommande.....	236
Commande à la souris	236
Guide de démarrage rapide	252
Avant de commencer	252
Monjours du disque dur	252
Branchements.....	252
Configuration de l'appareil	252
Consignes de sécurité importantes	253
Explication des symboles.....	253
Utilisation appropriée	253
Généralités.....	253
Alimentation en courant	253
Surcharge/surtension.....	254
Câbles.....	254
Lieu d'installation/Environnement	254
Télécommande	254
Maintenance et entretien	255
Accessoires.....	255
Mise en service	255
Enfants	255
Préface	256
Informations d'ordre général	256
Déballage	256
Contenu de la livraison	256
Clavier virtuel	257
Démarrage de l'appareil.....	257
Arrêter, verrouiller, redémarrer l'appareil.....	257
Indicateurs d'état	258

Contents

Généralités.....	258
Voyant d'état DVR	258
Voyant d'état touches de sélection de caméra	258
Indicateurs sur le moniteur.....	258
Assistant de paramétrage.....	259
Paramétrage du système.....	259
Paramétrage de l'administrateur.....	259
Date / temps.....	259
Paramètres réseau	260
Gestion des disques durs	260
Configuration de caméras réseau.....	260
Enregistrement caméra.....	261
Mode live.....	262
Vue d'ensemble	262
Symboles d'état	262
Menu contextuel en cas de commande à la souris	262
Barre de sélection sur l'image de la caméra.....	263
Réglages.....	264
Configuration de la sortie caméra	264
Restitution	265
Généralités.....	265
L'écran de visualisation	265
Commande via champ de contrôle.....	265
Clic droit sur lecture en cours.....	266
Menu principal.....	267
Vue d'ensemble des menus	267
Description de la menu.....	267
Configuration de système.....	269
Aperçu	269
Général.....	269
Terminologie.....	270
Agencement d'un réseau	271
Configuration réseau	271
RS-232	276
Aperçu directe.....	276
Avertissement	277
Utilisateur	277
Caméra	279
Caméra	279
OSD	279
Image	279
PTZ	280
Mouvement	280
Alarme.....	281
Configuration d'Enregistrement.....	282
Configuration.....	282
Planning.....	282
Codage.....	283
Autres paramètres (TVVR45021 uniquement).....	284
Vacances.....	284
Disque management.....	285

Disque	285
Monjours du disque dur	285
Paramètres d'administration du disque dur	285
Configurations disques durs des caméras	286
Vérification de l'état du disque dur	287
Configuration des alertes de disque dur	287
S.M.A.R.T	287
Relecture	288
Enregistrement par horaire	288
Sur événement	288
Repérage	288
Image	289
Maintenance	290
Info système	290
Recherche de journal	290
Configuration	291
Mise à jour de firmware	292
Défaut	292
Réseau	292
Sauvegarder	294
Enregistrement par horaire	294
Événement (type d'événement « Entrée alarme »)	295
Événement (type d'événement « Détection de mouvement »)	295
Manuel Management	296
Enregistrer	296
Capture continue	296
Alarme manuel	296
.....	296
Dépannage	297
Entretien et nettoyage de l'appareil	297
Spécifications techniques	298
Capacité de mémoire HDD	299
Élimination des déchets	300
Remarque concernant la directive européenne sur les appareils électriques et électroniques	300
Remarques concernant la manipulation de piles	300
Remarque importante concernant l'élimination de piles	301
Remarque concernant la directive européenne RoHS	301
Glossaire	302
Termes techniques utilisés	302
A propos du mécanisme interne d'un disque dur	304
Oversigt over apparatet	308
Kvikguide	325
Før du starter	325
Installation af harddisken	325
Etablering af tilslutninger	325
Konfiguration af apparatet	325
Vigtige sikkerhedshenvisninger	326
Symbolforklaring	326
Korrekt anvendelse	326

Contents

Generelt	326
Strømforsyning.....	326
Overbelastning/overspænding.....	327
Kabler.....	327
Opstillingssted/driftsomgivelser	327
Fjernbetjening	327
Vedligeholdelse og pleje	328
Tilbehør	328
Idriftsættelse	328
Børn	328
Indledning	329
Generelle informationer	329
Udpakning	329
Leveringsomfang	329
Systembetjening	330
Generelt	330
Betjeningsenheder på apparatet.....	330
Tilslutninger på bagsiden.....	331
Fjernbetjeningens betjeningsenheder.....	331
Betjening med musen	332
Skærmtastatur	333
Start af apparatet	333
Nedlukning, Logout og genstart af apparatet.....	333
Statusvisninger	334
Generelt	334
DVR status-LED.....	334
Taster til valg af kamera status-LED.....	334
Visninger på monitoren	334
Indstillingsassistent	335
Indstilling af systemet.....	335
Indstilling af administratoren	335
Dato / tid.....	335
Netværksindstillinger.....	336
Forvaltning af harddisk.....	336
Indstilling af netværkskameraer	336
Kameraoptagelse.....	337
Live-visning	338
Overblik	338
Statussymboler.....	338
Popup-menu ved musebetjening	338
Menulinje i kamerabilledet	339
Indstillinger	340
Indstilling af kameraudgangen	340
Live-afspilning.....	341
Generelt	341
Afspilningsskærmen	341
Styring via kontrolfelt	341
Højreklik under løbende afspilning	342
Apparatmenu	343
Menuoversigt	343
Menubeskrivelse.....	343

Konfigurering	345
Overblik	345
Generelt	345
Begreber	346
Netværksopbygning	347
Netværkskonfiguration	347
RS-232	352
Live-visning	352
Advarsel	353
Bruger	353
Kamera	355
Kamera	355
OSD	355
Billede	355
PTZ	356
Bevægelse	356
Reaktion	357
Optagelse	358
Definition	358
Tidsplan	358
Kodning	358
Udvidede indstillinger (kun TVVR45021)	360
Ferie	360
HDD	361
Harddisks	361
Indbygning af en harddisk	361
Harddiskforvaltningens parametre	361
Kameraets harddiskindstillinger	362
Kontrol af harddiskstatus	363
Indstilling af harddiskalarmer	363
S.M.A.R.T.	363
Afspilning	364
Normal	364
Hændelse	364
Markering	364
Billede	365
Vedligeholdelse	366
Systeminfo	366
Protokolsøgning	366
Import / Eksport	367
Opdatering	368
Udførelse af Standard	368
Netværk	368
Video Export	370
Normal	370
Hændelse (hændelsestype ,Alarmindgang')	371
Hændelse (hændelsestype ,Bevægelsesregistrering')	371
Panikoptagelse	372
Optagelse	372
Fortløbende øjeblikkelige billeder	372
Alarm	372

Contents

Nedlukning	372
Rengøring og pleje af apparatet	373
Henvi sning	373
Udbedring af fejl	373
Tekniske data	374
HDD-lagerkapacitet	375
Bortskaffelse	376
Henvi sning til EF-direktivet vedr. gamle elektro- og elektronikapparater	376
Henvi sning vedr. håndteringen af batterier	376
Vigtigt henvi sning vedr. bortskaffelse af batterier	376
Henvi sning til RoHS EF-direktivet.....	376
Ordforklaring	377
Anvendte fagbegreber	377
Om det interne harddiskdrev	379
Przegląd urządzenia	383
Skrócona instrukcja	400
Zanim zaczniesz	400
Instalacja twardego dysku.....	400
Wykonanie podłączeń.....	400
Konfigurowanie urządzenia.....	400
Ważne zasady bezpieczeństwa	401
Objaśnienie symboli.....	401
Użycie zgodne z przeznaczeniem	401
Ogólne informacje.....	401
Zasilanie elektryczne	401
Przeciążenie/przepięcie	402
Kable	402
Miejsce ustawienia/środowisko pracy.....	402
Pilot	402
Konservacja i pielęgnacja	403
Akcesoria	403
Uruchomienie	403
Dzieci	403
Wprowadzenie	404
Ogólne informacje.....	404
Rozpakowanie	404
Zakres dostawy.....	404
Obsługa systemu	405
Ogólne.....	405
Elementy obsługowe na urządzeniu	405
Złącza z tyłu urządzenia	406
Elementy obsługowe pilota	407
Obsługa myszą	408
Klawiatura ekranowa.....	409
Uruchamianie urządzenia	409
Wyłączanie, blokowanie, restartowanie urządzenia	409
Wskaźniki stanu	410
Ogólne.....	410
Dioda LED stanu DVR	410

Klawisze wyboru kamery dioda stanu LED.....	410
Wskaźniki na monitorze	410
Asystent konfiguracji	411
Konfigurowanie systemu.....	411
Konfigurowanie administratora	411
Czas i data systemowa	411
Ustawienia sieci	412
Zarządzanie twardym dyskiem	412
Ustawianie kamer sieciowych	412
Zapis z kamery.....	413
Widok na żywo	414
Przegląd	414
Symbole stanu	414
Menu wyskakujące przy obsłudze myszą.....	414
Pasek wyboru na obrazie kamery.....	415
Ustawienia	416
Ustawianie wyjścia kamery	416
Odtwarzanie w widoku na żywo	417
Ogólne.....	417
Ekran odtwarzania	417
Sterowanie za pomocą pola kontrolnego	417
Klikięcie prawym przyciskiem podczas odtwarzania	418
Menu urządzenia	419
Przegląd menu	419
Opis menu	419
Ustawienia	420
Opis menu	420
Konfiguracja	421
Przegląd	421
Ustawienia ogólne	421
Pojęcia	422
Budowa sieci	423
Konfiguracja sieci	423
RS-232	428
Widok na żywo	428
Ostrzeżenie	429
Użytkownicy	429
Kamera.....	431
OSD	431
Obraz	431
PTZ	432
Ruch.....	432
Reakcja	432
Konfigur. nagrywania	434
Ustawianie	434
Harmonogram.....	434
Kodowanie.....	435
Zaawansowane ustawienia (tylko TVVR45021).....	435
Urlop	436
Zarządzanie HDD.....	437
Twarde dyski.....	437

Contents

Montaż twardego dysku	437
Parametry zarządzania twardymi dyskami.....	437
Ustawienia twardych dysków kamer.....	438
Ustawienia twardych dysków	438
Sprawdzanie stanu twardego dysku	439
Konfigurowanie alarmów twardego dysku.....	439
S.M.A.R.T.....	439
Odtwarzanie.....	440
Czas	440
Zdarzenie	440
Znacznik.....	440
Obraz	441
Konserwacja	442
Informacja o systemie	442
Wyszukiwanie protokołu	442
Import/Eksport.....	443
uaktualnienie.....	443
Resetowanie systemu.....	444
Net Detect	444
Eksport.....	446
Czas	446
Zdarzenie (typ zdarzenia,Wejście alarmowe')	447
Zdarzenie (typ zdarzenia,Ruch')	447
Zapis panika	448
Nagrywarka.....	448
Ciągłe obrazy natychmiastowe	448
Alarm.....	448
Zamknij.....	449
Usuwanie zakłóceń	450
Czyszczenie i pielęgnacja urządzenia	450
Wskazówka	450
Dane techniczne.....	451
Utylizacja.....	453
Uwaga: dyrektywa WE o wyeksploatowanych urządzeniach elektrycznych i elektronicznych	453
Zasady obchodzenia się z bateriami	453
Ważna informacja o utylizacji baterii.....	454
Informacja o Dyrektywie WE RoHS	454
Glosariusz.....	455
Zastosowane pojęcia fachowe.....	455
O wewnętrznym twardym dysku	457

Quick guide

Before you start

The following preparatory steps must be made:

1. Pay attention to the general information, safety information and notes on setting up and connecting the device (see page 80).
2. Check the contents of the package for completeness and damages.
3. Insert the batteries into the remote control.



Note

Pay attention to the information in the separate quick guide.

Installing the HDD



Warning

Switch off the device and disconnect it from the mains power supply.
Pay attention to the required earthing of the device to avoid static discharge.

1. Install one or more HDDs (see the separate quick guide).
2. Firstly, establish the connection to the motherboard using the red data cable (small connector).
3. Connect the power supply cable (large 5-pin connector).
4. Check that the connections are secure.
5. Close the housing.



Note

Only use HDD's that are approved for video recording and 24/7 usage.

Establishing the connections



Note

Pay attention to the minimum radius when laying cables. Do not kink the cable.

1. Connect all network cameras with your network
2. Connect the audio connections.
3. Connect the sensors to the alarm inputs.
4. Connect the monitor to the HDMI/VGA or BNC connection.
5. Connect the mouse to the USB port.
6. Establish a connection to the mains power supply.
7. Switch on the device using the POWER switch on the rear. The DVR status display on the front of the device lights up.

Configuring the device



Note

Pay attention to the information in the separate quick guide.

- Proceed through the individual steps in the setup wizard (see page 106).
- The following settings are configured in sequence:
 - Language selection for the user interface
 - Administrator setup
 - General settings (date, time etc.)
 - HDD management (initialisation etc.)
 - Network settings
 - Camera management



Note

Subsequent changes to the date and time can lead to the loss of data!



Note

Check the ABUS homepage (www.abus.com) if for this device any firmware updates are available and install these

- Pay attention to the menu overview on page 114, plus the notes and explanations on basic system operation on page.





Pay attention to the notes on the following:

Live view	Page 109
Playback	Page 112
PTZ	Page 128
Export	Page 138
Troubleshooting	Page 145

Important safety information

Explanation of symbols

The following symbols are used in this manual and on the device:

Symbol	Signal word	Meaning
	Warning	Indicates a risk of injury or health hazards.
	Warning	Indicates a risk of injury or health hazards caused by electrical voltage.
	Important	Indicates possible damage to the device/accessories.
	Note	Indicates important information.

The following labels are used in the text:

	Meaning
1. ...	Set of tasks or instructions with a defined sequence in the text
2. ...	Set of points or warnings without a defined sequence in the text
• ...	Set of points or warnings without a defined sequence in the text
• ...	Set of points or warnings without a defined sequence in the text

Proper use

Only use the device for the purpose which it was designed and built for. Any other use is considered inappropriate.

This device may only be used for the following purpose(s):

- This NVR recorder is used in combination with connected video signal sources (network cameras) and video output devices (CRT or TFT monitors) for object surveillance.

Note

Data storage is subject to national data-protection guidelines.

During installation, inform your customers regarding the existence of these guidelines.

General information

Before using the device for the first time, read the following instructions carefully and pay attention to all warnings, even if you are already familiar with electronic devices.



Warning

All guarantee claims become invalid for damages caused by non-compliance with these operating instructions.

We cannot be held liable for resulting damages.



Warning

We cannot be held liable in the event of material or personal damage caused by improper operation or non-compliance with the safety information.

All guarantee claims are invalid in such cases.

Keep this manual in a safe place for future reference.

If you pass on or sell the device, you must also include this user manual.

This device has been manufactured in accordance with international safety standards.

Power supply

- Only operate this device through a power source which supplies the mains power specified on the type plate.
- If you are unsure of the power supply at the installation location, contact your power supply company.



Warning

Avoid data loss!

Always use an uninterruptible power supply (UPS) with overvoltage protection.

- Disconnect the device from the mains power supply before carrying out maintenance or installation work.
- The on/off switch does not completely disconnect the device from the mains power supply.
- To disconnect the device completely from the mains power supply, the plug must be disconnected from the mains socket. Therefore, the device should be positioned so that direct and unobstructed access to the mains socket is guaranteed at all times and the plug can be disconnected immediately in an emergency.

To avoid the possibility of fires, the plug should always be disconnected from the network socket if the device is not used for long periods. Disconnect the device from the mains power supply before impending electrical storms, or use an uninterruptible power supply.



Warning

Never open the device on your own! There is a risk of electric shocks!

If it is necessary to open the device, consult trained personnel or your local maintenance specialist.

- The installation or modification of a HDD should only be made by trained personnel or your local maintenance specialist.



Warning

The installation of additional equipment or modification of the device invalidates your guarantee if not carried out by trained personnel.

We recommend having the HDD installed by a maintenance specialist.

Your guarantee is invalidated in the event of improper installation of the HDD.

Overloading / overvoltage

- Avoid overloading of mains sockets, extension cables and adapters as this can result in fires or electric shocks.
- Use overvoltage protection to prevent damages caused by overvoltage (e.g. electrical storms).

Cables

- Always hold cables by the connector, and do not pull the cable itself.
- Never touch the mains cable with wet hands, as this can lead to a short circuit or electric shock.
- Never position the device, furniture or other heavy items on the cable. Ensure that the cable does not become kinked, especially on the connector and sockets.
- Never knot the cable, and do not tie it to other cables.
- All cables should be laid so that they cannot be stepped on or cause an obstruction.
- A damaged mains cable can cause a fire or electric shock. Check the mains cable from time to time.
- Never modify or manipulate the mains cable or plug.
- Do not use plug adapters or extension cables that do not conform to the applicable safety standards, and do not make alterations to power supply cables or mains cables.

Installation location / operating environment

- Position the device on a firm, level surface and do not place any heavy objects on the device.
- The device is not designed for operation in rooms subject to high temperatures or moisture (e.g. bathrooms), or in excessively dusty rooms.
- Operating temperature and ambient humidity: -10 °C to 55 °C, maximum 85% relative humidity. The device may only be operated in moderate climate conditions.

Ensure the following:

- Sufficient ventilation must be present at all times (do not place the device in a storage rack, on thick carpets, on a bed or anywhere where the ventilation slots are covered. Make sure that a gap of at least 10 cm is present on all sides).
- The device must not be exposed to direct heat sources (e.g. heaters).
- The device must not be exposed to direct sunlight or strong artificial light.
- The device must not be placed in close proximity to magnetic fields (e.g. loudspeakers).
- Naked flames (e.g. candles) must not be placed on or near the device.
- Contact with spraying or dripping water and aggressive liquids must be avoided.
- The device must not be operated in close proximity to water, and must not be submerged under any circumstances (do not place objects containing water on or near the device, such as vases or drinks).
- Foreign objects must not penetrate the device.
- The device must not be exposed to strong variations in temperature, as this can lead to condensation and electrical short circuits.
- The device must not be exposed to excessive jolts or vibrations.

Remote control

- Remove all batteries if the device will not be used for a sustained period, as these can leak and damage the device.

Care and maintenance

Maintenance is necessary if the device has been damaged. This includes damage to the plug, mains cable and housing, penetration of the interior by liquids or foreign objects, exposure to rain or moisture or when the device does not work properly or has fallen.

- Disconnect the device from the mains power supply before maintenance (e.g. cleaning).
- If smoke develops or unusual noises or odours are detected, then switch off the device immediately and pull the mains plug from the socket. In such cases, the device should not be used until it has been inspected by a qualified technician.
- Maintenance work should only be carried out by qualified specialists.
- Never open the housing on the device or accessories. There is a risk of fatal injury due to an electric shock when the housing is opened.
- Clean the device housing and remote control with a damp cloth.
- Do not use solvents, white spirit or thinners as these can damage the surface of the device.
- Do not use any of the following substances:
- Salt water, insecticides, solvents containing chlorine or acids (ammonium chloride) or scouring powder.
- Gently rub the surface with a cotton cloth until it is completely dry.



Warning

The device works under dangerous voltages. The device must only be opened by authorised specialists. All maintenance and service work must be carried out by authorised firms. Improper repairs can expose device users to the risk of fatal injury.

Accessories

- Only connect devices that are suitable for the intended purpose. Otherwise, hazardous situations or damage to the device can occur.

Putting into operation

- Observe all safety and operating instructions before putting the device into operation for the first time.
- Only open the housing to install the HDD.



Warning

When installing the device in an existing video surveillance system, ensure that all devices are disconnected from the mains power supply and low-voltage circuit.



Warning

If in doubt, have a specialist technician carry out assembly, installation and connection of the device.

Improper or unprofessional work on the mains power supply or domestic installation puts both you and other persons at risk.

Connect the installations so that the mains power circuit and low-voltage circuit always run separately from each other. They should not be connected at any point or become connected as a result of a malfunction.

Children and the device

- Do not allow children access to electrical devices. Never allow children to use electrical devices without supervision. Children may not be able to accurately detect possible risks. Small parts can be life-threatening if swallowed.
- Keep batteries away from small children. Call for medical assistance immediately if a battery is swallowed.
- Keep packaging materials away from children (danger of suffocation).
- This device should not be used by children. If used improperly, spring-loaded parts can be ejected and cause injuries to children (e.g. eye injuries).

Introduction

Dear customers,

Thank you for purchasing this product.

This product complies with current domestic and European regulations. Conformity has been proven, and all related certifications are available from the manufacturer on request (www.abus.com).

To maintain this status and to guarantee safe operation, it is your obligation to observe these operating instructions!

Read the entire operating manual carefully before putting the product into operation and pay attention to all operating and safety information!

All company names and product descriptions are trademarks of the corresponding owner. All rights reserved.

In the event of questions, please contact your local maintenance specialist or dealer.



Disclaimer

These operating instructions have been produced with the greatest care. Should you discover any missing information or inaccuracies, please contact us under the address shown on the back of the manual. ABUS Security-Center GmbH does not accept any liability for technical and typographical errors, and reserves the right to make changes to the product and operating instructions at any time and without prior warning. ABUS Security-Center GmbH is not liable or responsible for direct or indirect damages resulting from the equipment, performance and use of this product. No forms of guarantee are accepted for the contents of this document.

General information

In order to use the device correctly, read this user manual carefully and keep it in a safe place for later use.

This manual contains instructions on recorder operation and maintenance. Consult an authorised specialist if the device needs to be repaired.

Unpacking the device

Handle the device with extreme care when unpacking it.

The packaging is made of reusable materials, and should always be passed on for recycling.

We recommend the following:

Paper, plastic packaging, cardboard and corrugated cardboard should be disposed of in the appropriate recycling containers.

If recycling containers are not available in your local area, then you can dispose of these materials as domestic waste.

If the original packaging has been damaged, inspect the device. If the device shows signs of damage, then return it in the original packaging and contact the manufacturer.

Scope of delivery


- ABUS 16 channel NVR / 8 channel NVR
- Mains cable
- SATA cable and screws for HDD
- Bracket and screws for server racks
- Software CD
- User manual (On CD or enclosed)
- Quickguide (On CD or enclosed)
- Terminal connectors
- BNC/RCA adapter (TVVR35011 only)

On-screen keyboard

The on-screen keyboard appears after clicking on a text entry field with the mouse:



The following screen keyboard appears during mere numerical entry:



The keys have the same function as on a computer keyboard.

- To enter the character, left-click the mouse.
- To finish data entry, press **Enter**.
- To delete the character in front of the cursor, click on **←**.
- To switch between upper and lower case, click on the framed **a** symbol. The current setting is displayed above the keyboard.
- To cancel the entry or exit the field, press **ESC**.

Starting the device



Important

The device must only be operated with the mains power specified on the type plate.


For safety reasons, use an uninterruptible power supply (UPS).

After the device has been connected to the power supply and the main switch on the rear of the device is switched on, the DVR status LED lights up.

1. The device carries out a self-test during the start-up procedure.
2. The setup wizard appears. Exit the wizard to access the live view.

Switching off, locking and rebooting the device

Click on "ShutDown" in the main menu. The overview appears.



1. To switch off the device, select **ShutDown** and confirm by pressing **Yes**. The device is then switched off.
 - Do not press any keys during the shutdown procedure.
2. To lock the system, select the corresponding **Lock** symbol on the left. The user interface is now locked and a password must be entered to access the menu.
3. To reboot the device, select the corresponding **Reboot** symbol on the right. The device is then rebooted.

Switching on the device

- Press and hold the **OK** key for 5 seconds to switch the device back on.

Status displays

General information

The following status displays indicate the current operating state:

- LEDs on the front of the device
- Acoustic signal tones
- Icons (display elements) on the monitor



Note

Pay attention to the information in the separate quick guide.

DVR status LED

State	Function
White (constantly lit):	System status is OK
White (flashing):	System status is OK, recording settings are stored, surveillance mode is active
Blue (constantly lit):	At least one camera is currently recording
Red (constantly lit):	System maintenance required

Camera selection keys – status LED

State	Function
Off:	No camera connected
White (constantly lit):	Camera is connected
Blue (constantly lit):	Camera is currently recording

Displays on the monitor

The device shows the date and time, camera name and whether a recording is in progress.

- Continuous recording: Blue “R”
- Alarm recording: Red “R”
- Motion recording: Yellow “R”

Setup wizard

Setting up the system


The setup wizard guides you through the necessary basic system settings. The DVR is then set up for recording and surveillance.



Note

All detailed settings can be found in the device menu (see overview on 114).

The language selection appears after switching on for the first time:



1. Click the entry field and select the desired language from the list. Click on **Apply** to continue. The following query appears:



- Click on **Next** to start the wizard.



Note

After the system is set up, you can untick the box. The setup wizard is then no longer started automatically.


Setting up the administrator



Warning

Note down the admin password. The following password is preset

“1 2 3 4 5”



1. Click the entry field and enter your admin password.
2. To assign a new password, tick the box next to **New Admin Password**.
3. Enter the new password and confirm in the field below.
4. Click on **Next**.

Time / Date



Enter the system time (date and time). Click on **Next** to accept the data.

Network Settings

Wizard	
Working Mode	Multi-address
Select NIC	LAN1
NIC Type	10M/100M/1000M Self-adaptive
Enable DHCP	<input checked="" type="checkbox"/>
IPv4 Address	192.168.0.50
IPv4 Subnet Mask	255.255.255.0
IPv4 Default Gateway	192.168.0.1
Preferred DNS Server	
Alternate DNS Server	
Default Route	LAN1

Note

To check whether DHCP can be selected (or if you have to set the IP address and other settings manually), consult your network administrator.

1. **DHCP activated:** If DHCP is set up in the network router, then tick the DHCP box. All network settings are then made automatically.
2. **DHCP not activated:** Enter the data manually (IPv4 address, IPv4 subnet mask and IPv4 default gateway = IPv4 address of the router). You can also optionally enter the address of the DNS server that you need for sending the E-mail.

A typical address specification is as follows:

- IPv4 address: 192.168.0.50
- IPv4 Subnet mask: 255.255.255.0
- IPv4 Default gateway: 192.168.0.1
- Preferred DNS server: 192.168.0.1

Note

When the device is accessed remotely via the internet, it should be given a fixed network address.

HDD Management

Wizard					
<input type="checkbox"/> Label	Capacity	Status	Property	Type	Free Space
<input checked="" type="checkbox"/> 1	1.863GB	Normal	R/W	Local	0KB

1. To set up a new hard disc, activate the “Check box” with a left click and then click on **Init**.



Warning

All data on the drive is deleted!

2. Confirm the prompt by pressing **OK**. The HDD is then set up for operation. The progress is displayed on the status bar.
3. Exit the setting by pressing **Next**.

Setting up network cameras

Assistent					
<input checked="" type="checkbox"/> Sync. Netzwerkkamera					
<input type="checkbox"/> Nr.	IP-Adresse	Anzahl Ka...	Gerät Typ	Protokoll	Port verwa
<input checked="" type="checkbox"/> 1	192.168.0.134	1	IPC	ABUS	80
<input checked="" type="checkbox"/> 2	192.168.0.171	1	IPC	ABUS	80
<input type="checkbox"/> 3	192.168.0.48	1	IPC	ABUS	80
<input type="checkbox"/> 4	192.168.0.184	1	IPC	ABUS	80

1. To setup network cameras, click on **Search**.
2. You can find an overview of all the network cameras found below.
3. Activate the “Checkbox” with a left-click to select the network camera and then click on Add.
4. Click on **Next**

Camera recording



1. At “Camera” select a camera with which you would like to record.
2. Activate the check box “Start recording”.
3. Select the type of recording. You can choose between “Time plan” and “Motion recognition”. Arm the motion detection inside the camera for recording motion.
4. Press **Copy** to take on the setting for other cameras. For this, select the cameras that appear in the new window. Activate the respective check box with a mouse click.
5. Finalize the setting and end the installation assistant with **OK**.

Live view

Overview

The live view starts automatically after the device is switched on.

You can also go back to the live view by pressing the **Menu** key repeatedly.



The following menus are found in the screen header:

- Menu
- Playback
- PTZ

The view pop-up menu is found on the right. The time and date are displayed on the right.

- To open the view pop-up menu, click on the rectangular symbol at the top-right of the menu bar.
- Click on one of the symbols to switch between the different views.



The signals of the connected cameras are displayed on the main screen.

- By double-clicking the left mouse key, you can display the camera image as a full-screen view or switch back to the original view.

Status symbols

- The following symbols are displayed depending on the operating status of the device:

Symbol	Meaning
R	Red: Event Recording <ul style="list-style-type: none"> • Event recording
R	Yellow: Motion Recording <ul style="list-style-type: none"> • Recording at motion detection
R	Blue: Recording <ul style="list-style-type: none"> • Continuous recording


Pop-up menu for mouse operation



Note

Press the right mouse button when the cursor is positioned on a live image.

The following settings can be made. The arrow pointing to the right indicates that a sub-menu is opened for selection:



Menu	Opens the main menu
Single Screen	Full-screen view for selected camera
Multi Screen	Various camera layouts
Previous Screen	Changing the presentation of the previous camera
Next Screen	Displays the next camera(s)
Start Auto-Switch	Starts the camera sequence
All-day Playback	Switches to playback mode
Aux Monitor	to spot monitor

**Note**

Stop Auto-switch:
Specify the delay in the image sequence in the display settings.

**Note**

Activation of "AUX monitor" without a connected spot monitor:
Mouse pointer function is deactivated.

Selection bar in the camera image

Click on the camera image in single or multi view. A selection bar appears:



(1) (2) (3) (4) (5) (6) (7) (8)

Nr.	Meaning of symbol
(1)	Area to move the miniature bar
(2)	Activate / deactivate manual recording
(3)	Immediate playback of the last 5 minutes
(4)	Activate / deactivate audio output of video output
(5)	Immediate image of selected channel
(6)	PTZ-control
(7)	digital zoom
(8)	Leaving the selection bar

Settings



Note

The live view can be set as follows.

Open the main menu, then click on “Configuration”. Then click on “Liveview”:



The following settings are available in the TAB “General”:

Video Output Interface	VGA/HDMI, Main CVBS Select the connection where the settings are changed
Live View Mode	Different camera layouts
Dwell Time	Switching time between the individual cameras and the sequence display
Enable Audio Output	Activate/deactivate audio output of the video output The audio signal is only given if the corresponding camera input is presented as a full screen.
Event Output	Allocate monitor for the output of events
Full Screen Monitoring Duration	in seconds, where the event on the allocated monitor will be displayed.
Post Event Display Time	in seconds, the duration of the Pop-up window when an event occurs.



Note

The recorder image can either be shown on an HDMI or a VGA monitor. The combination of HDMI and VGA output is supported.
The BNC output can be used either for a spot monitor or a separate monitor.



Note

VGA monitor connected:
A connected HDMI/VGA monitor automatically becomes the main monitor where the audio output is also assigned. The BNC output Video Spot Out output displays the cameras in sequence and in full screen.

If during the boot process of the DVR the HDMI/ VGA cable is not connected, the main video signal is displayed at BNC out-


put MAIN. Connect the HDMI/VGA cable and reboot the DVR in order to display the main video signal at the VGA output.

No HDMI/VGA monitor connected:
The main video signal is displayed at BNC output MAIN. The BNC output Video Spot Out output displays the cameras in sequence and in full screen.

Setting the camera output

You can display a maximum of 8/16 cameras (TVVR35011/TVVR45021) in the live cast at the same time.

1. Click on the TAB “View”.



2. Select the display mode.
 - 1 x 1
 - 2 x 2
 - 3 x 3
 - 1 + 5
 - 1 + 7
 - 4 x 4 (only TVVR45021)
3. The camera signal is assigned to the corresponding image section using the navigation keys.
 - “X” means that this camera is not displayed.
4. Click on **Apply** to accept the settings.

Playback

General information

Playback can be made in three different ways:

- Through the video search in the main menu
- From the live view
- Through the log file in the maintenance menu

Note
The buttons “previous file/day/event” are used differently depending on the playback mode:

Normal playback:
By pressing the button the playback jumps to the previous/next day.


Video Search:
By pressing the button the playback jumps to the previous/next event day.

Video Export:
By pressing the button the playback jumps to the previous/next file.

Note
It is possible to start a simultaneous playback with up to 4/8 cameras.

Playback screen


Playback is controlled on the control panel:



No.	Area
1	Running playback with date and time
2	Used to select the camera for feedback
3	Calendar with recording type
4	Control panel with time bar (see right)

Using the control panel

The control panel (4) is used for controlling the running playback. The symbols have the following meaning:



No.	Meaning / function
1	Zoom in / Zoom out the time line (24/12/1 hours)
2	Audio playback switch on/ off
3	Define start point / end point of a video for securing data
4	Add marking
5	Add user-defined marking
6	Administer marking
7	Backwards playback
8	Stop
9	Playback start / pause
10	Jump backward 30 seconds
11	Jump forward 30 seconds
12	Slow forward (slow motion) (1/16x - 1x)
13	Fast forward (1x - 16x)
14	Previous recording, previous day
15	Next file/day/event
16	Time bar: <ul style="list-style-type: none"> • Click on the time bar with the mouse to continue playback from another point • To start playback from a specific time, click on the slider and drag it to the required time
17	Recording type Blue = Continuous recording Red = Event recording
18	Hides the control panel

Playback

19 Exits playback

Note
 You can zoom in on the screen image.


- Right-click in the running playback.
- Please choose 'Digital Zoom'.
- The zoom mode is active. Shift the zoom area by means of the window in the miniature screen.
- Right-click the image to finish.

- In order to change the description of your marking, click on the process symbol. To remove, click on the delete symbol.

Right click when playback is running

Perform a right click on the playback image. The following options are available:

Please click on ,Tag management' (6):



Camera	Camera to be set
Digital Zoom	Enlarges the selected screen section digitally

Control Panel	Fades in/out the control field for playback control
Exit	Ends playback

Main menu

Menu overview

The following overview shows the main menus used to set and control the device.

Furthermore you can find important information regarding the device on the right side of the menu.

- Click on the menu to open it.
- Click **Exit** to close the menu overview.

The screenshot shows the main menu of an ABUS DVR. The interface is dark-themed. On the left is a sidebar with four menu items: Settings (wrench icon), Maintenance (gears icon), Video Export (folder icon), and Manual Management (hand icon). The main area features the ABUS logo at the top, followed by 'DVR Model' and 'Firmware Version V0.0.0, Build 000000'. Below this are two tables. The first table shows network settings for Port #1 and Port #2, including IP-Address, MAC Address, and DHCP status. The second table shows port settings for HTTP, DVR, and RTSP. At the bottom, there are 'Shutdown' and 'Exit' buttons.


	Port #1	Port #2
IP-Address		
MAC Address	00:00:00:00:00:00	00:00:00:00:00:00
DHCP	On	Off

	HTTP	DVR	RTSP
Port	80	8000	554

HDD #1	Normal	HDD #2	
HDD #3		HDD #4	
HDD #5		HDD #6	
HDD #7		HDD #8	

Menu description


Menü	Beschreibung	siehe S.
Settings	Includes the menus Configuration, Camera, Record, HDD, Playback.	90
Maintenance	Device maintenance (new firmware update, log search, import/export configuration, reset to factory defaults etc Display network utilization).	138
Video Export	Feature for exporting saved recordings onto USB media.	142
Manual Management	Starts or ends the manual video and image recording of selected cameras, as well as the manual switching of alarm outputs.	144
Shutdown	Lock, shutdown or restart the device.	144



Menu description

Menu	description	page
Configuration	Used for managing all device settings (General, Camera, Record, Network, Alarm, PTZ, RS232, Display, Exception, User).	116
Camera	Menu for setting camera parameters (OSD configuration, image mode, PTZ configuration, motion recognition etc.)	129
Record	Menu to set recording parameters (time plan, camera resolution, camera stream etc.).	130
HDD	Used for initialising or managing installed HDDs (assigning read/write functions, cameras, network HDD management etc.).	133
Playback	Parameter-controlled search for video or image recordings which were started by events like alarms or motion recognition, as well as alarm events and markings set in playback.	136

Settings Configuration



User	Adding and changing users, assigning authorisation rights	125
------	---	-----

Note
Pay attention to the instructions in the corresponding sections.


Note
The “Configuration” menu is used to manage all device settings.

Warning
Ensure that the date and time are set correctly. **IMPORTANT:** Subsequent changes to the settings can lead to data loss!
Ensure a data backup has been made in good time beforehand.

Overview

Menu	Setting	Page
General	Language, video, time, date, mouse pointer, password, time zones and other settings	116
Network	Required network settings (manual IP, DHCP, PPPOE, DDNS etc.)	119
Alarm	Assignment and parameterisation of detectors to alarm inputs and relay outputs	125
RS-232	Parameters on the serial connection	125
Live View	Display settings and assignment of the event output	125
Warning	Behaviour of the device in exceptional cases (HDD full, network disconnected etc.)	125

General



“General” tab	Setting
Language	Language on the OSD
CVBS Output Standard	PAL / NTSC
Resolution	Resolution on the monitor
Time Zone	GMT (Greenwich Mean Time)
Date Format	MM-DD-YYYY, DD-MM-YYYY, YYYY-MM-DD
System Date/Time	Date and time
Mouse Pointer Speed	Set on the scroll bar (left = low speed; right = high speed)
Enable Wizard	Box not ticked: Wizard will not appear after restart of the device. Box ticked: Wizard will appear after restart of the device.
Enable ID Authentication	Box not ticked: In order to enter a menu no password has to be entered. At access by network the password has to be entered. Box ticked: Password must be entered in order to

	use the menu.
--	---------------

Settings

TAB "DST settings"	Setting
Auto DST Adjustment	With an activated check box, the device converts automatically to summer time.
Enable DST	With an activated check box, an exact start / end date can be selected
From / To	Date of DST start / end
DST Bias	Daylight Saving Time Bias: Correction of the DST to the reference time
TAB "More Settings"	Setting
Device Name	Unique specification of the device
Device Number	Used for unique identification when using remote control
Output Mode	Makes the image softer or sharper.
CVBS Output Brightness	Scroll bar (left = darker; right = brighter)
Operation Timeout	Never / 1 to 30 minutes – regulates how long the menu is shown

Confirm the settings by clicking **Apply** and leave the menu with **OK**.

Network configuration

Correct network settings are essential in the following cases:

- When using remote control of the device and surveillance over your server



Note

Please read the following basic instructions before setting up the device.

A network is a connection of at least two network-capable devices.

Transmission types:

- Wired networks (e.g. CAT5 cable)
- Wireless networks (WLAN)
- Other transmission types (Powerline)

All systems have certain similarities, but can also differ in many ways.

Terms and definitions

An overview of relevant terms when using the device in a network can be found below.

Parameter	Setting
IP address	An IP address is the unique address of a network device within a network. This address may only appear once within a network. Certain IP address ranges are reserved for public networks (e.g. the Internet).
Private address range	e.g. 10.0.0.0 – 10.255.255.255 Subnet mask: 255.0.0.0 172.16.0.0 - 172.31.255.255 Subnet mask: 255.255.0.0 192.168.0.0 - 192.168.255.255 Subnet mask: 255.255.255.0
Subnet mask	A subnet mask is a bit mask used for making decisions and assignments during routing. 255.255.255.0 is the standard subnet mask in home networks.
Gateway	A gateway is a network device which allows all other network devices to access the Internet. This can be the computer connected to the DSL modem or – usually – the router or access point within the network.

Parameter	Setting
Name server	The name server is responsible for assigning a unique IP address to a web address or URL (e.g. www.google.de). Also known as DNS (Domain Name Server). When a domain name is entered into a browser, the DNS searches for the corresponding IP address of the server and forwards the query on. The IP of the provider's DNS can be entered here. However, it is often sufficient to select the IP of the gateway. This then forwards the queries independently to the provider DNS.
DHCP	The DHCP server automatically assigns the IP address, subnet mask, gateway and name server to a network device. DHCPs are available in current routers. The DHCP service must be specially set and activated (see the corresponding manual for more information). Note: When using fixed IP addresses and a DHCP server, make sure that the fixed IP addresses are outside the address range assigned by DHCP. Otherwise, problems could occur.

Port	A port is an interface used for communication by different programs. Certain ports are fixed (23: Telnet, 21: FTP), whilst others can be freely selected. Ports are important for different applications (e.g. external access to the device over a browser).
MAC address	The MAC address (Media Access Control or Ethernet ID) is the specific hardware address of the network adapter. This is used for the unique identification of the device in a computer network.

Network layout


The device must be physically connected to the network over a CAT5 cable (see the connections on page 81).

Note
Pay attention to the specific information and instructions on the network devices.

Several switches, routers and access points can be connected to each other. Firewalls and other security software can affect the network.

Warning
When using a router, the network clients (e.g. the recorder) can be connected to the Internet and vice versa. Make sure to use protective measures to prevent unauthorised external access (e.g. firewall, changing passwords, changing ports)!

Network-configuration



TAB	Settings
General	Settings for the local net and selecting the network mode.
PPPOE	PPPOE is used on ADSL connections and when using modems in Germany. Click on "Set" to enter the access data (ID and password) for your provider.
DDNS	Server for Dynamic Domain Name System management. Used for updating host names or DNS entries
NTP	Network Time Protocol Server for time synchronisation
Email	Used to specify the e-mail settings which are sent as an e-mail to a specific address in the event of an alarm.
FTP	Configure the address of an FTP server and the path for saving the files.
SNMP	Configure the parameters to receive information about the device status.
More Settings	Communication and HTTP port.

TAB General


Parameter	Setting
Working Mode	See explanation, p. 118
Select NIC	Select the connection for which to make the network settings.
NIC Typ	Set the transmission speed of the installed network card here. Tip: 10M/100/1000M self adaptive
Enable DHCP	Tick the box if the IP addresses are assigned dynamically via DHCP in the network. DHCP activated: Subsequent entry fields are inactive (parameters assigned via DHCP). Note: If the IP addresses are assigned manually, ensure that DHCP is not active (box not ticked).
IPv4 Adress	Address of the network device in the network (manual assignment)
IPv4 Subnet Mask	Usually 255.255.255.0
IPv4 Default Gateway	Address of the gateway for Internet access
IPv6 Adress 1	Currently no functioning
IPv6 Adress 2	Currently no functioning
IPv6 Standard Gateway	Currently no functioning
MAC Adress	Hardware address of the installed network card
MTU (Bytes)	Describes the max. size of the largest protocol data .
Preferred DNS Server	Address of the Domain Name Server (usually the IP address of the gateway)
Alternate DNS	IP address of the alternative DNS server
Default Route	LAN 1 or LAN 2



Note

In certain modes some of these settings cannot be selected.

PPPOE




1. Tick the PPPOE box, enter the user name (Internet access ID) and password, then confirm the password.
2. Confirm the settings by pressing **Apply**.



Warning


Use PPPOE only if there is no router available.

DDNS



1. To use the ABUS DDNS function, you must first set up an account under www.abus-server.com. Please note the FAQs on the website when doing this.
2. Tick the “Enable DDNS” box, enter ‘ABUS DDNS’ as the “DDNS Type”, then enter www.abus-server.com or “62.153.88.107” under “Server Address”.
3. Confirm the settings by pressing **Apply**. The IP address of your Internet connection is now updated on the server every minute.

NTP




Note

The recorder can synchronise the time with an external server. Several server addresses are available on the Internet for this purpose.

1. Tick the “Enable NTP” box and then enter the interval at which the synchronisation should be made again. Enter the IP address of the NTP server and the NTP port.
2. Confirm the settings by pressing **Apply**.

Email

In the event of an alarm, the device can send a message by e-mail. Enter the e-mail configuration here:



Parameter	Setting
Enable Server Authentica...	Tick the box when authentication is made on the server of the Internet provider
User Name	E-mail account at the provider
Password	Password connected to the e-mail account
SMTP Server	SMTP server address of the provider
SMTP Port	Enter the SMTP port here (Default: 25)
Enable SSL	Tick the box to activate the e-mail encryption
Sender	Name of the sender

Sender's Adresse	Corresponding e-mail address for the e-mail account
Sender's Re-ceiver	Select three possible recipients for the e-mail
Receiver	Enter the name of the recipient here
Receiver's Adresse	Enter the e-mail address of the recipient here
Enable Attached Picture	Tick the box when camera images should also be sent with the e-mail as photo files
Interval	Select the interval between the individual recordings (2 to 5 seconds)

1. Enter the parameters of the e-mail notification.
2. Click on **Test** to send a test e-mail.
3. Please clarify if your settings are correct and you have received a confirmation mail. Then click on **Apply**.



Note

The device sends an e-mail to the specified recipients.

If the e-mail is not received, check the settings and correct them.


If necessary, check the spam filter of your e-mail client.



Note

Because of the cause of compatibility please do only use E-Mail clients where a dial-up via SMTP is possible.

SNMP



Parameter	Setting
Enable SNMP	Activate the checkbox to create a connection to SNMP software
SNMP Version	Version of the SNMP system
SNMP Port	Enter the SNMP port (Default: 161)
Read Community	Enter the “Key” according to the settings of your SNMP software.

Settings


Write Community	Enter the "Key" according to the settings of your SNMP software.
Trap Adresse	Enter the IP address of the SNMP manager
Trap Port	Enter the trap port (Default: 162)

i Note

SNMP is used for monitoring the device status. For this you need SNMP software not available from ABUS.

Confirm the settings by clicking **Apply** and leave the menu with **Back**.

More settings



Parameter	Setting
Alarm Host IP	Network address of the PC where the CMS is installed
Alarm Host Port	Port of your CMS Station
Server Port	Port for data communication (General: 8000)
HTTP Port	Port for web server (General: 80)
Multicast IP	In order to minimize traffic you can enter a Multicast IP. The IP address has to match the IP address of the PC running the CMS software.
RTSP Service Port	RTSP-port (Default: 554)

i Note

Server port 8000 and HTTP port 80 are the standard ports for remote clients and remote Internet browser access.

i Note

With Alarm Host IP/Port you configure the address of your CMS software. The CMS software is notified when there is an alarm, and performs various reactions depending on the setting.


Alarm

Alarm status



Here you see a list with all the alarm inputs and outputs and their current status.

Alarm input




- Select a reaction in the case of an alarm by clicking the 'Setting' symbol for "Handling".

Parameter	Setting
Alarm Input No.	Select the alarm input to make the settings
Alarm Name	Enter a clear description here (e.g. door contact on warehouse)
Type	N.O.: Normally open circuit N.C.: Normally closed circuit

- Activate the alarm input by ticking the checkbox for "Setting".
- Define the response of the recorder when there is an alarm under "Handling".
- Click **Copy** to apply these settings for other cameras.
- Confirm the settings by clicking **Apply** and leave the menu with **OK**.


Handling

TAB Trigger channel



Tick a checkbox to select which camera channel is triggered in the case of an alarm.

TAB Arming schedule



- Define the time at which the responses selected in the TAB "Handling" are activated when there is an alarm.
- Click **Copy** to apply these settings for other days of the week or the entire week.

TAB Handling



Define the response in the case of an alarm:

Parameter	Setting
Full Screen Monitoring	A message appears on the monitor.
Audible Warning	The device emits a repeating tone.
Notify Surveillance Center	Sends an alarm signal to a PC with ABUS CMS software. The software must be enabled and the recorder set to surveillance mode on the PC.
Send E-Mail	An e-mail is sent to a specific e-mail address (see page 119).
Trigger Alarm Output	see also page Fehler! Textmarke nicht definiert.

Confirm the settings by clicking **Apply** and leave the menu with **OK**.




Note

To record with the aid of an alarm, you must set up the schedule under **Recording** (see p. 130).

TAB PTZ Linking

Currently no functioning.

Alarm output



1. Select an alarm output to be configured in the drop-down menu under "Alarm Output No."
2. Assign any name to the alarm output in "Alarm Name".
3. In "Dwell Time", select how long the alarm is triggered for.
4. In "Handling", select the schedule for the alarm output.
5. Click **Copy** to apply these settings for other alarm outputs.
6. Confirm the settings by clicking **Apply** and leave the menu with **OK**.

Settings

RS-232

Currently no functioning.

Live view

See page 109.

Warning



Note


Enter the trigger under “Exception Type”, for example:

- HDD Full
- Disconnected

After doing this, specify the device behaviour.

Confirm the settings by clicking **Apply** and leave the menu with **Back**.

User




Warning

Note down the admin password.
The following password is preset

“1 2 3 4 5”

You can add new users, delete existing users and change the settings in the “User Management” menu.

1. To add a new user, select **Add**.



Parameter	Setting
User Name	Unique identification
Password	Access code for the device (device management) Note: Change all passwords on a regular basis, using a combination of letters and numbers. Note down all passwords in a safe place.
Confirm	Enter the access code again here
Level	IMPORTANT: More access rights can be set on the Manager level than on the User level.
User's MAC Address	MAC address of the network adapter on the PC of the corresponding user Note: This limits access to the PC whose MAC address is entered here!

2. Enter the name and password and confirm the password in the field below.
3. Select the level and enter the MAC address.
4. Confirm the settings by clicking **Apply**.




Warning

Pay attention to the instructions below on assigning access rights.

Permission

Control the access rights of the user by clicking the “Permission” symbol. Only the access data of users added manually can be changed:



Note

The user can make the settings locally (i.e. on the device) or change the parameters.

The user can access the device via the network connection.

The “Camera Permission” tab is used to set access rights for individual cameras (network or local).

Parameter	Setting
Local Configuration	Local Log Search Local Parameters Settings Local Advanced Operation Local Shutdown / Reboot
Remote Configuration	Remote Log Search Remote Parameters Settings Remote Serial Port Ctnrol Remote Video Output Ctnrol Two-way Audio Remote Alarm Control Remote Advanced Operation Remote ShutDown / Reboot
Camera Configuration	Camera Permission




Warning

Change the general settings of the user (name, password, level, MAC address) by clicking the “Edit” symbol or in the TAB “Change password”.

Camera

Camera



No.	Shows the camera number
Camera address	Shows the set IP address of the camera
Log	Selecting the log
Managing the port	Setting for http ports of the camera
Channel no.	Channel number display
User name	Enter the user names of the camera here
Admin password	Enter the administrator password here
Display mode	Settings for displaying the camera name and date

Click on Add to link a camera to the system.


Click on "Search" to search the network for the available ABUS network cameras. Mark the required cameras and then click on "Quick Add" to link the cameras.

i Note

In some cases, you need to enter the user names, password and http port by hand afterwards.


The available bandwidth shows you how much bandwidth is still available for setting up the network camera.

OSD



Camera	Camera to be set
Camera Name	Allocation of camera name
Display Name	Activate / deactivate display of camera name in the live view
Display Date	Activate / deactivate display of date in the live view
Display Week	Activate / deactivate display of week in the live view
Date Format	Selection of date display type
Time Format	12 hours / 24 hours
Display Mode	Settings relating to the presentation of camera name and date
OSD font	Changing the font size

Image




Select the camera channel to be processed at "Camera". Adapt the camera image to light conditions at "Mode" by means of specified settings or with user-defined settings.

PTZ



Note

Here you can set up presets and patrols for the TVIP2xxx network cameras.



Saving and retrieving presets

1. Use the arrow buttons to move the network camera to the required image section and save the position, for example as Preset 1
2. Click on Call up to move to Preset 1.

Setting up and calling up patrols

1. Create several presets to use for the patrol
2. Click on + to select a preset
3. Add more presets to set up the required patrol.
4. Then click on the play symbol to start the patrol.




Note

You can also start the patrol directly in the live image of the respective network camera.

Motion

Select the camera channel under “Camera”.



Select the checkbox for motion detection.

The motion detection in the network camera must also be activated. For further details, refer to the network camera manual.




Note

In order to record using the motion recognition, you must set the time plan at recording (see p. 130).

Handling

Trigger Channel

When “Reaction” is clicked, the TAB **Trigger channel** appears (only with motion recognition):




Select one or more camera channels that should carry out a reaction in the event of an alarm.

Confirm the settings by clicking **Apply** and leave the menu with **OK**.

Armin Schedule

Select the TAB **Arming Schedule**.

Here you set the times when the reactions in the TAB **Reaction** are triggered.



1. Select the day and enter the schedule.

i Note


You can define up to 8 time periods (each from 00:00 to 00:00). The times in the individual periods must not overlap.

2. Select whether the settings should be applied to all days of the week with using **Copy**.
3. Confirm the settings by clicking **Apply** and leave the menu with **OK**.

Handling

Click on the TAB **Handling**.

Here you can configure the behavior of the recorder during a detected event (for example: motion got detected) by clicking the respective check box.



Parameter	Notification
Full Screen Monitoring	The camera is displayed as a full-screen picture in live cast

Audible Warning	The device emits a repeating tone
Notify Surveillance Center	Sends an alarm signal to a PC with the ABUS CMS software. For this, the software must be running and the recorder must be in surveillance mode.
Send E-Mail	An e-mail is sent to a specific e-mail address (see page 119)
Trigger Alarm Output	see page 119

- Confirm the settings by clicking **Apply** and leave the menu with **OK**

Record

Setting up

Open the main menu and click on record:

Schedule

The schedule is used to specify the recording times and triggers (recording type) for the cameras. Click on the “Schedule” tab:

i Note

Because there is no difference between the settings for the TABs record and instant image, these are only listed once.



In the OSD, the hours of the respective days are listed from left to right (the days are listed from top to bottom). A colour key is shown underneath the days (i.e. the recording periods in the schedule are shown in colour according to the trigger (recording types)).

Colour symbol	Key
Blue	Normal recording: Period in hours
Yellow	Motion detection
Light blue	Motion detection and alarm
Red	Alarm
Grey	No selection
Brown	Motion or alarm

- Select the camera and click on the check box **Enable Schedule**.
- Click on **Edit** to specify the type and duration of the time plan



1. Define the day to be set in the pull-down menu at ‘Schedule’.
2. Activate/deactivate ‘All day’. If the full day is active, no definite times can be entered as the setting is now valid for the whole day.
3. To make specific time settings, deactivate the “All Day” box.

i Application example

Recording should run from 11:00 to 07:00. 2 time zones must be set up for this:

1. 11:00 AM - 24:00PM
2. 00:00 AM - 7:00 AM

4. Specify the recording type in the drop-down menu:
 - Time
 - Motion detection
 - Alarm
 - Motion detection or alarm
 - Motion detection and alarm

i Note

To record using motion detection or the alarm, you must first set this up in the Camera menu (see p. **Fehler! Textmarke nicht definiert.** “Setting up of zones”) or Configuration (see p. **Fehler! Textmarke nicht definiert.** “Alarm”).

5. When making a specific time setting, you can define up to 8 time periods (each from 00:00 to 24:00). The times in the individual periods must not overlap.

i Note


The “Time” recording type defines the time window where a recording is made.

The other events (e.g. motion detection and/or alarm) only trigger the recording after the specific event has occurred.

- At **Copy** you can take on this setting for other days or the whole week.
6. Finalize your settings in the record screen with **Apply** and then **OK**.

Encoding

TAB Record



The following setting options are available in this sub-menu:


Confirm the settings by clicking on **Apply** and exit the menu with **OK**.

Pre-record	Recording period before an alarm (in seconds)
Post-record	Recording period after an alarm (in seconds)
Record Audio	Audio record yes/no

Confirm the settings by clicking on **Apply** and leave the menu with **OK**.

Settings

TAB Captured




The following parameters are adjustable:

Camera	Camera to be set
Parameter Type	Schedule or event
Resolution	Auto, 4CIF(704x576), CIF(352x288), QCIF(176x144)
Picture Quality	different qualities +++ : middle quality +++++ : high quality
Interval	Single images are saved every 1-5 seconds according to event or time plan

Confirm the settings by clicking **Apply** and leave the menu with **Back**.

Advanced settings (only TVVR45021)



Overwrite	You can specify whether older recordings are deleted when the HDD memory is full
eSATA	Specify if an eSATA hard disc connected by USB should be used for exporting, or for additional recording/image storing.

Holidays



In this sub-menu, 32 different recording settings for vacations or public holidays can be applied.

To apply these settings click on the "Edit" symbol:



Holiday Name	Manual name entry of the vacation or holiday
Enable	Activate or deactivate the set vacation
Mode	According to date / week / month
Start Date	Selection of start date / start time
End Date	Selection of end date / end time

Confirm your settings with **Apply** and **OK**.

HDD

HDDs



Note

The device manages up to eight 3.5" SATA hard disk drives (only TVVR45021). For additional data security, an e-SATA hard disc can be optionally connected.

Each of the installed HDDs must be initialised before the device can be used for recording. The device only detects the HDD and its assignment after initialisation has been made.



Warning

All data is deleted from the HDD during initialisation.

Ensure a data backup has been made in good time beforehand.

Installing the HDD

1. Disconnect the device from the mains power and open the cover.
2. Observe the applicable ESD guidelines when handling electronic devices and ensure they are earthed.
3. Do not open the device in rooms with carpets or other surfaces that can become electro statically charged.
4. Avoid bodily contact with all components on the PCB.



Warning

If you have questions regarding the information or cannot find the information you need, please contact your maintenance specialist.


5. Install the HDD and then connect it.
6. Reattach the cover and connect the device to the mains power supply.
7. Switch on the device and start the HDD menu.



Note

If the initialised HDD is not displayed, check the connections

Click on "HDD" in the menu to define settings relating to hard disc administration



HDD Management parameters


HDD information	
Label	Shows the internal connection number
Capacity	HDD capacity (in GB)
Status	Shows the current status of the HDD: Not initialised Normal Error
Property	<ul style="list-style-type: none"> • Redundancy: Works redundantly for data security • Read-only: Read-only protection • R/W: Read and write
Type	Local: Device HDD NFS: Network HDD If possible, avoid using NFS storage due to compatibility problems that may occur.
Free Space	Shows the approximate free memory for recordings
Group	HDD group (1 is preset) Recordings can be assigned to groups
Edit	Define hard disc settings (First adjust the camera groups; see also p.32)
Delete	Removal of the hard disc

1. Select the HDD by ticking the corresponding box.
2. Start the process by clicking on **Init**.
3. Confirm the prompt by pressing **OK**.
4. The status bar shows the progress of the initialisation.

HDD settings of the cameras


Click on the sub-menu “Advanced”.

Mode: Quote



Specify the maximum recording size per camera on the hard disc.

Mode: Group




1. Select a hard disc group in the drop-down menu.
2. By activating the check box, specify which cameras should be saved on the hard disc group.
3. Click on **Apply** and confirm the restart in the next window with **OK**.


Hard disc setting



Note
To be able to define these settings, you must have allocated cameras to a hard disc group (see **HDD settings of cameras**).



Click on the “Edit” symbol. A pop-up window appears:



HDD No.	Selecting hard disc by means of internal connection number
HDD Property	<ul style="list-style-type: none"> • R/W: Readable and writable • Read-only: Write protection • Redundant: operating redundantly for data security.
Group	Selection of hard disc group
HDD Capacity	Hard disc memory

Confirm the settings by clicking **Apply** and leave the menu with **OK**.



Warning:
If only one HDD is installed and this is set to “Read-only”, then the device cannot make recordings.



Redundancy:
At least two HDDs are installed. The redundant HDD makes an extra copy of the recordings. This is used as a data backup.

**Warning:**

If you want to use redundancy you have to activate the redundant storage in the recording menu (see also p. 131)

**R/W**

At least one HDD must have the R/W status (Read/Write). Otherwise, no recordings are possible.

Checking the HDD status

The status of each HDD can be checked in the “Maintenance” menu. S.M.A.R.T. information (Self-Monitoring, Analysis and Reporting Technology) is stored in the log data.

- Call up the log file and search according to the information/S.M.A.R.T. HDD (see page 135).

Setting up the HDD alarm

You can specify alarms to inform you of HDD errors.

- To do this, call up **Warning** in the “System Settings” menu (see page 125).

S.M.A.R.T.

S.M.A.R.T. means **S**elf-**M**onitoring **A**nalysis and **R**eporting **T**echnology.

ID	Attribute Name	Status	Flags	Thresh	Value	Worst	Raw Value
0x1	Raw Read Error Rate	OK	1	44	78	63	62643883
0x3	Spin Up Time	OK	3	0	100	100	0
0x4	Start/Stop Count	OK	32	20	100	100	0
0x5	Reallocated Sector Count	OK	33	36	99	99	64
0x7	Seek Error Rate	OK	1	30	78	60	8728271543
0x9	Power-on Hours Count	OK	32	0	87	87	12197
0xa	Spin Up Retry Count	OK	13	87	100	100	0
0xc	Power Cycle Count	OK	32	20	100	100	188
0xb8	Unknown Type Value: 18	OK	32	99	100	100	0
0xb6	Reported Uncorrectable	OK	32	0	94	94	6
0xbc	Unknown Type Value: 181	OK	32	0	100	99	4295032833
0xbd	High Fly Writes	OK	3a	0	1	1	183
0xba	Temperature Difference	OK	22	45	69	49	522125343
0xb7	C-Sense Error Data	OK	32	0	100	100	0

Information on the hard disc status is displayed in this sub-menu.

This information helps to recognize hard disc errors. For this reason, do not deactivate this feature if possible.


**Note**

The log files saved for S.M.A.R.T. can be found in the menu **Maintenance** at “Log search” (see page 138).

Playback

Press **Configuration** in the main menu and then **Playback** to search for video recordings after an event or a marking, or to view your saved images.


Continuous Recording



The following settings are available:

A1 - A4	Camera to be set
Record Type	Schedule, motion detection, alarm or motion detection and/or alarm, manual recording, all
File Type	Locked, unlocked, all
Start Time	Enter the date and time
End Time	

- Click on **Search** to search for recordings with the corresponding settings. The results are then shown:



- Select the recording by clicking on the line and then on "Play"-symbol.

i Note

You can return to events search at any time in the playback mode by performing a right click and selecting 'Video Search'.

i Note


The sub-menus 'Tag' and 'Picture' are almost identical with the menu described above and are therefore not listed separately.

In the sub-menu 'Tag', searching does not take

place according to recording type, rather according to identification or a keyword of the markings' name

Event

Please click on the TAB „Event“.



A list with all alarm inputs is displayed.

Select at 'Event type' whether the search should take place at alarm 'Alarm input' or motion 'Motion recognition' after recording.


Select one or more alarm inputs by activating the check box.

Click on **Search**.

Select one of more alarm recordings on the list that appears. Click on **Details** to receive more exact information on the recordings.

Marking

Click on the "Marking" tab.



Select one or more network cameras by activating the checkbox.

Click on **Search**.

Select one or more markings from the list which appears. Click on **Details** to obtain more information about the markings.


Image

Click on the "Image" tab.

Select one or more network cameras by activating the checkbox.

Click on **Search**.


Select one or more images from the list which appears.
Click on **Details** to obtain more information about the images.



Maintenance


Note

This menu is used for device maintenance, and should only be operated by experienced users.



Menu	Setting	P.
System Info	Device information (serial number, firmware status etc.)	138
Log Search	A search of recordings or information (S.M.A.R.T. HDD status) can be made in the log file according to certain criteria (alarms, exceptions, operation or information).	138
Import/Export	Used to export or import the settings	139
Upgrade	Carries out a firmware upgrade	139
Default	System reset	140
Network	Displays the transmission and reception rate of the recorder	140


System Info



Note

The information menu shows the technical data for the device and information on the various settings of the cameras, recording etc. This can be useful for support queries, for example.

Log Search



Note


An event search can be made according to the following main types, events and parameters:

- All
- Alarm
- Exception
- Operation
- Information

Filter1	Filter2
All	-
Alarm	<ul style="list-style-type: none"> • All • Alarm Input / Output • Start / Stop Motion Detection • Start / Stop Tamper-proof
Exception	<ul style="list-style-type: none"> • All • Video Loss Signal • Video Signal Exception • Illegal Login • HDD Full • HDD Error • IP Conflicted • Network Disconnected • Record / Capture Exception • Input / recording resolution mismatch
Operation	<ul style="list-style-type: none"> • All

	<ul style="list-style-type: none"> • Power On • Abnormal Shutdown • Start / Stop Audio • Local Operation, e.g.: Shutdown / Reboot / Login / Logout / Configure Parameters / Upgrade / Start Recording • Remote Operation, e.g.: Export Record File / Alarm Arming / ...
Information	<ul style="list-style-type: none"> • All • Local HDD Information • HDD S.M.A.R.T. • Start / Stop Recording • Start / Stop Capture • Delete Expired Record • NetHDD Information

1. Select the event you wish to search for in the log, then select the sub-parameter.
2. Enter the date and time under “Start Time” and “End Time”, then click on **Search**.
3. The results are then displayed:



- The pages are changed using the navigation bar:




(1) (2) (3) (4) (5) (6)

Note
 To scroll forwards or backwards press (3) or (2).
 To jump to the first or last page press (4) or (1).
 To go to a specific page number enter it in (5) and confirm by clicking (6).


- Click on **Details** to see more detailed information.
- Click on **Play** to start the recording for the event, when necessary.
- Click on **Export** to back up the log file on a USB medium.

Import / Export



Note
 The configuration data contains all settings made on the device since the start of operation. This data can be saved on a USB medium. You can then configure another device identically, for example.

Upgrade




Note
 A device upgrade can be made from a USB device or over the network via FTP.

- Copy the upgrade file to the main directory of a USB stick.
- Connect the USB stick to a USB port on the device.

1. Select the USB port (click on **Refresh**, if necessary).
2. Select the upgrade file and click on **Upgrade**.
3. Wait until the device reboots.
4. Check the firmware status in the “Maintenance” menu under “System Info”.


Default



Note
In this process, the device is reset to the factory default settings.

Warning
All settings made since the start of operation are deleted (cameras, recording settings, PTZ, alarms etc.)!
Avoid data loss by backing up the settings in advance. These can be imported again following the system reset.

Network




Note
Information regarding the network traffic and network interfaces are shown here.

TAB network load




The amount of received and sent data is displayed graphically.
Depending on the network settings, the status and information for one or two network connections is shown in the field underneath the graph.

TAB Network Detection



In “Destination Address”, you can check the connection to another device, such as a computer (‘pinging’). Enter the network address of the device to be checked (e.g. 192.168.0.25) and press **Test**.




Information on two parameters appears:

Parameter	Setting
Average delay	The time the pinged device needs to reply.
Packet loss Rate:	Displays the percentage of packets that were not transmitted

- i Note**
If the packet loss rate is high, we recommend that the “Network Test” is repeated.
- i Note**
If the packet loss rate is still high, you should check that the cables are correct and not damaged. The higher the packet loss rate, the poorer the connection between the pinged device and recorder.

For “Network Packet Export”, you can export the settings of the individual connections or – depending on the setting – the connection.

3. For “Device Name”, select a storage medium to save the settings to.
4. Click **Export**.




After the progress display finishes and initialization is successful, an information window appears. Close it with **OK**.

- Click **Status** to display the status of the LAN connections (connected/not connected).

- Click **Network** to change your network settings (see p. 119).


TAB Network Stat.



Displays all used in- and outgoing bandwidth.

Video Export

Duration




Note

The export function is used to store important recordings on connected external media, such as:

- USB media
- USB HDD
- DVD writer

- When “Quick export” is selected, all recordings of the selected time span are exported. Please note that not more than 24 hours can be exported.

1. Enter the parameters.
2. Click on “Details” to limit the search



- The file size of the individual recording and the total size of all found recordings are displayed.
 - By clicking the “Playback” symbol you can view the respective recording.
 - To block or unblock a file click on the “Lock” symbol.
3. Click on **Export** to access the export screen.



1. Select the connected medium used for data storage from the drop-down menu.
2. If the medium is not displayed, click on **Refresh**.
 - If the medium is still not displayed, disconnect it from the device and reconnect the medium again. See also the manufacturer’s specifications.
3. Click on **Export** to start the export process. The progress of the export process is then displayed.



Note

After the storage process is completed, the data on the medium can be selected and played on the player (which was also backed up). In this way, you can check whether the export has been made successfully.

Event (event type 'Alarm input')



Define the time span of the recording being searched for by means of the selection fields at "Start time" and "End time". Select the alarm input by activating or deactivating the check box and click **Search**.

Event (event type 'Motion')



Define the time span of the recording being searched for by means of the selection fields at "Start time" and "End time". Select the camera by activating or deactivating the check box and click **Search**.

For both types of event, the following window appears after activating the **Search** button:



Select the files to be exported by activating or deactivating the check box. You can set the pre-alarm and post-alarm time at "Pre-play" or "Post-play". In this way you can define the length of your export video.

Click on **Details** to view the selected video. For more exact information on the Details window, see **DURATION** (p. 142).

i Note

The "Pre-play" recordings can only be viewed when recording has been carried out before the alarm.


i Note

The sub-menus "Normal" and "Picture" are similar and are therefore not listed separately.

Manual Management

Press the REC button or go to panic recording in the main menu in order to start a manual image / video recording or to switch to an alarm output.

Record




Select the camera to start manual recording by clicking the corresponding button.



Note


Click "Analog" to record all connected cameras.

Continuous Capture




Select the camera to manually record continuous instant images. You can set the time interval in which these are recorded in the recording menu (see p. 130). Click the control button for this.

Alarm



In order to switch on one of the alarm outputs, select the alarm output with a left click and click on **Trigger** for one, or **Trigger All**, to switch on all outputs. To reset the output(s) again, click on **Clear** or **Clear all**.

Shutdown



Note

- Select "Lock" to lock the operating menu.
- Select "ShutDown" to switch off the device.
- Select "Reboot" to reboot the system (switch off and back on).

Troubleshooting

Before calling the Service department, read the following information to determine the possible cause of a malfunction.

Malfunction	Cause	Solution
No power	Mains cable not connected	Connect the mains cable securely to the socket
	Power switch set to OFF	Turn the power switch to ON
	No current in the power socket	Use another device on the socket, where necessary
No image	Screen not set for reception	Set the correct video input mode until an image from the recorder appears
	Video cable not connected properly	Connect the video cable securely
	Connected modem is switched off	Switch on the monitor
No sound	Audio cables not connected properly	Connect the audio cables securely
	Devices connected over the audio cables are not switched on	Switch on the devices connected over the audio cables
	Audio connection cable is damaged	Replace the cable
HDD is not working	Connection cables not connected properly	Connect the cables securely
	HDD defective or not system-compatible	Replace with a recommended HDD
USB port not working	Device not supported	Connect a compatible USB medium (USB 2.0)
	USB hub is in use	Connect the USB medium directly
Network access not possible	Network cable connections are loose	Connect the network cable
	Network settings are incorrect (DHCP, IP address etc.)	Check the network configuration and correct it, if necessary (see page 119).
Remote control is not working	Batteries inserted with the wrong polarity or are empty	Replace the batteries. To control the device with the remote control, point it at the remote control sensor on the device
	Remote control too far away from the recorder	Use the remote controller within 7 metres from the device
	Signal blocked by obstruction between the remote control and recorder	Remove the obstruction
	Lighting too bright or fluorescent tubes in use?	Switch off strong fluorescent lighting in the immediate vicinity
Recording not possible	No HDD or HDD is not initialised	Install and initialise the HDD
Sudden deactivation of the device	Temperature inside the device is too high	Clean the device and remove any obstructions from the ventilation area

Device cleaning and care

Note

- Your device requires no maintenance.
- Protect the device from dust, dirt and moisture.

Technical data

Subject is to alterations and errors. The dimensions are approximate values.

ABUS digital recorder	TVVR35011	TVVR45021
Video compression	H.264	
Hybrid-compatible	-	
Camera inputs	8	16
Camera outputs	none	
Monitor outputs	Monitor: 1 x BNC (1.0 V p-p, 75 Ω), 1 x VGA, 1 x HDMI	Monitor: 1 x BNC (1.0 V p-p, 75 Ω), 1 x VGA, 1 x HDMI
Operating mode	Triplex	
Resolution (live view)	HDMI: 1920*1080/60Hz(1080P),1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz VGA: 1920*1080/60Hz,1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz BNC Output: PAL: 704x576, NTSC: 704x480	
Resolution @ frame rate per camera (recording)	Max. 1920 x 1080p @ 25fps	
Total frame rate	200 fps	400 fps
Compression levels	Depends on used network camera	
Pre-alarm/post-alarm memory	0–30 sec. / 5–900 sec.	
Storage medium	2x SATA HDD	8x SATA HDD
Data backup	3 x USB 2.0	
Views	1 / 4	1 / 4 / 6 / 8 / 9 / 16
Recording modes	Manual, schedule, motion detection, alarm, motion detection and alarm, motion detection or alarm	
Search modes	By event, date and time	
Alarm inputs (NO/NC)	4	16
Alarm outputs	2 (Loading capacity: 12VDC/1A)	4 (Loading capacity: 12VDC/1A)
User levels	2 (max. 31 users)	
Network connection	2 x RJ45 10/100/1000 Mbps	
Parallel network access	128 camera connections	
Network functions	Live view, playback, data export, settings	
DDNS	√	
NTP	√	
PTZ control	RS-485	
PTZ protocols	PELCO-D, PELCO-P, Samsung, LG-MULTIX	
Alarms	Acoustic warning, OSD signal, e-mail,CMS	
Audio	Line In: 1 x BNC (2.0 V p-p, 1000 Ω) – only for network transmission Audio Out: 2 x BNC (600 Ω)	Line In: 1 x Cinch (2.0 V p-p, 1000 Ω) – only for network transmission Audio Out: 2 x Cinch (600 Ω)
Control	USB Mouse, remote control	
Software	ABUS CMS software	
OSD languages	German, English, French, Dutch, Danish, Italian, Polish, Czech, Spanish	
Power supply	12 VDC, 3.0 A, 50–60 Hz	100–240VAC, 6.3A, 47–63Hz
Power consumption	<40W (without HDD)	<55W (without HDD)
Operating temperature	-10 °C–+55 °C	
Dimensions (WxHxD)	470 x 90 x 445 mm	
Weight	≤ 8 kg (without HDD)	
Certification	CE	

Technical data

HDD storage capacity

In addition to the actual storage capacity of the installed HDD, the required storage space for recording and surveillance depends on the set resolution and frame rate of the recording.

On the included CD you can find a program in order to calculate the required amount of memory. In addition you find this software for download on our homepage together with the ABUS CMS software.

Overview monitor output combination

HDMI + VGA	HDMI + CVBS	VGA + CVBS	HDMI only	VGA only	CVBS only
✓	✓	✓	✓	✓	✓

Disposal

Information on the EU directive on waste electrical and electronic equipment

To protect the environment, do not dispose of the device with domestic waste at the end of its service life. It can be disposed of at one of the appropriate collection points in your country. Please obey your local regulations when disposing of material.



Dispose of the device in accordance with EU directive 2002/96/EC – WEEE (Waste Electrical and Electronic Equipment). If you have any questions, please contact the department of your local authority which is responsible for waste disposal. Used equipment can be disposed of, for example, by your local or municipal authority, the local waste disposal company or your dealer.

Information on handling batteries

- Always insert batteries with the correct polarity. Never attempt to recharge the batteries supplied and do not throw them into naked flames under any circumstances. Do not use different batteries at the same time (old and new, alkaline and zinc-carbon etc.). Remove the batteries if the device is not used for a long period of time. If used improperly, there is a risk of explosion and leaking batteries!
- Take environmental protection into account – used batteries should not be disposed of in domestic waste! They must be taken to a collection point for used batteries.
- Make sure that batteries are kept away from small children. Children may put batteries in their mouths and swallow them. This can cause serious harm to their health. If this happens, consult a doctor immediately.
- Do not charge normal batteries, heat them up or throw them into naked flames (they may explode).

- Change low batteries in good time.
- Always change all the batteries at the same time and use batteries of the same type.



Important

Leaky or damaged batteries can cause chemical burns on contact with the skin.

- ▶ In this case, wear protective gloves.
- ▶ Clean the battery compartment with a dry cloth.


Important information on disposing of batteries

Your product uses batteries which are subject to the European directive 2006/66/EC and may not be disposed of with domestic waste.

Find out about the regulations for the separate collection of batteries which apply in your country.

Proper disposal of batteries helps prevent harm to health and the environment.

Batteries that contain harmful chemicals are labelled with these signs:



Pb = battery contains lead

Cd = battery contains cadmium

Hg = battery contains mercury

Information on the European RoHS directive

The device complies with the RoHS directive.

Compliance with the RoHS directive means that the product or component does not contain more than the following maximum concentrations of the following substances in homogeneous materials, unless the substance is part of an application that is excluded from the RoHS directive:

- 0.1% lead (by weight)
- Mercury
- Hexavalent chromium
- Polybrominated biphenyl (PBB) and polybrominated diphenyl ether
- 0.01% cadmium (by weight)

Glossary

Overview of specialist terms

1080i

HDTV image signal with 1080 pixels and interlaced display.

16:9

Cinematographic aspect ratio on widescreen displays.

720p

HDTV image signal with 1280 x 720 pixels and progressive display.

CIF

Common Intermediate Format

Originally planned for converting PAL to the NTSC standard. CIF corresponds to a video resolution of 352 x 288 pixels (2CIF = 704 x 288 pixels; 4CIF = 704 x 576 pixels).

CINCH

Socket type used for analogue audio or CVBS video signals.

CVBS

Colour, Video, Blank and Sync – The simplest variation of video signals (also known as composite video). The image quality is comparatively low.

DDNS

Dynamic Domain Name System entry

Network service which provides and updates IP addresses of its clients in a database.

DHCP

Dynamic Host Configuration Protocol

Network protocol which allows the automatic connection of devices (clients) in existing networks. DHCP servers (e.g. Internet routers) automatically assign the IP address, network mask, gateway, DNS server and WINS server (when required). Only the automatic acquisition of IP addresses must be activated for the client in this case.

Domain

Name used for the identification of websites on the Internet (e.g. www.abus-sc.de).

Dual Stream

Dual stream is a video transmission method. A high-resolution recording and lower-resolution transmission are made over the network, for example. The main stream has a 4CIF resolution and the sub-stream has a CIF resolution.

DVR

Digital Video Recorder – A device used for recording different video and audio sources (analogue, digital). The data is compressed for recording and saved on hard disk drives (HDD).

H.264

(MPEG-4 AVC) – Standard method for the highly-efficient compression of video signals. Used on Blu-ray discs or video conference systems, for example.

HDD

Hard Disk Drive

Digital data storage on computers or DVRs.

GIGABYTE

Unit of capacity for storage media (HDD, USB, SD/MMC cards).

HDVR

Hybrid DVR – DVR used for recording analogue cameras and network cameras.

http

Hypertext Transfer Protocol

Method for transmitting data across networks. Primarily used for displaying websites in a browser.

INTERLACED

Method for improving the picture quality of a video signal without consuming extra bandwidth (scan pattern on every second line).

IP address

An address in the computer network based on the Internet protocol. Allows different devices to identify themselves in a network so that they are accessed specifically.

JPEG

Compression method for photo images with minimal loss. Most digital cameras save photos in JPEG format.

MPEG

Moving Picture Experts Group – International standard for the compression of moving images. On some DVDs, the digital audio signals are compressed and recorded in this format.

NTP

Network Time Protocol

Method for synchronising the time across networks. SNTP (Simple Network Time Protocol) is also available, offering a simplified protocol.

NTSC

Standard television format in the USA. The method is different from the European PAL system in certain ways. A full-screen NTSC image is comprised of 480 visible lines and a total of 525 lines. 60 half-images are displayed per second. Compared to PAL, the system is more susceptible to colour errors.

PAL

Phase Alternating Line – European colour TV system. Uses 576 visible image lines. Together with the lines used for signal management, a full-screen image is comprised of 625 lines. 50 half-images are displayed per second. The phase position of the colour signal changes from line to line in the image.

PANEL

Interior of a flatscreen display (e.g. LCD or plasma panels).

PC

Personal Computer – Can be used as a remote site, either with the software supplied or over a browser.

Pixel

Short for “picture element”, the smallest unit for digital image transmission or display.

PIP

Picture in Picture – Where two signal sources are shown on the screen at the same time. The second signal source is stored above the first.

PPPoE

PPP over Ethernet (point-to-point protocol)

Network transmission method used for establishing a connection over dial-up lines. Used in ADSL connections, for example).

PROGRESSIVE

Method for displaying, storing or transmitting moving images in which all the lines of each frame are drawn in sequence. This is in contrast to the interlacing used in traditional television systems.

PTZ

Pan-Tilt-Zoom

Pan, tilt and zoom function on motor-driven cameras.

RESOLUTION

Normal PAL television systems show images in 576 lines, normally with 768 pixels. HDTV works with at least 1280 x 720 pixels.

SCREEN SIZE

Size of the display from the bottom-left corner to the top-right corner in inches or centimetres.

Browser

Program for viewing websites on the Internet.

USB

Universal Serial Bus

Serial bus connection, used for connecting media whilst in operation. Maximum data rate for USB 2.0: ca. 320 Mbit/s (ca. 40 MB/s).

VGA

Video Graphics Array – Standard interface for analogue video signals in PCs (primarily deals with RGB signals).

ZOLL (inches)

Typical unit of screen size. One inch is equivalent to 2.54 centimetres. The most common sizes of 16:9 displays are 26 inch (66 cm), 32 inch (81 cm), 37 inch (94 cm), 42 inch (106 cm), 50 inch (127 cm) and 65 inch (165 cm).

Internal HDD

The internal hard disk drive (HDD) is very sensitive. Operate the device according to the following instructions in order to avoid drive errors. Important recordings should be backed up on external media to avoid unexpected data loss.



Note

- Do not move the device during operation.
- Moisture inside the device can condense and lead to HDD malfunctions.
- When the device is turned on, never remove the mains plug from the socket or interrupt the power supply using the safety switch.
- Do not move the device immediately after switching it off. To move the device, carry out the following steps:
 1. Wait until OFF has been shown on the display for at least two minutes.
 2. Remove the mains plug from the socket.
 3. Move the device.
- Data on the HDD can be lost in the event of a power failure during operation. Use an uninterruptible power supply (UPS)!
- The HDD is very sensitive. Improper use or unsuitable surroundings can damage the HDD after some years of use. This may be indicated by the playback stopping unexpectedly or visible “mosaic” effects in the image. In some circumstances, there are no prior signs of a HDD malfunction.
- In the event of a malfunction, no recordings can be played. The HDD must be replaced in this case.

ABUS Network video recorder NVR

TVVR45021 / TVVR35011

Manufacturer:
ABUS Security-Center GmbH & Co. KG
Linker Kreuthweg 5
86444 Affing (Germany)