

The user guide

March 24, 2004

Warning: This document is updated regularly. In its current form it describes the handling of UrQMD **revision 1.3** . If you are using a newer version of UrQMD, please contact one of the authors in order to obtain the latest version of this document.

The authors give no warranty to the correct functioning of the UrQMDprogram. Use this program at your own risk. Please send all bug-reports to the following e-mail address:

`urqmd@th.physik.uni-frankfurt.de`

Contents

1	General Information	1
2	Copyright	1
3	Compiling and running the program	2
4	The input file	3
4.1	Input Parameters	5
5	Output files	17
5.1	Standard output-files: file13/file14	17
5.2	Collision history file: file15	17
5.3	Decay output: file16	19
5.4	OSC1997A output (OSCAR 1997A format): file19	21
5.5	OSC1999A output (OSCAR 1999A format): file20	23
A	Appendix: Changes from version 1.0/1.1 to 1.2	26
B	Appendix: Changes from version 1.2 to 1.3	29
C	Appendix: Known problems and inconsistencies in UrQMD	30

List of Figures

1	running the UrQMD program	2
2	sample input file for UrQMD	3
3	sample header of an UrQMDoutput file.	22
4	beginning of a sample body of an UrQMDstandard output file.	22
5	excerpts of a sample body of an UrQMDcollision history file.	22
6	Sample output in the OSC1997A format.	24
7	Sample output in the OSC1999A format.	27

1 General Information

The Ultra Relativistic Quantum Molecular Dynamics (UrQMD) model is a transport model for simulating heavy ion collisions in the energy range from SIS to RHIC. It runs on various UNIX-based computing platforms. Current implementations include IBM/AIX (xlf), GNU/Linux (g77, ifc), SGI/IRIX, DEC-UNIX and Sun/Solaris.

UrQMD is designed as a multipurpose tool for studying a wide variety of heavy ion related effects ranging from multifragmentation and collective flow to particle production and correlations.

This document is no introduction to the physics of UrQMD. Its purpose is to serve as a short guide to the experienced physicist on how to run the program. A detailed model description can be found in the following two articles.

1. *Microscopic Models for Ultrarelativistic Heavy Ion Collisions*

S. A. Bass, M. Belkacem, M. Bleicher, M. Brandstetter, L. Bravina, C. Ernst, L. Gerland, M. Hofmann, S. Hofmann, J. Konopka, G. Mao, L. Neise, S. Soff, C. Spieles, H. Weber, L. A. Winckelmann, H. Stöcker, W. Greiner, C. Hartnack, J. Aichelin and N. Amelin.
Prog. Part. Nucl. Phys. **41** (1998) 225–370.

2. *Relativistic Hadron-Hadron Collisions and the Ultra-Relativistic Quantum Molecular Dynamics Model (UrQMD)*

M. Bleicher, E. Zabrodin, C. Spieles, S.A. Bass, C. Ernst, S. Soff, H. Weber, H. Stöcker and W. Greiner.
J. Phys. **G25** (1999), 1859–1896.

2 Copyright

UrQMD source and documentation are provided freely for the purpose of checking and reproducing published results of the authors.

The Open Standard Codes and Routines (OSCAR)-Group has established - for good reasons - guidelines for reproducibility, usage and quality control of simulation codes for pA and AA collisions.

UrQMD is a complex model. In order to ensure that it is used correctly that all results are reproducible and that the proper credits are given we ask for your agreement to the following copyright and safeguard mechanisms in the OSCAR spirit.

The UrQMD collaboration favors cooperation and joint projects with outside researchers. We encourage experimental collaborations to compare their results to UrQMD. We support you and/or cooperate on any sensible project related to UrQMD.

If you are interested in a project, please contact us.

Projects without the participation of the UrQMD-Collaboration are accepted, if the project is not a current thesis topic of any UrQMD-Collaboration member.

We expect that the code authors are informed about any changes and modifications made to the code. Any changes to the official version must be documented.

The code or any fragments of it shall not be given away to third parties. Similarly, events generated with UrQMD shall not be given to third parties without consent of the code authors.

3 Compiling and running the program

To compile UrQMD one needs a FORTRAN77 compiler and GNU-make. The GNU-make program is available on `ftp.gnu.org` (note: on many UNIX systems GNU-make is called `gmake`). Compilation is initiated by issuing the `make` command at the command-prompt in the UrQMD subdirectory. After successful compilation the binary has the name `urqmd.TYPE` where TYPE is the machine type as given by the `uname` command.

In order to run UrQMD one needs to define the running parameters with an input file. The input-file is made accessible to UrQMD by attaching its name has to be to the environment-variable `ftn09`. The output files are attached in the same fashion via the environment variables `ftn14` and `ftn15`. Figure 1 shows, how UrQMD is started on a generic UNIX system (here AIX using the Korn Shell):

```
$ export ftn09=inputfile
$ export ftn13=outputfile_with_freezeout
$ export ftn14=outputfile
$ export ftn15=collisionfile
$ export ftn16=outputfile_with_decaying_resonances
$ export ftn19=outputfile_for_OSCAR97
$ export ftn20=outputfile_for_OSCAR99
$ urqmd.AIX
or, if you want to compress your files on-line:
$ export ftn09=inputfile
$ mknod outputfile p
$ mknod collisionfile p
$ export ftn14=outputfile
$ export ftn15=collisionfile
...
$ cat outputfile | gzip > outputfile.gz &
$ cat collisionfile | gzip > collisionfile.gz &
...
$ urqmd.AIX
```

Figure 1: running the UrQMD program

4 The input file

Figure 2 shows a typical input-file for UrQMD. The general format of the inputfile is 1A3,1A77. This means that every input line consists of two sections: First a three character flag followed by a 77 character string, the contents of which varies according to the flag specified.

```
# this is a sample input file for uqmd
# projectile
#   Ap Zp
pro  197 79
# optional: special projectile: ityp, iso3
# PRO 101 2
# target
#   At Zt
tar  197 79
# number of events
nev 1
# time to propagate and output time-interval (in fm/c)
tim  40 40
#
# incident beam energy in AGeV
ene  10.7
#
imp  3.0
#
# equation of state
eos  0          # CASCADE mode
# some options and parameters
cto  4  1      # output of initialization
ctp  1  1.d0    # scaling for decay width of Resonances
#
f15  # no output to file15
# end of file
xxx
```

Figure 2: sample input file for UrQMD

The input-file does not have a predefined sequence. However, it is mandatory that the input contains definitions for projectile, target, impact parameter and incident beam energy.

Table 1 shows a quick summary of all possible flags with their respective parameters.

label	arguments	description
#		comment line
xxx		last line of input-file
pro	Ap Zp	define projectile
PRO	ityp iso3	define special projectile
tar	At Zt	define target
TAR	ityp iso3	define special target
nev	nevents	number of events to calculate
tim	totttime outtime	define time of calculation and output
ene	ebeam	incident kinetic beam energy (lab frame)
elb	ebeam	incident kinetic beam energy (lab frame)
plb	pbeam	incident beam momentum (lab frame)
PLB	pmin pmax npbin	incident (min/max) beam momentum for excitation function
PLG	pmin pmax npbin	like PLB, log-weighted
ecm	srt	\sqrt{s} for two particle collision
ENE	srtmin srtmax nsrt	incident min/max \sqrt{s} for excitation function
ELG	srtmin srtmax nsrt	incident min/max \sqrt{s} for excitation function (log-weighted)
imp	bmax	define impact parameter (bmin=0)
IMP	bmin bmax	define impact parameter
eos	EoS	define equation of state
box	dim edens solid para	define box for infinite matter calculation
bpt	ityp iso3 npart pmax	define particle population for box-mode
bpe	ityp iso3 npart	like bpt, for given energy density
rsd	seed	seed for random number generator
stb	ityp	keep particle stable
cdt	deltat	Δt between full collision load
f13		suppress output to unit 13
f14		suppress output to unit 14
f15		suppress output to unit 15
f16		suppress output to unit 16
f19		suppress output to unit 19
f20		suppress output to unit 20
ctp	index value	set optional parameter in CTParam array
cto	index value	set option in CTOption array

Table 1: possible flags in the input-file with their respective arguments

4.1 Input Parameters

In this section all input labels with their respective arguments are explained. A complete sample input file can be seen in figure 2.

comment

```
# string
```

string can be used to insert comments into the input file.

end of file

```
xxx string
```

string should contain at least one blank, xxx marks the end of the input file.

define projectile

```
pro Ap Zp  
PRO ityp iso3
```

Ap mass of projectile

Zp charge of projectile

Instead of defining an ordinary nucleus (with pro one can also define a special non-composite projectile with PRO:

ityp ID of projectile (see tables 2 and 3 for available itypes)

iso3 $2 \cdot I_{spin_3}$ of particle

define target

```
tar Ap Zp  
TAR ityp iso3
```

Ap mass of target

Zp charge of target

Instead of defining an ordinary nucleus (with tar one can also define a special non-composite target with TAR:

ityp ID of target (see tables 2 and 3 for available itypes)

iso3 $2 \cdot I_{spin_3}$ of particle

define number of events

```
nev nevents
```

nevents number of events to calculate

define calculation time

```
tim tottime outtime
```

tottime total time span (in fm/c) to calculate

outtime time interval (in fm/c) after which output is written to files 13 and 14

define incident beam energy

```
ene ebeam  
elb ebeam  
ecm srtmin  
ENE srtmin srtmax nsrt  
ELG srtmin srtmax nsrt  
plb pbeam  
PLB pmin pmax npbin  
PLG pmin pmax npbin
```

ebeam kinetic energy of the beam-particle (in case of nuclei it is the nucleon) in the laboratory frame

srtmin minimal value for \sqrt{s} between projectile and target particles (in case of nuclei it is the nucleon)

srtmax maximal value for \sqrt{s} between projectile and target particles (in case of nuclei it is the nucleon)

nsrt number of \sqrt{s} values from srtmin to srtmax for which events shall be calculated (excitation function)

pbeam momentum of the beam-particle (in case of nuclei it is the nucleon)

pmin minimal value for p_{lab} (for excitation functions)

pmax maximal value for p_{lab} (for excitation functions)

npbin number of p_{lab} values from pmin to pmax for which events shall be calculated (excitation function)

For single momenta/energies the definitions `ene/elb`, `ecm` and `plb` are used, for excitation functions `ENE`, `ELG`, `PLB`, `PLG` are needed. The binning of the excitation function is linear for `ENE` and `PLB` and logarithmic for `ELG` and `PLG`. In the case of an excitation function the number of events `nev` refers to the **full** excitation function, i.e. the number of events per bin would be `nev/nsrt` or `nev/npbin` respectively.

Only one of the above seven definitions is needed. The priority of definition increases from `ene` and `ENE` to `PLG`. Make sure to only use one of the above commands for the beam energy in order to avoid ambiguities in the input file.

define impact parameter

```
imp bmax
IMP bmin bmax
```

`bmin` minimum impact parameter (0 for `imp` and `CTOption(5)=0`).

`bmax` maximum impact parameter

In case of `imp` the value of `bmin` is automatically set to 0.0. Two different methods of weighting the impact parameter distribution are accessible via `CTOption(5)`.

A minimum bias calculation can be performed for `bmin=0, bmax > $R_p + R_t$` and `CTOption(5) ≠ 0`.

In case of negative values of `bmax` in the `imp` command, a calculation from $b = 0$ fm to $b = |bmax|$ fm with quadratic weighting (`CTOption(5)=1`) is performed.

infinite matter (box) calculations

```
box dim edens solid para
bpt ityp iso3 npart pmax
bpe ityp iso3 npart
```

`dim` width of (cubic) box

`edens` total energy content of box in GeV

`solid` 1: reflecting walls, 0: periodic boundary conditions

`para` 0: standard, 1: use “old” periodic boundary conditions

`ityp` ID of species (see tables 2 and 3 for available itypes)

`iso3` $2 \cdot I_{spin_3}$ of species

`npart` number of particles for species

`pmax` maximum momentum for fermi-sphere in momentum space.

define equation of state

```
eos EoS
```

EoS equation of state for the calculation

Currently only CASCADE mode (EoS=0) or a hard Skyrme equation of state (EoS=1) are available. The default mode is CASCADE, the hard Skyrme equation of state is limited to incident beam-energies below 4.0 GeV/nucleon.

Important: This option also changes the initialization mode (see CTOption(24)).

set random number generator seed

```
rsd seed
```

seed (integer) seed for random number generator

Depending on the computer system the omission of the `rsd` command or the value `seed=0` cause the generation of an automated (supposedly unique) seed for each calculated event. This feature is sofar only implemented for IBM RISC/6000 running AIX. For all other systems the definition of a seed is **mandatory**.

set forces/collision load update interval

```
cdt deltat
```

deltat timeinterval (in fm/c) for the update of potentials and a full particle scan for the collision arrays

In the CASCADE mode a regular full particle scan for the collision arrays is not necessary, therefore this command should be only used in calculations including potentials, infinite matter calculations or for debug purposes.

suppress output files

```
f13  
f14  
f15  
f16  
f19  
f20
```

The output to the respective files is omitted if the above command is used.

set particles stable

stb ityp

ityp ID of particle (see tables 2 and 3 for available itypes)

Treat all particles with this ID as stable particles.

set special parameter

ctp index value

index index of CTParam() array

value value for CTParam(index) (see tables 4 and 5 for available parameters)

set special option

cto index value

index index of CTOption() array

value value for CTOption(index) (see table 6 for available options)

ID	nucleon	ID	delta	ID	lambda	ID	sigma	ID	xi	ID	omega
1	N_{938}	17	Δ_{1232}	27	Λ_{1116}	40	Σ_{1192}	49	Ξ_{1317}	55	Ω_{1672}
2	N_{1440}	18	Δ_{1600}	28	Λ_{1405}	41	Σ_{1385}	50	Ξ_{1530}		
3	N_{1520}	19	Δ_{1620}	29	Λ_{1520}	42	Σ_{1660}	51	Ξ_{1690}		
4	N_{1535}	20	Δ_{1700}	30	Λ_{1600}	43	Σ_{1670}	52	Ξ_{1820}		
5	N_{1650}	21	Δ_{1900}	31	Λ_{1670}	44	Σ_{1775}	53	Ξ_{1950}		
6	N_{1675}	22	Δ_{1905}	32	Λ_{1690}	45	Σ_{1790}	54	Ξ_{2025}		
7	N_{1680}	23	Δ_{1910}	33	Λ_{1800}	46	Σ_{1915}				
8	N_{1700}	24	Δ_{1920}	34	Λ_{1810}	47	Σ_{1940}				
9	N_{1710}	25	Δ_{1930}	35	Λ_{1820}	48	Σ_{2030}				
10	N_{1720}	26	Δ_{1950}	36	Λ_{1830}						
11	N_{1900}			37	Λ_{1890}						
12	N_{1990}			38	Λ_{2100}						
13	N_{2080}			39	Λ_{2110}						
14	N_{2190}										
15	N_{2200}										
16	N_{2250}										

Table 2: Baryon-ID's used in UrQMD. A particle is fully defined, when its ityp and $2 \cdot I_3$ are known. Antibaryons carry a negative sign.

ID	0^{-+}	ID	1^{--}	ID	0^{++}	ID	1^{++}
101	π	104	ρ	111	a_0	114	a_1
106	K	108	K^*	110	K_0^*	113	K_1^*
102	η	103	ω	105	f_0	115	f_1
107	η'	109	ϕ	112	f_0^*	116	f_1'
ID	1^{+-}	ID	2^{++}	ID	$(1^{--})^*$	ID	$(1^{--})^{**}$
122	b_1	118	a_2	126	ρ_{1450}	130	ρ_{1700}
121	K_1	117	K_2^*	125	K_{1410}^*	129	K_{1680}^*
123	h_1	119	f_2	127	ω_{1420}	131	ω_{1662}
124	h_1'	120	f_2'	128	ϕ_{1680}	132	ϕ_{1900}

Table 3: Meson-ID's in UrQMD, sorted with respect to spin and parity, included into the UrQMD model. Mesons with strangeness -1 carry a negative sign.

CTParam(X)	default	function
1	1.d0	scaling factor for resonance widths
2	0.52d0	minimal stringmass and el/inel. cut in makestr
3	2.0d0	velocity exponent for modified AQM
4	0.3d0	transverse pion mass, used in strexct and make22
5	0.0d0	probability for quark rearrangement in cluster
6	0.37d0	strangeness probability in makestr
7	0.d0	charm probability (not yet implemented in UrQMD)
8	0.093d0	probability to create a diquark
9	0.35d0	kinetic energy cut-off for last string break
10	0.25d0	min. kinetic energy for hadron (in string)
11	0.0d0	percentage of non groundstate resonances (in string)
21	0.d0	deformation parameter
25	0.9d0	probability for diquark not to break
28	1.d0	scaling factor for transverse fermi motion
29	0.4d0	strange di-quark suppression factor
30	1.5d0	radius offset for initialization
31	1.6d0	σ of Gaussian for transverse momentum transfer
32	0.d0	$\alpha - 1$ for valence quark distribution
33	2.5d0	β_v for valence quark distribution
34	0.1d0	minimal x multiplied with $E_{c.m.}$
35	3.0d0	offset for cut for the FSM
36	0.275d0	fragmentation function parameter a (nucleons)
37	0.42d0	fragmentation function parameter b (nucleons)
38	1.08d0	diquark p_t scaling factor
39	0.8d0	strange quark p_t scaling factor
40	0.5d0	$\beta_s - 1$ for valence quark distribution
41	0.d0	distance between nuclei at initialization
42	0.55d0	width of Gaussian for p_t -distribution in string-fragmentation
43	5.0d0	maximum kinetic energy in mesonic cluster
46	8.0d5	maximum number of rejections during initialization of nuclei
47	1.0d0	Field-Feynman fragmentation func. parameter a (prod. part.)
48	2.0d0	Field-Feynman fragmentation func. parameter b (prod. part.)

Table 4: Optional parameters used in UrQMD

CTParam(X)	default	function
50	1.0d0	enhancement factor for 0^{-+} mesons
51	1.0d0	enhancement factor for 1^{--} mesons
52	1.0d0	enhancement factor for 0^{++} mesons
53	1.0d0	enhancement factor for 1^{++} mesons
54	1.0d0	enhancement factor for 2^{++} mesons
55	1.0d0	enhancement factor for 1^{+-} mesons
56	1.0d0	enhancement factor for $(1^{--})^*$ mesons
57	1.0d0	enhancement factor for $(1^{--})^{**}$ mesons
58	1.0d0	scaling factor for DPF time-delay

Table 5: Optional parameters used in UrQMD

CTOption(X)	default / options	description
1	0	mass dependent resonance decay widths
	0	enabled
	1	disabled
2	0	2-particle scattering plane:
	0	stochastic selection of $\varphi(1, 2)$
	1	conserve plane
3	0	detailed balance selection
	0	take finite resonance widths into account
	1	use standard detailed balance
4	0	initial configuration output to file14
	0	output according to <code>tim</code> statement
	1	additional output of initialization
5	0	impact parameter weighting
	0	use <code>bmax</code> as fixed impact parameter
	1	random b from <code>bmin</code> to <code>bmax</code> , <i>bdb</i> weighted
	2	random b from <code>bmin</code> to <code>bmax</code> , flat distribution
6	0	first collisions within target/projectile
	0	block first collisions within proj./target
	1	all collisions allowed
7	0	suppress elastic NN collisions
	0	elastic collisions are allowed
	1	no elastic NN collisions; $\sigma_{in} = \sigma_{tot}$
8	0	mass dependent partial decay widths
	0	enabled
	1	disabled, use fixed widths
9	0	tabulated p+p inelastic cross sections
	0	enable table-lookup
	1	disable table-lookup
10	0	Pauli-blocker
	0	enable Pauli-blocker
	1	disable Pauli-blocker

CTOption(X)	default / options	description
11	0	mass reduction (binding energy) in CASCADE mode
	0	enable mass reduction according to binding energy
	1	disable mass reduction
12	0	string production
	0	enable string production
	1	disable string production
13	0	enhanced file16 output
	0	disabled
	1	enabled
14	0	angular distribution in binary scattering
	0	enable angular distribution
	1	disable distribution ($\cos(\vartheta) = 1$ forward peak)
15	0	meson-meson and meson-baryon scattering
	0	enable MM and MB scattering
	1	disable MM and MB scattering
16	0	molecular dynamics switch
	0	enable collision term
	1	propagate with forces only (disable collision term)
17	0	collision-table update mode
	0	update only collision partners after interaction
	1	initialize complete table after every interaction
18	0	decay of unstable particles at end of event
	0	perform decay after final timestep
	1	unstable particles do not decay after final timestep
19	0	$B\bar{B}$ annihilation
	0	enabled
	1	disabled
20	0	e^+e^- annihilation instead of $B\bar{B}$ annihilation
	0	disabled (normal $\bar{B}B$ mode)
	1	enabled (e^+e^- mode)

CTOption(X)	default / options	description
21	0	string fragmentation function
	0	field-Feynman fragmentation function
	1	Lund fragmentation function
	2	QGSM fragmentation function
22	1	string mass excitation
	-1	simple $1/M$ excitation
	1	FRITIOF ansatz
	2	QGSM ansatz
23	0	Lorenz contraction of projectile and target
	0	enabled
	1	disabled
24	1	initialization mode
	0	hard sphere (used for EOS \neq 0)
	1	Woods-Saxon (used for CASCASE mode)
25	0	phase space correction for resonance masses
	0	disabled
	1	enabled
27	0	reference frame for calculation
	0	N.N. (equal speed) frame
	1	target (lab) frame
	2	projectile frame
29	2	p_t for last two particles in string (<code>clustr</code>)
	0	isotropic
	1	isotropic, baryon goes into forward hemisphere
	2	baryon goes into forward hemisphere, $p_t = 0$
30	1	frozen Fermi approximation in CASCADE mode
	0	disabled
	1	enabled
32	0	distribute resonance masses according to mass-dep. Breit-Wigner
	0	enabled
	1	disabled

CTOption(X)	default / options	description
33	0	use table-lookup for calculation of $\langle p_{CMS} \rangle$ in pmean
	0	enabled
	1	disabled
34	1	resonance life-times
	0	$\tau = 1/\Gamma(M)$
	1	$\tau = 1/\Gamma_{pole}$
	2	DPF formalism
35	1	generate high-precision tables (file tables.dat)
	0	disabled
	1	enabled
36	0	correct normalization for mass-dependent Breit-Wigner distributions
	0	enabled
	1	disabled
37	0	Heavy Quark Clusters
	0	disabled
	1	enabled
38	0	scale p-pbar to b-bbar with equal p_lab
	0	disabled
	1	enabled
39	0	compute collision densities via call to Pauli-blocker
	0	enabled
	1	disabled
40	0	use old file14 as initial state for calculation
	0	disabled
	1	enabled
41	0	extended file14 output (needed for cto(40))
	0	disabled
	1	enabled
	2	different counting rules for origin
42	0	color fluctuations in high energy hadron-hadron collisions
	0	disabled
	1	enabled

Table 6: available options in UrQMD

5 Output files

The UrQMD program has several different output files. The *standard output files* (`file13` and `file14`) contain all particles of a given event at a certain time-step. The *collision history file* (`file15`) contains information on all collisions/decays of a given event. The *decay file* (`file16`) contains information on all particle decays as well as information on all stable particles after the final timestep. The *OSC files* (`file19`, `file20`) generates output compliant with the Open Standards And Codes (OSCAR) format. Consecutive timesteps (only `file13` and `file14`) and events are added sequentially to the files.

Each event consists of a header and a body. The standard header is identical for `file13`, `file14` and `file16` and `file15` use an abbreviated header and the format of `file19` and `file20` is fixed by the OSCAR requirements.

5.1 Standard output-files: `file13/file14`

The standard output files contain the phase-space of the event at a given timestep (e.g. final output after last timestep). `file13` contains the same information as `file14`, but additionally lists the freeze-out coordinates in configuration- and momentum-space for all particles.

Figure 3 shows a standard header as used in `file13`, `file14` and `file16`. Only one header per event is written to file. Consecutive time-steps of the same event are added body to body without additional headers between them.

The general format of the standard-fileheader can be found in table 7, its contents is self-explanatory – please consult figure 3.

The body of the *standard output files* contains in its first line the number of particles N_{part} to follow (there are as many lines to follow as there are particles) and the time (in fm/c) of the output (two unformatted integers). The next line contains counters for the number of collisions, decays and produced resonances per event (`format(8i8)`), it is described in table 8.

The subsequent N_{part} lines then contain the information on the individual particles. The exact format of the particle vector depends on the chosen output file and the selected options. Table 9 lists the different possibilities. Figure 4 shows the beginning of a sample event body for `file14`.

The standard output files should suffice for most types of analysis. They provide the event information at a given timestep (mostly the final timestep). The contents of the particle vectors is described in table 10. All reference frame dependent values are given in the computational frame, which has been fixed by `CTOption(27)`.

5.2 Collision history file: `file15`

The collision file `file15` contains each binary interaction, resonance decay and string-excitation which occurred in the course of the heavy-ion reaction. It can be used to reconstruct the entire space-time evolution of the event. Each entry (collision, decay or annihilation) consists of a header line followed by 3 to N lines (three lines for annihilations/decays, four lines for scattering, more lines for string-decays) with the individual particle information.

line#	format
1	format(a20,3i7,a15,i2)
2	format(a13,a13,i4,i4,a12,a13,i4,i4,a1)
3	format(a36,3f10.7)
4	format(a36,3f6.2,a31,1f9.2)
5	format(a20,i3,a15,e10.4,a15,e10.4,a15,e10.4)
6	format (a7,i9,a13,i12,a9,a20,i4,a20,f7.3)
7	format(a2,15(i3,a2))
8	format(a2,15(i3,a2))
9	format(a2,15(i3,a2))
10	format(a2,12(e11.4,a2))
11	format(a2,12(e11.4,a2))
12	format(a2,12(e11.4,a2))
13	format(a2,12(e11.4,a2))
14	format(a171)

Table 7: format for the standard event header.

column#	contents
1	# of collisions
2	# of elastic collisions
3	# of inelastic collisions
4	# of Pauli-blocked collisions
5	# of decays
6	# of produced <i>hard</i> baryon resonances
7	# of produced <i>soft</i> baryon resonances
8	# of baryon resonances produced via a decay of another resonance

Table 8: description of the collision/decay counters in the standard output file

format	
<code>format(9e16.8,i5,2i3,i6,i5,i4)</code>	standard file14 and file16
<code>format(9e16.8,i5,2i3,i6,i5,i10,3e16.8,i8)</code>	file14 with CTOption(41)=1
<code>format(9e16.8,i5,2i3,i6,i5,i4,8e16.8)</code>	standard file13
<code>format(9e15.7,i5,2i3,i6,i5,i4,2i4)</code>	file16 with CTOption(13)

Table 9: particle-vector format for different output-options in the standard output files.

The event-header consists of a single line of the format:

`format(i1,i8,i4,i7,f8.3,4e12.4)`

The format is identical to the header line for the respective binary interactions and decays which follow in the the file. In order to distinguish the beginning of an event from the beginning of a collision/decay entry, the first integer in the event header is a 0. It is then followed by the number of the event, the mass of projectile and target, the impact parameter, the two-particle c.m. energy of the heavy-ion reaction (i.e. \sqrt{s} for proton-proton reactions), the total cross section of the heavy-ion reaction and the beam energy and momentum (per particle) in the laboratory frame.

Figure 5 shows a sample collision entry. The header line contains first the number of in- and outgoing particles (scattering: 2 2; decay: 1 2; annihilation: 2 1; Pauli-blocked collision: 2 0; Pauli-blocked decay: 1 0 and string decay with 5 outgoing particles: 2 5), the ID of the respective process (e.g. elastic scattering, decay, string excitation ...) then the number of the collision (in the respective event), the collision time in fm/c, the the total CM energy (\sqrt{s} in GeV), the total cross section (σ_{tot} in mbarn), the partial cross section (σ_i in mbarn) for the respective exit channel and finally the baryon density at the collision point (in units of nuclear ground state density). Note that the cross sections are ill-defined in the case of a decay.

One of the purposes of the collision file is to have the possibility to track the trajectory of a single particle in the course of the reaction or the time evolution of the available CM-energy per binary collision. The contents of the particle vectors has the format:

`format(i5,9e16.8,i5,2i3,i6,i5,i3,i15)`

and is described in table 11.

5.3 Decay output: file16

The header of the decay output file is identical to that of the *standard output files* (see figure 3 and table 7). The body of the *decay file* contains entries for each particle which has decayed during the event as well as a list of all stable particles after the final timestep of the event. Since the number of decays and particles listed in the event-body is not determined at the point where the first output is written to file, the event body directly starts with particle-vector entries (see tables 9 and 10). The end of the event is marked with a line of the format `format(a1,8i8)`, which contains an E as a marker in the first column, followed by the collision counters listed in table 8.

For CTOption(13)=1 all outgoing particles of all collisions and decays are listed instead of the decaying particles alone. The *decay output file* provides additional information about the produced

column#	contents
1	t : eigentime of particle in fm/c
2	r_x : x coordinate in fm
3	r_y : y coordinate in fm
4	r_z : z coordinate in fm
5	E : energy of particle in GeV
6	p_x : x momentum component in GeV
7	p_y : y momentum component in GeV
8	p_z : z momentum component in GeV
9	m : mass of particle in GeV
10	$ityp$: particle-ID
11	$2 \cdot I_3$: isospin z-projection (doubled)
12	ch : charge of particle
13	index of last collision partner
14	N_{coll} number of collisions
15	history information (parent process)
16	t_{fr} : freeze-out time of particle in fm/c (file13 only)
17	$r_{x,fr}$: freeze-out x coordinate in fm (file13 only)
18	$r_{y,fr}$: freeze-out y coordinate in fm (file13 only)
19	$r_{z,fr}$: freeze-out z coordinate in fm (file13 only)
20	E_{fr} : freeze-out energy of particle in GeV (file13 only)
21	$p_{x,fr}$: freeze-out x momentum component in GeV (file13 only)
22	$p_{y,fr}$: freeze-out y momentum component in GeV (file13 only)
23	$p_{z,fr}$: freeze-out z momentum component in GeV (file13 only)
16	τ_{dec} decay time of particle (file14 with CTOption(41)=1)
17	τ_{form} formation time of particle (file14 with CTOption(41)=1)
18	R_σ cross section reduction factor (file14 with CTOption(41)=1)
19	unique particle number (not ID!) (file14 with CTOption(41) =1)
16	$ityp_{old,1}$: particle-ID of parent particle # 1 (file16 with CTOption(13)=1)
17	$ityp_{old,2}$: particle-ID of parent particle # 2 (file16 with CTOption(13)=1)

Table 10: contents of the particle vector in the standard output files

column#	contents
1	ind : index of particle
2	t : eigentime of particle in fm/c
3	r_x : x coordinate in fm
4	r_y : y coordinate in fm
5	r_z : z coordinate in fm
6	E : energy of particle in GeV
7	p_x : x momentum component in GeV
8	p_y : y momentum component in GeV
9	p_z : z momentum component in GeV
10	m : mass of particle in GeV
11	$ityp$: particle-ID
12	$2 \cdot I_3$: isospin z-projection (doubled)
13	ch : charge of particle
14	index of last collision partner
15	N_{coll} number of collisions
16	S : strangeness
17	history information (parent process)

Table 11: contents of the particle vector in the collision file

baryon- and meson-resonances when compared to the *standard output file*. Since it contains particle output at different times during the event, however, one has to be very careful when extracting cross sections. All reference frame dependent values are given in the computational frame, which has been set by `CTOption(27)`.

5.4 OSC1997A output (OSCAR 1997A format): file19

The OSC output format has been defined by the OSCAR group in order to create a well defined easily accessible output-format which is supported by all OSCAR compliant transport models, event generators and other heavy-ion related models. For a full overview of the goals of the OSCAR collaboration, please consult the web-site

<http://rhic.phys.columbia.edu/oscar/index.html>

UrQMD supports the OSC1997A output format. The file-header consists of three lines: The first two lines have the format `format(a12)` and specify the format (e.g. OSC1997A) and the file contents. Currently, this is `final_id_p_x`, i.e. the final event output including particle ID, the momentum space information and the freeze-out coordinates in configuration space. The third line has the format `format(2(a8,2x),(' ',i3,',',' ',i6,')+((' ',i3,',',' ',i6,')',2x,a4,2x,e10.4,2x,i8)`


```

UQMD version:      10000  1000  10001  output_file 14
projectile: (mass, char) 32 16 target: (mass, char) 32 16
transformation betas (NN,lab,pro) .0000000 .7183285 -.7183285
impact_parameter_real/min/max(fm): .00 .00 .00 total_cross_section(mbarn): .00
equation_of_state: 0 E_lab(GeV/u): .2000E+01 sqrt(s)(GeV): .2697E+01 p_lab(GeV/u): .2784E+01
event#          1 random seed: 1944955121 (fixed) total_time(fm/c): 60 Delta(t)_O(fm/c): 60.0
op 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
op 0 0 0 0 0 0 1 0 1 0 0 0 0 0 2 1
op 0 0 0 1 1 0 0 0 0 0 0 0 0 0 0 0
pa .1000E+01 .5200E+00 .5000E+00 .3000E+00 .0000E+00 .3700E+00 .0000E+00 .9300E-01 .3500E+00 .2500E+00 .0000E+00 .5000E+00
pa .2700E+00 .4900E+00 .2700E+00 .1000E+01 .1600E+01 .8500E+00 .1550E+01 .0000E+00 .0000E+00 .0000E+00 .0000E+00 .0000E+00
pa .9000E+00 .5000E+02 .1000E+01 .1000E+01 .4000E+00 .1500E+01 .1600E+01 .0000E+00 .2500E+01 .1000E+00 .3000E+01 .2750E+00
pa .4200E+00 .1080E+01 .8000E+00 .5000E+00 .0000E+00 .5500E+00 .5000E+01 .8000E+00 .5000E+00 .8000E+06 .1000E+01 .2000E+01
pvec: r0 rx ry rz p0 px py pz m ityp 2i3 chg lcl# ncl or
... start of event body ...

```

Figure 3: sample header of an UrQMDoutput file.

```

83 60
248 105 141 2 78 165 0 0
.60000000E+02 -.35597252E+02 -.76801184E+01 .30121505E+01 .11839331E+01 -.70109432E+00 -.16633296E+00 .51512840E-01 .93800002E+00 1 1 1 1 9 20
.60000000E+02 .81996126E+01 .19904670E+02 -.24104662E+02 .11707300E+01 .14606801E+00 .47854791E+00 -.49032721E+00 .93800002E+00 1 -1 0 2 17 20
.60000000E+02 .54067910E+01 .30092770E+02 .35340946E+02 .15291829E+01 .14462310E+00 .74024320E+00 .94322867E+00 .93800002E+00 1 1 1 37 3 30
.60000000E+02 .72953637E+00 -.35051235E+01 -.14941324E+02 .96631053E+00 .47106723E-02 -.60615381E-01 -.22408834E+00 .93800002E+00 1 1 1 13 2 19
...

```

Figure 4: beginning of a sample body of an UrQMDstandard output file.

```

...
2 2 1 1 .398 .2650E+01 .4565E+02 .1834E+02 .1742E+01
31 .39812730E+00 .10071119E+01 .11882873E+01 .10408219E+00 .13016664E+01 -.64792705E-01 -.13898806E-01 .91198600E+00 .92640464E+00 1 -1 0 0 0 0
64 .39812730E+00 .28051872E+00 .15413296E+01 .10408219E+00 .13490995E+01 .11074780E+00 .15481079E-01 -.97761791E+00 .92294520E+00 1 -1 0 0 0 0
31 .39812730E+00 .10071119E+01 .11882873E+01 .10408219E+00 .15827584E+01 -.15319538E+00 .62127758E-01 -.53196784E+00 .14814876E+01 17 -3 -1 64 1 0
64 .39812730E+00 .28051872E+00 .15413296E+01 .10408219E+00 .10680074E+01 .19915048E+00 -.60545484E-01 .46633592E+00 .93800002E+00 1 1 1 31 1 0
2 2 5 2 .743 .2791E+01 .4448E+02 .8529E+00 .1857E+01
25 .74262809E+00 -.11192341E+01 -.13384231E+01 .25707630E-01 .14261601E+01 .32413590E-01 -.82195855E-01 .10840402E+01 .92248724E+00 1 -1 0 0 0 0
50 .74262809E+00 -.97716182E+00 -.18394695E+01 .25707630E-01 .13692160E+01 -.13287008E-01 -.56741371E-01 -.10054827E+01 .92755640E+00 1 -1 0 0 0 0
25 .74262809E+00 -.11192341E+01 -.13384231E+01 .25707630E-01 .14831149E+01 .14886580E+00 -.27346802E+00 -.36638117E+00 .14030142E+01 2 -1 0 50 1 0
50 .74262809E+00 -.97716182E+00 -.18394695E+01 .25707630E-01 .13122612E+01 -.12973922E+00 .13453079E+00 .44493867E+00 .12202985E+01 17 -1 0 25 1 0
...
1 2 20 4 .858 .1481E+01 .0000E+00 .1718E+02 .1928E+01
31 .85784130E+00 .96261609E+00 .12063324E+01 -.50428488E-01 .15827584E+01 -.15319538E+00 .62127758E-01 -.53196784E+00 .14814876E+01 17 -3 -1 64 1 0
31 .85784130E+00 .96261609E+00 .12063324E+01 -.50428488E-01 .11582730E+01 -.45590325E+00 -.19299762E+00 -.46546376E+00 .93800002E+00 1 -1 0 31 2 0
65 .85784130E+00 .96261609E+00 .12063324E+01 -.50428488E-01 .42448534E+00 .30270787E+00 .25512538E+00 -.66504080E-01 .13800000E+00 101 -2 -1 31 1 0
...

```

Figure 5: excerpts of a sample body of an UrQMDcollision history file.

and contains first the model-name and version, followed by mass and charge of projectile and target, the reference frame of the calculation, the incident beam energy and the number of test-particles used per nucleon.

The event header consists of one line with the format:

```
format(i10,2x,i10,2x,f8.3,2x,f8.3)
```

This line lists the number of the event, the number of particles in the event, the impact parameter and an azimuthal angle ϕ with which the event-plane might be rotated with respect to the xz -plane. The subsequent particle entries of the event-body have the format:

```
format(i10,2x,i10,2x,9(e12.6,2x))
```

and contain first the particle number, its ID, then the four-momentum vector of the particle (p_x, p_y, p_z, E), followed by the mass of the particle and finally its freeze-out location (x_f, y_f, z_f, τ_f).

The particle ID is given according to the definitions of the *Review of Particle Properties* Monte-Carlo naming scheme. Composite clusters (nuclei) are marked with 7AAAZZZ (AAA: mass, ZZZ: charge of cluster). If other objects than nuclei are used as projectile or target, then a -1 is listed in the mass-slot followed by the PDG-ID in the charge slot. Figure 6 shows a sample output in the OSC format.

5.5 OSC1999A output (OSCAR 1999A format): file20

The OSC1999A is an improvement to the OSC97A output and allows to write out the complete event history – starting with the initial state, including all binary collisions, string-fragmentations and hadronic decays. In its scope it is comparable to the UrQMD file15 collision output file, but includes also the full initial configuration and final state information. An abbreviated OSC199A output format without the intermediate collision history can be used as replacement for the OSC97A output format. The first three lines of the header are almost identical to the OSC97A format, but are preceded by a comment marker # and a blank space in each line.

The first two lines thus have the format `format(a20)` and specify the format (e.g. # OSC1999A) and the file contents. Currently, this can be # `full_event_history`, the final output tag `final_id_px` referring to the OSC1997A format. The third line has the format

```
format('# (',i3,',',i6,')+(',i3,',',i6,')',2x,a4,2x,e10.4,2x,i8)
```

and contains first the model-name and version, followed by mass and charge of projectile and target, the reference frame of the calculation, the incident beam energy and the number of test-particles used per nucleon. OSCAR further recommends that additional information be provided in subsequent comment lines, e.g.

```
# Initial Condition:  Au + Au @ 200
GeV/c
# Cascade Time Ordering:  Center of
Mass
# [additional parameters supplied for
the run]
```

The remaining file after the comments contains the full history of each event in blocks of data. Each block describes one interaction and has the following format:

```
block header  (one line)
particle list (one or more lines)
```

```

OSC1997A
final_id_p_x
  UrQMD      1.0  ( 32,      16)+( 32,      16)  eqsp  .2000E+01      1
      1      83      .000      .000
      1      2212  -.701094E+00  -.166333E+00  .515128E-01  .118393E+01  .938000E+00  -.355973E+02
      2      2112  .146068E+00  .478548E+00  -.490327E+00  .117073E+01  .938000E+00  .819961E+01
      3      2212  .144623E+00  .740243E+00  .943229E+00  .152918E+01  .938000E+00  .540679E+01
      4      2212  .471067E-02  -.606154E-01  -.224088E+00  .966311E+00  .938000E+00  .729536E+00
      5      2212  -.225070E-01  -.148103E-01  .231440E+00  .966506E+00  .938000E+00  -.866336E+00
      6      2212  -.241272E+00  .159999E+00  -.574162E+00  .113724E+01  .938000E+00  -.126123E+02
...

```

Figure 6: Sample output in the OSC1997A format.

The block header contains:

```
nin nout [optional information]
```

with `nin` and

`tt nout` being integers denoting the number of ingoing and outgoing particles of that particular reaction – e.g. 2 2 for two particles scattering into two particles or 1 2 for a resonance decaying into two particles. Optional information can be anything that fits on one line. For example one could put `g q -> g q` to characterize the block as describing elastic quark-gluon scattering. Thus the minimum format for that line is `format (2(i7,2x))`. In UrQMD additional information is supplied analogously to the file15 output: after `nin` and `nout` the ID of the respective process (e.g. elastic scattering, decay, string excitation ...) is listed, followed by the number of the collision (in the respective event), the collision time in fm/c, the total CM energy (\sqrt{s} in GeV), the total cross section (σ_{tot} in mbarn), the partial cross section (σ_i in mbarn) for the respective exit channel and finally the baryon density at the collision point (in units of nuclear ground state density). Note that the cross sections are ill-defined in the case of a decay.

The next `nin` lines are incoming particles followed by `nout` lines of outgoing particles, the format of these lines is

```
ipart id ist px py pz p0 mass x y z t [optional information]
```

This format is identical to the particle entries of the OSC1997A format with two additions: `ist` is an integer containing additional information related to the particle ID – this is needed in some event generators indicating the status of the particular entry. The optional information can be anything useful or relevant to the particular model, but has to fit into the same output line. Thus, each particle entry line contains first the particle number, its ID, the 2nd ID-tag, then the four-momentum vector of the particle (p_x, p_y, p_z, E), followed by the mass of the particle (all in GeV) and finally its production vertex $[(x, y, z, \tau);$ in fm and fm/c]. The minimal format for this line is `format (3(i10,2x),9(e12.6,2x))`.

It should be noted that the particle number `ipart` is a unique particle identifier (not equivalent to the memory slot information used in OSC1997A) which is created for a particle at its production point and is retired for the duration of the event at the destruction/scattering vertex of the respective particle. It thus can be used to track trajectories of particles in the course of the reaction.

The particle ID is given according to the definitions of the *Review of Particle Properties* Monte-Carlo naming scheme. Composite clusters (nuclei) are marked with 7AAAZZZ (AAA: mass, ZZZ: charge of cluster). If other objects than nuclei are used as projectile or target, then a -1 is listed in the mass-slot followed by the PDG-ID in the charge slot.

The very first block of each event describes the initial distribution of the nucleons (partons, or other species). In this case the header contains `nin=0` and `nout` is the number of initial particles, followed by the respective particle vectors in the body of the block. OSCAR recommends optional information for the event header to include the event number, impact parameter and azimuthal angle/orientation of that event. Thus the header of the first event block is very similar to the OSC1997A format:

```
format (3(i7,2x),2(f8.3,2x))
```

listing a zero, the number of initial particles, the number of the event, the impact parameter and an azimuthal angle ϕ with which the event-plane might be rotated with respect to the xz -plane.

The very last block of each event describes the final (freezeout) configuration of all particles. Here the header comes with `nin` as the number of final particles and `nout = 0`.

Figure 7 shows a sample output in the OSC1999A format.

A Appendix: Changes from version 1.0/1.1 to 1.2

New OSCAR output

The OSC1999A OSCAR intermediate file output format has been added. Caution: to remain consistent with our input-file convention, you have to insert `f20` into your `urqmd-inputfile` in order **not** to get any `file20` output. If you forget this, you will get a `fort.20` which will surely explode your quota, since the output on this file is **huge**.

This format is similar to our collision-file output format, but adheres to the new OSCAR OSC1999A output convention. Output is written to Fortran-unit 20.

New features include particle ID according to the PDG Monte-Carlo ID scheme and a new global quantum number, `uid` (stands for Unique Particle ID), i.e. a serial number the particle gets at creation and which is retired from the event after the particle undergoes an interaction. This ID is supposed to make the tracing of a particle through the collision file easier, since it does not change dynamically as our particle-slots/numbers do, due to the internal `UrQMD` memory management. Most file modifications are due to the introduction of this new `uid`-array. As usual all output statements are found in `output.f`

Heavy quark clusters

A mechanism to cluster strange quarks into di-quarks is introduced. This can explain the strangeness enhancement at SPS. It can be switched on with `CTOption(37)=1`.

Bug-fixes and improvements

- In `GNUmakefile` there is a small modification for the code to run on Alpha-machines.
- Complete rewrite of `gnuranf`. `gnuranf` is now the default for Linux.
- A new angular distribution in the meson-baryon channel is used. I.e. isotropic resonance decays below an inv. mass of 6 GeV and a forward-backward behavior above. `angdis.f`: for collisions with `sroot` larger than 6 GeV zero degree scattering is enforced (only deflection from string decay).
- A sign-error in `angdis.f` has been corrected. This error led to a wrong symmetry in meson-baryon collisions (only visible when running `UrQMD` for elementary hadron-hadron collisions).
- New environment variable `URQMD_TAB` to find `tables.dat` (think of `export URQMD_TAB=tables.`uname``)
- Higher meltpoint for resonant meson absorption on baryons (only eta, rho, omega and all hyperon channels).

```

# OSC1999A
# full_event_history
# UrQMD 1.2
# ( 4, 2)+( 4, 2) nncm 0.5000E+02 1
# 0 8 1 0.200 0.000
1 2212 0 -.521296E-01 0.525298E-01 0.405082E+01 0.415387E+01 0.916548E+00 0.
2 2212 0 -.723310E-01 0.239309E-01 0.517619E+01 0.525948E+01 0.929208E+00 0.
3 2112 0 0.596589E-01 -.202471E-02 0.544394E+01 0.552250E+01 0.926260E+00 0.
4 2112 0 0.648017E-01 -.744360E-01 0.487618E+01 0.496485E+01 0.928902E+00 0.
5 2212 0 -.442186E-01 0.180513E-01 -.437103E+01 0.446873E+01 0.928092E+00 0.
6 2212 0 -.385991E-01 0.383077E-01 -.431142E+01 0.441015E+01 0.926336E+00 0.
7 2112 0 -.489669E-01 0.150743E-01 -.557163E+01 0.564798E+01 0.924068E+00 0.
8 2112 0 0.131784E+00 -.714333E-01 -.532665E+01 0.540741E+01 0.918942E+00 0.
2 4 15 1 0.118 0.9420E+01 0.3847E+02 0.2506E+02 0.1508E+01
4 2112 0 0.648017E-01 -.744360E-01 0.487618E+01 0.496485E+01 0.928902E+00 0.
5 2212 0 -.442186E-01 0.180513E-01 -.437103E+01 0.446873E+01 0.928092E+00 -J
9 2114 0 0.376577E+00 -.473402E+00 0.223060E+01 0.261298E+01 0.121909E+01 0.
10 2212 0 -.311133E+00 -.221868E+00 -.318752E+01 0.334457E+01 0.938000E+00 -J
11 -3112 0 0.235318E+00 -.485507E+00 0.890289E+00 0.158258E+01 0.119200E+01 0.
12 3114 0 -.280179E+00 0.112439E+01 0.571773E+00 0.189345E+01 0.138400E+01 0.
...
2 2 19 3 0.290 0.9240E+01 0.3840E+02 0.7584E+01 0.1680E+01
14 2112 0 -.425527E-01 0.836121E-01 0.366816E+01 0.378736E+01 0.938000E+00 -J
7 2112 0 -.489669E-01 0.150743E-01 -.557163E+01 0.564798E+01 0.924068E+00 -J
18 2112 0 0.845839E-02 -.167264E+00 0.366215E+01 0.378408E+01 0.938000E+00 -J
19 2112 0 -.999780E-01 0.265951E+00 -.556562E+01 0.565126E+01 0.938000E+00 -J
...
1 2 20 7 1.257 0.1687E+01 0.0000E+00 0.5665-265 0.7609E+00
26 1212 0 -.163056E+00 -.115806E+00 -.522476E+01 0.549408E+01 0.168722E+01 0.
32 2214 0 -.352471E+00 -.203853E-01 -.320625E+01 0.345977E+01 0.125111E+01 0.
33 -211 0 0.189415E+00 -.954203E-01 -.201851E+01 0.203431E+01 0.138000E+00 0.
...
26 0
39 2112 0 -.207591E+00 -.539088E-01 -.306519E+01 0.321267E+01 0.938000E+00 0.
28 2212 0 -.362984E+00 0.210145E+00 0.446340E+01 0.458015E+01 0.938000E+00 0.
35 2112 0 0.130921E+00 0.811300E-01 0.324282E+01 0.337927E+01 0.938000E+00 -J
46 2112 0 0.321851E+00 -.147599E+00 0.166698E+01 0.194526E+01 0.938000E+00 0.
21 2212 0 0.234665E+00 0.398535E+00 -.210678E+00 0.106683E+01 0.938000E+00 -J
29 2212 0 0.746550E+00 -.257338E+00 -.701843E+00 0.141279E+01 0.938000E+00 0.
...
0 0

```

Figure 7: Sample output in the OSC1999A format.

- Bugfix in meson-meson annihilation cross section.
- `string.f`: subroutine `ityp2id` case of u-quark anti-u quark: quark ids corrected from 2 and -2 to 1 and -1.
- `string.f`: subroutine `gausspt` comment with respect to the calculated distribution is corrected
- `make22.f`: sighera warning only active if new logical variable - `warn` - is true. analogously defined as variables - `check` - and - `info` - in `tt.coms.f`. As default the variable `warn` is set as false to avoid countless warnings.
- `coms.f`: new logical variable - `warn` - `nmax` = maximum number of particles increased from 5000 to 40000.
- `input.f` Due to the enhancement of `nmax` in `coms.f` a warning is added if calculations are performed for energies smaller than $200 \text{ A GeV} = E_{lab}$ or p_{lab} or `sroot` smaller 20 A GeV: parameter `nmax` in `coms.f` may be decreased!
- `colltab.f`: `ncollmax`: maximum number of entries in collision table is increased from 5000 to 10000.

B Appendix: Changes from version 1.2 to 1.3

Initialization

In UrQMD version 1.3 a new initialization method for cascade mode has been implemented. The initialization method used in UrQMD 1.0-1.2 led to an increased nucleon density on the surface of the nucleus and a too small total collision crosssection. For calculations with Skryme equation of state (eos<>1) the old initialization method is still the recommended one.

Caution! Due to the new initialization method calculations made with UrQMD version 1.3 may give results deviating from the results published with earlier versions of UrQMD!

To reproduce old results you can set `cto 24 0` to get the old initialization.

New Options

- New parameter `ctp 21` allows the initialization of deformed nuclei. The parameter 25 gives the deformation parameter (default is 0.0).
- New option `stb [ityp]` prevents the decay of a particle type [ityp]. Multiple definitions of `stb` in the input file are allowed.
- Phasespace correction for upper mass limit of resonances. This feature is important for correct dilepton spectra. To enable this feature set `cto 25` to 1. Default is 0.
- Alternate parametrisation of the p-pbar annihilation crosssection. You can switch with `cto 38`. For a detailed description of the two parametrizations see Phys.Rev.C66:054903,2002.
- New option `cto 41 2`:
`origin(i)` modified: elastic collisions no longer overwrite the production process. Instead elastic collisions increment the 3rd digit of origin (`origin+=100`). A process with `iline=27` and no color exchange is treated as an elastic collision.

New Channels

To improve the description of Kaon production at low energies the following channels have been implemented:

$$p + p \Longrightarrow p + \Sigma^+ + K^0 \quad (1)$$

$$p + p \Longrightarrow p + \Sigma^0 + K^+ \quad (2)$$

$$p + p \implies p + p + f_0 \implies p + p + K^+ + K^- \quad (3)$$

$$p + p \implies p + p + a_0 \implies p + p + \bar{K}^0 + \bar{K}^- \quad (4)$$

$$\pi^- + p \implies N^* \implies n + f_0 \implies n + K^+ + K^- \quad (5)$$

Changes from version 1.3 to 1.3p1

A bug in the tabulated decay width of higher resonances, led to an overpopulation of a0-Mesons at SIS energies. This bug is fixed in version 1.3 patchlevel 1.

C Appendix: Known problems and inconsistencies in UrQMD

- Discrepancies to 12 GeV pp data: pions at mid-rapidity are too low. Proton stopping not perfect. Hyperon/ Φ -meson production in pp not in line with data.
- Meson-meson cross sections are very ugly and have discontinuities at the meltpoint to siphera cross section (1.7 GeV) . They should better be treated in a similar way as the meson-baryons.
- Parametrisation of Ω production is unknown.
- For the total cross sections we should use the Regge parametrisation instead of siphera. It is more common and valid at higher energies.
- Phase space must be considered when resonance masses are generated. This is an argument of Jörn Knoll (GSI) (see also nucl-th/9811099). He attacked the Giessen transport group for doing it wrong, but some inconsistencies also remain in UrQMD
- The spline routine can cause discontinuities in the widths and cross sections.
- The angdis fix (meson-baryon channel) is still only an ad-hoc fix. Furthermore we need to improve angular distributions also for decays.
- Coherent scattering may become important at high energies. I.e. modifies energy distribution for the different binary collisions (see Nexus, K. Werner).
- Perturbative QCD effects need to be included from RHIC energies on. This enhances particle production at RHIC energies by at least 15%.
- Detailed balance is violated due to string decays and other multi-particle ($n \geq 3$) decays, e.g. $\omega \rightarrow 3\pi$, for which no inverse reactions are implemented.
- The frame dependence of the code (target vs. projectile vs. CMS-frame) leads to asymmetric distributions and different yields in forward-backward hemispheres at RHIC.