

## HX-191DPB



--	--	--	--	--	--	--	--	--	--	--

### Technical Specifications

1. Display Size/Type	19" Active Matrix TFT LCD	20. Input Voltage	AC 100~240V, 50/60Hz Autodetect
2. Resolution	1280 x 1024 (SXGA)	21. Power Consumption	42W Maximum
3. Aspect Ratio	5:4	22. Operating Temperature	5~35°C / 41~95°F
4. Pixel Pitch	0.294(H)mm x 0.294(V)mm	23. Humidity	10%~85%
5. Brightness	300cd/m <sup>2</sup>	24. Net Dimensions	16.38"(W) x 16.29"(H) x 8"(D)
6. Response Time	5ms (Typical)	25. Net Weight	12.5 lbs.
7. Contrast Ratio	1000:1 (Typical)	26. Gross Dimensions	20"(W) x 17.5"(H) x 5"(D)
8. Displayable Colors	16.7 Million	27. Gross Weight	15.9 lbs.
9. Viewing Angle (H/V)	170°/160°	28. Certifications	FCC, UL, C-UL, CE, BSMI, CB, TUV, NOM, TCO'99, EPA Energy Star,
10. Color Temperature	9300K, 6500K, 5500K, User Mode	29. Package Contents	HX-191DPB, VGA Cable, Audio Cable, Power Cable, User Manual CD-ROM, Quick Start Guide, Warranty Card
11. Panel Treatment	Anti-Glare Hardcoating	30. UPC Code	842651000370
12. Horizontal Frequency	31kHz to 80kHz	31. Warranty	3-Year Limited (3-Year Parts/Labor, 1-Year LCD/Backlight)
13. Vertical Frequency	55Hz to 75Hz		
14. Video Input(s)	15-Pin D-SUB (VGA), DVI		
15. Speakers	1W x 2 Channel Built-in Stereo		
16. Headphone Out	NA		
17. Tilt	0°~20°		
18. Kensington Slot	Yes		
19. VESA Mounting	100 x 100mm		



**Beverly Hills Store** 420 N. Beverly Drive, Beverly Hills, CA 90210 310.288.0208  
**San Francisco Store** 400 Sutter Street, San Francisco, CA 94108 415.986.3300

©2009 HANNSPREE North America, Inc. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screen shot is simulated.

[www.hannsg.com/us](http://www.hannsg.com/us)  
Version 02132009