

# ULTRA

## Uninterrupted Power Supply (UPS)

### The Ultimate Power Protection!

If you're looking for the most complete, technologically advanced power protection unit for the money, the Ultra UPS line is exactly what you need. An Ultra UPS is an absolute must for anyone running a small server, workstation or a powerful PC. You simply cannot afford to cut corners when it comes to safeguarding your valuable equipment, and these UPS's deliver the comprehensive protection for computer, peripherals and data files at a remarkably low price.

### Features

- Line Interactive Design
- AVR (Automatic Voltage Regulation)
- Fully Digitized Microprocessor Controlled
- Protects up to 4 Devices at Once
- Energy Saving Function (UPS Green Mode)
- 50/60Hz Frequency Auto Sensing and Selection
- USB Communication Port
- Advanced Battery Management (ABM Technology)



Includes  
UPS Monitoring  
Software



		1000VA	1025VA	1500VA	2000VA
General	SKU	ULT31502	ULT33044	ULT33045	ULT33046
	Backup Time	About 50 Minutes	About 50 Minutes	About 60 Minutes	About 65 Minutes
	Net Weight Kg. (lbs)	28.6(63.0)	28.6(63.0)		
Output	Digital Display	Yes	Yes	Yes	Yes
	Watts	615	615	900	1200
	UPS Capacity	1025VA	1025VA	1500VA	2000VA
Input	No. of Sockets	Style A UPSx4, Bypassx2			
	Voltage (Battery)	Simulated square wave output at nominal +/-5%			
	Frequency (Battery)	50 or 60Hz +/- 0.3Hz			
	Transfer Time	2-4 milliseconds, including detection time	2-4 milliseconds, including detection time	2-4 milliseconds, including detection time	2-4 milliseconds, including detection time
Protection	Voltage (Single Phase)	120V +15%/-20% at line input			
	Frequency	50 or 60Hz +/- 10% (auto sensing)			
	Unit Input	Circuit breaker for overload & short circuit protection	Circuit breaker for overload & short circuit protection	Circuit breaker for overload & short circuit protection	Circuit breaker for overload & short circuit protection
Battery	Overload Protection	UPS automatic power off if overload exceeds 110% of nominal at 60 seconds and 130% at 3 seconds	UPS automatic power off if overload exceeds 110% of nominal at 60 seconds and 130% at 3 seconds	UPS automatic power off if overload exceeds 110% of nominal at 60 seconds and 130% at 3 seconds	UPS automatic power off if overload exceeds 110% of nominal at 60 seconds and 130% at 3 seconds
	Short Circuit	UPS output shuts off immediately			
	Surge Protection	2100 Joules	2100 Joules	2100 Joules	2100 Joules
Interface	Type	Sealed, maintenance-free lead acid battery, with 3-6 years typical lifetime	Sealed, maintenance-free lead acid battery, with 3-6 years typical lifetime	Sealed, maintenance-free lead acid battery, with 3-6 years typical lifetime	Sealed, maintenance-free lead acid battery, with 3-6 years typical lifetime
	Typical Recharge Time	6 hours (to 90% of full capacity)			
	Protection	Automatic self-test, Over discharge protection, short circuit protection by fuse	Automatic self-test, Over discharge protection, short circuit protection by fuse	Automatic self-test, Over discharge protection, short circuit protection by fuse	Automatic self-test, Over discharge protection, short circuit protection by fuse
Alarm	USB	Battery low detecting, UPS on/off scheduling AC input/output power status display.	Battery low detecting, UPS on/off scheduling AC input/output power status display.	Battery low detecting, UPS on/off scheduling AC input/output power status display.	Battery low detecting, UPS on/off scheduling AC input/output power status display.
	Battery Backup	Slow beeping sound every 4 seconds			
	Battery Low	Rapid beeping sound every second			
	Abnormal Charge	AC Mode: Rapid beeping sound every 0.5 second	AC Mode: Rapid beeping sound every 0.5 second	AC Mode: Rapid beeping sound every 0.5 second	AC Mode: Rapid beeping sound every 0.5 second
Environment	Overload	Continue beeping sound	Continue beeping sound	Continue beeping sound	Continue beeping sound
	Ambient Operation	3,500m max, Humidity: 0%-95%(without condensation formation). Temperature: 0-30 °C	3,500m max, Humidity: 0%-95%(without condensation formation). Temperature: 0-30 °C	3,500m max, Humidity: 0%-95%(without condensation formation). Temperature: 0-30 °C	3,500m max, Humidity: 0%-95%(without condensation formation). Temperature: 0-30 °C



**Automatic Voltage Regulation (AVR)**  
Protect your computer from electrical damage caused by dangerous "spikes and sags".  
**\$125,000 Limited Warranty**

Includes  
UPS Monitoring  
Software

**ULTRA**  
**1-800-830-0051**  
[www.ultraproducts.com](http://www.ultraproducts.com)

# ULTRA