

Michelangelo LAN CX



DESCRIPTION

Michelangelo LAN CX is an **ADSL2/2+ Router** ideal for SOHO (Small Office Home Office) applications over the ADSL line.

It supports the most popular **ADSL2/2+ and ADSL protocols** and has got routing features to carry out and configure your LAN in the best way.

Thanks to the Web based configuration, Michelangelo LAN CX can be simply and quickly configured from Windows®, Macintosh®, Linux, etc., using a common browser (Explorer, Netscape, etc.).

You don't need to connect several times at a day to send and receive the e-mails as your Internet connection will be always on and the telephone line always free for faxes and calls, etc.

Using Michelangelo LAN CX you will exploit all the advantages of the ADSL connection and you will be able to download images, videos and mpeg files in few seconds.

It has an USB port for the direct connection of a Windows® PC.

The built-in Stateful Packet Inspection Firewall protects your LAN from Internet attacks and intrusions.

Code: 8E4224

- Asymmetric data speed
- Downstream max.speed: 24Mbps (ADSL2+), 8Mbps (dmt)
- Upstream max.speed: 1Mbps (ADSL2+), 1Mbps (dmt)
- ADSL standard: ADSL2+, ADSL2, DELT, READSL2, ADSL Full-rate ANSI T1.413 Issue 2, G.dmt, G.lite, G.hs
- Flash upgradable
- NAT and NAT Export supported
- Supported protocols:
 - RFC-2364 (PPP over ATM)
 - RFC-2516 (PPP over Ethernet)
 - RFC-1483 (Bridged and Routed Ethernet over ATM)
- ATM UNI3.1/4.0 PVC, ATMSAR, ATM AAL5 and OAM F5 support
- ADSL WAN interface: RJ 11 connector
- 10/100 Mbps LAN port
- 1 USB 1.1 port
- Built-in Stateful Packet Inspection Firewall support
- Nat and NAT Export support
- DHCP server and client
- Static and RIPv2 routing
- Packet filtering (block & forward)
- DMZ and IN & OUT VPN Passthrough support
- PAP and CHAP authentication
- FTP TFTP upgradable
- WEB based configuration
- Remote configuration
- LAN, ADSL and ATM autodiagnostic functions
- Power Supply: 12Vac 1A through external power supply 220Vac
- CE Mark

