

10.4" LCD HD Monitors in Metal Housing

LCD-1048HDM

LCD-1048HDM2

3mm Thick
Tempered Glass



LCD-1048HDM



LCD-1048HDM2



Side View

- 3mm thick tempered glass helps to protect display panel from damage in the field
- HD compatible (supports 480p/i, 720p, 1080p/i)
- RS-232 serial control provided
- Composite video BNC IN/OUT provides security for video connections
- Underscan capability
- On-screen display controls, with front controls for Power, Select, Menu, and Volume Up/Down
- Wireless remote control with hot key allows easy toggling between sources
- Rear IR jack allows direct connection for use with IR repeater systems
- Screw-down DC feature provides additional security for power connection
- Speaker output on board allows screw down connection for R/L audio
- Built-in amplifier provides ample power to drive right and left stereo 8 ohm speakers
- Made of durable metal with black powder coating
- Built-in interface and proper cable exiting for wall arm mounting, VESA 75mm compliant
- Response time: 15/25 ms (rising/falling)
- SPS included, 100~240 VAC

Dual Rack-mounted 10.4" Monitors Model LCD-1048HDM2 (shown above)

Dimensions (WHD): 19" x 8.75" x 2.3" (Occupies 5 RU)

Optional Accessories

DC-1500	Factory approved car cord
HM-400	Under-cabinet hinge mount
WM-31	Wall mount bracket (fixed)
WM-302	Wall mount with swing arm & 4-way adjustable

Display: 10.4" TFT LCD active matrix

Back Light: 2 x CCFT

Input Signal: [Composite, component, & S-Video, NTSC/PAL auto sensing]
analog RGB

Dot Pitch: 0.206 (H) x 0.206 (V)mm

Resolution: 1024(H) x 768(V) [700 lines for CCTV] or

Number of Pixels: 786,432 dots

Brightness Rating: 350 cd/m² (Nit)

Colors: 262,144

Contrast Ratio: 500:1

Viewing Angle L/R/T/B: 90/90/90/90 degrees

Pixel Configuration: RGB Vertical Stripe

Audio output: 5W x 2, 8 ohm

Dimensions including BNC jack (WHD): 247 x 215 x 58mm / 9.7" x 8.5" x 2.3"

LCD-1048HDM2: Dimensions (WHD): 19" x 8.75" x 2.3" (Occupies 5 RU)

Actual visible screen size (WH): 210 x 158mm / 8.3" x 6.2"

Operating temperature: 50 ~ 104°F or 10 ~ 40°C

Storage temperature: 14 ~ 158°F or -10 ~ 70°C

Power requirement/consumption: 12VDC, 2A, negative ground / 24W

Rear Terminal Connections: Composite: BNC IN/OUT jacks, 2 RCA IN jacks

Component: 3 RCA IN jacks

S-Video IN jack

Audio: 3.5 PC audio IN, RCA L/R audio inputs,
L/R screw down speaker connectors,
and 3.5 audio line OUT

PC: 15-pin mini D-sub

RS-232: 9-pin

3.5 IR IN

Power: 2.1mm DC jack, screw down DC connector

LCD-1048HDM Weight: Net: 2.4 kg. / 5.3 lbs.

Gross: 3.7 kg. / 8.05 lbs

LCD-1048HDM2 Weight: Net: 6.07 kg. / 13.4 lbs.

Gross: 8.77 kg. / 19.35 lbs



Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50