

Proxima DP9260 Projector

Technical and Functional Specifications

- Display Technology: 1.3 in. polysilicon TFT LCD x 3 with micro lens array
- Resolution: XGA (1024 x 768)
- Resolutions Supported: XGA (1024 x 768); Fit-to-View display of VGA (640 x 480), SVGA (800 x 600), SXGA (1280 x 1024)
- Brightness: 2200 ANSI lumens
- Contrast Ratio: 350:1 (full on, full off)
- Computer Compatibility: IBM PC, PS/2, Pentium and compatibles, SUN, SGI, IBM, HP, DEC, Apple Macintosh, Power Macintosh, and PowerBook families
- Video Compatibility: NTSC, NTSC 4.3, PAL, PAL-M, SECAM, HDTV (480p, 720p, 1080i, 1035i)
- Sources: 2 computer, 1 S-video, 1 composite video, 1 component video, audio for computer and video
- H-Sync Range: 15 to 100 KHz
- V-Sync Range: 50 to 100 Hz
- Dot Clock: 165 MHz
- Horizontal Resolution: 800 TV lines
- Aspect Ratio: std: 4:3 - wide: 16:9
- Image Size Diagonal: 2.5 ft to 25 ft (.76 m to 7.6 m)
- Projection Lens: (Standard) Power zoom and focus lens
- Focal Length: 48.4 mm to 62.8 mm, F 1.8 to F 2.1
- Throw Ratio: 1.8 - 2.4:1
- Projection Distance (From Screen): 4.6 ft to 35.4 ft (1.4 m to 10.8 m)
- Keystone Correction: (Optical) 11 fixed
- Keystone Correction: (Digital) 30 adjustable
- Number of Colors: 16.7 million
- Lamp: 200-watt UHP
- Audio: 2-watt stereo
- Dimensions: 10.7 in. W x 16.2 in. L x 6.1 in. H (27.2 cm W x 41.2 cm L x 15.4 cm H)
- Weight: 15.2 lbs. (6.9 kg)
- Power Consumption: 300 watts
- Power Requirements: 100 to 120V / 220 to 240V at 50/60 Hz
- Operating Temperature: (Sea Level) 41 to 95 F (5 to 35 C)
- Approvals: FCC Class A, UL, c-UL, CE
- Warranty: Two year parts and labor (excluding lamp)
90 days or 500 hours on lamp, whichever comes first