



LCD MONITOR

Display size	19" (48,26 cm) WIDE					
Panel Type	Active Matrix TFT					
Brightness	300 cd/m ² (typ.)					
Contrast (typ.)	1000:1					
X-Contrast (dyn.)	-					
Pixel pitch	0,283(H) x 0,283(V) mm					
Resolution (H x V)	WXGA+ 1440 x 900					
Response time	5 ms (typ.)					
View angles (CR>10)	H/V 170°/160°					
View angles (CR>5)						
Display colors	16,7 Mio colors					
Display Surface	Anti-Glare					
Input 1	VGA, Audio					
Input 2						
Input 3						
Headphone						
Speakers	1 W x 2					
Supply	AC 100~240V, 50~60Hz					
Consumption	On:	55 W	Stand-by:	<2 W	Off:	<1 W
Operation Temp/Hum	0 ~ 35°C			10 ~ 85%		
Dimension (W*D*H)	453 x 200 x 343 mm					
Net weight	4,4 kg					
Tilt	0°~ 20°					
Kensington Lock	✓					
VESA mounting	VESA Standard, 100mm					
On screen display	EN,TC,DE,FR,ES,IT,PT,NL,SC,JS,KR,RU					
Safety	CE,FCC,BSMI,C-Tick, VCCI, CB, UL/CUL, TUV/Bur-Mark,CCC, GOST					
Emission	TCO03					
Power saving	EPA Energy Star					
Extras 1						
Extras 2						
Extras 3						
EAN	4710859555038					
incl Accessory	powercord, VGA cable, audio cable, users manual (CD), quickstart guide (paper), warranty card					



© HANNspree Europe GmbH. Information in this document is subject to change without notice. All brand-, product-, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated.