Model #: P606-015

Computer Cable, 15-ft. IEEE 1284 AB Parallel Gold Cable Cen36M to DB25M

Highlights

- Superior molded cables with integral strain relief and foil-shielding for maximum EMI/RFI protection
- IEEE 1284 cables' gold-plated connectors provide superior conductivity and support high-speed bi-directional printing

Description

Tripp Lite's 15-ft. IEEE 1284 A-B gold parallel printer cable connects computers with a DB25 female parallel port to parallel printers with a Centronics 36 female parallel port. It supports high-speed IEEE 1284 bi-directional communication. The cable features gold plated DB25 male/Cent36 male connectors and gold plated copper contacts for superior conductivity. It is manufactured from superior molded cable with integral strain relief and double shielding for maximum EMI/RFI protection. It contains low-capacitance, impedance matched, twisted-pair conductors that protect against cross-talk and other transmission problems. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

- Computers with a DB25 Female parallel port
- Parallel printers with a Centronics 36 Female parallel port with high-speed IEEE 1284 Bi-Directional communication (although not essential).

Package Includes

- 15-ft. IEEE 1284 AB Parallel Gold Cable DB25M to Cen36M

Features

- Supports high-speed IEEE 1284 bi-directional communication (modes: standard compatible nibble byte ECP and EPP)
- Length: 15-ft. Connectors: DB25 male/Cent36 male
- Gold plated connectors and gold plated copper contacts offer superior conductivity
- Superior molded cable with integral strain relief and double shielding (foil and braid) for maximum EMI/RFI protection
- Low-capacitance impedance matched twisted-pair conductors protect against cross-talk and other transmission problems
- Bi-directional communication allows your printer to broadcast printer error messages back to network computers
- Molded ends with easy-grip textured overmold
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW	
Intended Application	Connecting Peripherals
PHYSICAL	

Color	Black
Style	Printer Cables
Length	15 ft.
CONNECTIONS	
Connector A	DB25 (MALE)
Connector B	CENTRONICS 36 (MALE)

Related Items

Surge Protectors		
DB25-PAR	Network Surge Suppressor - Essential protection for data and communication lines	Qty: [optional]

Switches		
B105-002-R	Switch - 2 Position Manual Data Switch	Qty: [optional]
B105-004-R	Switch - 4 Position Manual Data Switch	Qty: [optional]
B170-002-R	Switch - Reversible 2 Position IEEE Autoswitch	Qty: [optional]
B170-004-R	Switch - Reversible 4 Position IEEE Autoswitch	Qty: [optional]
P606-006	Computer Cable, 6-ft. IEEE 1284 AB Parallel Gold Cable Cen36M to DB25M	Qty: [optional]
P606-010	Computer Cable, 10-ft. IEEE 1284 AB Parallel Gold Cable Cen36M to DB25M	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at
www.tripplite.com/en/products/model.cfm?txtModelID=2294.