



SPECIFICATIONS  
**AKCV35**  
 CENTRAL VACUUMS

**CENTRAL VACUUM POWER UNIT**

- **Motor**  
 Two stage 120 volt, double ball bearing with tangential bypass discharge and thermoset fan end bracket. 11.7 amps.
- **Power Unit Body**  
 Durable textured powder coated all steel body.
- **Performance**  
 CFM at 2" opening: 112  
 Water Lift: 107"  
 Air Watts: 404
- **Collection**  
 5 Gallon Bagged or Bagless collection canister with maintenance free single ply Micro-Tex® polyester fiber filter.
- **Recommended Home Size**  
 Homes up to 3,000 square feet.
- **Mounting**  
 Includes metal mounting bracket and an extra utility inlet.
- **Shipping Information**  
 UPC: 0-83162-  
 Shipping Weight: lbs.



<b>PROJECT</b>							<b>ARCHITECT</b>			
<b>LOCATION</b>							<b>ENGINEER</b>			
<b>CONTRACTOR</b>							<b>SUBMITTED BY</b>			<b>DATE</b>
<b>FAN NUMBER</b>	<b>MODEL NUMBER</b>	<b>CFM</b>	<b>IN W.C.</b>	<b>RPM</b>	<b>WATTS</b>	<b>AMPS</b>	<b>SONES</b>	<b>QTY</b>	<b>OPTIONAL EQUIPMENT &amp; REMARKS</b>	



**U.S.:** 820 Lincoln Drive  
 West Chester, Pennsylvania 19380-4466  
 Tel: (610) 692-7400 • 877-304-3785  
 Fax: (610) 696-8048

**Canada:** 110 Glidden Road  
 Brampton, Ontario L6T 2J3  
 Tel: (905) 456-2033  
 Fax: (905) 456-1015