Hitachi Deskstar® T7K500

HITACHI Inspire the Nexi

3.5-INCH HARD DISK DRIVES

500GB, 400GB, 320GB and 250GB 7200 RPM Parallel ATA 133 and Serial ATA 3.0Gb/s

High Performance Storage.

Highlights

- > SATA 3.0 Gb/s and PATA 133 interfaces
- > Capacities from 250GB up to 500GB
- > Native Command Queuing for maximum data speeds
- > Thermal Monitoring and Fly Height Control for enhanced reliability
- > SMART Command Transport optimized response times

Applications

- > Consumer computers
- > Low duty cycle servers
- > External storage
- > Extreme PC gaming
- > Video editing arrays

Serial ATA Features

- > 3.0Gb/s interface data rate
- > Native Command Queuing
- > Staggered spin up
- > Hot plug capability
- > Click connect connector
- > Scalable performance
- > System improvements

Deskstar T7K500

The Deskstar T7K500 builds on Hitachi's award winning tradition with new 160GB per platter areal density technology. Consumer personal computers and low duty cycle servers demand high capacity and high performance storage to meet consumers digital media needs and growth ATA server application requirements. The Deskstar T7K500 meets these performance requirements and delivers the high capacity for today's applications.

Features and Benefits

	Feature / Function	Benefits	
Performance	High interface transfer rate	Faster system boot-up	
		Quicker screen refreshes	
	Up to 16MB buffer	Faster data processing	
	NCQ (Native Command Queuing)	Faster data processing	
Capacity	500GB, 400GB, 320GB, and 250GB	Popular capacity points	
Reliability	Thermal Fly Height Control (TFC)	Improves error rate	
	Head load/unload	Protects disk during non-operation	
		Reduces power during idle periods	
	ECC and CRC protection	Data integrity enhanced throughout circuits	
	SMART Command Transport (SCT)	Adaptive error correction	
	Internal thermal sensor	Improves data integrity	

Hitachi Quality and Service

The Hitachi Deskstar T7K500 extends on the companies reliability and performance leadership. Hitachi's standardized features in consumer and low duty cycle server solutions enable faster transfer rates, scalable performance and guicker boot up times.

Hitachi is dedicated to providing a breadth of hard disk drive products to satisfy all of today's demanding computing needs. Hitachi hard drives are backed by an array of technical support and services which may include customer and integration service.



Hitachi Deskstar® T7K500

Product Model numbers	Deskstar T7K500 HDT725050VLAT80 HDT725040VLAT80 HDT725032VLAT80 HDT725025VLAT80	Deskstar T7K500 HDT725050VLA360 HDT725050VLA380 HDT725040VLA360 HDT725040VLA380 HDT725032VLA360 HDT725032VLA380 HDT725025VLA360 HDT725025VLA380
Specifications		
Configuration	Parallel-ATA	Serial-ATA
Interface Capacity (GB) ¹ Data heads (physical) Data disks	PATA-133 500/400/320/250 6/6/4/4 3/3/2/2	SATA 3.0Gb/s ← ←
Performance		
Data buffer ² Rotational speed (rpm) Media transfer rate (max. Mbits/sec) Interface transfer rate (max. MB/sec) Average seek time (ms) (read, typical) ³	8 MB 7,200 998 133 8.5	16 MB / 8 MB ← 300 ←
Reliability		
Error rate (non-recoverable) Start/stops (at 40° C) Availability ⁴	1 in 10E14 50,000 24x7	← ← ←
Acoustic		
ldle (Bels, typical)	3.0 (3 disk) 2.8 (2 disk)	←
Power		
Requirement Dissipation Startup current (max. A)	+5 VDC (+/- 5%) +12 VDC (+10 %/-8%) 2.0 (+12V) & 1.1 (+5V)	← ← 2.0 (+12V) & 1.3 (+5V)
ldle (W)	6.0 (3 disk) 5.0 (2 disk)	7.0 (3 disk) 6.0 (2 disk)
Physical Size		
Height (max.mm) Width (mm) Depth (mm) Weight (max.g)	26.1 101.6 147 640	← ← ←
Environmental characteristics		
Operating Ambient temperature (C) Relative humidity (non-condensing) Shock (half sine wave, 2ms) (G) Vibration (random (RMS)) (G)	0° to 60° 8% to 90% 70 0.67 for horizontal 0.67 for vertical	← ← ←
Non-operating Ambient temperature (C) Relative humidity (non-condensing) Shock (half sine wave, 2ms) (G) Vibration (random (RMS)) (G) RoHS compliant ⁵	-40° to 65° 5% to 95% 300 (3 disk) 350 (2 disk) 1.04 rms (XYZ)	← ← ← ←
Kons compliant	Yes	`

¹ GB equals one billion bytes when referring to hard drive capacity; accessible capacity may be less.

² Buffer capacity includes 270 or less KB used for drive firmware.

³ Does not include command overhead

⁴ Low duty cycle, non mission-critical applications in PC, nearline and consumer electronics customer environments are different from application to application.

⁵ RoHS refers to the European Union Directive 2002/95/EC on the restriction of certain hazardous substances in electrical and electronic equipment.

Specific application environments such as temperature and duty cycle will affect the overall reliability rates. For specific application environment reliability rates, please consult Hitachi technical support.

Hitachi Global Storage Technologies

How to Read the Deskstar Model Number

(40 = 400GB, 32 = 320GB, 25 = 250GB)

HDT725050VLA360 = 500GB/16MB

For more information:

V = generation code L = 1-inch form factor

Internet:

0 = Reserved

Example:

H = Hitachi D = Deskstar T = Two- or three-disk 72 = 7200 RPM 50 = full capacity = 500GB 50 = model capacity = 500GB

> www.hitachigst.com (Main Web site)

A3 = SATA 3.0 Gb/s (AT = Parallel ATA) 6 = 16 buffer (8 = 8M buffer)

> www.hitachigst.com/vpp (Reseller Web site)

Technical Support E-mail:

- > support_usa@hitachigst.com (N. America)
- > support_ap@hitachigst.com (Asia Pacific)
- > support_uk@hitachigst.com (EMEA and UK)

Technical Support Phone Numbers:

- > 1888 426-5214 (N. America)
- > 65 6840 9595 (Asia Pacific)
- > 44 20 7133 0032 (EMEA and UK)
- > 49 6929 993601 (Germany Support)

© 2006 Hitachi Global Storage Technologies

Hitachi Global Storage Technologies 3403 Yerba Buena Road San Jose, CA 95135

Produced in the United States 3/06 All rights reserved.

Deskstar[®] is a trademark of Hitachi Global Storage Technologies. References in this publication to Hitachi Global Storage Technologies products, programs or services, do not imply that Hitachi Global Storage Technologies intends to make these available in all countries in which it operates.

Product information is provided for information purposes only, and does not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual results may vary. This publication is for general guidance only. Photographs may show design models.