

Imation USB Floppy Drive

for Macintosh and PC



Hot-swappable, Convenient Storage Solution

The Imation USB Floppy Drive for Macintosh™ and PC computers is designed to easily add a floppy disk drive using a USB port. Its simple, one cable connection, low power consumption and small space requirement make the Imation USB Floppy Drive a reliable and affordable addition to your operating system. The sleek, lightweight design provides instant portability and compatibility to your computer for backup, file transfer, software installation and more.



System Requirements

APPLE iMAC, iBOOK OR POWER MACINTOSH G3 OR G4 WITH:

- ▶▶ Mac OS® 8.6 or later
- ▶▶ USB port
- ▶▶ 32MB of RAM
- ▶▶ 1MB of available hard drive space
- ▶▶ CD-ROM drive

PC RUNNING WINDOWS® 98, 2000, ME OR XP WITH:

- ▶▶ USB port
- ▶▶ 32MB of RAM
- ▶▶ 1MB of available hard drive space
- ▶▶ CD-ROM drive

Features

- ▶▶ Instant floppy compatibility
- ▶▶ Lightweight, sleek design
- ▶▶ Simple one-cable connection
- ▶▶ Plug and play convenience
- ▶▶ Attractive color compliments most systems





Imation Enterprises Corp.
1 Imation Place
Oakdale, MN 55128-3414
651 704.4000
888 466.3456 phone
800 537.4675 fax
www.imation.com
info@imation.com

Imation Canada Inc.
P.O. Box/C.P. 5440
London, Ontario
N6A 5Z6 Canada
888 466.3456 phone (tél)
888 864.2260 fax (télé)

Product Specifications

USB Floppy Drive

General Information	
Type	External
Size	3.5"
Interface	USB Version 1.1
Capacity/Compatibility	1.4MB Mac format, 720KB or 1.44MB PC format
Dimensions	5.7" L x 4.1" W x 0.7" H
USB cable length	11.8"
Weight	.681 lbs.
Operating position	Horizontal only
Country of manufacture	Drive made in Taiwan, Kit assembled in U.S.A.
Approvals	CE, TUV, CSA, UL Listed
Warranty	1 year
Reliability	30,000 POH
Number of sides	Double sided media
Track positioning	Stepper motor w/lead screw
Performance	
USB transfer rate	12Mb/s
Media data rate	500Kb/s
Average latency	100 ms
Buffer capacity	2Kb
Power requirements	DC + 5V+/- 5%, 500 mA (Supplied by USB port on computer)
Rotational speed	300 RPM
Max. bit density	27,034 BPI
Track density	135 TPI
Recording method	MFM
Operating Environment	
Temperature	41 to 104° F (5 to 40° C)
Humidity	20 to 80% RH (non-condensing)
Maximum wet bulb temperature	85° F (29.4° C)
Non-Operating Environment	
Temperature	-8 to 140° F (-20 to 60° C)

Ordering Information

Product	UPC
Imation USB Floppy Drive	0-51122-41343-8