

The palm-size powerhouse.

The ViewSonic® PJ256D micro-portable DLP® projector is a small powerhouse that UNVEILS REMARKABLE PRESENTATIONS ANYWHERE your work takes you. Its small footprint easily fits in your briefcase and weighs a mere 2.2 pounds. A PERFECT IMAGE IS GUARANTEED IN VIRTUALLY ANY SETTING with the optical zoom lens and vertical keystone correction. Experience lifelike pictures with incredible contrast and clarity from 1024x768 native XGA resolution and support for HD signals. Additional features include a wireless remote with mouse control and laser pointer. Unlock the power of your presentations with the micro-portable, powerhouse PJ256D.

PJ256D

MICRO-PORTABLE PROJECTOR
WITH KEYSTONE CORRECTION



IDEAL FOR PROFESSIONALS

- > **Bright in virtually any setting with 1,500 lumens**
Packs 1,500 lumens in just 2.2 lbs. It's the bright choice for mobile presenters.
- > **DLP® technology**
Stunning all-digital clarity delivers lifelike color, sharp graphics, and outstanding video.
- > **Ultimate video source flexibility**
Connect a computer or add a video source for dynamic meetings and presentations.
- > **Supports HD signals including 720p and 1080i**
Capable of displaying HD signals as well as other video and data sources.*
- > **The perfect image in any setting**
Digital keystone correction and zoom function ensure the perfect size image in virtually any room.
- > **Whisper-mode extends lamp life**
Extend the life of your lamp up to 3,000 hours** and reduce noise output.
- > **The best warranty in the business**
Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic® 
the choice of professionals

PJ256D

MICRO-PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



Optional Accessories

- Replacement lamp RLC-009
- Rolling soft case with notebook bag . . PRJ-SCA-004
- Extended Express Exchange® PRJ-EE-03-03
- VGA to component video adapter . . ADPT-002

PROJECTOR	Type	0.7" DDR DMD, DLP®
	Pixel Format	1024x768 XGA
	Lens	Manual zoom, manual focus
	Zoom Factor	1.2
	Keystone	Vertical ± 8°
DISPLAY	Size	31.7"–246" (diagonally)
	Throw Distance	59"–394"
	Throw Ratio	2–2.3
	Lamp	156W, 2,000 hours**
	Brightness	1,500 ANSI lumens
	Contrast Ratio	2000:1
	Aspect Ratio	4:3 (native), 16:9
INPUT SIGNAL	Computer and Video	RGB analog, NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N60), SECAM (B, D, G, K, K1, L), 480i/p, HDTV (720p, 1080i)
	Frequency	F _H : 31.5–79.8kHz; F _V : 56–85Hz
COMPATIBILITY	PC	Analog: from VGA to SXGA (scaled)
	Mac®†	Analog: to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	15-pin HD, D-sub cable
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-Din 4-pin (x1)
	Component Video (input)	VGA to RCA component adapter (optional)
	USB	For mouse control
POWER	Voltage	100–240 VAC, 50/60Hz (universal)
	Consumption	200W (typ)
CONTROLS	Basic	Standby/On, input, menu
	OnView®	Display (mode, brightness, contrast, white intensity, color temp, saturation), management (menu location, projection, keystone, source lock, high altitude, translucence, reset), frequency, phase, H. position, V. position, degamma, aspect ratio, V. shift 16:9, OSD language, color setting, lamp setting
OPERATING CONDITIONS	Temperature	41–95°F (5–35°C)
	Humidity	85% (non-condensing)
NOISE LEVEL	Normal	38 dB (typ)
	Whisper Mode	37 dB (typ)
DIMENSIONS (W x H x D)	Physical (mm)	198mm x 57mm x 148mm
	Physical (in.)	7.9" x 2.5" x 6"
WEIGHT	Net	2.2 lb. (1.0 kg)
	Gross	5.5 lb. (2.5 kg)
REGULATIONS	UL, C-UL, FCC-B, CB, CE, TUV/GS, CCC, PSB	
OTHER	Whisper mode, front and rear projection, optical zoom, wireless remote control, soft carrying case, progressive scan	
PACKAGE CONTENTS	Projector, power cords, VGA cable, RCA video cable, remote control, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide	
WARRANTY	Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp***	

ViewSonic® 
the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***Visit ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. DLP is a registered trademark of Texas Instruments Inc. in the United States and other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12744-00B-01/06] PJ256D-1

For more product information, visit us on the web at ViewSonic.com