
MaXLine III SATA Hard Disk Drive Family

CAPACITIES:

| MODEL | ACT CYLS | HDS:SECT | MAX CYLS | MAXLBA | GB CAPACITY |
|---------|----------|----------|----------|-------------|-------------|
| 7B250S0 | 486,344 | 16:63 | 16,383 | 490,234,752 | 250GB |
| 7B300S0 | 588,422 | 16:63 | 16,383 | 593,129,376 | 300GB |

SATA = Serial ATA

Attaching SATA Power Cables:



PLEASE NOTE: Unlike standard ATA drives, Serial ATA drives DO NOT require the use of jumpers to configure the drive. Please disregard any references to jumper settings and Master, Slave and Cable Select configurations in the Maxtor Installation Guide.


Key Features:

- SATA interface
- Burst Data Transfer Speeds up to 150 MB/sec
- Up to 300GB capacities
- 9.3 ms average seek time
- 16MB Cache Buffer
- 100% FDB Motors
- 7200 RPM

Misc Drive Info:

For more information on step-by-step installation procedures, troubleshooting procedures and more go to the Maxtor.com Knowledge Base

GB = 1 billion bytes. Total accessible capacity varies depending on operating environment.



SATA Interface Cable Requirements:

7-pin Serial ATA interface cable (Gen. 1- or Gen. 2-compliant) up to 1 meter in length.

Document #: 42104 Rev: 00 Date: 6/21/04